

BOREAS S LED

Modern LED Floodlight with Symmetric Reflector



Type: A modern range of compact design LED floodlights with IP65 water and dust protection for use in adverse conditions.

Specification: Symmetric reflector in anodized aluminium. Tempered glass diffuser with aluminium clip.
Body in die-cast aluminium in dark grey finish.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for any horizontal and/or vertical surfaces.

Application: Outdoor. For building facades and perimeters, billboards, displays, car parks, etc.



A compact design with integral gear and light outputs in 2 body sizes: small and medium.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Boreas SS LED1x2200 C061 T850	220x182x57	50000	2154	19	80+	5000	1,40
Boreas SM LED1x4000 C062 T850	296x246x75	50000	3956	34	80+	5000	2,60
Boreas SM LED1x5400 C063 T850	296x246x75	50000	5358	48	80+	5000	2,60

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- DALI- DALI driver
- SDIM- Switch-control/dimming
- T830- Colour temperature 3000K (subject to min. quantity)
- T840- Colour temperature 4000K
- T850- Colour temperature 5000K

BOREAS SM LED1X4000 C062 T850

