

## WING D LED

### Unique Design Recessed LED Luminaire with Microprismatic or Opal Diffuser



<b>Type:</b>	A unique recessed LED luminaire with microprismatic or opal diffuser for most commercial lighting applications.
<b>Specification:</b>	Microprismatic (MPRZ LT92) or opal (OP LT80) diffuser. Fully enclosed white steel body. Luminaire is plastic wrapped and boxed individually.
<b>Installation:</b>	Fits 15-24mm exposed T-Bar ceiling 600x600mm. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use recessed mounting kit S620x620 (to be ordered separately).
<b>Application:</b>	Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Wing D LED2x1700 D079 T840 MPRZ LT92	595x595x96	50000	3243	29	80+	4000	3,50
Wing D LED2x2400 D080 T840 MPRZ LT92	595x595x96	50000	4635	39	80+	4000	3,50
Wing D LED2x1700 D079 T840 OP LT80	595x595x96	50000	2959	29	80+	4000	3,50
Wing D LED2x2400 D080 T840 OP LT80	595x595x96	50000	4230	39	80+	4000	3,50

\* Tolerance range for optical and electrical data: ±10 %

#### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
TW-	Tunable white
BLT-	Bluetooth unit (for wireless control via mobile device)
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
OP LT80-	Opal diffuser with 80% light transmission
MPRZ LT92-	Microprismatic diffuser for a better glare protection
WIE-	3-pole Wieland or similar connector
W625-	To fit 625x625 suspended ceiling (subject to minimum quantity)
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

#### WING D LED2X1700 D079 T840 MPRZ LT92

