

BRUBU LED

Recessed Luminaire for Use in Petrol Stations



Type:	LED Recessed Luminaire for use in petrol stations.
Specification:	IP65 version is made with tempered glass diffuser. Optics: 45°, 60° or 120x60° beam. Body in steel in white finish. Luminaire is plastic-wrapped and packed individually.
Installation:	Recessed luminaire is designed to be fixed to ceiling of any type.
Application:	For use in petrol stations.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Brubu LED1x8600 D440 T750 L60	425x425x190	50000	9085	80	70+	5000	8,80
Brubu LED1x10800 D441 T750 L60	425x425x190	50000	11356	99	70+	5000	8,80
Brubu LED1x12900 D442 T750 L60	425x425x190	50000	13627	119	70+	5000	8,80
Brubu LED1x8600 D440 T750 L60x120	425x425x190	50000	9085	80	70+	5000	8,80
Brubu LED1x10800 D441 T750 L60x120	425x425x190	50000	11356	99	70+	5000	8,80
Brubu LED1x12900 D442 T750 L60x120	425x425x190	50000	13627	119	70+	5000	8,80

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

DIM-	Dimmable driver 1-10V
SDIM-	Switch-control/dimming
DALI-	DALI driver
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
T750-	Colour temperature 5000K
L45-	Lens 45°
L60-	Lens 60°
L60x120-	Lens 60x120°

BRUBU LED1X10800 D441 T750 L60

