

ALGOL

IP66 Slim-line Road and Street Lights



Type:	A range of IP65 slim street lights with optimal light output at competitive prices.
Specification:	Bright anodized aluminium reflector with transparent PMMA bowl. UV stable polyamide clips with stainless steel springs enable tool-free bowl and gear compartment cover removal. Upper canopy is made of injection moulded glass-fibre UV stabilized polypropylene in grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Side entry mounting with two screws on pole Ø60mm. Suggested mounting height from 4 to 6 meters.
Application:	Outdoor. Suitable for many applications including car parks, minor and major roads, residential areas and public places.

Name	Description	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Algol 170 E95	HS	1x70 (E27)	438x308x162	2,95	85
Algol 1125 F17 HM	HM	1x125 (E27)	438x308x162	2,78	138

Options available on request:

HS-	For high pressure sodium lamps
HM-	For high pressure mercury lamps
HI-	For metal halide lamps
WCoffPRD-	Power reduction device with control wire (reduce when phase is OFF)
WConPRD-	Power reduction device with control wire (reduce when phase is ON)
AC5hPRD-	Power reduction device with automatic reduction after 5h. No control wire needed.
ACmidPRD-	Power reduction device with automatic reduction and middle night detection (for 7h). No control wire needed.
TIM-	Timed ignitor