

CORONA C LED

Recessed LED Luminaire with Circular Diffuser



Type: A recessed mounted LED luminaire with circular opal diffuser for most commercial lighting applications.

Specification: Diffuser: high transmission opal (OP LT80).
Fully enclosed white steel body.
Luminaire is plastic-wrapped and boxed individually.

Installation: Fits 15-24mm exposed T-Bar ceiling 600x600mm.

Application: Indoor. Office buildings, shops and other commercial environments.

| Name | Overall dimensions (LxWxH), mm | Lifetime | Luminaire output*, lm Ta=25°C | System power*, W | CRI (Ra) | CCT, K | Weight, kg |
|--------------------------------------|--------------------------------|----------|----------------------------------|------------------|----------|--------|------------|
| Corona C LED1x3100 D067 T840 OP LT80 | 595x595x70 | 50000 | 3006 | 29 | 80+ | 4000 | 3,10 |
| Corona C LED1x4300 D068 T840 OP LT80 | 595x595x70 | 50000 | 4227 | 39 | 80+ | 4000 | 3,10 |
| Corona C LED1x5900 D069 T840 OP LT80 | 595x595x70 | 50000 | 5859 | 57 | 80+ | 4000 | 3,10 |

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

| | |
|----------|--|
| SDIM- | Switch-control/dimming |
| DALI- | DALI driver |
| TW- | Tunable white |
| BLT- | Bluetooth unit (for wireless control via mobile device) |
| EMG- | Emergency version 1 hour |
| EM3- | Emergency version 3 hours |
| OP LT80- | Opal diffuser with 80% light transmission |
| W625- | To fit 625x625 suspended ceiling (subject to minimum quantity) |
| IP44- | IP44 protection degree |
| RAL- | RAL colours |
| T830- | Colour temperature 3000K |
| T840- | Colour temperature 4000K |

CORONA C LED1X4300 D068 T840 OP LT80

