```sql
-- 1. How many customers have not placed any orders?
select user_id from users
where user_id not in (
    select distinct user_id from orders
    where user_id is not null
);
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

user_id
6
7

```sql
-- 2. What is the average price of food for each restaurant?
SELECT
    r.R_Name,
    ROUND(AVG(m.price),2) AS Avg_Price
FROM restaurants r
JOIN menu m
ON r.r_id = m.r_id
GROUP BY r.R_Name
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

R_Name	Avg_Price
box8	126.67
China Town	216.67
dominos	316.67
Dosa Plaza	176.67
kfc	215.00

```sql
-- 3. Find the top restaurant in terms of the number of orders for all months
WITH res_grouped AS (
    SELECT
        MONTH(STR_TO_DATE(o.date,'%d-%m-%Y')) AS order_month,
        r.r_name,
        COUNT(*) AS order_count
    FROM orders o
    JOIN restaurants r
    ON o.r_id = r.r_id
    GROUP BY MONTH(STR_TO_DATE(o.date,'%d-%m-%Y')), r.r_name
),
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_month	r_name
5	Dosa Plaza
6	kfc
7	kfc

```sql
-- 4. Find the top restaurant in terms of the number of orders for the month of June
SELECT r.r_name, COUNT(*) AS total_orders
FROM restaurants r
JOIN orders o
ON r.r_id = o.r_id
WHERE MONTH(STR_TO_DATE(o.date,'%d-%m-%Y')) = 6
GROUP BY r.r_name
ORDER BY total_orders DESC
LIMIT 1;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

r_name	total_orders
kfc	3

```sql
-- 5. Restaurants with monthly revenue greater than 500
SELECT
  MONTH(STR_TO_DATE(o.date,'%d-%m-%Y')) AS order_month,
  r.r_name,
  SUM(m.price) AS revenue
FROM restaurants r
JOIN orders o
ON r.r_id = o.r_id
JOIN menu m
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_month	r_name	revenue
5	dominos	1900
5	Dosa Plaza	1590
5	kfc	1290
6	box8	760
6	China Town	650
6	dominos	950
6	Dosa Plaza	530

```sql
-- 6. Show all orders with order details for a particular customer in a date range
SELECT *
FROM users u
JOIN orders o
ON u.user_id = o.user_id
WHERE u.user_id = 1
AND STR_TO_DATE(o.date,'%d-%m-%Y')
BETWEEN '2022-05-15' AND '2022-06-15';
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

user_id	name	email	password	order_id	user_id	r_id	amount	date	partner_id	delivery_time	delivery_ra
1	Nitish	nitish@gmail.com	p252h	1002	1	2	415	26-05-2022	1	19	5
1	Nitish	nitish@gmail.com	p252h	1003	1	3	240	15-06-2022	5	29	4

```sql
-- 7. Which restaurant has the highest number of repeat customers?
WITH repeated_cust AS (
  SELECT
    r.r_name,
    o.user_id,
    COUNT(*) AS order_count
  FROM restaurants r
  JOIN orders o
  ON r.r_id = o.r_id
  GROUP BY r.r_name, o.user_id
  HAVING COUNT(*) > 1
)
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

r_name	repeated_customers
kfc	2

```sql
-- 8. Month over month revenue growth of Swiggy
WITH month_rev AS (
  SELECT
    MONTH(STR_TO_DATE(o.date,'%d-%m-%Y')) AS order_month,
    SUM(m.price) AS monthly_rev
  FROM orders o
  JOIN menu m
  ON o.r_id = m.r_id
  GROUP BY MONTH(STR_TO_DATE(o.date,'%d-%m-%Y'))
)
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_month	rolling_monthly_revenue
5	4780
6	9605
7	16030

```sql
-- 9. Find the top 3 most ordered dish
SELECT
  f.f_name,
  COUNT(*) AS order_count
FROM order_details od
JOIN food f
ON f.f_id = od.f_id
GROUP BY f.f_name
ORDER BY order_count DESC
LIMIT 3;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

f_name	order_count
Choco Lava cake	13
Chicken Wings	8
Non-veg Pizza	5

```sql
-- 10. Overall revenue generated during a specific period
SELECT
SUM(amount) AS total_revenue
FROM orders
WHERE STR_TO_DATE(date,'%d-%m-%Y')
BETWEEN '2022-05-01' AND '2022-06-01';
```

total_revenue
2425

```sql
-- 11. What is the average order value per user?
SELECT
user_id,
ROUND(AVG(amount),2) AS avg_order_value
FROM orders
GROUP BY user_id;
```

user_id	avg_order_value
1	333.00
2	534.00
3	264.00
4	360.00
5	607.00

```sql
-- 12. What is the average delivery time for each restaurant and how it affects customer satisfaction?
SELECT
r.r_name,
ROUND(AVG(o.delivery_time),2) AS avg_delivery_time,
ROUND(AVG(o.delivery_rating),2) AS avg_delivery_rating
FROM orders o
JOIN restaurants r
ON o.r_id = r.r_id
```

r_name	avg_delivery_time	avg_delivery_rating
dominos	24.40	4.00
kfc	42.50	3.25
box8	40.50	3.00
Dosa Plaza	39.00	2.80
China Town	54.33	2.67

```sql
-- 13. Average rating for each restaurant
SELECT
r.r_name,
ROUND(AVG(o.restaurant_rating),2) AS avg_restaurant_rating
FROM orders o
JOIN restaurants r
ON o.r_id = r.r_id
GROUP BY r.r_name
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

r_name	avg_restaurant_rating
China Town	3.67
box8	3.5
Dosa Plaza	2.2
kfc	1.38
dominos	1

```sql
-- 14 Delivery Partner Ratings
SELECT
dp.partner_name,
ROUND(AVG(o.delivery_rating),2) AS avg_delivery_rating
FROM orders o
JOIN delivery_partner dp
ON o.partner_id = dp.partner_id
GROUP BY dp.partner_name
ORDER BY avg_delivery_rating DESC;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

partner_name	avg_delivery_rating
Lokesh	4.00
Gyandeep	3.50
Kartik	3.00
Amit	3.00
Suresh	2.86

```sql
-- 15. Correlation between restaurant rating and delivery rating
SELECT
(
SUM((restaurant_rating - avg_r) * (delivery_rating - avg_d)) /
SQRT(
SUM(POW(restaurant_rating - avg_r,2)) *
SUM(POW(delivery_rating - avg_d,2))
)
) AS rating_correlation
FROM (
SELECT
restaurant_rating,
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

rating_correlation
-0.12194348607936739

```sql
-- 17. How many orders were delivered by each delivery partner  and what is their average delivery rating?
SELECT
DAYNAME(STR_TO_DATE(date,'%d-%m-%Y')) AS order_day,
COUNT(order_id) AS order_count
FROM orders
GROUP BY order_day
ORDER BY order_count DESC;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_day	order_count
Thursday	6
Friday	6
Wednesday	4
Sunday	4
Tuesday	2
Monday	2
Saturday	1

```sql
-- 18. What is the distribution of delivery partners in the Delivery_Partner table?
SELECT
partner_name,
COUNT(*) AS partner_count
FROM delivery_partner
GROUP BY partner_name
ORDER BY partner_count DESC;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

partner_name	partner_count
Suresh	1
Amit	1
Lokesh	1
Kartik	1
Gyandeep	1