

```

from sqlalchemy.orm import Session

import models
import schemas
from auth import hash_password

# ----- Users -----

def get_user_by_username(db: Session, username: str):
    return db.query(models.User).filter(models.User.username == username).first()

def get_user_by_email(db: Session, email: str):
    return db.query(models.User).filter(models.User.email == email).first()

def create_user(db: Session, user: schemas.UserCreate) -> models.User:
    db_user = models.User(
        username=user.username,
        email=user.email,
        hashed_password=hash_password(user.password),
    )
    db.add(db_user)
    db.commit()
    db.refresh(db_user)
    return db_user

# ----- Items (CRUD resource, scoped to the authenticated user) -----

def get_items(db: Session, owner_id: int, skip: int = 0, limit: int = 100):
    return (
        db.query(models.Item)
        .filter(models.Item.owner_id == owner_id)
        .offset(skip)
        .limit(limit)
        .all()
    )

def get_item(db: Session, item_id: int, owner_id: int):
    return (
        db.query(models.Item)

```

```

        .filter(models.Item.id == item_id, models.Item.owner_id == owner_id)
        .first()
    )

def create_item(db: Session, item: schemas.ItemCreate, owner_id: int) -> models.I
    db_item = models.Item(**item.model_dump(), owner_id=owner_id)
    db.add(db_item)
    db.commit()
    db.refresh(db_item)
    return db_item

def update_item(db: Session, db_item: models.Item, updates: schemas.ItemUpdate) -
    for field, value in updates.model_dump(exclude_unset=True).items():
        setattr(db_item, field, value)
    db.commit()
    db.refresh(db_item)
    return db_item

def delete_item(db: Session, db_item: models.Item) -> None:
    db.delete(db_item)
    db.commit()

```