

Importance of N_2H_x Reaction Pathways to Optimize Okafor Reduced Mechanism for NH_3/H_2 Flame Chemistry

UROTHIYIL Aahil Ashraf (1TE23533T)

Department of Mechanical Engineering
Reactive Gas Dynamics Laboratory

June 15, 2026

Research Background

Traditional sources of energy rely on combustion of fossil fuels that produce carbon emissions which have adverse effects on the environment:

- Global Warming
- Climate Change

New carbon-free alternative fuels are needed to prevent exacerbating the effects of carbon pollutants

- The Japanese government seeks to reduce total greenhouse gas emissions by 46% before 2030
- By 2050, Japan envisions its cities to be carbon-neutral

Research Background

Ammonia, NH_3 , is gaining interest among researchers for its potential to meet energy needs in a variety of applications.

Ammonia is a suitable fuel for combustion application because:

- Ammonia combustion produces no CO_2
- Ammonia has a high volumetric energy density
- Easier to store than hydrogen
- Infrastructure to produce and transport ammonia already exists
- Used as H_2 carrier




Figure: Hideaki Kobayashi et al. (Jan. 1, 2019). "Science and Technology of Ammonia Combustion". In: *Proceedings of the Combustion Institute* 37.1, pp. 109–133. ISSN: 1540-7489. DOI: 10.1016/j.proci.2018.09.029

Objectives

- Validate Abe Mechanism, at varying combustion conditions, for fuels:
 - $\text{NH}_3/\text{H}_2/\text{Air}$
 - $\text{CH}_4/\text{NH}_3/\text{Air}$
- Flame properties being evaluated:
 - Laminar burning velocity
 - Specie profiles
 - Intermediate species profiles
- Optimize reaction mechanism to fit experimental data for all conditions above satisfactorily

- Validate Abe Mechanism, at varying combustion conditions, for fuels:
 - $\text{NH}_3/\text{H}_2/\text{Air}$
 - $\text{CH}_4/\text{NH}_3/\text{Air}$
- Flame properties evaluated:
 - Laminar burning velocity

Prior Findings — $\text{NH}_3/\text{H}_2/\text{Air}$

Abe mechanism reproduces LBV of $\text{NH}_3/\text{H}_2/\text{Air}$ flame to match experimental data




Figure: Laminar burning velocities of $\text{NH}_3/\text{H}_2/\text{Air}$ flames at varying H_2 concentrations while pressure and equivalence ratio is kept constant at 1atm and 1.0 respectively

Prior Findings — CH₄/NH₃/Air

Plotting of experimental data from Okafor 2019¹ was corrected




Figure: Laminar burning velocities of CH₄/NH₃/Air flames at varying NH₃ concentrations while pressure and equivalence ratio is kept constant at 1atm and 0.7 respectively

¹Ekenechukwu Chijioka Okafor et al. (June 1, 2019). "Measurement and Modelling of the Laminar Burning Velocity of Methane-Ammonia-Air Flames at High Pressures Using a Reduced Reaction Mechanism". In: *Combustion and Flame* 204, pp. 162–175. ISSN: 0010-2180. DOI: 10.1016/j.combustflame.2019.03.008.

Prior Findings — Failed Conditions

- LBV overprediction by Abe mech observed across most CH₄/NH₃/Air conditions.
 - Pressure = 1 atm, $\phi = 1.4$
 - Pressure = 1 atm, $\phi = 1.6$
- Experimental data for higher pressures, 3atm and 5atm, are lacking for both fuels
- Numerical simulations with Okafor reduced mechanism failed to converge
 - Unable to compare LBV from Okafor Reduced Mechanism and Abe mech at the conditions discussed

Next Steps

- Validating Abe mech's specie profiles with experimental data from literature
- Speciation data for relevant fuels and corresponding fuels selected
 - CH₄/NH₃: NH₃, NO, CO
 - NH₃: OH, NH, NO
 - NH₃/H₂: NH₂, NH, NO_x
- For each speciation dataset, simulation methodology employed in the corresponding paper must be used for validating Abe mech

Specie Profiles — CH₄/NH₃

- From Mendiara and Glarborg 2009, the speciation data is used to validate NH₃, NO and CO profiles
- Plug Flow Reactor
 - Diameter = 12 mm
 - Length = 120 cm
 - Gas flow rate = 1 dm³/min
 - Temperature = 973-1773 K

Table: Experimental conditions that need to be simulated with the plug flow reactor. [Teresa Mendiara and Peter Glarborg \(Oct. 1, 2009\)](#). "Ammonia Chemistry in Oxy-Fuel Combustion of Methane". In: *Combustion and Flame* 156.10, pp. 1937–1949. ISSN: 0010-2180. DOI: 10.1016/j.combustflame.2009.07.006

Run	CH ₄ /ppm	O ₂ /ppm	NH ₃ /ppm	N ₂ /%	ϕ	Residence time/s
1	2515	3479	484	99.35	1.55	1296/ T (K)
2	2513	5036	468	99.20	1.07	1296/ T (K)
3	2508	40062	468	95.69	0.13	1293/ T (K)

Specie Profiles — NH₃

- From Brackmann et al. 2016, speciation data of OH, NH and NO profiles are used to validate Abe mech.
- Stagnation Flame Reactor
 - Steel disk to stabilize the flame
 - Flame stabilized at ~6 mm above burner surface so domain should be > 6 mm
 - Temperature profiles from the experiment used as input
 - GRAD parameter was set to 0.02

Table: Experimental conditions that need to be simulated with the stagnation flame reactor. [Christian Brackmann et al. \(Jan. 1, 2016\)](#). "Structure of Premixed Ammonia + Air Flames at Atmospheric Pressure: Laser Diagnostics and Kinetic Modeling". In: *Combustion and Flame* 163, pp. 370–381. ISSN: 0010-2180. DOI: [10.1016/j.combustflame.2015.10.012](https://doi.org/10.1016/j.combustflame.2015.10.012)

Flame	NH ₃ (L _n /min)	Air (L _n /min)	N ₂ -flame (L _n /min)	N ₂ -coflow (L _n /min)
$\phi = 0.9$	2.62	10.3	0	1.2
$\phi = 1.0$	3.38	12.1	0.87	1.2
$\phi = 1.2$	3.9	11.6	0	1.2

Specie Profiles — NH₃/H₂

- From Alturaifi, Mathieu, and Petersen 2023, speciation data of NH₃, NO, NO_x, N₂O and NH₂ profiles used.
- Premixed Laminar Flame-Speed Reactor/Burner-stabilized flat flame
 - Domain/width of ~ 20 mm
 - Experimental flame's temperature profile used as input

Table: Experimental conditions that need to be simulated. [Sulaiman A. Alturaifi, Olivier Mathieu, and Eric L. Petersen \(Jan. 1, 2023\)](#). "A Shock-Tube Study of NH₃ and NH₃/H₂ Oxidation Using Laser Absorption of NH₃ and H₂O". In: *Proceedings of the Combustion Institute* 39.1, pp. 233–241. ISSN: 1540-7489

Flame	X_{NH_3}	X_{H_2}	X_{O_2}	X_{Ar}	V_0 (cm/s)	Φ	p (mbar)
I	0.25	0.05	0.21	0.48	35.1	1	60
II	0.24	0.07	0.21	0.47	42.1	1	50
III	0.22	0.10	0.21	0.46	42.1	1	50
IV	0.21	0.13	0.21	0.45	42.0	1	50
V	0.22	0.10	0.24	0.43	42.2	0.9	50
VI	0.22	0.10	0.20	0.48	42.5	1.1	50
VII	0.25	0.05	0.21	0.48	23.4	1	90
VIII	0.25	0.05	0.21	0.48	17.6	1	120

Thank You