

# Semistochastic importance sampling of second-quantized operators in determinant space

Adam Holmes

Valeev Group Meeting  
June 7, 2021

# Overview

- 1 Motivation
- 2 Algorithm
- 3 Applications

# Motivation

# Types of quantum chemistry algorithms

- 1 Operator-based algorithms:

# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➋ Coupled cluster

# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➊ Coupled cluster
  - ➋ Moller-Plesset perturbation theory

# Types of quantum chemistry algorithms

- 1 Operator-based algorithms:
  - 1 Coupled cluster
  - 2 Moller-Plesset perturbation theory
- 2 Wavefunction-based/determinant-space algorithms:

# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➊ Coupled cluster
  - ➋ Moller-Plesset perturbation theory
- ➋ Wavefunction-based/determinant-space algorithms:
  - ➊ Full CI



# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➊ Coupled cluster
  - ➋ Moller-Plesset perturbation theory
  
- ➋ Wavefunction-based/determinant-space algorithms:
  - ➊ Full CI
  - ➋ Selected CI

# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➊ Coupled cluster
  - ➋ Moller-Plesset perturbation theory
  
- ➋ Wavefunction-based/determinant-space algorithms:
  - ➊ Full CI
  - ➋ Selected CI
  - ➌ Epstein-Nesbet perturbation theory

# Types of quantum chemistry algorithms

- ➊ Operator-based algorithms:
  - ➊ Coupled cluster
  - ➋ Moller-Plesset perturbation theory
  
- ➋ Wavefunction-based/determinant-space algorithms:
  - ➊ Full CI
  - ➋ Selected CI
  - ➌ Epstein-Nesbet perturbation theory
  - ➍ Full CI Quantum Monte Carlo (FCIQMC)

In determinant-space algorithms, one of the key steps is applying a second-quantized operator (usually  $H$ ) to a Slater determinant!

In determinant-space algorithms, one of the key steps is applying a second-quantized operator (usually  $H$ ) to a Slater determinant!

- 1 Full CI: Iterative diagonalization of the Hamiltonian (e.g. using Davidson) diagonalizes in the basis of Krylov vectors

$$\{v_i = f(Hv_{i-1})\} \quad (1)$$

In determinant-space algorithms, one of the key steps is applying a second-quantized operator (usually  $H$ ) to a Slater determinant!

- 1 Full CI: Iterative diagonalization of the Hamiltonian (e.g. using Davidson) diagonalizes in the basis of Krylov vectors

$$\{v_i = f(Hv_{i-1})\} \quad (1)$$

- 2 Selected CI: New determinants are 'selected' using a criterion that is a function of  $H\psi_0$

In determinant-space algorithms, one of the key steps is applying a second-quantized operator (usually  $H$ ) to a Slater determinant!

- 1 Full CI: Iterative diagonalization of the Hamiltonian (e.g. using Davidson) diagonalizes in the basis of Krylov vectors

$$\{v_i = f(Hv_{i-1})\} \quad (1)$$

- 2 Selected CI: New determinants are 'selected' using a criterion that is a function of  $H\psi_0$
- 3 Epstein-Nesbet perturbation theory:

$$\Delta E = \left\langle \psi_0 \left| V \frac{1}{E_0 - H_0} V \right| \psi_0 \right\rangle \quad (2)$$

In determinant-space algorithms, one of the key steps is applying a second-quantized operator (usually  $H$ ) to a Slater determinant!

- 1 Full CI: Iterative diagonalization of the Hamiltonian (e.g. using Davidson) diagonalizes in the basis of Krylov vectors

$$\{v_i = f(Hv_{i-1})\} \quad (1)$$

- 2 Selected CI: New determinants are 'selected' using a criterion that is a function of  $H\psi_0$
- 3 Epstein-Nesbet perturbation theory:

$$\Delta E = \left\langle \psi_0 \left| V \frac{1}{E_0 - H_0} V \right| \psi_0 \right\rangle \quad (2)$$

- 4 FCIQMC: Stochastically simulate the power method,

$$\psi_0 \propto \lim_{n \rightarrow \infty} (1 - \tau H)^n \psi_T \quad (3)$$



# Approaches for computing $H |D_i\rangle$

Broadly, there are three main approaches:

- 1 **Deterministic:** Simply evaluating all single and double excitations from the initial Slater determinant. Complexity:  $\mathcal{O}(N^2(M - N)^2)$

# Approaches for computing $H |D_i\rangle$

Broadly, there are three main approaches:

- 1 **Deterministic:** Simply evaluating all single and double excitations from the initial Slater determinant. Complexity:  $\mathcal{O}(N^2(M - N)^2)$
- 2 **Stochastic:** Sampling excitations according to some distribution. Reduces the complexity, but introduces a stochastic uncertainty (and in projector methods, the fermion sign problem!)

# Approaches for computing $H |D_i\rangle$

Broadly, there are three main approaches:

- 1 **Deterministic:** Simply evaluating all single and double excitations from the initial Slater determinant. Complexity:  $\mathcal{O}(N^2(M - N)^2)$
- 2 **Stochastic:** Sampling excitations according to some distribution. Reduces the complexity, but introduces a stochastic uncertainty (and in projector methods, the fermion sign problem!)
- 3 **Semistochastic:** Evaluating the largest-magnitude components, and sampling the remaining, smaller components. Reduces complexity relative to the deterministic approach, but with a **greatly reduced stochastic uncertainty** relative to fully stochastic methods. In projector methods, it also mitigates the bias incurred in taming the fermion sign problem, such as the initiator bias in FCIQMC.

# Semistochastic approach

# Semistochastic approach

- 1 Separate out the sum into a **few large terms** and **many small terms** using some threshold  $\epsilon$

# Semistochastic approach

- 1 Separate out the sum into a **few large terms** and **many small terms** using some threshold  $\epsilon$
- 2 Compute the sum of the few large terms deterministically (and quickly)

# Semistochastic approach

- 1 Separate out the sum into a **few large terms** and **many small terms** using some threshold  $\epsilon$
- 2 Compute the sum of the few large terms deterministically (and quickly)
- 3 Importance sample the many small terms

# Semistochastic approach

- 1 Separate out the sum into a **few large terms** and **many small terms** using some threshold  $\epsilon$
- 2 Compute the sum of the few large terms deterministically (and quickly)
- 3 Importance sample the many small terms

$$H |D_i\rangle = \sum_j H_{ji} \quad (4)$$

$$= \underbrace{\sum_j H_{ji} \Big|_{|H_{ji}| \geq \epsilon}}_{\text{few large terms: sum deterministically}} + \underbrace{\sum_j H_{ji} \Big|_{|H_{ji}| < \epsilon}}_{\text{many small terms: importance sample}} \quad (5)$$



# Algorithm

# Deterministic component

- **Setup:**

# Deterministic component

- **Setup:**

- For each pair of orbitals  $\{p, q\}$ , store a list of  $\{r, s, |H(rs \leftarrow pq)|\}$ , sorted by  $|H(rs \leftarrow pq)|$  in decreasing order

# Deterministic component

- **Setup:**

- For each pair of orbitals  $\{p, q\}$ , store a list of  $\{r, s, |H(rs \leftarrow pq)|\}$ , sorted by  $|H(rs \leftarrow pq)|$  in decreasing order
- Also compute (for sampling algorithm):

$$\sum_{rs \in \text{remaining}} |H(rs \leftarrow pq)| \quad (6)$$

# Deterministic component

- **Setup:**

- For each pair of orbitals  $\{p, q\}$ , store a list of  $\{r, s, |H(rs \leftarrow pq)|\}$ , sorted by  $|H(rs \leftarrow pq)|$  in decreasing order
- Also compute (for sampling algorithm):

$$\sum_{rs \in \text{remaining}} |H(rs \leftarrow pq)| \quad (6)$$

- **Finding important connected determinants  $D_j$**  (for which  $|H_{ji}| \geq \epsilon$ ):

# Deterministic component

- **Setup:**


- For each pair of orbitals  $\{p, q\}$ , store a list of  $\{r, s, |H(rs \leftarrow pq)|\}$ , sorted by  $|H(rs \leftarrow pq)|$  in decreasing order
- Also compute (for sampling algorithm):

$$\sum_{rs \in \text{remaining}} |H(rs \leftarrow pq)| \quad (6)$$

- **Finding important connected determinants  $D_j$  (for which  $|H_{ji}| \geq \epsilon$ ):**

- For each pair of occupied orbitals  $\{p, q\}$ , look up the stored list of  $\{r, s, |H(rs \leftarrow pq)|\}$  and iterate until  $|H(rs \leftarrow pq)| < \epsilon$

# Deterministic component



# Discrete sampling algorithms

- **Alias sampling:**



# Discrete sampling algorithms

- **Alias sampling:**

- 1 Sample an element with uniform probability

# Discrete sampling algorithms

- **Alias sampling:**

- ① Sample an element with uniform probability
- ② If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element

# Discrete sampling algorithms

- **Alias sampling:**

- ① Sample an element with uniform probability
  - ② If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

# Discrete sampling algorithms

- **Alias sampling:**

- ① Sample an element with uniform probability
  - ② If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

- **Cumulative distribution function (CDF) searching:**

# Discrete sampling algorithms

- **Alias sampling:**

- 1 Sample an element with uniform probability
  - 2 If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

- **Cumulative distribution function (CDF) searching:**

- 1 Sample a real number  $r$  uniformly between 0 and 1

# Discrete sampling algorithms

- **Alias sampling:**

- 1 Sample an element with uniform probability
  - 2 If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

- **Cumulative distribution function (CDF) searching:**

- 1 Sample a real number  $r$  uniformly between 0 and 1
- 2 Binary-search the CDF for  $r$  (i.e., find the smallest index  $i$  for which  $r < \text{CDF}_i$ )

# Discrete sampling algorithms

- **Alias sampling:**

- 1 Sample an element with uniform probability
  - 2 If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

- **Cumulative distribution function (CDF) searching:**

- 1 Sample a real number  $r$  uniformly between 0 and 1
  - 2 Binary-search the CDF for  $r$  (i.e., find the smallest index  $i$  for which  $r < \text{CDF}_i$ )
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(\log N)$

# Discrete sampling algorithms

- **Alias sampling:**

- 1 Sample an element with uniform probability
  - 2 If a low-probability element was selected, it has some probability of 'aliasing' to another, high-probability element
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(1)$

- **Cumulative distribution function (CDF) searching:**

- 1 Sample a real number  $r$  uniformly between 0 and 1
  - 2 Binary-search the CDF for  $r$  (i.e., find the smallest index  $i$  for which  $r < \text{CDF}_i$ )
- Setup time:  $\mathcal{O}(N)$ , Time per sample:  $\mathcal{O}(\log N)$

- Usually, Alias sampling is preferred because it has lower sampling complexity, but CDF searching has a unique use case that we will need...



# CDF searching's unique use case

Suppose we have a stored CDF, and we want to be able to efficiently sample one of the first  $n$  elements, where  $n$  is not known ahead of time. CDF searching can do this efficiently with a small modification:

- 1 Sample a real number  $r$  uniformly between 0 and  $\text{CDF}_n$   
(Note that  $\text{CDF}_N = 1$  reduces to the original algorithm)

## CDF searching's unique use case

Suppose we have a stored CDF, and we want to be able to efficiently sample one of the first  $n$  elements, where  $n$  is not known ahead of time. CDF searching can do this efficiently with a small modification:

- 1 Sample a real number  $r$  uniformly between 0 and  $\text{CDF}_n$   
(Note that  $\text{CDF}_N = 1$  reduces to the original algorithm)
- 2 Binary-search the CDF for  $r$  (i.e., find the smallest index  $i$  for which  $r < \text{CDF}_i$ )

# Importance-sampling excitations

- Recall that we have already described how to treat the large-magnitude ( $|H_{ji}| \geq \epsilon$ ) excitations deterministically

# Importance-sampling excitations

- Recall that we have already described how to treat the large-magnitude ( $|H_{ji}| \geq \epsilon$ ) excitations deterministically
- Now, we want to “importance-sample” the remaining small-magnitude ( $|H_{ji}| < \epsilon$ ) excitations, i.e.:

$$P(H_{ji}) \begin{cases} \propto f(|H_{ji}|), & \text{if } |H_{ji}| < \epsilon; \\ = 0, & \text{if } |H_{ji}| \geq \epsilon. \end{cases} \quad (7)$$

# Importance-sampling excitations

- Recall that we have already described how to treat the large-magnitude ( $|H_{ji}| \geq \epsilon$ ) excitations deterministically
- Now, we want to “importance-sample” the remaining small-magnitude ( $|H_{ji}| < \epsilon$ ) excitations, i.e.:

$$P(H_{ji}) \begin{cases} \propto f(|H_{ji}|), & \text{if } |H_{ji}| < \epsilon; \\ = 0, & \text{if } |H_{ji}| \geq \epsilon. \end{cases} \quad (7)$$

- Examples of importance-sampling distributions include:

$$f(|H_{ji}|) = |H_{ji}|, \quad f(|H_{ji}|) = |H_{ji}|^2 \quad (8)$$

# Importance-sampling excitations

We divide the sampling of an excitation into two stages:

- 1 Sample an exciting electron pair

# Importance-sampling excitations

We divide the sampling of an excitation into two stages:

- 1 Sample an exciting electron pair
  - with probability proportional to the sum of remaining (small-magnitude) targets it could excite to

# Importance-sampling excitations

We divide the sampling of an excitation into two stages:

- 1 Sample an exciting electron pair
  - with probability proportional to the sum of remaining (small-magnitude) targets it could excite to
- 2 Sample a target orbital pair



# Importance-sampling excitations

We divide the sampling of an excitation into two stages:

- ① Sample an exciting electron pair
  - with probability proportional to the sum of remaining (small-magnitude) targets it could excite to
- ② Sample a target orbital pair
  - with probability proportional to its excitation magnitude

## Sampling an exciting electron pair

- During the deterministic step, for each exciting electron pair, we iterate over the sorted excitation magnitudes

# Sampling an exciting electron pair

- During the deterministic step, for each exciting electron pair, we iterate over the sorted excitation magnitudes
- As soon as the threshold is reached, we record the sum of remaining excitation magnitudes as that electron pair's relative probability

# Sampling an exciting electron pair

- During the deterministic step, for each exciting electron pair, we iterate over the sorted excitation magnitudes
- As soon as the threshold is reached, we record the sum of remaining excitation magnitudes as that electron pair's relative probability
- After doing this for all electron pairs, we set up the Alias sampling data structure in  $\mathcal{O}(N^2)$  time

# Sampling an exciting electron pair

- During the deterministic step, for each exciting electron pair, we iterate over the sorted excitation magnitudes
- As soon as the threshold is reached, we record the sum of remaining excitation magnitudes as that electron pair's relative probability
- After doing this for all electron pairs, we set up the Alias sampling data structure in  $\mathcal{O}(N^2)$  time
- This enables **importance-sampling an exciting electron pair in  $\mathcal{O}(1)$  time**

## Sampling a target orbital pair

- Once an exciting electron pair is selected, we now have to sample a target orbital pair to excite to

# Sampling a target orbital pair

- Once an exciting electron pair is selected, we now have to sample a target orbital pair to excite to
- Since the deterministic stage has already been completed, we know which target orbital pair  $(r, s)$  is the first one that hasn't been treated deterministically

# Sampling a target orbital pair

- Once an exciting electron pair is selected, we now have to sample a target orbital pair to excite to
- Since the deterministic stage has already been completed, we know which target orbital pair  $(r, s)$  is the first one that hasn't been treated deterministically
- We have a CDF (in reverse order) corresponding to all target orbital pairs, and we need to sample one of the orbital pairs whose index is at least as high as this one



# Sampling a target orbital pair

- Once an exciting electron pair is selected, we now have to sample a target orbital pair to excite to
- Since the deterministic stage has already been completed, we know which target orbital pair  $(r, s)$  is the first one that hasn't been treated deterministically
- We have a CDF (in reverse order) corresponding to all target orbital pairs, and we need to sample one of the orbital pairs whose index is at least as high as this one
- So, we just use CDF searching to **sample a target orbital pair in  $\mathcal{O}(\log M)$  time**

# What about single excitations?

- Unlike double excitations, single excitation matrix element magnitudes depend on the orbital occupancies of the exciting determinant

## What about single excitations?

- Unlike double excitations, single excitation matrix element magnitudes depend on the orbital occupancies of the exciting determinant
- But we can compute upper bounds to the single excitation magnitudes:

$$|H(p \rightarrow r)| \leq |H(p \rightarrow r)|_{\max}, \quad (9)$$

where  $|H(p \rightarrow r)|_{\max}$  is the largest magnitude the  $p \rightarrow r$  excitation can have from *any* initial determinant

# What about single excitations?

- Unlike double excitations, single excitation matrix element magnitudes depend on the orbital occupancies of the exciting determinant
- But we can compute upper bounds to the single excitation magnitudes:

$$|H(p \rightarrow r)| \leq |H(p \rightarrow r)|_{\max}, \quad (9)$$

where  $|H(p \rightarrow r)|_{\max}$  is the largest magnitude the  $p \rightarrow r$  excitation can have from *any* initial determinant

- The simplest way to incorporate singles is to sample them with probability  $P(|H(p \rightarrow r)|) \propto f(|H(p \rightarrow r)|_{\max})$  and skip them in the deterministic step

## Sampling 'invalid' excitations

- Sometimes this algorithm will sample 'invalid' excitations to already-occupied orbitals

## Sampling 'invalid' excitations

- Sometimes this algorithm will sample 'invalid' excitations to already-occupied orbitals
- While unbiased, this increases the variance in the samples

# Sampling 'invalid' excitations

- Sometimes this algorithm will sample 'invalid' excitations to already-occupied orbitals
- While unbiased, this increases the variance in the samples
- We can fix this as follows:

# Sampling 'invalid' excitations

- Sometimes this algorithm will sample 'invalid' excitations to already-occupied orbitals
- While unbiased, this increases the variance in the samples
- We can fix this as follows:
  - ① If an 'invalid' excitation is sampled, discard it and resample until a valid excitation is sampled



# Sampling 'invalid' excitations

- Sometimes this algorithm will sample 'invalid' excitations to already-occupied orbitals
- While unbiased, this increases the variance in the samples
- We can fix this as follows:
  - 1 If an 'invalid' excitation is sampled, discard it and resample until a valid excitation is sampled
  - 2 Scale the sample probabilities by a constant factor so they remain normalized (can be performed in  $\mathcal{O}(N^4 + N_{\text{det}}N^3)$  time during deterministic step)

# Applications

# Epstein-Nesbet perturbation theory

Given a variational wavefunction  $\psi_0 = \sum_i c_i |D_i\rangle$  with energy  $E_0$ , the Epstein-Nesbet perturbative correction to the energy is give by

$$\Delta E [V | \psi_0] = \left\langle \psi_0 \left| V \frac{1}{E_0 - H_0} V \right| \psi_0 \right\rangle \quad (10)$$

$$= \sum_{\substack{a \in \mathcal{C}(\mathcal{V}) \\ \notin \mathcal{V}}} \frac{1}{E_0 - E_a} \left( \sum_{ij \in \mathcal{V}} c_j H_{ja} H_{ai} c_i \right), \quad (11)$$

so we can now evaluate the  $H_{ai}$  components semistochastically using importance sampling.

# Semistochastic Epstein-Nesbet Perturbation Theory

- 1 Divide  $V |\psi_0\rangle$  into two pieces:

$$V |\psi_0\rangle = (V |\psi_0\rangle)_{\geq \epsilon} + (V |\psi_0\rangle)_{< \epsilon}. \quad (12)$$

# Semistochastic Epstein-Nesbet Perturbation Theory

- 1 Divide  $V |\psi_0\rangle$  into two pieces:

$$V |\psi_0\rangle = (V |\psi_0\rangle)_{\geq \epsilon} + (V |\psi_0\rangle)_{< \epsilon}. \quad (12)$$

- 2 Estimate  $\Delta E$  deterministically:

$$\Delta E [V |\psi_0\rangle] \approx \Delta E \left[ (V |\psi_0\rangle)_{\geq \epsilon} \right] \quad (13)$$

# Semistochastic Epstein-Nesbet Perturbation Theory

- 1 Divide  $V |\psi_0\rangle$  into two pieces:

$$V |\psi_0\rangle = (V |\psi_0\rangle)_{\geq \epsilon} + (V |\psi_0\rangle)_{< \epsilon}. \quad (12)$$

- 2 Estimate  $\Delta E$  deterministically:

$$\Delta E [V |\psi_0\rangle] \approx \Delta E \left[ (V |\psi_0\rangle)_{\geq \epsilon} \right] \quad (13)$$

- 3 Stochastically evaluate the difference between the exact and approximate  $\Delta E$

# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):

# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):
  - Sample a batch of determinants  $\{D_i\}$  from  $\psi_0$ , compute  $\sum_a H_{ai} c_i$  deterministically for each sampled  $D_i$



# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):
  - Sample a batch of determinants  $\{D_i\}$  from  $\psi_0$ , compute  $\sum_a H_{ai} c_i$  deterministically for each sampled  $D_i$
  - Drawbacks:

# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):
  - Sample a batch of determinants  $\{D_i\}$  from  $\psi_0$ , compute  $\sum_a H_{ai} c_i$  deterministically for each sampled  $D_i$
  - Drawbacks:
    - No importance sampling of  $H$  matrix elements

# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):
  - Sample a batch of determinants  $\{D_i\}$  from  $\psi_0$ , compute  $\sum_a H_{ai} c_i$  deterministically for each sampled  $D_i$
  - Drawbacks:
    - No importance sampling of  $H$  matrix elements
    - Memory-limited because requires computing all determinants  $\{D_a\}$  for which  $H_{ai} \neq 0$

# Sampling algorithm in Epstein-Nesbet PT

How to evaluate the stochastic component?

- Old approach (SHCI):
  - Sample a batch of determinants  $\{D_i\}$  from  $\psi_0$ , compute  $\sum_a H_{ai} c_i$  deterministically for each sampled  $D_i$
  - Drawbacks:
    - No importance sampling of  $H$  matrix elements
    - Memory-limited because requires computing all determinants  $\{D_a\}$  for which  $H_{ai} \neq 0$
    - Wastes time on small-magnitude  $H_{ai}$  elements

# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):

# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):
  - Sample pairs of determinants  $\{D_i, D_a\}$  using importance sampling:

$$P(D_i, D_a) \propto (H_{ai}c_i)^2 \quad (14)$$

# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):
  - Sample pairs of determinants  $\{D_i, D_a\}$  using importance sampling:

$$P(D_i, D_a) \propto (H_{ai}c_i)^2 \quad (14)$$

- Use those samples to evaluate the stochastic component of  $\Delta E$ , whose largest-magnitude component is

$$\sum_{ai} \frac{(H_{ai}c_i)^2}{E_0 - E_a} \quad (15)$$

# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):
  - Sample pairs of determinants  $\{D_i, D_a\}$  using importance sampling:

$$P(D_i, D_a) \propto (H_{ai}c_i)^2 \quad (14)$$

- Use those samples to evaluate the stochastic component of  $\Delta E$ , whose largest-magnitude component is

$$\sum_{ai} \frac{(H_{ai}c_i)^2}{E_0 - E_a} \quad (15)$$

- Advantages:



# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):
  - Sample pairs of determinants  $\{D_i, D_a\}$  using importance sampling:

$$P(D_i, D_a) \propto (H_{ai}c_i)^2 \quad (14)$$

- Use those samples to evaluate the stochastic component of  $\Delta E$ , whose largest-magnitude component is

$$\sum_{ai} \frac{(H_{ai}c_i)^2}{E_0 - E_a} \quad (15)$$

- Advantages:
  - Uses importance sampling to greatly reduce the variance!

# Sampling algorithm in Epstein-Nesbet PT

- New approach (Importance sampling):
  - Sample pairs of determinants  $\{D_i, D_a\}$  using importance sampling:

$$P(D_i, D_a) \propto (H_{ai}c_i)^2 \quad (14)$$

- Use those samples to evaluate the stochastic component of  $\Delta E$ , whose largest-magnitude component is

$$\sum_{ai} \frac{(H_{ai}c_i)^2}{E_0 - E_a} \quad (15)$$

- Advantages:
  - Uses importance sampling to greatly reduce the variance!
  - No time or memory is wasted on deterministically evaluating contributions from small-magnitude  $H_{ai}$  elements!

# FCIQMC Overview

- Power method to project out the Full CI ground state:

$$\psi_0 \propto \lim_{n \rightarrow \infty} (1 - \tau H)^n \psi_T \quad (16)$$

# FCIQMC Overview

- Power method to project out the Full CI ground state:

$$\psi_0 \propto \lim_{n \rightarrow \infty} (1 - \tau H)^n \psi_T \quad (16)$$

- When the Hilbert space is too large, we can simulate each iteration of the power method

$$\psi^{(t)} = (1 - \tau H) \psi^{(t-1)} \quad (17)$$

by applying  $H$  stochastically (or semistochastically)

# FCIQMC Overview

- Power method to project out the Full CI ground state:

$$\psi_0 \propto \lim_{n \rightarrow \infty} (1 - \tau H)^n \psi_T \quad (16)$$

- When the Hilbert space is too large, we can simulate each iteration of the power method

$$\psi^{(t)} = (1 - \tau H) \psi^{(t-1)} \quad (17)$$

by applying  $H$  stochastically (or semistochastically)

- The energy can be estimated using a mixed estimator:

$$E_0 = \frac{\langle \psi_T | H | \psi_0 \rangle}{\langle \psi_T | \psi_0 \rangle}, \quad (18)$$

using a precomputed  $\psi_T$  (e.g. from Selected CI)

# Semistochastic algorithm in FCIQMC

How to perform the semistochastic projection

$$\psi^{(t)} = (1 - \tau H)\psi^{(t-1)}?$$

- Old approach (Semistochastic FCIQMC):

# Semistochastic algorithm in FCIQMC

How to perform the semistochastic projection

$$\psi^{(t)} = (1 - \tau H)\psi^{(t-1)}?$$

- Old approach (Semistochastic FCIQMC):
  - 1 Choose a fixed set of 'important' determinants  $\mathcal{D}$  (e.g., using Selected CI) before the run

# Semistochastic algorithm in FCIQMC

How to perform the semistochastic projection

$$\psi^{(t)} = (1 - \tau H)\psi^{(t-1)}?$$

- Old approach (Semistochastic FCIQMC):
  - 1 Choose a fixed set of 'important' determinants  $\mathcal{D}$  (e.g., using Selected CI) before the run
  - 2 Deterministically apply the diagonal Hamiltonian matrix elements, and the off-diagonal elements between pairs of important determinants



# Semistochastic algorithm in FCIQMC

How to perform the semistochastic projection

$$\psi^{(t)} = (1 - \tau H)\psi^{(t-1)}?$$

- Old approach (Semistochastic FCIQMC):
  - 1 Choose a fixed set of 'important' determinants  $\mathcal{D}$  (e.g., using Selected CI) before the run
  - 2 Deterministically apply the diagonal Hamiltonian matrix elements, and the off-diagonal elements between pairs of important determinants
  - 3 Importance-sample off-diagonal elements, discard the ones that were already treated deterministically

# Semistochastic algorithm in FCIQMC

- New approach (Dynamic, importance-sampled semistochastic FCIQMC):

# Semistochastic algorithm in FCIQMC

- New approach (Dynamic, importance-sampled semistochastic FCIQMC):
  - 1 Apply the Hamiltonian using semistochastic importance sampling to each determinant in  $\psi^{(t)}$

# Semistochastic algorithm in FCIQMC

- New approach (Dynamic, importance-sampled semistochastic FCIQMC):
  - 1 Apply the Hamiltonian using semistochastic importance sampling to each determinant in  $\psi^{(t)}$
- Advantages:

# Semistochastic algorithm in FCIQMC

- New approach (Dynamic, importance-sampled semistochastic FCIQMC):
  - 1 Apply the Hamiltonian using semistochastic importance sampling to each determinant in  $\psi^{(t)}$
- Advantages:
  - Deterministic/stochastic division is dynamic: it depends on the current  $\psi^{(t)}$ , which should greatly reduce the stochastic fluctuations and mitigate the fermion sign problem

# Semistochastic algorithm in FCIQMC

- New approach (Dynamic, importance-sampled semistochastic FCIQMC):
  - 1 Apply the Hamiltonian using semistochastic importance sampling to each determinant in  $\psi^{(t)}$
- Advantages:
  - Deterministic/stochastic division is dynamic: it depends on the current  $\psi^{(t)}$ , which should greatly reduce the stochastic fluctuations and mitigate the fermion sign problem
  - Directly samples the off-diagonal  $H$  elements that were not treated deterministically, which should greatly reduce the computational time