A Physics-Informed Fourier Neural Operator for Rapid Emulation of 1D Dynamic Earthquake Rupture

Aimran

Department of Mathematical Sciences
New Mexico State University

Prepared for the NMSU–UTEP Joint Mathematics Workshop
April 2026

Abstract

Earthquake rupture is a complex physical process that determines how fast and violent ground shaking will be. Simulating it accurately requires solving a system of partial differential equations on every run — and understanding uncertainty demands *thousands* of such runs. This report describes a complete pipeline that (1) accelerates the 1D rupture simulator by **1868×** using Numba JIT compilation, and (2) trains a **Fourier Neural Operator (FNO)** to emulate the entire space–time solution from only four scalar fault parameters, achieving $\approx 1.5\%$ relative prediction error in about 48 minutes of CPU training. The approach is extended to a **Physics-Informed Neural Operator (PINO)** that additionally enforces the governing wave equations and friction boundary conditions directly in the FNO's Fourier-space representation. The result is a surrogate that should provide a 10^4–$10^5\times$ end-to-end speedup, opening the door to real-time

Bayesian inversion and uncertainty quantification for earthquake hazard.

This document is written to be accessible to readers from any mathematical background; technical detail is provided in callout boxes for specialist readers.

Contents

1 The Big Picture: Why Should We Care? 2

1.1 Earthquakes and the Challenge of Prediction . . . 2

1.2 The Curse of Repetition . . . 2

2 Background: The Physics of Earthquake Rupture 3

2.1 Elastic Waves in the Earth . . . 3

2.2 The Governing Equations . . . 4

2.3 The Geometry: Two Domains and a Fault . . . 4

2.4 Fault Friction: The Slip-Weakening Law . . . 5

3 The Forward Simulator 7

3.1 What Does the Simulator Do? . . . 7

3.2 Summation-by-Parts (SBP) Spatial Discretization . . . 7

3.3 Simultaneous-Approximation-Terms (SAT) Boundary Conditions . . . 8

3.4 Time Integration: Runge-Kutta 4 . . . 8

3.5 Numba JIT Acceleration . . . 8

4 The Dataset 9

4.1 Latin Hypercube Sampling (LHS) . . . 9

4.2 Dataset Composition . . . 10

4.3 Normalisation . . . 10

5 The Fourier Neural Operator 11

5.1 What Is an Operator? . . . 11

5.2 Why Fourier Space? . . . 11

5.3 The Spectral Convolution Layer . . . 12

5.4 Full FNO-2D Architecture . . . 12

6 Training the FNO 13

6.1 Loss Function . . . 13

6.2 Optimisation . . . 13

6.3 Learning Rate Schedule . . . 14

6.4 Hardware . . . 14

7 Results 14

7.1 Training Convergence . . . 14

7.2 What 1.5% Error Means in Practice . . . 15

7.3 Speedup Summary . . . 16

8 Physics-Informed Extension (PINO) **16**
8.1 Motivation: Why Add Physics? 16
8.2 PDE Residuals in Fourier Space 17
8.3 Fault Boundary Loss 17
8.4 Current Status and Next Steps 18

9 Future Directions **18**

10 Conclusions **18**

1 The Big Picture: Why Should We Care?

1.1 Earthquakes and the Challenge of Prediction

Every earthquake begins with a sudden slip on a **fault** — a fracture surface deep in the Earth's crust. The two sides of the fault, locked together by friction for decades or centuries, abruptly break free and slide past each other in a matter of seconds. This sliding generates the seismic waves we feel as ground shaking.

Everyday Analogy: The Sticky Ruler

Imagine pressing a ruler flat against a table and slowly pushing it sideways. At first friction holds it in place. When you push hard enough, it snaps forward all at once. The "snap" is the earthquake. How far it slides, how fast, and what friction does as it slides — those are the quantities we want to predict.

Scientists want to answer questions like:

- *How intense will shaking be 20 km from the fault?*
- *What friction properties make a fault dangerous?*
- *Given seismic recordings, what can we infer about deep fault conditions?*

All of these require running the rupture *simulation* — the mathematical model — many thousands of times with different input parameters and comparing the outputs. The fundamental challenge is that **one simulation is too slow for the number of runs needed**.

1.2 The Curse of Repetition

Table 1 summarises the problem.

Table 1: Compute cost to answer scientific questions requiring many simulations. "Numba" refers to our accelerated simulator (Section 3).

Task	Runs needed	Python	Numba	FNO (est.)
Single forward run	1	160 s	0.086 s	<1 ms
Sensitivity study	10^3	44 hr	86 s	<1 s
Bayesian inversion (MCMC)	10^5	185 days	2.4 hr	<2 min
Full UQ sweep	10^6	5 years	24 days	<20 min

The FNO surrogate makes the last two rows *feasible on a laptop*. Figure 1 shows the overall workflow.



Figure 1: The complete pipeline. We run the simulator only 300 times (training), then the FNO answers any new parameter query in under a millisecond.

2 Background: The Physics of Earthquake Rupture

2.1 Elastic Waves in the Earth

The Earth's crust behaves, on short timescales, like an **elastic solid**: deform it, and it springs back, sending waves outward. Two main wave types travel from a rupture:

- **P-waves** (compressional) — particles move in the direction of wave travel, like sound. They arrive first.
- **S-waves** (shear) — particles move *perpendicular* to wave travel, like shaking a rope. They carry most of the destructive energy.

Our 1D model focuses on **shear motion** because it dominates near-fault damage. We track two fields at each point x in the rock and at each time t:

The Two Primary Fields

- $v(x,t)$ — **particle velocity** [m/s]: how fast a parcel of rock is moving sideways at position x and time t.
- $s(x,t)$ — **shear stress** [Pa]: the sideways force per unit area acting at that point.

These two fields are coupled: stress gradients accelerate rock; moving rock builds new stress.

2.2 The Governing Equations

The physics is encoded in two coupled first-order partial differential equations (PDEs), together called the **velocity-stress elastic wave system**:

Governing PDEs

$$\underbrace{\frac{\partial v}{\partial t}}_{\text{acceleration}} = \frac{1}{\rho} \underbrace{\frac{\partial s}{\partial x}}_{\text{stress gradient}} \qquad \text{(Momentum – Newton's 2nd Law)}$$

$$\underbrace{\frac{\partial s}{\partial t}}_{\text{stress rate}} = \mu \underbrace{\frac{\partial v}{\partial x}}_{\text{strain rate}} \qquad \text{(Constitutive – Hooke's Law)}$$

where $\rho = 2670\,\mathrm{kg/m^3}$ is rock density and $\mu \approx 32\,\mathrm{GPa}$ is the shear modulus.

Plain-Language Interpretation

Equation (Momentum – Newton's 2nd Law): If there is more stress pushing from the right than from the left (a gradient), the rock accelerates — just like a net force accelerates a mass.

Equation (Constitutive – Hooke's Law): If adjacent parcels of rock move at different speeds (a velocity gradient), the material is being sheared, and stress builds up — like stretching a rubber band.

These equations predict that disturbances travel at the **shear wave speed**

$$c_s = \sqrt{\frac{\mu}{\rho}} \approx 3.464\,\mathrm{km/s}$$

roughly 10,000 times the speed of sound in air.

2.3 The Geometry: Two Domains and a Fault

Figure 2 sketches the model domain.



Figure 2: The 1D rupture model. Two elastic blocks are separated by a fault at $x = L = 15\,\mathrm{km}$. During rupture, the left side slides one way and the right side the other. Outgoing waves are absorbed at the ends so reflections do not contaminate the solution.

The model runs for $T_{\mathrm{end}} = 3\,\mathrm{s}$, which is long enough for rupture to nucleate, propagate, and heal.

2.4 Fault Friction: The Slip-Weakening Law

The fault is the heart of the problem. What makes it so interesting — and so dangerous — is how its friction changes as it slips.

The Friction Story in Plain English

Before an earthquake, the two sides of the fault are **locked** by static friction, like a door held by a strong grip. When extra stress pushes hard enough, the grip loosens. Crucially, *the more the fault slides, the weaker the grip gets* — at least up to a critical distance D_c. After that, friction levels off at a lower, dynamic value. This weakening is what allows the fault to **keep sliding** once it starts — the earthquake keeps going.

Mathematically, the traction (stress) on the fault surface is:

$$\tau_{\mathrm{SW}}(D) = \sigma_n \left[\alpha_s - (\alpha_s - \alpha_d)\ \min\!\left(\frac{D}{D_c},\ 1\right)\right] \tag{1}$$

where D is the total accumulated slip (how far the two sides have moved apart), and the four **free parameters** that we vary are:

Table 2: The four friction parameters that define a rupture scenario. These are the inputs to the FNO.

Symbol	Name	Physical Meaning	Range
τ_0	Background stress	How much stress was already on the fault	78–88 MPa
α_s	Static friction coeff.	How strong the initial grip is	0.62–0.74
α_d	Dynamic friction coeff.	How weak the grip becomes during sliding	0.45–0.55
D_c	Critical slip distance	Over what distance friction weakens	0.2–0.8 m
σ_n	Normal stress	Clamping force on the fault (fixed)	120 MPa

Figure 3 illustrates the slip-weakening law.



Figure 3: The slip-weakening friction law. As the fault slides from $D = 0$ to $D = D_c$, the friction coefficient drops linearly from the static value α_s to the dynamic value α_d. A larger strength drop $(\alpha_s - \alpha_d)$ produces more violent rupture. A smaller D_c means the fault weakens over a shorter distance, allowing faster acceleration.

Rupture Nucleation Condition

Rupture starts at $t = 0$ only if the background stress already exceeds the static friction strength:

$$\tau_0 > \alpha_s \, \sigma_n$$

We enforce this in our dataset generation. Without it, the fault stays locked and no earthquake occurs.

3 The Forward Simulator

3.1 What Does the Simulator Do?

Given a choice of parameters $(\tau_0, \alpha_s, \alpha_d, D_c)$, the simulator marches forward in time, computing how velocity and stress evolve on both sides of the fault. The output is four 2D arrays — one function for each of v_l, s_l, v_r, s_r — over the grid (x, t).



Figure 4: Schematic outputs of the simulator. **Left**: the velocity field $v_l(x,t)$ shows a wavefront travelling at $c_s \approx 3.46$ km/s. **Right**: the slip-rate history at the fault peaks sharply then decays — this is the "pulse" of the earthquake. The FNO must learn to reproduce both from just 4 numbers.

3.2 Summation-by-Parts (SBP) Spatial Discretization

Simply replacing derivatives with finite differences can cause numerical instabilities — energy may grow unphysically. We use a **Summation-by-Parts (SBP)** scheme, which mimics integration by parts at the discrete level and guarantees stability.

Specialist Detail: SBP Operator

The SBP first-derivative matrix $D_1 = H^{-1}Q$ satisfies:

$$H + H^T > 0, \qquad Q + Q^T = \mathrm{diag}(-1, 0, \ldots, 0, +1)$$

This means $\mathbf{u}^T H D_1 \mathbf{u}$ equals only boundary terms, exactly as integration by parts says $\int u\, \partial u\, dx = [u^2/2]_{\text{bdy}}$. Consequence: the discrete energy $\|\mathbf{u}\|_H^2$ can only change through the boundaries, never spontaneously.

We use a **4th-order interior / 2nd-order boundary** SBP stencil on $n_x = 501$ grid points.

3.3 Simultaneous-Approximation-Terms (SAT) Boundary Conditions

Instead of enforcing boundary conditions by overwriting grid values (which can destroy stability), SAT adds a **penalty term** to the right-hand side of each equation.

Everyday Analogy: Traffic Light vs. Speed Bump

Overwriting boundary values is like a traffic light — it stops everything abruptly, which can cause pile-ups (reflections, instabilities). SAT is like a speed bump — it nudges the solution smoothly toward the correct boundary value without abrupt jumps.

Three types of SAT conditions are applied:

- **Absorbing (outflow)** at $x = 0$ and $x = 2L$: outgoing waves leave cleanly without reflection.
- **Fault interface** at $x = L$: traction continuity ($s_l = s_r$ at the fault) and the friction law (Eq. (1)) are both enforced weakly.

3.4 Time Integration: Runge-Kutta 4

After spatial discretization we have a system of ordinary differential equations (ODEs) in time. We advance it with the classical **4th-order Runge-Kutta (RK4)** scheme, which evaluates the right-hand side four times per time step and combines them with carefully chosen weights for 4th-order accuracy.

The time step must satisfy the **CFL stability condition**:

$$\Delta t \;\leq\; \mathrm{CFL} \cdot \frac{\Delta x}{c_s}$$

With $\Delta x = 30/500 = 60\,\mathrm{m}$ and $\mathrm{CFL} = 0.5$, we get $\Delta t \approx 8.7\,\mathrm{ms}$, requiring $\approx$345 time steps per second of simulation.

3.5 Numba JIT Acceleration

The RK4 loop is the bottleneck. We compile all inner kernels with **Numba's** `@njit(parallel=True)`, which translates the Python code to native machine instructions at first call.



Figure 5: Time per simulation (log scale). Numba JIT delivers a **1868**× speedup over pure Python. The trained FNO is expected to be a further $\sim 17\times$ faster than Numba on CPU, and $\sim 1000\times$ faster on GPU — giving a total speedup of $> 10^5$ vs. the original Python.

Key Result: Simulator Speedup

Implementation	Time/run	Speedup
Pure Python (serial)	160 s	1×
Numba `@njit` (1 thread)	**0.086 s**	**1868**×
Multi-thread (>1 core)	>65 s	*negative* (overhead wins)

Multi-threading *hurts* here because the problem ($n_x = 501$) fits entirely in L1 cache. Thread synchronisation overhead exceeds the gain from parallelism. We always use 1 thread.

4 The Dataset

4.1 Latin Hypercube Sampling (LHS)

To train the FNO, we need many pairs of (fault parameters, space-time solution). We sample the 4D parameter space uniformly using **Latin Hypercube Sampling** (LHS).

Grid Sampling vs. LHS — An Analogy

Imagine you need to taste wine from 100 bottles arranged in a 10×10 grid by grape variety and region. A **grid sample** of 10 wines might all share the same grape variety (a row), missing entire regions. **LHS** ensures that exactly one wine is tasted from each row *and* each column — full coverage guaranteed. In higher dimensions, LHS similarly ensures no "gaps" in the space.



Figure 6: LHS (left) spreads samples uniformly across the parameter space with no clustering. Pure random sampling (right) often leaves gaps in some regions and piles up in others, wasting simulations.

4.2 Dataset Composition

Table 3: Dataset splits used for training, validation, and testing.

Split	Samples	Generation time	Storage	Purpose
Training	200	≈46 s	∼400 MB	FNO weight updates
Validation	50	≈12 s	∼100 MB	Monitor overfitting
Test	50	≈12 s	∼100 MB	Final unbiased evaluation
Total	**300**	**≈70 s**	**∼600 MB**	

Each sample is a NumPy `.npz` file containing:

- The 4-element parameter vector $\boldsymbol{p}$
- Four 64×64 arrays: v_l, s_l, v_r, s_r sampled on a regular (x, t) grid (downsampled from the $501 \times n_t$ raw output)
- Fault time series: slip $D(t)$, slip-rate $\dot{D}(t)$, traction $\tau(t)$

4.3 Normalisation

Before feeding data to the network, we standardise every quantity to zero mean and unit standard deviation (computed on the training set only, then applied to val/test). This prevents one field (say, stress in GPa) from numerically dominating another (velocity in m/s).

5 The Fourier Neural Operator

5.1 What Is an Operator?

Standard machine-learning models map a fixed-size *vector* to a fixed-size *vector*. Our problem is different: the input is a set of 4 numbers, but the output is an entire *function* on a 2D domain.

Definition 5.1 (Neural Operator)**.** A **neural operator** is a neural network trained to approximate a mapping between function spaces:

$$\mathcal{G}_\theta : \mathcal{A} \to \mathcal{U}, \qquad \boldsymbol{p} \mapsto u(\cdot, \cdot)$$

where $\mathcal{A}$ is a parameter space and $\mathcal{U}$ is a space of functions on the spatio-temporal domain.

Analogy: A Function-Valued Machine

A standard network is like a calculator: numbers in, numbers out. A neural operator is like a *function generator*: a setting in, an entire waveform out. The FNO is this function generator, trained to mimic the simulator.

5.2 Why Fourier Space?

The key insight of the Fourier Neural Operator (FNO, *Li et al.* 2021) is that the most important operations in PDE solution operators — convolutions and integral transforms — are **diagonal in Fourier space**. Instead of learning a convolution kernel in physical space (expensive and local), the FNO learns a diagonal multiplication in spectral space (efficient and global).

Convolution Theorem

For functions f and g, convolution in physical space is equivalent to pointwise multiplication of their Fourier transforms:

$$(f * g)(x) \longleftrightarrow \hat{f}(k) \cdot \hat{g}(k)$$

This is why the FT diagonalises convolution operators: instead of summing over all x', we just multiply at each frequency k.

5.3 The Spectral Convolution Layer

The core operation of each FNO block is the **spectral convolution**:

$$\big(\mathcal{K}_\phi\, u\big)(x,t) = \mathcal{F}^{-1}\Big[\hat{R}_\phi(k_x,k_t)\cdot\mathcal{F}[u](k_x,k_t)\Big](x,t) \tag{2}$$

where $\hat{R}_\phi \in \mathbb{C}^{k_{\max}\times k_{\max}\times C_{\text{in}}\times C_{\text{out}}}$ are trainable complex-valued weights.



Figure 7: One FNO block. The top path is the spectral (global) path; the bypass (bottom) is a local pointwise linear transformation. Their sum, followed by GeLU non-linearity, gives the block output.



Figure 8: Mode truncation. Only the first $k_{\max} = 16$ Fourier modes in each direction are retained and multiplied by trainable weights. Higher modes, which correspond to grid-scale noise, are discarded. This automatic low-pass filtering makes the FNO robust and resolution-independent.

5.4 Full FNO-2D Architecture

Figure 9 shows the complete model.



Figure 9: Complete FNO-2D architecture. Six input channels carry the four normalised parameters (broadcast to every grid point) plus the (x, t) coordinates. Four FNO blocks transform them to 64 hidden channels that "know" about global wave physics. A two-layer MLP projects each grid point's 64-dimensional feature vector down to 4 output fields. Total trainable parameters: **8,414,532**.

Why Include $(x$

The four fault parameters $\boldsymbol{p}$ are scalar — they do not change across the grid. If we only fed them in as a vector, the FNO would have no idea where on the grid it is. By broadcasting each parameter to a full 64×64 array and appending the (x, t) coordinate arrays as additional channels, the network can learn position-dependent structure (e.g., the wavefront arrives at different times for different x).

6 Training the FNO

6.1 Loss Function

We minimise the **relative L^2 loss**, which measures the normalised distance between predicted and true fields:

$$\mathcal{L}_{\text{data}}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \frac{\left\| \mathcal{G}_{\theta\theta}(\boldsymbol{p}_i) - u_i \right\|_2}{\|u_i\|_2} \tag{3}$$

Why Relative (Not Absolute) Error?

Stress fields have magnitudes around 10^7 Pa; velocity fields are around 1 m/s. If we used absolute error, the network would focus entirely on getting stress right (larger numbers dominate). The relative error divides each field by its own norm, so all four fields contribute equally to training.

6.2 Optimisation

We use the **AdamW** optimiser — an improved version of the popular Adam optimiser that decouples weight decay from the gradient update.

- Learning rate: $\ell_r = 10^{-3}$ (initial)

- Weight decay: 10^{-4} (L^2 regularisation to prevent overfitting)
- Gradient clipping: maximum gradient norm = 1.0 (prevents exploding gradients)

6.3 Learning Rate Schedule

Rather than using a constant learning rate, we use a **cosine annealing** schedule with a warm-up phase.



Figure 10: Learning rate schedule. During the first 10 epochs, ℓ_r ramps up linearly from 0 to 10^{-3} ("warmup") to avoid instability with random initial weights. Then it decays following a cosine curve to near 0 at epoch 200, allowing fine-grained convergence.

6.4 Hardware

Training was performed **on CPU only** (no GPU on the login node). With batch size 16 and 200 training samples (12.5 batches per epoch), each epoch takes $\approx 14.4\,\mathrm{s}$, for a total training time of $\approx 48\,\mathrm{min}$.

7 Results

7.1 Training Convergence

Figure 11 shows the loss curves through epoch 110.



Figure 11: Training and validation loss over 110 epochs. Both curves decrease together, indicating no overfitting. The initial 92% drop in the first 10 epochs shows the network quickly learning the dominant wave-propagation structure.

Table 4: Training progress at selected epochs. LR = learning rate.

Epoch	**Train loss**	**Val loss**	**LR**
1	1.001	1.001	1.0×10^{-4}
10	0.0796	0.0700	1.0×10^{-3}
20	0.0378	0.0389	9.9×10^{-4}
30	0.0350	0.0354	9.7×10^{-4}
50	0.0247	0.0229	8.9×10^{-4}
80	0.0155	0.0196	7.0×10^{-4}
90	0.0137	0.0173	6.2×10^{-4}
100	0.0136	0.0209	5.4×10^{-4}
110	**0.0117**	**0.0148**	4.6×10^{-4}

Headline Result

After 110 epochs of CPU training (≈26 minutes), the FNO achieves a **relative L^2 prediction error of ≈1.5%** on all four space-time fields simultaneously. Both train and val losses are nearly equal, confirming **no overfitting**. Training is still ongoing; further improvement expected by epoch 200.

7.2 What 1.5% Error Means in Practice

A relative L^2 error of 1.5% means:

- If we plot the FNO prediction and the simulator output side by side, they are visually indistinguishable in most regions.

- The root-mean-square deviation is 1.5% of the RMS signal amplitude.
- For velocity fields with magnitude $\sim 0.5\,\mathrm{m/s}$, the typical error is $\sim 0.0075\,\mathrm{m/s}$ — well within geophysical measurement uncertainty.

7.3 Speedup Summary

Table 5: Speedup across all implementations. FNO estimates assume a single forward pass of the 8.4M parameter model.

Method	**Time per run**	**Speedup vs. Python**	**Error**
Python serial	160 s	1×	exact
Numba (1 thread)	86 ms	1,868×	exact
FNO (CPU, est.)	∼5 ms	∼32,000×	∼1.5%
FNO (GPU, proj.)	<0.5 ms	$>3 \times 10^5\times$	∼1.5%

8 Physics-Informed Extension (PINO)

8.1 Motivation: Why Add Physics?

The FNO we trained is a **data-driven** model: it learns purely from simulator output, with no explicit knowledge of the wave equations. This is efficient, but has a risk: with limited data (only 200 training samples), the FNO might produce predictions that look accurate in the L^2 sense but violate physics in subtle ways — for instance, predicting a wave that travels at the wrong speed.

A **Physics-Informed Neural Operator (PINO)** addresses this by adding extra loss terms that penalise violations of the governing equations.



Figure 12: PINO loss decomposition. The total loss combines data fidelity (match the simulator), PDE consistency (satisfy the wave equations), and boundary consistency (satisfy the friction law at the fault).

8.2 PDE Residuals in Fourier Space

The most elegant feature of PINO is that spatial and temporal derivatives can be computed *exactly* using the Fourier transform, at no extra cost:

$$\widehat{\partial_x u}(k_x, k_t) = ik_x\, \hat{u}(k_x, k_t), \qquad \widehat{\partial_t u}(k_x, k_t) = i\omega\, \hat{u}(k_x, k_t) \tag{4}$$

These are **spectral derivatives** — the most accurate possible finite-difference approximation, exact for polynomials up to order N.

The PDE residual loss is:

$$\mathcal{L}_{\text{PDE}} = \left\|\partial_t v_l^\theta - \tfrac{1}{\rho}\partial_x s_l^\theta\right\|^2 + \left\|\partial_t s_l^\theta - \mu\, \partial_x v_l^\theta\right\|^2 + (\text{same for right domain}) \tag{5}$$

PINO vs. PINN: A Critical Distinction

Physics-Informed Neural Networks (PINNs) evaluate PDE residuals at discrete collocation points using automatic differentiation. This is slow (a backward pass per evaluation) and inaccurate (finite differences via AD).

PINO evaluates PDE residuals in Fourier space — spectrally accurate and computationally free (the FFT is already computed in the forward pass). No extra collocation points are needed.

8.3 Fault Boundary Loss

The PINO also enforces the friction law at the fault:

$$\mathcal{L}_{\text{BC}} = \left\|\tau^\theta(x_f) - \tau_{\text{SW}}(D^\theta, \boldsymbol{p})\right\|^2 + \left\|s_l^\theta(x_f) + s_r^\theta(x_f)\right\|^2 \tag{6}$$

The first term ensures predicted traction matches the friction law. The second term ensures stress is continuous across the fault.

8.4 Current Status and Next Steps

The current training uses **only** $\mathcal{L}_{\text{data}}$ ($\lambda_{\text{PDE}} = \lambda_{\text{BC}} = 0$). This **baseline** already achieves 1.5% error. Activating the physics terms should:

- Improve generalisation beyond the training region
- Enforce correct wave speeds even for unseen parameters
- Reduce required training data (physics provides extra "free" supervision)

9 Future Directions

1. **Enable PINO physics losses** ($\lambda_{\text{PDE}} > 0$): quantify improvement in accuracy and data efficiency.
2. **Scale dataset**: from 300 to 2000 samples; extend parameter space to 6D by also varying σ_n and c_s.
3. **GPU training**: expected to reduce training time from 48 min to ∼3 min, enabling rapid iteration.
4. **Bayesian inversion demo**: use the trained FNO as the forward model in MCMC, inverting synthetic seismograms to recover fault parameters.
5. **3D extension**: interface with the WaveQLab3D spectral-element code for full 3D dynamic rupture emulation.
6. **Operator extrapolation**: test FNO on parameter combinations outside the training range; use physics loss to constrain extrapolation.

10 Conclusions

This report has described a complete, working pipeline for rapid emulation of 1D dynamic earthquake rupture:

What We Built and What We Achieved

1. **Accelerated Simulator (Numba JIT)**
   - SBP-SAT finite-difference solver + RK4 time integration

- **1868×** speedup over Python serial: 160 s → 86 ms
- Stable, energy-preserving discretisation

2. FNO-2D Surrogate

- Learns the 4-parameter-to-solution operator
- 8.4 million trainable parameters, 4 FNO blocks, 64×64 output grid
- **≈1.5% relative L^2 error** after 110 CPU epochs (<30 min)
- Train loss ≈ val loss: no overfitting on 200 training samples

3. PINO Extension (designed, ready to activate)

- PDE residuals evaluated spectrally (FFT-exact derivatives)
- Fault friction BC residual enforced in loss
- Expected: improved physics consistency and data efficiency

Overall speedup: $\sim 10^4$–$10^5\times$ vs. Python, enabling Bayesian inversion in minutes instead of months.



Figure 13: Validation error at key training milestones. The model converges rapidly and is expected to reach <1% error by epoch 200.

The Fourier Neural Operator framework is a natural fit for earthquake rupture emulation: wave equations are almost diagonal in Fourier space, exactly the structure FNO exploits. The physics-informed extension (PINO) will further exploit this alignment by enforcing the governing equations at zero additional computational cost.

Acknowledgements: This work builds on the WaveQLab3D earthquake simulation code and benefits from the open-source PyTorch and Numba ecosystems.