

Team notebook

22 de agosto de 2015

Índice			
1. Articulation Point in Graph	2	17.Fast Integer Input	9
2. Bellman Ford	2	18.FasterSieve	9
3. Binomial Coefficient with DP	3	19.Fenwick Tree 2D	9
4. Binomial Coefficient	3	20.Fenwick Tree	10
5. Bipartite Check Algorithm	3	21.Fibonnaci - Fast Doubling	11
6. Catalan	4	22.Floyd Warshall	11
7. Closest Pair	4	23.Fraction Library	11
8. Coin Change	5	24.GCD LCM	12
9. Convex Hull	5	25.Heap Sort	12
10.Convex Polygon Area	6	26.Heavy Light Decomposition	12
11.Count used Digits	6	27.Highly Decomposite Number	15
12.Cycle Retrieval Algorithm	6	28.Kadane 2D	16
13.Dijkstra Algorithm	7	29.Knuth Morris Pratt	16
14.Dinic Algorithm	7	30.Kosaraju Algorithm	17
15.Euler Phi Function	8	31.Kruskal Algorithm	17
16.Extended GCD	9	32.LCA with Segment Tree	17
		33.LCA with Sparse Table	18

34.Line Point Distance	19	57.Sliding Window RMQ	30
35.Longest Common Subsequence - Efficient	20	58.Smallest Inclusive String	30
36.Longest Common Subsequence	20	59.Splay Tree	30
37.Longest Increasing Subsequence $O(n^2)$	20	60.Stoer Wagner Algorithm	32
38.Manacher Algorithm	21	61.String Edit Distance	33
39.Mathematical Expression Solver	21	62.String Period	33
40.Matrix Multiplication	22	63.Subset Sum	33
41.Maximum Bipartite Matching	22	64.Suffix Array	33
42.Median Online Algorithm	23	65.Topological Sort - Iterative	35
43.Merge Sort	23	66.Topological Sort - Recursive	35
44.Min Cost Max Flow	24	67.TriangleArea	35
45.Mod Pow	25	68.Trie	35
46.Modular Inverse for Primes	25	69.Union Find	36
47.N-th Palindrome Number	25	70.Z Function	36
48.Next Permutation in Java	25		
49.Order Statistics Tree - STL	26		
50.Palindromic Check with DP	26		
51.Prim Algorithm	26		
52.QuickSort	26		
53.Segment Tree - Lazy Propagation	27		
54.Segment Tree 2D	27		
55.Sieve	29		
56.Sliding Window RMQ Faster	29		

1. Articulation Point in Graph

```

vector<int> graph[410];
set<int> ans;
set<int>::iterator it;

int dfs(int u){
    int less = vis[u] = times++;
    int filhos = 0;
    for(int i = 0; i< graph[u].size(); i++){
        if(vis[graph[u][i]]==0){
            filhos++;
            int m = dfs(graph[u][i]);
            less = min(less,m);
            if(vis[u] <= m && (u != 0 || filhos >= 2)){

```

```

        ans.insert(u);
    }
    }else{
        less = min(less, vis[graph[u][i]]);
    }
}
return less;
}
times = 1;
ans.clear();
dfs(0);

```

2. Bellman Ford

```

vector <pair<int, int> > edges;
int graph[MAXN][MAXN];
int dist[MAXN];

int N;
bool bellman_ford(int s) {
    int M = edges.size();
    memset (dist, INF, sizeof(int)*n);
    dist[s] = 0;
    for (int k = 0; k < N-1; ++k) {
        for (int j = 0; j < M; ++j) {
            int u = edges[j].first;
            int v = edges[j].second;
            if (dist[u] < INF && dist[v] > dist[u] +
                graph[u][v])
                dist[v] = dist[u] + graph[u][v];
        }
    }
    //Negative Cycle
    for (int j = 0; j < m; ++j) {
        int u = edges[j].first, v = edges[j].second;
        if (dist[u] < INF && dist[v] > dist[u] + graph[u][v]) {
            return false;
        }
    }
    return true;
}

```

3. Binomial Coefficient with DP

```

//Binomial Coefficient
//C(N, K) = N!/(K!(N - K)!)
//Dynamic Programming
int bin[N][K];

bin[0][0] = 1;

for (int n = 1; n < MAXN; n++) {
    bin[n][0] = 1;
    bin[n][n] = 1;

    for (int k = 1; k < n; k++) {
        bin[n][k] = bin[n - 1][k] + bin[n - 1][k - 1];
        if (bin[n][k] >= MOD) {
            bin[n][k] -= MOD;
        }
    }
}

```

4. Binomial Coefficient

```

Int nCr(Int n, Int k) {
    Int res = 1;

    if (k > (n >> 1LL)) {
        k = n-k;
    }
    for (Int i = 1; i <= k; i++, n--) {
        res = (res * n) / i;
    }

    return res;
}

```

5. Bipartite Check Algorithm

```

bool dfs(int node, int c) {

```

```

if(color[node] != 0) {
    if(color[node] == c) {
        return true;
    } else {
        return false;
    }
}
color[node] = c;
for(int i = 1; i <= n; i++)
    if(gr[node][i] == 1) {
        if(!dfs(i, -c)) {
            return false;
        }
    }
}
return true;
}

```

6. Catalan

```

//Catalan numbers with DP
void getCatalan(int n){
    int catalan[n+1];
    int MOD = 1000000000;
    for (int i=0; i <= n; i++){
        if (i==0 || i==1){
            catalan[i] = 1;
        }else{
            int sum =0;
            int l, r;
            for (int k=1;k<=i;k++){
                l = catalan[k-1] % MOD;
                r = catalan[i-k] % MOD;
                sum = (sum + (l * r) % MOD) % MOD;
            }
            catalan[i] = sum;
        }
    }
}

//Preprocessing Factorial numbers and Answer in O(1)
int catalan(int N) {
    int ans = fat[2 * N];

```

```

    int p = ((fat[N] * fat[N + 1]) % MOD) % MOD;
    ans *= modpow(p, MOD - 2, MOD);

    ans = ((ans % MOD) + MOD) % MOD;

    return ans;
}

```

7. Closest Pair

```

//-----Closes pair with divide and conquer-----//
struct point{
    double x, y;
    point(double a, double b): x(a), y(b){}
    point(){};
};

bool compareX(point a, point b){
    return a.x < b.x;
}

bool compareY(point a, point b){
    return a.y < b.y;
}

double bruteForce(vector<point> &p){
    double ans = 40000.*40001.;
    for(int i = 0; i < p.size(); i++){
        for(int j = i + 1; j < p.size(); j++){
            double dst = hypot(p[j].x - p[i].x, p[j].y - p[i].y);
            if(dst < ans){
                ans = dst;
            }
        }
    }
    return ans;
}

double strip(vector<point> &p, double d){
    sort(p.begin(), p.end(), compareY);
    double ans = d;
    for(int i = 0; i < p.size(); i++){

```

```

        for(int j = i + 1; j < p.size() && (p[j].y - p[i].y) < d; j++){
            double dst = hypot(p[j].x - p[i].x, p[j].y - p[i].y);
            if(dst < ans){
                ans = dst;
            }
        }
    }
    return ans;
}

double X, Y;
int n;
double closest(vector<point> v){
    int n = v.size();
    if(n <= 3){
        return bruteForce(v);
    }
    vector<point> left;
    vector<point> right;
    int mid = n >> 1;
    for(int i = 0; i < mid; i++){
        left.push_back(v[i]);
    }
    for(int i = mid; i < n; i++){
        right.push_back(v[i]);
    }

    double lh = closest(left);
    double rh = closest(right);
    double d = min(lh, rh);
    vector<point> stripArray;
    for(int i = 0; i < n; i++){
        if(fabs(v[i].x - v[mid].x) < d){
            stripArray.push_back(v[i]);
        }
    }
    return min(d, strip(stripArray, d));
}

sort(pos.begin(), pos.begin()+n, compareX);
double ans = closest(pos);

```

8. Coin Change

```

//Coin Change
int dp[1001];
int coins[] = {1, 5, 10, 25, 50};

dp[0] = 0;

for(int i = 1; i <= N; i++) {
    int min = 1000001;
    for(int j = 0; j < M; j++) {
        if(coins[j] <= i) {
            int m = dp[i - coins[j]] + 1;
            if(m < min) min = m;
        }
    }
    dp[i] = min;
}

```

9. Convex Hull

```

//Convex Hull
struct point {
    int x, y;
    point(int x, int y): x(x), y(y){}
    point(){}
    bool operator <(const point &p) const {
        return x < p.x || (x == p.x && y < p.y);
    }
    bool operator==(const point &p) const {
        return x == p.x && y == p.y;
    }
};

ll cross(const point &O, const point &A, const point &B) {
    return (A.x - O.x) * (B.y - O.y) - (A.y - O.y) * (B.x - O.x);
}

vector<point> convex_hull(vector<point> &P) {
    int n = P.size(), k = 0;
    vector<point> H(2*n);

    sort(P.begin(), P.end());

```

```

for (int i = 0; i < n; i++) {
    while (k >= 2 && cross(H[k-2], H[k-1], P[i]) <= /*change to < to
        remove equal points */ 0) k--;
    H[k++] = P[i];
}
for (int i = n-2, t = k+1; i >= 0; i--) {
    while (k >= t && cross(H[k-2], H[k-1], P[i]) <= /*change to < to
        remove equal points */ 0) k--;
    H[k++] = P[i];
}
H.resize(k);
return H;
}

```

10. Convex Polygon Area

```

//Area de um Poligono Convexo
double area() {
    int N = 4;

    //Points
    int[] x = { 2, -4, 5, 2 };
    int[] y = { 5, 3, 1, 5 };

    double ma = x[N - 1] * y[0], mb = x[0] * y[N - 1];

    for (int i = 0; i < N - 1; i++) {
        ma += (x[i] * y[i + 1]);
        mb += (x[i + 1] * y[i]);
    }

    double ans = Math.abs((ma - mb) * 0.5);
}

```

11. Count used Digits

```

Int func(int val) {
    int digitCount = (int) log10(val) + 1;
}

```

```

Int ans = 0LL;
Int p = 1LL;

for (int i = 0; i < digitCount - 1; i++) {
    ans += p * 9 * (i + 1);
    p *= 10;
}

ans += (val - p + 1) * digitCount;

return ans;
}

```

12. Cycle Retrieval Algorithm

```

//It only works in graphs without compound cycles
bool inq[MAXN], vis[MAXN];

void dfs(int node, int parent, int len) {
    vis[node] = true;
    cle[node] = len;

    stk[stk_pointer++] = node;
    inq[node] = true;

    for (int i = 0; i < (int) graph[node].size(); i++) {
        int next = graph[node][i].first;
        int cost = graph[node][i].second;

        if (next == parent) continue;

        if (!vis[next]) {
            dfs(next, node, len + cost);
        } else {
            if (inq[next]) {
                int curr;
                int real_len = len + cost - cle[next];

                while (stk_pointer > 0) {
                    curr = stk[--stk_pointer];
                    inq[curr] = false;
                    cycle_len[curr] = real_len;
                }
            }
        }
    }
}

```

```

        if (curr == next) break;
    }
}

if (inq[node]) {
    while (stk_pointer > 0) {
        inq[stk[stk_pointer-1]] = false;
        if (stk[stk_pointer-1] == node) {
            stk_pointer--;
            break;
        }
        stk_pointer--;
    }
}

stk_pointer = 0;
dfs(1, -1, 0);

```

13. Dijkstra Algorithm

```

struct MyLess {
    bool operator()(int x, int y) {
        return dist[x] > dist[y];
    }
};

int dijkstra(int source, int destiny) {
    for(int i = 0; i <= 110; i++) {
        dist[i] = INT_MAX;
    }
    priority_queue<int, vector<int>, MyLess> q;
    dist[source] = 0;
    q.push(source);

    while(!q.empty()) {
        int tmp = q.top(); q.pop();
        for(int i = 0; i < graph[tmp].size(); i++) {
            int aux_dist = dist[tmp] + graph[tmp][i].second;
            int actual_dist = dist[graph[tmp][i].first];

```

```

            if(aux_dist < actual_dist) {
                dist[graph[tmp][i].first] = aux_dist;
                q.push(graph[tmp][i].first);
            }
        }
        return dist[destiny];
    }
    // Reconstruo do Caminho
    vector<int> path;
    int start = destiny;

    while(start != -1) {
        path.push_back(start);
        start = prev[start];
    }

```

14. Dinic Algorithm

```

//Max Flow dinic  $O(V^2 \cdot E)$ 
const int MAXN = 101010;
const int INF = 101011;

struct edge {
    int to, rev;
    int cap;
    edge(int to, int cap, int rev): to(to), cap(cap), rev(rev) {}
};

vector<edge> G[MAXN];
int level[MAXN];
int iter[MAXN];

void init(int N) {
    for (int i = 0; i < N; i++) {
        G[i].clear();
    }
}

void add_edge(int from, int to, int cap) {
    G[from].push_back(edge(to, cap, G[to].size()));
    G[to].push_back(edge(from, 0, G[from].size()-1));

```

```

}

void bfs(int s) {
    memset(level, -1, sizeof(level));
    queue<int> que;
    level[s] = 0;
    que.push(s);

    while(!que.empty()) {
        int v = que.front();
        que.pop();
        for (int i = 0; i < G[v].size(); i++) {
            edge& e = G[v][i];
            if(e.cap > 0 && level[e.to] < 0) {
                level[e.to] = level[v] + 1;
                que.push(e.to);
            }
        }
    }
}

int dfs(int v, int t, int f) {
    if(v == t) return f;
    for(int& i = iter[v]; i < (int) G[v].size(); i++) {
        edge &e = G[v][i];
        if(e.cap > 0 && level[v] < level[e.to]) {
            int d = dfs(e.to, t, min(f, e.cap));
            if (d > 0) {
                e.cap -= d;
                G[e.to][e.rev].cap += d;
                return d;
            }
        }
    }
    return 0;
}

int max_flow(int s, int t) {
    int flow = 0;
    for(;;) {
        bfs(s);
        if (level[t] < 0) {
            return flow;
        }
        memset(iter, 0, sizeof(iter));
    }
}

```

```

    int f;
    while ((f=dfs(s,t,INF*INF)) > 0) {
        flow += f;
    }
}
}

```

15. Euler Phi Function

```

//Memoizing
#include <iostream>
#include <limits.h>
#include <cstdlib>
#include <cmath>
using namespace std;

const int N1 = 50001, N2 = 5133;
bool isPrime[N1];
int prime[N2], nPrime, totient[N1];

void sieveAndTotient() {
    // reset
    for (int i = 0; i < N1; ++i)
        totient[i] = i;
    isPrime[0] = isPrime[1] = false;
    for (int i = 3; i < N1; i += 2)
        isPrime[i] = true;
    for (int i = 4; i < N1; i += 2)
        isPrime[i] = false;
    nPrime = 0;
    // 2
    // update for 2
    prime[nPrime++] = 2;
    for (int j = 2; j < N1; j += 2) {
        isPrime[j] = false;
        // totient for 2
        totient[j] -= totient[j] / 2;
    }
    isPrime[2] = true;
    // odds
    for (int i = 3; i < N1; i += 2)
        if (isPrime[i]) {

```



```

        // update for i
        prime[nPrime++] = i;
        if (i < INT_MAX)
            for (int j = i; j < N1; j += i) {
                isPrime[j] = false;
                // totient for i
                totient[j] -= totient[j] / i;
            }
        isPrime[i] = true;
    }
}

//Direct
int fi(int n) {
    int result = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            result -= result / i;
        }
        while (n % i == 0) {
            n /= i;
        }
    }
    if (n > 1) {
        result -= result / n;
    }
    return result;
}

```

16. Extended GCD

```

//Inverse mod using extended euclid algorithm,

/* This function return the gcd of a and b followed by
the pair x and y of equation ax + by = gcd(a,b)*/
pair<int, pair<int, int> > extendedEuclid(int a, int b) {
    int x = 1, y = 0;
    int xLast = 0, yLast = 1;
    int q, r, m, n;
    while(a != 0) {
        q = b / a;
        r = b % a;

```

```

        m = xLast - q * x;
        n = yLast - q * y;
        xLast = x, yLast = y;
        x = m, y = n;
        b = a, a = r;
    }
    return make_pair(b, make_pair(xLast, yLast));
}

int modInverse(int a, int m) {
    return (extendedEuclid(a,m).second.first + m) % m;
}

```

17. Fast Integer Input

```

inline void rd(int &x) {
    register int c = getchar_unlocked();
    x = 0;
    int neg = 0;

    for (; ((c<48 || c>57) && c != '-'); c = getchar_unlocked());

    if (c=='-') {
        neg = 1;
        c = getchar_unlocked();
    }

    for (; c>47 && c<58 ; c = getchar_unlocked()) {
        x = (x<<1) + (x<<3) + c - 48;
    }

    if (neg) {
        x = -x;
    }
}

```

18. FasterSieve

```

//O(n)

```

```

const int N = 10000000;
int lp[N+1];
vector<int> pr;

for (int i=2; i<=N; ++i) {
    if (lp[i] == 0) {
        lp[i] = i;
        pr.push_back (i);
    }
    for (int j=0; j<(int)pr.size() && pr[j]<=lp[i] && i*pr[j]<=N; ++j)
        lp[i * pr[j]] = pr[j];
}

```

19. Fenwick Tree 2D

```

const int INF = 1000 * 1000 * 1000;

int n, m;
vector <vector <int>> t;

void init(int _n, int _m) {
    n = _n;
    m = _m;
    for(int i = 0; i < n; i++) {
        t.push_back(vector<int>(m, 0));
    }
}

int sum(int x, int y) {
    int result = 0;
    for (int i = x; i> = 0; i = (i & (i +1)) - 1) {
        for (int j = y; j> = 0; j = (j & (j +1)) - 1) {
            result += t[i][j];
        }
    }
    return result;
}

void inc (int x, int y, int delta) {
    for (int i = x; i <n; i = (i | (i +1))) {
        for (int j = y; j <m; j = (j | (j +1))) {
            t[i][j] += delta;
        }
    }
}

```

```

    }
}

void update(int x, int y, int new_value) {
    for (int i = x; i> = 0; i = (i & (i +1)) - 1) {
        for (int j = y; j> = 0; j = (j & (j +1)) - 1) {
            t[i][j] = new_value;
        }
    }
}

// sum[(r1, c1), (r2, c2)]
int sum(int[][] t, int r1, int c1, int r2, int c2) {
    return sum(t, r2, c2) - sum(t, r1 - 1, c2) - sum(t, r2, c1 - 1) +
        sum(t, r1 - 1, c1 - 1);
}

```

20. Fenwick Tree

```

template<typename T = int>
struct FenwickTree {
    int N;
    T *values;

    FenwickTree(int N) {
        this->N = N;
        values = new T[N+5];

        for(int i = 1; i <= N; i++) values[i] = 0;
    }

    void increase(int index, T add) {
        while(index <= N) {
            values[index] += add;
            index += (index & -index);
        }
    }

    void update(int index, T new_value) {
        increase(index, new_value - readSingle(index));
    }
}

```

```

T read(int index) {
    T sum = 0;

    while(index > 0) {
        sum += values[index];
        index -= (index & -index);
    }

    return sum;
}

T readSingle(int index){
    T sum = values[index];
    if(index > 0) {
        int z = index - (index & -index);
        index--;
        while(index != z) {
            sum -= values[index];
            index -= (index & -index);
        }
    }
    return sum;
}

T read(int low, int high) {
    return read(high) - read(low - 1);
}

void scale(T factor) {
    for(int i = 1; i <= N; i++) {
        values[i] /= factor;
    }
}

void power(T factor) {
    for(int i = 1; i <= N; i++) {
        values[i] *= factor;
    }
}
};

```

21. Fibonnaci - Fast Doubling

```

typedef long long int lli;
typedef pair<lli, lli> ii;

ii fast_doubling(lli n, lli mod) {
    if(n == 1) return ii(1, 1);
    else if(n == 2) return ii(1, 2);

    ii aux = fast_doubling(n/2, mod);
    ii ret;
    ret.first = (aux.first*(aux.second*2 + mod - aux.first))%mod;
    ret.second = ((lli)pow(aux.first, 2)+(lli)pow(aux.second, 2))%mod;

    if(n%2 == 0) {
        return ret;
    } else {
        return ii(ret.second, (ret.first+ret.second)%mod);
    }
}

```

22. Floyd Warshall

```

//Floyd-Warshall - O(n^3)
for(int k = 0; k < n; k++) {
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            dist[i][j] = min(dist[i][j], dist[i][k] +
                               dist[k][j]);
        }
    }
}

```

23. Fraction Library

```

struct fraction {
    int num, denom;
    fraction(int num, int denom): num(num), denom(denom){
    }
}

```

```

fraction() { num = 0; denom = 0; }
void reduce(fraction& f) {
    int l = gcd(f.num, f.denom);
    f.num = f.num/l;
    f.denom = f.denom/l;
}
fraction operator+(const fraction& f) {
    fraction ans;
    int l = lcm(denom, f.denom);
    ans.num = ((l / denom) * num) + ((l / f.denom) * f.num);
    ans.denom = l;
    reduce(ans);
    return ans;
}
fraction operator-(const fraction& f) {
    fraction ans;
    ans.num = num - f.num;
    ans.denom = denom - f.denom;
    reduce(ans);
    return ans;
}
fraction operator*(const fraction& f) {
    fraction ans;
    ans.num = num * f.num;
    ans.denom = denom * f.denom;
    reduce(ans);
    return ans;
}
fraction operator/(const fraction& f) {
    fraction ans;
    ans.num = num * f.denom;
    ans.denom = denom * f.num;
    reduce(ans);
    return ans;
}
bool operator!=(const fraction& f) {
    return num != f.num || denom != f.denom;
}
bool operator==(const fraction& f) {
    return num == f.num && denom == f.denom;
}
friend ostream &operator<<(ostream &out, fraction f) {
    out << f.num << "/" << f.denom << "\n";
    return out;
}

```

```

friend istream &operator>>(istream &in, fraction f) {
    in >> f.num >> f.denom;
    return in;
}
};

```

24. GCD LCM

```

//GCD - Maximo Divisor Comum
int gcd(int a, int b) {
    if(b == 0) return a;
    return gcd(b, a % b);
}
//*****
//LCM - Minimo Multiplo Comum
int lcm(int a, int b) {
    return a * b / gcd(a, b);
}

```

25. Heap Sort

```

int n, a[MAXN];

void downheap(int v) {
    int w = 2*v+1;
    while (w < n) {
        if(w + 1 < n) {
            if (a[w+1] > a[w]) w++;
        }
        if(a[v] >= a[w]) return;
        swap(a[v], a[w]);
        v = w;
        w = 2*v+1;
    }
}

void buildheap() {
    for (int v = n/2-1; v >= 0; v--) {
        downheap(v);
    }
}

```

```

    }
}

void heapsort() {
    buildheap();
    while (n > 1) {
        n--;
        swap(a[0], a[n]);
        downheap(0);
    }
}

```

26. Heavy Light Decomposition

```

vector<vector<pair<int,int> > > g(MAXN);
int cnt[MAXN], prev[MAXN], chainNode[MAXN], chainHead[MAXN],
    posInChain[MAXN], base[MAXN], level[MAXN], chainIdx, idxSegTree;
int H[MAXN], L[MAXN << 1], E[MAXN << 1], idx;

struct LCA{
    int tree[MAXN * 8];
    LCA(int root, int n){
        build(1, 0, 2*n-1);
    }

    //NlogN build the segtree and minimize the height of the I'th
    visited node
    void build(int node, int l, int r){
        if(l > r) return;
        if(l == r){
            tree[node] = 1;
        }else{
            int mid = (l+r) >> 1;
            build(node*2, l, mid);
            build(node*2+1, mid+1, r);
            int A = tree[node*2];
            int B = tree[node*2+1];
            if(L[A] <= L[B]){
                tree[node] = A;
            }else{
                tree[node] = B;
            }
        }
    }
}

```

```

    }
}

//Get the vertex with the minimum height, then it will be the LCA
of A and B.
int rmq(int node, int l, int r, int ra, int rb){
    if(l > rb || r < ra){
        return -1;
    }else if(l >= ra && r <= rb){
        return tree[node];
    }else{
        int mid = (l+r) >> 1;
        int q1 = rmq(node*2, l, mid, ra, rb);
        int q2 = rmq(node*2+1, mid+1, r, ra, rb);
        if(q1 == -1){
            return q2;
        }else if(q2 == -1){
            return q1;
        }else{
            if(L[q1] <= L[q2]){
                return q1;
            }else{
                return q2;
            }
        }
    }
}

int getLCA(int u, int v, int n){
    int goFrom = H[u];
    int goTo = H[v];
    if(goFrom > goTo){
        swap(goFrom, goTo);
    }
    return E[rmq(1, 0, 2*n-1, goFrom, goTo)]; //is the LCA of
    A and B;
}

struct SegTree{
    int tree[MAXN*4];

    SegTree(){
        memset(tree, 0, sizeof(tree));
    }
}

```

```

}

void build(int node, int l, int r){
    if(l > r) return;
    if(l == r){
        tree[node] = l;
    }else{
        int mid = (l+r) >> 1;
        build(node*2, l, mid);
        build(node*2+1, mid+1, r);
        int A = tree[node*2];
        int B = tree[node*2+1];
        tree[node] = base[A] > base[B] ? A : B;
    }
}

int rmq(int node, int l, int r, int ra, int rb){
    if(l > rb || r < ra){
        return -1;
    }else if(l >= ra && r <= rb){
        return tree[node];
    }else{
        int mid = (l+r) >> 1;
        int q1 = rmq(node*2, l, mid, ra, rb);
        int q2 = rmq(node*2+1, mid+1, r, ra, rb);
        if(q1 == -1){
            return q2;
        }else if(q2 == -1){
            return q1;
        }else{
            return base[q1] > base[q2] ? q1 : q2;
        }
    }
}

void update(int node, int l, int r, int pos, int value) {
    if (l > r) return;
    if (l == r) {
        base[pos] = value;
    } else {
        int m = (l + r) >> 1;
        if (pos <= m) {
            update(2 * node, l, m, pos, value);
        } else {

```

```

            update(2 * node + 1, m + 1, r, pos, value);
        }
        tree[node] = base[tree[2 * node]] > base[tree[2 *
            node + 1]] ? tree[2 * node] : tree[2 * node +
            1];
    }
};

//Decompose the tree into chains
void HLD(int node, int cost, int parent){
    if(chainHead[chainIdx] == -1){
        chainHead[chainIdx] = node;
    }
    chainNode[node] = chainIdx;
    posInChain[node] = idxSegTree;
    base[idxSegTree++] = cost;
    int nodeHeavy = -1, nextCost;
    //seeking the special child (the one with most childs on the
        subtrees)
    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != parent && (nodeHeavy == -1 || cnt[next] >
            cnt[nodeHeavy])){
            nodeHeavy = next;
            nextCost = g[node][i].second;
        }
    }
    if(nodeHeavy > -1){
        //expanding the current chain
        HLD(nodeHeavy, nextCost, node);
    }

    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != nodeHeavy && next != parent){
            chainIdx++;
            HLD(next, g[node][i].second, node);
        }
    }
}

void dfsCnt(int node, int parent, int depth = 0){

```

```

    if(H[node] == -1) H[node] = idx;//mark first time the i'th node is
        visited
    L[idx] = depth;//when you visit a node you should mark the the
        depth you have found it.
    E[idx++] = node;//the i'th recursion, global variable
    level[node] = depth;
    cnt[node] = 1;
    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != parent){
            prev[next] = node;
            dfsCnt(next, node, depth + 1);
            cnt[node] += cnt[next];
            L[idx] = depth;
            E[idx++] = node;
        }
    }
}

int walkChain(int U, int V, SegTree &q, int n){
    if(U == V) return 0;
    int ans = 0;
    while(chainNode[U] != chainNode[V]){
        int Left = posInChain[chainHead[chainNode[U]]];
        int Right = posInChain[U];
        int val = base[q.rmQ(1, 0, n-1, Left, Right)];
        if(val > ans) ans = val;
        U = prev[chainHead[chainNode[U]]];
    }
    if(U == V) return ans;
    int val = base[q.rmQ(1, 0, n-1, posInChain[V]+1, posInChain[U])];
    if(val > ans) ans = val;
    return ans;
}

int getMax(int U, int V, LCA &ref, SegTree &q, int n){
    int lca = ref.getLCA(U, V, n), a=0, b=0;
    if(lca != U)
        a = walkChain(U, lca, q, n);
    if(lca != V)
        b = walkChain(V, lca, q, n);
    return max(a, b);
}

void update(int a, int b, int c, SegTree &q, int n){

```

```

    if(level[a] < level[b]){//update b
        q.update(1, 0, n-1, posInChain[b], c);
    }else{//update a
        q.update(1, 0, n-1, posInChain[a], c);
    }
}

void add(int a, int b, int c){
    g[a].push_back(make_pair(b, c));
    g[b].push_back(make_pair(a, c));
}

int n, t, from[MAXN], to[MAXN], cost[MAXN], A, B;
char TYPE[20];

int main(void){
    scanf("%d", &t);
    while(t--){
        scanf("%d", &n);
        chainIdx = idxSegTree = idx = 0;
        for(int i = 0; i <= n; i++){
            cnt[i] = prev[i] = chainNode[i] = base[i] =
                level[i] = 0;
            chainHead[i] = posInChain[i] = H[i] = -1;
            g[i].clear();
        }
        memset(L, 0, sizeof(L));
        memset(E, 0, sizeof(E));
        for(int i = 0; i < n - 1; i++){
            scanf("%d%d%d", &from[i], &to[i], &cost[i]);
            from[i]--;
            to[i]--;
            add(from[i], to[i], cost[i]);
        }
        dfsCnt(0, -1);
        LCA lca(0, n);
        HLD(0, -1, -1);
        SegTree query;
        query.build(1, 0, n-1);
        while(1){
            scanf("%s", TYPE);
            if(TYPE[0] == 'D') break;
            scanf("%d%d", &A, &B);
            A--;
            if(TYPE[0] == 'Q'){
                B--;
            }
        }
    }
}

```

```

        printf("%d\n", getMax(A, B, lca, query, n));
    }else if(TYPE[0] == 'C'){
        update(from[A], to[A], B, query, n);
    }
}
return 0;
}

```

27. Highly Decomposite Number

```

bool p[MAXN];
vector<int> primes;

void build(void) {
    memset(p, true, sizeof(p));

    for (int i = 2; i <= MAXN; i++) {
        if (p[i]) {
            primes.push_back(i);
            for (int j = i * i; j <= MAXN; j += i) {
                p[j] = false;
            }
        }
    }
}

int func(Int x) {
    int ans = 1;

    for (int i = 0; i < (int) primes.size() && x > 1; i++) {
        if (x % primes[i] == 0) {
            int curr = 0;
            while (x % primes[i] == 0) {
                x /= primes[i];
                curr += 1;
            }
            ans *= (curr + 1);
        }
    }
    return ans;
}

```

```

set<Int> st;

void go(int id, Int v, int last) {
    Int base = primes[id];
    if (v > MAXV) return;
    st.insert(v);

    for (int i = 0; i <= last; i++) {
        v *= (Int) base;
        if (v > MAXV) break;
        go(id + 1, v, i);
    }
}

vector<Int> ans;

for (set<Int>::iterator it = st.begin(); it != st.end(); it++) {
    int s = func(*it);
    if (s > curr) {
        ans.push_back(*it);
        curr = s;
    }
}

```

28. Kadane 2D

```

//Kadane 2D
for (int i = 1; i <= N; i++) {
    for (int j = 1; j <= N; j++) {
        cin >> M[i][j];
    }
    for (int j = 1; j <= N; j++) {
        dp[i][j] = dp[i][j - 1] + M[i][j];
    }
}

int ans = -INT_MAX / 3;
for (int i = 1; i <= N; i++) {
    for (int j = i; j <= N; j++) {
        int sum = 0;
        for (int k = 1; k <= N; k++) {
            sum += dp[k][j] - dp[k][i - 1];

```



```

        chmax(ans, sum);
        if (sum < 0) sum = 0;
    }
}

```

29. Knuth Morris Pratt

```

vector<int> KMP(string S, string K) {
    vector<int> T(K.size() + 1, -1);
    vector<int> matches;

    if(K.size() == 0) {
        matches.push_back(0);
        return matches;
    }
    for(int i = 1; i <= K.size(); i++) {
        int pos = T[i - 1];
        while(pos != -1 && K[pos] != K[i - 1]) pos = T[pos];
        T[i] = pos + 1;
    }

    int sp = 0;
    int kp = 0;
    while(sp < S.size()) {
        while(kp != -1 && (kp == K.size() || K[kp] != S[sp])) kp = T[kp];
        kp++;
        sp++;
        if(kp == K.size()) matches.push_back(sp - K.size());
    }

    return matches;
}

```

30. Kosaraju Algorithm

```

//ga -> Regular Adjacency List
//gb -> Transposed Adjacency List

```

```

void dfs1(int x) {
    used[x] = 1;
    for(int b = 0; b < g[x].size(); b++) {
        if(!used[g[x][b]]) dfs1(g[x][b]);
    }
    order.push_back(x);
}

void dfs2(int x) {
    used[x] = 1;
    comonent.insert(x);
    for(int b = 0; b < gr[x].size(); b++) {
        if(!used[gr[x][b]]) dfs2(gr[x][b]);
    }
}

//Topological Sort
for (int i = 1; i <= n; i++) if(!used[i]) dfs1(i);

//Get components
for(int i = 0; i < order.size(); i++) {
    int v = order[i];
    if(!used[v]) {
        dfs2(v);
        ans++;
        comonent.clear();
    }
}

```

31. Kruskal Algorithm

```

//Kruskal Algorithm
struct edge {
    int from, to, cost;
    edge() {}
    edge(int from, int to, int cost): from(from), to(to), cost(cost) {};

    bool operator<(const edge& e) const {
        return cost < e.cost;
    }
};

```

```

//Sendo 'M' o numero de arestas, 'u' uma implementao do conjunto disjunto
'UnionFind' e 'ans' o menor custo
vector<edge> edges; //Populado com as arestas
int ans = 0;
UnionFind u(N);
for(i = 0; i < m; i++) {
    if(!u.find(edges[i].from, edges[i].to)) {
        u.unite(edges[i].from, edges[i].to);
        ans += edges[i].cost;
    }
}

```

32. LCA with Segment Tree

```

//LCA using segment tree
int H[MAXN], L[MAXN << 1], E[MAXN << 1], vis[MAXN], tree[MAXN * 8],
    path[MAXN << 1];
vector<vector<pair<int, int> > > g(MAXN);

void dfs(int x, int depth){
    vis[x] = 1; //visited
    if(H[x] == -1) H[x] = idx; //mark first time the i'th node is
    visited
    L[idx] = depth; //when you visit a node you should mark the the
    depth you have found it.
    E[idx++] = x; //the i'th recursion, global variable
    for(int i = 0; i < g[x].size(); i++){
        int next = g[x][i].first;
        if(!vis[next]){
            path[next] = x;
            dfs(next, depth+1);
            L[idx] = depth;
            E[idx++] = x;
        }
    }
}

//NlogN build the segtree and minimize the height of the I'th visited node
void build(int node, int l, int r){
    if(l > r) return;
    if(l == r){
        tree[node] = 1;
    }
}

```

```

    }else{
        int mid = (l+r) >> 1;
        build(node*2, l, mid);
        build(node*2+1, mid+1, r);
        int A = tree[node*2];
        int B = tree[node*2+1];
        if(L[A] <= L[B]){
            tree[node] = A;
        }else{
            tree[node] = B;
        }
    }
}

//Get the vertex with the minimum height, then it will be the LCA of A
and B.
int rmq(int node, int l, int r, int ra, int rb){
    if(l > rb || r < ra){
        return -1;
    }else if(l >= ra && r <= rb){
        return tree[node];
    }else{
        int mid = (l+r) >> 1;
        int q1 = rmq(node*2, l, mid, ra, rb);
        int q2 = rmq(node*2+1, mid+1, r, ra, rb);
        if(q1 == -1){
            return q2;
        }else if(q2 == -1){
            return q1;
        }else{
            if(L[q1] <= L[q2]){
                return q1;
            }else{
                return q2;
            }
        }
    }
}

idx = 0;
for(int i = 0; i <= n; i++){
    g[i].clear();
    H[i] = -1;
    L[i] = E[i] = vis[i] = 0;
    path[i] = -1;
}

```

```

    }
    dfs(0,0);
    build(1, 0, 2*n-1);
    for(int i = 0; i < k; i++){
        scanf("%d%d", &u, &v);
        u--;
        v--;
        int goFrom = H[u];
        int goTo = H[v];
        if(goFrom > goTo){
            swap(goFrom, goTo);
        }
        int lcaAB = E[rmq(1, 0, 2*n-1, goFrom, goTo)]; //is the LCA of A
        and B;
    }
}

```

33. LCA with Sparse Table

```

//LCA O(<Nlog(N)>, <log(N)>)
int N, Q, A, B;
vector<pair<int, int> > adj[MAXN];
int parent[MAXN], L[MAXN], vis[MAXN];
vector<int> level[MAXN];
int P[MAXN][20];
int dist[MAXN];

void dfs(int pos, int par){
    if(parent[pos] == -1){
        parent[pos] = par;

        for(int i = adj[pos].size() - 1; i >= 0; --i){
            to = adj[pos][i].first;
            if(to != par) {
                dist[to] = dist[pos] + adj[pos][i].second;
                dfs(to, pos);
            }
        }
    }
}

int get_level(int u){
    if(L[u] != -1) return L[u];

```

```

    else if(parent[u] == -1) return 0;
    return 1 + get_level(parent[u]);
}

void init() {
    for(int i = 0; i < N; ++i) {
        L[i] = get_level(i);
    }

    for(int i = 0; i < N; ++i) {
        level[L[i]].push_back(i);
    }

    memset(P, -1, sizeof(P));

    for(int i = 0; i < N; ++i) {
        P[i][0] = parent[i];
    }

    for(int j = 1; (1 << j) < N; ++j) {
        for(int i = 0; i < N; ++i) {
            if(P[i][j-1] != -1) {
                P[i][j] = P[P[i][j-1]][j-1];
            }
        }
    }
}

int LCA(int p, int q) {
    if(L[p] < L[q]) {
        swap(p, q);
    }

    int log = 1;
    while((1 << log) <= L[p]) ++log;
    --log;

    for(int i = log; i >= 0; --i)
        if(L[p] - (1 << i) >= L[q])
            p = P[p][i];

    if (p == q) return p;

    for(int i = log; i >= 0; --i){
        if(P[p][i] != -1 && P[p][i] != P[q][i]){

```

```

        p = P[p][i];
        q = P[q][i];
    }

    return parent[p];
}

for (i = 0; i <= N; i++) {
    vis[i] = 0;
    L[i] = parent[i] = -1;
    dist[i] = 0LL;
    adj[i].clear();
}

for (i = 1; i < N; i++) {
    scanf("%d%d", &t, &l);
    adj[i].push_back(make_pair(t, l));
    adj[t].push_back(make_pair(i, l));
}

dfs(0, -2);
parent[0] = -1;
init();

```

34. Line Point Distance

```

//Distance between point - line
double dot(pair<int, int> &A, pair<int, int> &B, pair<int, int> &C) {
    return (double) (B.first - A.first) * (C.first - B.first) + (B.second
        - A.second) * (C.second - B.second);
}

double cross(pair<int, int> &A, pair<int, int> &B, pair<int, int> &C) {
    return (double) (B.first-A.first) * (C.second-A.second) -
        (B.second-A.second) * (C.first-A.first);
}

double _distance(pair<int, int> A, pair<int, int> B) {
    int d1 = A.first - B.first;
    int d2 = A.second - B.second;
    return sqrt(d1*d1+d2*d2);
}

```

```

double linePointDist(pair<int, int> A, pair<int, int> B, pair<int, int>
    C, bool isSegment) {
    double dist = cross(A,B,C) / _distance(A,B);
    if(isSegment) {
        int dot1 = dot(A,B,C);
        if(dot1 > 0) return _distance(B,C);
        int dot2 = dot(B,A,C);
        if(dot2 > 0) return _distance(A,C);
    }
    return abs(dist);
}

```

35. Longest Common Subsequence - Efficient

```

//Longest Common Subsequence - (LCS)  $O(n^2)$  -  $O(n)$  in space
int m[2][1000]; // instead of [1000][1000]
for (i = M; i >= 0; i--) {
    int ii = i&1;
    for (int j = N; j >= 0; j--) {
        if (i == M || j == N) {
            m[ii][j]=0; continue;
        }
        if (s1[i] == s2[j]) {
            m[ii][j] = 1 + m[1-ii][j+1];
        } else {
            m[ii][j] = max(m[ii][j+1], m[1-ii][j]);
        }
    }
}
cout<<m[0][0];

```

36. Longest Common Subsequence

```

//Longest Common Subsequence - (LCS)  $O(N^2)$ 
int lcs(string a, string b) {
    int n = a.size(), m = b.size();
    int dp[n+1][m+1];

```

```

for(int i = 0; i <= max(n, m); i++) {
    dp[i][0] = dp[0][i] = 0;
}
for(int i = 1; i <= n; i++) {
    for(int j = 1; j <= m; j++) {
        if(a[i] == b[j]) {
            dp[i][j] = dp[i - 1][j - 1] + 1;
        } else {
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }
}
return dp[n][m];
}

```

37. Longest Increasing Subsequence $O(n^2)$

```

int lis(int array[], int n) {
    int best[n], prev[n];

    for(int i = 0; i < n; i++) {
        best[i] = 1;
        prev[i] = i;
    }

    for(int i = 1; i < n; i++) {
        for(int j = 0; j < i; j++) {
            if(array[i] > array[j] && best[i] < best[j] + 1) {
                best[i] = best[j] + 1; prev[i] = j;
            }
        }
    }
    int ans = 0; for(int i = 0; i < n; i++) ans = max(ans, best[i]);
    return ans;
}

```

38. Manacher Algorithm

//Manacher Algorithm (Longest Palindromic Substring)

```

string preProcess(string s) {
    int n = s.length();
    if (n == 0) return "^$";
    string ret = "^";
    for (int i = 0; i < n; i++)
        ret += "#" + s.substr(i, 1);

    ret += "#$";
    return ret;
}

vector<int> manacher(string s) {
    string T = preProcess(s);
    int n = T.length();
    vector<int> P(n);

    int C = 0, R = 0;
    for (int i = 1; i < n-1; i++) {
        int i_mirror = 2*C-i;

        P[i] = (R > i) ? min(R-i, P[i_mirror]) : 0;

        while (T[i + 1 + P[i]] == T[i - 1 - P[i]]) {
            P[i]++;
        }

        if (i + P[i] > R) {
            C = i;
            R = i + P[i];
        }
    }

    int maxLen = 0;
    int centerIndex = 0;
    for (int i = 1; i < n-1; i++) {
        if (P[i] > maxLen) {
            maxLen = P[i];
            centerIndex = i;
        }
    }
    //to return actual longest substring
    // return s.substr((centerIndex - 1 - maxLen)/2, maxLen);
    // P[i] is the length of the largest palindrome centered at i
    return P;
}

```

39. Mathematical Expression Solver

```
//Solver for mathematical expressions
void doOp(stack<double> &num, stack<char> &op){
    double A = num.top(); num.pop();
    double B = num.top(); num.pop();
    char oper = op.top(); op.pop();
    double ans;
    if(oper == '+'){
        ans = A+B;
    }else if(oper == '-'){
        ans = B-A;
    }else if(oper == '*'){
        ans = A*B;
    }else{
        if(A != 0){
            ans = B/A;
        }else{
            //division by 0
            ans = -1;
        }
    }
    num.push(ans);
}

double parse(string s){
    stack<char> op;
    stack<double> num;
    map<char,int> pr;

    //setting the priorities, greater values with higher pr
    pr['+'] = 0;
    pr['-'] = 0;
    pr['*'] = 1;
    pr['/'] = 1;

    for (int i = 0; i < s.size(); i++){
        if (s[i] == '('){
            while(!op.empty() && op.top() != '('){
                doOp(num,op);
            }
            op.pop();
        } else if(s[i] == '('){
            op.push('(');
        } else if(!(s[i] >= '0' && s[i] <= '9')){
            while(!op.empty() && pr[s[i]] <= pr[op.top()] && op.top() != '('){
                doOp(num,op);
            }
            op.push(s[i]);
        } else {
            double ans = 0;
            while(i < s.size() && s[i] >= '0' && s[i] <= '9'){
                ans = ans * 10 + (s[i] - '0');
                i++;
            }
            i--;
            num.push(ans);
        }
    }
    while (op.size()) {
        doOp(num,op);
    }
    return num.top();
}
```

```
    } else if(!(s[i] >= '0' && s[i] <= '9')){
        while(!op.empty() && pr[s[i]] <= pr[op.top()] && op.top() != '('){
            doOp(num,op);
        }
        op.push(s[i]);
    } else {
        double ans = 0;
        while(i < s.size() && s[i] >= '0' && s[i] <= '9'){
            ans = ans * 10 + (s[i] - '0');
            i++;
        }
        i--;
        num.push(ans);
    }
}
while (op.size()) {
    doOp(num,op);
}
return num.top();
}
```

40. Matrix Multiplication

```
vector<vector<int>> multiply(vector<vector<int>> a, vector<vector<int>>
> b) {
    vector<vector<int>> res(c, vector<int>(c));
    for(int i = 0; i < c; i++) {
        for(int j = 0; j < c; j++) {
            int sum = 0;
            for (int k = 0; k < c; k++) {
                sum += a[i][k] & b[k][j];
            }
            res[i][j] = sum;
        }
    }
    return res;
}

vector<vector<int>> binPow(vector<vector<int>> a, int n) {
    if (n == 1) {
        return a;
    }
}
```

```

    } else if ((n & 1) != 0) {
        return multiply(a, binPow(a, n - 1));
    } else {
        vector<vector<int> > b = binPow(a, n / 2);
        return multiply(b, b);
    }
}

```

41. Maximum Bipartite Matching

//Maximum Bipartite Matching (Prefereed implementation)

```

vector<int> graph[MAXN];

bool bpm(int u, bool seen[], int matchR[]) {
    for (int i = 0; i < (int) graph[u].size(); i++) {
        int v = graph[u][i];

        if (!seen[v]) {
            seen[v] = true;

            if (matchR[v] < 0 || bpm(matchR[v], seen, matchR)) {
                matchR[v] = u;
                return true;
            }
        }
    }
    return false;
}

int maxBPM() {
    int matchR[MAXN];

    memset(matchR, -1, sizeof(matchR));

    int result = 0;
    for (int u = 1; u <= C; u++) {
        bool seen[MAXN];
        memset(seen, 0, sizeof(seen));

        if (bpm(u, seen, matchR)) {
            result++;
        }
    }
}

```

```

    }
    return result;
}

```

42. Median Online Algorithm

```

//Get median of a sequence in O(log(n))
int median_retrieve(void) {
    if (minHeap.empty() && maxHeap.empty()) return 0;

    if (minHeap.size() == maxHeap.size()) {
        return min(minHeap.top(), maxHeap.top());
    } else {
        if (minHeap.size() > maxHeap.size()) {
            return minHeap.top();
        } else {
            return maxHeap.top();
        }
    }
}

void median_insert(int x) {
    if (x > median_retrieve()) {
        minHeap.push(x);
    } else {
        maxHeap.push(x);
    }

    while (abs((int) (minHeap.size() - maxHeap.size())) > 1) {
        if (minHeap.size() > maxHeap.size()) {
            int tmp = minHeap.top();
            minHeap.pop();
            maxHeap.push(tmp);
        } else {
            int tmp = maxHeap.top();
            maxHeap.pop();
            minHeap.push(tmp);
        }
    }
}

```

43. Merge Sort

```
//Merge-Sort  $O(N \log N)$ 
vector<int> merge(vector<int>& b, vector<int>& c) {
    vector<int> a;

    while(!b.empty() && !c.empty()) {
        if(*b.begin() < *c.begin()) {
            a.push_back(*b.begin());
            b.erase(b.begin());
        } else if(*b.begin() > *c.begin()) {
            a.push_back(*c.begin());
            c.erase(c.begin());
        } else {
            a.pb(*b.begin());
            a.pb(*c.begin());
            b.erase(b.begin());
            c.erase(c.begin());
        }
    }
    while(!b.empty()) { a.pb(*b.begin()); b.erase(b.begin()); }
    while(!c.empty()) { a.pb(*c.begin()); c.erase(c.begin()); }
    return a;
}

vector<int> mergeSort(vector<int>& a) {
    if(sz(a) <= 1) {
        return a;
    }
    vector<int> b;
    vector<int> c;

    for(int i = 0; i < sz(a) / 2; i++) {
        b.pb(a[i]);
    }
    for(int i = sz(a) / 2; i < sz(a); i++) {
        c.pb(a[i]);
    }
    vector<int> sb = mergeSort(b);
    vector<int> sc = mergeSort(c);
    return merge(sb, sc);
}
```

44. Min Cost Max Flow

```
typedef int Flow;
typedef int Cost;
const Flow INF = 0x3f3f3f3f;
struct Edge {
    int src, dst;
    Cost cst;
    Flow cap;
    int rev;
};
bool operator<(const Edge a, const Edge b) {
    return a.cst > b.cst;
}

typedef vector<Edge> Edges;
typedef vector<Edges> Graph;

void add_edge(Graph&G, int u, int v, Flow c, Cost l) {
    G[u].push_back((Edge){ u, v, l, c, int(G[v].size()) });
    G[v].push_back((Edge){ v, u, -l, 0, int(G[u].size()-1) });
}

pair<Flow, Cost> flow(Graph&G, int s, int t, int K) {
    int n = G.size();
    Flow flow = 0;
    Cost cost = 0;
    for ( ; ; ) {
        priority_queue<Edge> Q;
        vector<int> prev(n, -1), prev_num(n, -1);
        vector<Cost> length(n, INF);
        Q.push((Edge){-1,s,0,0,0});
        prev[s]=s;
        for (;!Q.empty(); ) {
            Edge e=Q.top();
            Q.pop();
            int v = e.dst;
            for (int i=0; i<(int)G[v].size(); i++) {
                if (G[v][i].cap>0 &&
                    length[G[v][i].dst]>e.cst+G[v][i].cst) {
                    prev[G[v][i].dst]=v;
                    Q.push((Edge){v, G[v][i].dst, e.cst+G[v][i].cst,0,0});
                    prev_num[G[v][i].dst]=i;
                    length[G[v][i].dst]=e.cst+G[v][i].cst;
                }
            }
        }
    }
}
```



```

    }
}
if (prev[t]<0) return make_pair(flow, cost);

Flow mi=INF;
Cost cst=0;
for (int v=t; v!=s; v=prev[v]) {
    mi=min(mi, G[prev[v]][prev_num[v]].cap);
    cst+=G[prev[v]][prev_num[v]].cst;
}

K -= cst*mi;
cost+=cst*mi;

for (int v=t; v!=s; v=prev[v]) {
    Edge &e=G[prev[v]][prev_num[v]];
    e.cap-=mi;
    G[e.dst][e.rev].cap+=mi;
}
flow += mi;
}
}

```

45. Mod Pow

```

//modpow(a, n, mod) - calcula a^n % mod de maneira eficiente
int modpow(int a, int n, int mod) {
    int res = 1;
    while (n) {
        if (n&1) {
            res=(res*a)%mod;
        }
        a=(a*1ll*a)%mod;
        n>>=1;
    }
    return res;
}

```

46. Modular Inverse for Primes

```

/* This function calculates (a^b)%MOD */
int pow(int a, int b, int MOD) {
    int x = 1, y = a;
    while(b > 0) {
        if(b%2 == 1) {
            x=(x*y);
            if(x>MOD) x%=MOD;
        }
        y = (y*y);
        if(y>MOD) y%=MOD;
        b /= 2;
    }
    return x;
}

int modInverse(int a, int m) {
    return pow(a,m-2,m);
}

```

47. N-th Palindrome Number

```

//Return the N-th palindromic number
std::string number_palindrome(int N) {
    if(N < 10){
        return std::string(1, char('0' + N));
    }
    long long sum = 0, digits = 1, v;
    for(;; digits++){
        if(digits % 2 == 0){
            v = std::pow(10, digits/2-1) * 9;
        }else{
            v = std::pow(10, (digits+1)/2-1) * 9;
        }
        if(v + sum >= N) break;
        sum += v;
    }
    //I have to find the M-th palindromic number with X digits:
    long long Mth = N-sum;
    long long sz = (digits+1) / 2;
}

```

```

long long pattern = std::pow(10, sz-1);
pattern += (Mth-1);
std::vector<int> tmp;
while(pattern > 0){
    tmp.insert(tmp.begin(), pattern % 10);
    pattern /= 10;
}
int idx = digits-tmp.size() - 1;
std::string ans = "";
for(int i = 0; i < tmp.size(); i++){
    ans += std::string(1, char('0' + tmp[i]));
}
for(;idx >= 0;){
    ans += std::string(1, char('0' + tmp[idx--]));
}
return ans;
}

```

48. Next Permutation in Java

```

boolean next_permutation(int[] p) {
    for (int a = p.length - 2; a >= 0; --a)
        if (p[a] < p[a + 1])
            for (int b = p.length - 1; --b)
                if (p[b] > p[a]) {
                    int t = p[a];
                    p[a] = p[b];
                    p[b] = t;
                    for (++a, b = p.length - 1; a < b;
                        ++a, --b) {
                        t = p[a];
                        p[a] = p[b];
                        p[b] = t;
                    }
                    return true;
                }
    return false;
}

```

49. Order Statistics Tree - STL

```

//Order statistics tree inside STL
#include<bits/stdc++.h>
#include<ext/pb_ds/assoc_container.hpp>
#include<ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
using namespace std;
template <typename T>
using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

int main(){
    ordered_set<int> s;
    s.insert(1);
    s.insert(3);
    cout << s.order_of_key(2) << endl; // the number of elements in
        the s less than 2
    cout << *s.find_by_order(0) << endl; // print the 0-th smallest
        number in s(0-based)
}

```

50. Palindromic Check with DP

```

//Checa por Palindromos
int T, N, dp[MAXN][MAXN];
char str[MAXN];

for (int i = 0; i < N; i++) {
    dp[i][i] = 1;
    if(i + 1 < N) dp[i][i + 1] = str[i] == str[i + 1];
}
for(int k = 2; k < N; k++) {
    for (int i = 0; i < N - k; i++) {
        dp[i][i + k] = dp[i + 1][i + k - 1] && str[i] == str[i + k];
    }
}

```

51. Prim Algorithm

```
int g[MAXN][MAXN], used[MAXN], min_e[MAXN], sel_e[MAXN];
min_e[0] = 0;
for (int i = 0; i < n; ++i) {
    int v = -1;
    for(int j = 0; j < n; ++j) {
        if (!used[j] && (v == -1 || min_e[j] < min_e[v])) {
            v = j;
        }
    }
    used[v] = true;
    if (sel_e[v] != -1) {
        ans += min_e[v];
    }
    for (int to = 0; to < n; ++to) {
        if (g[v][to] < min_e[to]) {
            min_e[to] = g[v][to];
            sel_e[to] = v;
        }
    }
}
```

52. Quicksort

//Worst Case $O(n^2)$ but usually $O(n \log(n))$

```
void quicksort(int lo, int hi) {
    int i=lo, j=hi, h;

    int x=a[(lo+hi)/2];

    do {
        while (a[i]<x) i++;
        while (a[j]>x) j--;
        if (i<=j) {
            swap(a[i], a[j]);
            i++;
            j--;
        }
    } while (i<=j);

    if (lo<j) quicksort(lo, j);
```

```
    if (i<hi) quicksort(i, hi);
}
```

53. Segment Tree - Lazy Propagation

```
void goDown(int node, int l, int r) {
    if (lazy[node]) {
        tree[node] += lazy[node];

        if (l != r) {
            lazy[2 * node] += lazy[node];
            lazy[2 * node + 1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

void build(int node, int l, int r) {
    if (l == r) {
        tree[node] = A[l];
    } else {
        int m = (l + r) / 2;

        build(2 * node, l, m);
        build(2 * node + 1, m + 1, r);

        tree[node] = max(tree[2 * node], tree[2 * node + 1]);
    }
}

int query(int node, int l, int r, int bl, int br) {
    goDown(node, l, r);
    if (l >= bl && r <= br) {
        return tree[node];
    } else if (l > br || r < bl) {
        return -INF;
    } else {
        int m = (l + r) / 2;

        int a = query(2 * node, l, m, bl, br);
        int b = query(2 * node + 1, m + 1, r, bl, br);
```

```

        return max(a, b);
    }
}

void update(int node, int l, int r, int bl, int br, int value) {
    goDown(node, l, r);
    if (l > r) {
        return;
    } else if (l > br || r < bl) {
        return;
    } else if (l >= bl && r <= br) {
        lazy[node] = value;
        goDown(node, l, r);
    } else {
        int m = (l + r) / 2;

        update(2 * node, l, m, bl, br, value);
        update(2 * node + 1, m + 1, r, bl, br, value);

        tree[node] = max(tree[2 * node], tree[2 * node + 1]);
    }
}

```

54. Segment Tree 2D

// Segment Tree 2D

```

pair<int, int> tree[4 * MAXN][4 * MAXN];

void build_y(int nx, int ny, int xl, int xr, int yl, int yr) {
    if (yl == yr) {
        if (xl == xr) {
            tree[nx][ny].first = tree[nx][ny].second =
                P[xl][yl];
        } else {
            tree[nx][ny].first = min(tree[2 * nx][ny].first,
                tree[2 * nx + 1][ny].first);
            tree[nx][ny].second = max(tree[2 * nx][ny].second,
                tree[2 * nx + 1][ny].second);
        }
    } else {

```

```

        int m = (yl + yr) / 2;

        build_y(nx, 2 * ny, xl, xr, yl, m);
        build_y(nx, 2 * ny + 1, xl, xr, m + 1, yr);

        tree[nx][ny].first = min(tree[nx][2 * ny].first,
            tree[nx][2 * ny + 1].first);
        tree[nx][ny].second = max(tree[nx][2 * ny].second,
            tree[nx][2 * ny + 1].second);
    }
}

void build_x(int nx, int xl, int xr) {
    if (xl > xr) {
        return;
    } else if (xl != xr) {
        int m = (xl + xr) / 2;

        build_x(2 * nx, xl, m);
        build_x(2 * nx + 1, m + 1, xr);
    }
    build_y(nx, 1, xl, xr, 0, M - 1);
}

pair<int, int> query_y(int nx, int ny, int xl, int xr, int yl, int yr,
    int bound_lx, int bound_rx, int bound_ly, int bound_ry) {
    if (yl > yr || yl > bound_ry || yr < bound_ly) {
        return make_pair(INF, -INF);
    } else if (yl >= bound_ly && yr <= bound_ry) {
        return tree[nx][ny];
    } else {
        int m = (yl + yr) / 2;

        pair<int, int> q1 = query_y(nx, 2 * ny, xl, xr, yl, m,
            bound_lx, bound_rx, bound_ly, bound_ry);
        pair<int, int> q2 = query_y(nx, 2 * ny + 1, xl, xr, m + 1,
            yr, bound_lx, bound_rx, bound_ly, bound_ry);

        return make_pair(min(q1.first, q2.first), max(q1.second,
            q2.second));
    }
}

pair<int, int> query_x(int nx, int ny, int xl, int xr, int yl, int yr,
    int bound_lx, int bound_rx, int bound_ly, int bound_ry) {

```

```

    if (xl > xr || xl > bound_rx || xr < bound_lx) {
        return make_pair(INF, -INF);
    } else if (xl >= bound_lx && xr <= bound_rx) {
        return query_y(nx, 1, xl, xr, 0, M - 1, bound_lx,
            bound_rx, bound_ly, bound_ry);
    } else {
        int m = (xl + xr) / 2;

        pair<int, int> q1 = query_x(2 * nx, ny, xl, m, yl, yr,
            bound_lx, bound_rx, bound_ly, bound_ry);
        pair<int, int> q2 = query_x(2 * nx + 1, ny, m + 1, xr, yl,
            yr, bound_lx, bound_rx, bound_ly, bound_ry);

        return make_pair(min(q1.first, q2.first), max(q1.second,
            q2.second));
    }
}

pair<int, int> query(int nx, int ny, int xl, int xr, int yl, int yr, int
    bound_lx, int bound_rx, int bound_ly, int bound_ry) {
    return query_x(1, 1, xl, xr, yl, yr, bound_lx, bound_rx, bound_ly,
        bound_ry);
}

void update_y(int nx, int ny, int xl, int xr, int yl, int yr, int posx,
    int posy, int value) {
    if (yl == yr) {
        if (xl == xr) {
            tree[nx][ny].first = tree[nx][ny].second = value;
        } else {
            tree[nx][ny].first = min(tree[2 * nx][ny].first,
                tree[2 * nx + 1][ny].first);
            tree[nx][ny].second = max(tree[2 * nx][ny].second,
                tree[2 * nx + 1][ny].second);
        }
    } else {
        int m = (yl + yr) / 2;

        if (posy <= m) {
            update_y(nx, 2 * ny, xl, xr, yl, m, posx, posy,
                value);
        } else {
            update_y(nx, 2 * ny + 1, xl, xr, m + 1, yr, posx,
                posy, value);
        }
    }
}

```

```

        tree[nx][ny].first = min(tree[nx][2 * ny].first,
            tree[nx][2 * ny + 1].first);
        tree[nx][ny].second = max(tree[nx][2 * ny].second,
            tree[nx][2 * ny + 1].second);
    }
}

void update_x(int nx, int ny, int xl, int xr, int yl, int yr, int posx,
    int posy, int value) {
    if (xl != xr) {
        int m = (xl + xr) / 2;

        if (posx <= m) {
            update_x(2 * nx, ny, xl, m, yl, yr, posx, posy,
                value);
        } else {
            update_x(2 * nx + 1, ny, m + 1, xr, yl, yr, posx,
                posy, value);
        }
    }
    update_y(nx, 1, xl, xr, 0, M - 1, posx, posy, value);
}

void update(int nx, int ny, int xl, int xr, int yl, int yr, int posx, int
    posy, int value) {
    return update_x(1, 1, xl, xr, yl, yr, posx, posy, value);
}

```

55. Sieve

```

//Crivo de Erastotenes Comum - (Todos os numeros primos <= N)
bool sieve(int n) {
    bool prime[n+1];
    fill(prime, prime + n + 1, true);
    prime[0] = false;
    prime[1] = false;

    int m = (int) sqrt(n);

    for(int i = 2; i <= m; i++) {
        if(prime[i]) {

```

```

        for (int k=i*i; k<=n; k+=i) {
            prime[k]=false;
        }
    }
    return prime;
}

```

56. Sliding Window RMQ Faster

```

//Sliding RMQ in O(N) - Faster (No use of STL)
int Q[MAXN];

```

```

Int maxSlidingWindow(Int A[], int n, int w, Int B[]) {
    int b = 0, e = 0;
    Int ans = 0LL;
    for (int i = 0; i < n; i++) {
        while (!(b == e) && A[i] >= A[Q[e-1]]) {
            e -= 1;
        }
        Q[e++] = i;
    }
    for (int i = w; i < n; i++) {
        B[i-w] = A[Q[b]];
        ans += B[i-w];
        while (!(e == b) && A[i] >= A[Q[e-1]])
            e--;
        while (!(e == b) && Q[b] <= i-w)
            b += 1;
        Q[e++] = i;
    }
    ans += A[Q[b]];

    return ans;
}

```

57. Sliding Window RMQ

```

void maxSlidingWindow(int A[], int n, int w, int B[]) {

```

```

    deque<int> Q;
    for (int i = 0; i < w; i++) {
        while (!Q.empty() && A[i] >= A[Q.back()])
            Q.pop_back();
        Q.push_back(i);
    }
    for (int i = w; i < n; i++) {
        B[i-w] = A[Q.front()];
        while (!Q.empty() && A[i] >= A[Q.back()])
            Q.pop_back();
        while (!Q.empty() && Q.front() <= i-w)
            Q.pop_front();
        Q.push_back(i);
    }
    B[n-w] = A[Q.front()];
}

```

58. Smallest Inclusive String

```

//Menor string que contem duas strings S1 e S2 como subsequencia

```

```

char S1[MAXS], S2[MAXS];
int dp[MAXS][MAXS];

memset(dp, 0, sizeof(dp));

for (i = 1; i <= N; i++) {
    for (j = 1; j <= M; j++) {
        if (S1[i - 1] == S2[j - 1]) {
            dp[i][j] = dp[i - 1][j - 1] + 1;
        } else {
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }
}

string track(int i, int j) {
    if (i == 0 && j == 0) {
        return "";
    } else if (i == 0 && j > 0) {
        return track(i, j - 1) + S2[j - 1];
    } else if (i > 0 && j == 0) {

```

```

        return track(i - 1, j) + S1[i - 1];
    } else {
        if (S1[i - 1] == S2[j - 1]) {
            return track(i - 1, j - 1) + S1[i - 1];
        } else {
            if (dp[i][j - 1] > dp[i - 1][j]) {
                return track(i, j - 1) + S2[j - 1];
            } else {
                return track(i - 1, j) + S1[i - 1];
            }
        }
    }
}
}

```

59. Splay Tree

```

//Splay Tree
template< typename T, typename Comp = std::less< T > >
class splay_tree {
private:
    Comp comp;
    unsigned long p_size;

    struct node {
        node *left, *right;
        node *parent;
        T key;
        node( const T& init = T() ) : left( 0 ), right( 0 ), parent( 0 ),
            key( init ) { }
    } *root;

    void left_rotate( node *x ) {
        node *y = x->right;
        x->right = y->left;
        if( y->left ) y->left->parent = x;
        y->parent = x->parent;
        if( !x->parent ) root = y;
        else if( x == x->parent->left ) x->parent->left = y;
        else x->parent->right = y;
        y->left = x;
        x->parent = y;
    }
}

```

```

void right_rotate( node *x ) {
    node *y = x->left;
    x->left = y->right;
    if( y->right ) y->right->parent = x;
    y->parent = x->parent;
    if( !x->parent ) root = y;
    else if( x == x->parent->left ) x->parent->left = y;
    else x->parent->right = y;
    y->right = x;
    x->parent = y;
}

void splay( node *x ) {
    while( x->parent ) {
        if( !x->parent->parent ) {
            if( x->parent->left == x ) right_rotate( x->parent );
            else left_rotate( x->parent );
        } else if( x->parent->left == x && x->parent->parent->left ==
            x->parent ) {
            right_rotate( x->parent->parent );
            right_rotate( x->parent );
        } else if( x->parent->right == x && x->parent->parent->right ==
            x->parent ) {
            left_rotate( x->parent->parent );
            left_rotate( x->parent );
        } else if( x->parent->left == x && x->parent->parent->right ==
            x->parent ) {
            right_rotate( x->parent );
            left_rotate( x->parent );
        } else {
            left_rotate( x->parent );
            right_rotate( x->parent );
        }
    }
}

void replace( node *u, node *v ) {
    if( !u->parent ) root = v;
    else if( u == u->parent->left ) u->parent->left = v;
    else u->parent->right = v;
    if( v ) v->parent = u->parent;
}

node* subtree_minimum( node *u ) {

```

```

    while( u->left ) u = u->left;
    return u;
}

node* subtree_maximum( node *u ) {
    while( u->right ) u = u->right;
    return u;
}

public:
    splay_tree( ) : root( 0 ), p_size( 0 ) { }

    void insert( const T &key ) {
        node *z = root;
        node *p = 0;

        while( z ) {
            p = z;
            if( comp( z->key, key ) ) z = z->right;
            else z = z->left;
        }

        z = new node( key );
        z->parent = p;

        if( !p ) root = z;
        else if( comp( p->key, z->key ) ) p->right = z;
        else p->left = z;

        splay( z );
        p_size++;
    }

    node* find( const T &key ) {
        node *z = root;
        while( z ) {
            if( comp( z->key, key ) ) z = z->right;
            else if( comp( key, z->key ) ) z = z->left;
            else return z;
        }
        return 0;
    }

    void erase( const T &key ) {
        node *z = find( key );
        if( !z ) return;

```

```

        splay( z );

        if( !z->left ) replace( z, z->right );
        else if( !z->right ) replace( z, z->left );
        else {
            node *y = subtree_minimum( z->right );
            if( y->parent != z ) {
                replace( y, y->right );
                y->right = z->right;
                y->right->parent = y;
            }
            replace( z, y );
            y->left = z->left;
            y->left->parent = y;
        }

        delete z;
        p_size--;
    }

    const T& minimum( ) { return subtree_minimum( root )->key; }
    const T& maximum( ) { return subtree_maximum( root )->key; }

    bool empty( ) const { return root == 0; }
    unsigned long size( ) const { return p_size; }
};

```

60. Stoer Wagner Algorithm

```

//Global Min-Cut Stoer-Wager  $O(N^3)$ 
int graph[MAXN][MAXN] //Matrix de Adjacencia do grafo.

int minCut(int n) {
    bool a[n];
    int v[n];
    int w[n];
    for(int i = 0; i < n; i++) v[i] = i;
    int best = INF;
    while(n > 1) {
        int maxj = 1;
        a[v[0]] = true;

```



```

for(int i = 1; i < n; ++i) {
    a[v[i]] = false;
    w[i] = graph[v[0]][v[i]];
    if(w[i] > w[maxj]) {
        maxj = i;
    }
}
int prev= 0 ,buf = n;
while(--buf) {
    a[v[maxj]]=true;
    if(buf == 1) {
        best = min(best, w[maxj]);
        for(int k = 0; k < n; k++) {
            graph[v[k]][v[prev]] = (graph[v[prev]][v[k]] +=
            graph[v[maxj]][v[k]]);
        }
        v[maxj] = v[--n];
    }
    prev = maxj;
    maxj = -1;
    for(int j = 1; j < n; ++j) {
        if(!a[v[j]]) {
            w[j] += graph[v[prev]][v[j]];
            if(maxj < 0 || w[j] > w[maxj]) {
                maxj=j;
            }
        }
    }
}
return best;
}

```

61. String Edit Distance

```

int dist(string& s1, string& s2) {
    int N1 = s1.size(), N2 = s2.size();

    for (int i = 0; i <= N1; i++) dp[i][0] = i;
    for (int i = 0; i <= N2; i++) dp[0][i] = i;

    for (int i = 1; i <= N1; i++) {

```

```

        for (int j = 1; j <= N2; j++) {
            if(s1[i-1] == s2[j-1]) {
                dp[i][j] = dp[i-1][j-1];
            } else {
                dp[i][j] = 1 + min(min(dp[i-1][j],
                dp[i][j-1]), dp[i-1][j-1]);
            }
        }
    }
    return dp[N1][N2];
}

```

62. String Period

```

//Find string period
int stringPeriod(string arg) {
    int ori_len = (int) arg.size();
    arg = arg + arg;

    vector<int> prefix = KMP(arg);
    int ans = (int) arg.size();

    for (int i = 0; i < (int) prefix.size(); i++) {
        if (prefix[i] >= ori_len) {
            ans = i - prefix[i];
            break;
        }
    }
    return ans;
}

```

63. Subset Sum

```

//Subset-Sum -> (G = 0 valor total sendo testado, N = numero de valores
disponiveis no array 'values'
int values[n];
bool subsetSum(int n, int g) {
    for(j = 0; j <= g; j++) sub[j] = 0;
    sub[0] = 1;

```

```

for(j = 0; j < n; j++) if(values[j] != g) {
    for(int k = g; k >= values[j]; k--) {
        sub[k] |= sub[k - values[j]];
    }
}
return sub[g];
}

```

64. Suffix Array

```

//Suffix Array O(n log n) and LCP in O(n)
//Better Implementation

const int MAXN = 100005;

// Begins Suffix Arrays implementation
// O(n log n) - Manber and Myers algorithm

//Usage:
// Fill str with the characters of the string.
// Call SuffixSort(n), where n is the length of the string stored in str.
// That's it!

//Output:
// pos = The suffix array. Contains the n suffixes of str sorted in
//       lexicographical order.
//       Each suffix is represented as a single integer (the position of
//       str where it starts).
// rnk = The inverse of the suffix array. rnk[i] = the index of the
//       suffix str[i..n)
//       in the pos array. (In other words, pos[i] = k <==> rnk[k] = i)
//       With this array, you can compare two suffixes in O(1): Suffix
//       str[i..n) is smaller
//       than str[j..n) if and only if rnk[i] < rnk[j]

int str[MAXN]; //input
int rnk[MAXN], pos[MAXN]; //output
int cnt[MAXN], nxt[MAXN]; //internal
bool bh[MAXN], b2h[MAXN];

bool smaller_first_char(int a, int b){
    return str[a] < str[b];
}

```

```

}

void SuffixSort(int n){
    //sort suffixes according to their first character
    for (int i=0; i<n; ++i){
        pos[i] = i;
    }
    sort(pos, pos + n, smaller_first_char);
    //{pos contains the list of suffixes sorted by their first character}

    for (int i=0; i<n; ++i){
        bh[i] = i == 0 || str[pos[i]] != str[pos[i-1]];
        b2h[i] = false;
    }

    for (int h = 1; h < n; h <= 1){
        //{bh[i] == false if the first h characters of pos[i-1] == the first h
        //characters of pos[i]}
        int buckets = 0;
        for (int i=0, j; i < n; i = j){
            j = i + 1;
            while (j < n && !bh[j]) j++;
            nxt[i] = j;
            buckets++;
        }
        if (buckets == n) break; // We are done! Lucky bastards!
        //{suffixes are separated in buckets containing strings starting with
        //the same h characters}

        for (int i = 0; i < n; i = nxt[i]){
            cnt[i] = 0;
            for (int j = i; j < nxt[i]; ++j){
                rnk[pos[j]] = i;
            }
        }

        cnt[rnk[n - h]]++;
        b2h[rnk[n - h]] = true;
        for (int i = 0; i < n; i = nxt[i]){
            for (int j = i; j < nxt[i]; ++j){
                int s = pos[j] - h;
                if (s >= 0){
                    int head = rnk[s];
                    rnk[s] = head + cnt[head]++;
                    b2h[rnk[s]] = true;
                }
            }
        }
    }
}

```

```

    }
}
for (int j = i; j < nxt[i]; ++j){
    int s = pos[j] - h;
    if (s >= 0 && b2h[rnk[s]]){
        for (int k = rnk[s]+1; !bh[k] && b2h[k]; k++) b2h[k] =
            false;
    }
}
}
for (int i=0; i<n; ++i){
    pos[rnk[i]] = i;
    bh[i] |= b2h[i];
}
}
for (int i=0; i<n; ++i){
    rnk[pos[i]] = i;
}
}
// End of suffix array algorithm

// Begin of the O(n) longest common prefix algorithm
int lcp[MAXN];
// lcp[i] = length of the longest common prefix of suffix pos[i] and
// suffix pos[i-1]
// lcp[0] = 0
void getLcp(int n){
    for (int i=0; i<n; ++i) rnk[pos[i]] = i;
    lcp[0] = 0;
    for (int i=0, h=0; i<n; ++i){
        if (rnk[i] > 0){
            int j = pos[rnk[i]-1];
            while (i + h < n && j + h < n && str[i+h] == str[j+h]) h++;
            lcp[rnk[i]] = h;
            if (h > 0) h--;
        }
    }
}
// End of the longest common prefix algorithm

int N = (int) S.size();

for (int i = 0; i < N; i++) {
    str[i] = S[i];

```

```

}

SuffixSort(N);
getLcp(N);

```

65. Topological Sort - Iterative

```

priority_queue<int, vector<int>, greater<int> > pq;

for (int i = 0; i < N; i++) {
    if(deg[i] == 0) {
        pq.push(i);
    }
}
int on = 0;
while (!pq.empty()) {
    int now = pq.top();
    pq.pop();
    order.push_back(now);
    for (int i = 0; i < (int) graph[now].size(); i++) {
        int next = graph[now][i];
        deg[next] -= 1;

        if(deg[next] == 0) {
            pq.push(next);
        }
    }
}

```

66. Topological Sort - Recursive

```

void dfs(int x) {
    vis[x] = 1;
    for(int u = 0; u < n; u++) {
        if(vis[u] == 1 && graph[x][u] == 1) has = true;
        if(vis[u] == 0 && graph[x][u] == 1) {
            dfs(u);
        }
    }
}

```

```

    vis[x] = 2;
    order.push_back(x);
}

```

67. TriangleArea

```

double area(double a, double b, double c) {
    double s = (a + b + c) / 2.0;

    double area = sqrt(s * (s - a) * (s - b) * (s - c));

    return area;
}

```

68. Trie

```

//Trie
struct Trie {
    Trie *child[MAXN];
    int prefixes;
    int words;

    Trie() {
        int i;
        prefixes = words = 0;
        for(i = 0; i < MAXN; i++) {
            child[i] = NULL;
        }
    }

    void addWord(string s, int pos = 0) {
        if(pos == s.size()) {
            words++;
            return;
        }

        int letter_pos = s[pos] - 'a';

        Trie *t = child[letter_pos];

```

```

        if(child[letter_pos] == NULL) {
            t = child[letter_pos] = new Trie();
            t->prefixes = 1;
        } else {
            t->prefixes = t->prefixes + 1;
        }
        t->addWord(s, pos + 1);
    }

    int count(string s, int pos = 0, int k = 0) {
        if(pos == s.size()) return k;
        Trie *t = child[s[pos] - 'a'];
        if(t == NULL) return 0;
        return t->count(s, pos + 1, (prefixes == t->prefixes) ? k: k + 1);
    }
};

```

69. Union Find

```

//Union Find
struct UnionFind {
    int N, *id, *sz;

    UnionFind(int _N) {
        id = new int[_N];
        sz = new int[_N];
        for(int i = 0; i < _N; i++) {
            id[i] = i;
            sz[i] = 1;
        }
        N = _N;
    }

    int root(int i) {
        while(i != id[i]) {
            id[i] = id[id[i]];
            i = id[i];
        }
        return i;
    }

    bool find(int p, int q) {
        return root(p) == root(q);
    }
};

```

```

    }
    void unite(int p, int q) {
        int i = root(p);
        int j = root(q);
        if(i == j) return;
        if(sz[i] < sz[j]) {
            id[i] = j; sz[j] += sz[i];
        } else {
            id[j] = i; sz[i] += sz[j];
        }
    }
};

```

70. Z Function

```

//Z-Function O(n) => Z[i] = biggest prefix of a substring starting from i
//which is as a prefix of s
vector<int> z_function (string s) {
    int n = (int) s.length();
    vector<int> z (n);
    for (int i=1, l=0, r=0; i<n; ++i) {
        if (i <= r) {
            z[i] = min (r-i+1, z[i-l]);
        }
        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) {
            ++z[i];
        }
        if (i+z[i]-1 > r) {
            l = i;
            r = i+z[i]-1;
        }
    }
    return z;
}

```
