

Team notebook

10 de septiembre de 2015

Índice			
1. Aho Corasick	2	17.Euler Phi Function	9
2. Articulation Point in Graph	3	18.Extended GCD	10
3. Bellman Ford	4	19.Fast Integer Input	10
4. Binomial Coefficient with DP	4	20.FasterSieve	11
5. Binomial Coefficient	4	21.Fenwick Tree 2D	11
6. Bipartite Check Algorithm	4	22.Fenwick Tree	11
7. Catalan	5	23.Fibonnaci - Fast Doubling	12
8. Closest Pair	5	24.First Highest Value to the Left	12
9. Coin Change	6	25.Floyd Warshall	13
10.Convex Hull	6	26.Fraction Library	13
11.Convex Polygon Area	7	27.GCD LCM	14
12.Count used Digits	7	28.Geometry Utils	14
13.Cycle Retrieval Algorithm	7	29.Hash	16
14.Days Counting	8	30.Heap Sort	16
15.Dijkstra Algorithm	8	31.Heavy Light Decomposition	17
16.Dinic Algorithm	8	32.Highly Decomposite Number	20
		33.KD-Tree	20

34.Kadane 2D	21	57.N-th Palindrome Number	33
35.Knuth Morris Pratt	22	58.Next Permutation in Java	33
36.Kosaraju Algorithm	22	59.Order Statistics Tree - STL	34
37.Kruskal Algorithm	23	60.Palindromic Check with DP	34
38.LCA with Segment Tree	23	61.Point Inside Triangle	34
39.LCA with Sparse Table	24	62.Prim Algorithm	34
40.Line Point Distance	25	63.QuickSort	35
41.Line Point Intesection	25	64.Segment Tree - Lazy Propagation	35
42.Linha de Paretto - (LIS 2D)	26	65.Segment Tree 2D	36
43.Longest Common Subsequence - Efficient	27	66.Sieve	37
44.Longest Common Subsequence	27	67.Sliding Window RMQ Faster	38
45.Longest Increasing Subsequence $O(n \cdot \log(n))$	28	68.Sliding Window RMQ	38
46.Longest Increasing Subsequence $O(n^2)$	28	69.Smallest Inclusive String	38
47.Manacher Algorithm	28	70.Splay Tree	39
48.Mathematical Expression Solver	29	71.Stoer Wagner Algorithm	40
49.Matrix Multiplication	30	72.String Edit Distance	41
50.Maximum Bipartite Matching	30	73.String Period	41
51.Median Online Algorithm	30	74.Subset Sum	41
52.Merge Sort	31	75.Suffix Array	42
53.Min Cost Max Flow	31	76.Topological Sort - Iterative	43
54.Minimal Lexicografical Rotation $O(n)$	32	77.Topological Sort - Recursive	43
55.Mod Pow	32	78.TriangleArea	44
56.Modular Inverse for Primes	33	79.Trie	44

80. Union Find

44

81. Z Function

45

1. Aho Corasick

```
#define MAXS 1000
#define MAXT 100000
#define MAX 100000
#define cc 52

int T[MAX], term[MAX], sig[MAX][cc], cnt;
vector<int> indice[MAX];

void add (char s[MAXS], int id){
    int x = 0, n = strlen(s);
    for (int i = 0; i < n; i++){
        int c = s[i] - 'A';
        if (sig[x][c] == 0) term[cnt] = 0, sig[x][c] = cnt++;
        x = sig[x][c];
    }
    term[x] = 1;
}

void aho (){
    queue<int> Q;
    for (int i = 0; i < cc; i++){
        int v = sig[0][i];
        if (v) Q.push (v), T[v] = 0;
    }
    while (!Q.empty()){
        int u = Q.front(); Q.pop();
        for (int i = 0; i < cc; i++){
            int x = sig[u][i];
            if (x == 0) continue;
            int v = T[u];
            while (sig[v][i] == 0 && v != 0) v = T[v];
            int y = sig[v][i];
            Q.push(x), T[x] = y, term[x] |= term[y];
        }
    }
}
```

```
void busca (char s[MAXT]){
    int n = strlen (s);
    int pos = 0;
    for (int i = 0; i < n; i++){
        if (sig[pos][s[i] - 'A'] != 0){
            pos = sig[pos][s[i] - 'A'];
            if (term[pos]){
                for (int j = 0; j < indice[pos].size(); j++){
                    printf("%d ", indice[pos][j]);
                }
                printf("\n");
            }
        }
        else {
            if (pos != 0) i--;
            pos = T[pos];
        }
    }
}

int main (){
    char t[MAXS]; char texto[MAXT];
    int N;
    scanf("%d", &N);
    for (int i = 0; i < MAX; i++) indice[i].clear();
    cnt = 1;
    memset (sig, 0, sizeof (sig));
    for (int i = 0; i < N; i++){
        scanf("%s", t);
        add (t, i);
    }
    aho();
    scanf("%s", texto);
    busca (texto);
    return 0;
}
```

2. Articulation Point in Graph

```
vector<int> graph[410];
set<int> ans;
set<int>::iterator it;
```

```

int dfs(int u){
    int less = vis[u] = times++;
    int filhos = 0;
    for(int i = 0; i < graph[u].size(); i++){
        if(vis[graph[u][i]]==0){
            filhos++;
            int m = dfs(graph[u][i]);
            less = min(less,m);
            if(vis[u] <= m && (u != 0 || filhos >= 2)){
                ans.insert(u);
            }
        }else{
            less = min(less, vis[graph[u][i]]);
        }
    }
    return less;
}
times = 1;
ans.clear();
dfs(0);

```

3. Bellman Ford

```

vector <pair<int, int> > edges;
int graph[MAXN][MAXN];
int dist[MAXN];

int N;
bool bellman_ford(int s) {
    int M = edges.size();
    memset (dist, INF, sizeof(int)*n);
    dist[s] = 0;
    for (int k = 0; k < N-1; ++k) {
        for (int j = 0; j < M; ++j) {
            int u = edges[j].first;
            int v = edges[j].second;
            if (dist[u] < INF && dist[v] > dist[u] +
                graph[u][v])
                dist[v] = dist[u] + graph[u][v];
        }
    }
}

```

```

//Negative Cycle
for (int j = 0; j < m; ++j) {
    int u = edges[j].first, v = edges[j].second;
    if (dist[u] < INF && dist[v] > dist[u] + graph[u][v]) {
        return false;
    }
}
return true;
}

```

4. Binomial Coefficient with DP

```

//Binomial Coefficient
//C(N, K) = N!/(K!(N - K)!)
//Dynamic Programming
int bin[N][K];

bin[0][0] = 1;

for (int n = 1; n < MAXN; n++) {
    bin[n][0] = 1;
    bin[n][n] = 1;

    for (int k = 1; k < n; k++) {
        bin[n][k] = bin[n - 1][k] + bin[n - 1][k - 1];
        if (bin[n][k] >= MOD) {
            bin[n][k] -= MOD;
        }
    }
}

```

5. Binomial Coefficient

```

Int nCr(Int n, Int k) {
    Int res = 1;

    if (k > (n >> 1LL)) {
        k = n-k;
    }
}

```

```

    for (Int i = 1; i <= k; i++, n--) {
        res = (res * n) / i;
    }

    return res;
}

```

6. Bipartite Check Algorithm

```

bool dfs(int node, int c) {
    if(color[node] != 0) {
        if(color[node] == c) {
            return true;
        } else {
            return false;
        }
    }
    color[node] = c;
    for(int i = 1; i <= n; i++)
        if(gr[node][i] == 1) {
            if(!dfs(i, -c)) {
                return false;
            }
        }
    return true;
}

```

7. Catalan

```

//Catalan numbers with DP
void getCatalan(int n){
    int catalan[n+1];
    int MOD = 1000000000;
    for (int i=0; i <= n; i++){
        if (i==0 || i==1){
            catalan[i] = 1;
        }else{
            int sum =0;

```

```

        int l, r;
        for (int k=1;k<=i;k++){
            l = catalan[k-1] % MOD;
            r = catalan[i-k] % MOD;
            sum = (sum + (l * r) % MOD) % MOD;
        }
        catalan[i] = sum;
    }
}

//Preprocessing Fatorial numbers and Answer in O(1)
Int catalan(int N) {
    Int ans = fat[2 * N];
    Int p = ((fat[N] * fat[N + 1]) % MOD) % MOD;
    ans *= modpow(p, MOD - 2, MOD);

    ans = ((ans % MOD) + MOD) % MOD;

    return ans;
}

```

8. Closest Pair

```

///----Closes pair with divide and conquer----///
struct point{
    double x, y;
    point(double a, double b): x(a), y(b){}
    point(){};
};

bool compareX(point a, point b){
    return a.x < b.x;
}

bool compareY(point a, point b){
    return a.y < b.y;
}

double bruteForce(vector<point> &p){
    double ans = 40000.*40001.;
    for(int i = 0; i < p.size(); i++){
        for(int j = i + 1; j < p.size(); j++){

```

```

        double dst = hypot(p[j].x - p[i].x, p[j].y - p[i].y);
        if(dst < ans){
            ans = dst;
        }
    }
}
return ans;
}

double strip(vector<point> &p, double d){
    sort(p.begin(), p.end(), compareY);
    double ans = d;
    for(int i = 0; i < p.size(); i++){
        for(int j = i + 1; j < p.size() && (p[j].y - p[i].y) < d; j++){
            double dst = hypot(p[j].x - p[i].x, p[j].y - p[i].y);
            if(dst < ans){
                ans = dst;
            }
        }
    }
    return ans;
}
}

```

```

double X, Y;
int n;
double closest(vector<point> v){
    int n = v.size();
    if(n <= 3){
        return bruteForce(v);
    }
    vector<point> left;
    vector<point> right;
    int mid = n >> 1;
    for(int i = 0; i < mid; i++){
        left.push_back(v[i]);
    }
    for(int i = mid; i < n; i++){
        right.push_back(v[i]);
    }
}

```

```

double lh = closest(left);
double rh = closest(right);
double d = min(lh, rh);
vector<point> stripArray;
for(int i = 0; i < n; i++){

```

```

        if(fabs(v[i].x - v[mid].x) < d){
            stripArray.push_back(v[i]);
        }
    }
    return min(d, strip(stripArray, d));
}

sort(pos.begin(), pos.begin()+n, compareX);
double ans = closest(pos);

```

9. Coin Change

```

//Coin Change
int dp[1001];
int coins[] = {1, 5, 10, 25, 50};

dp[0] = 0;

for(int i = 1; i <= N; i++) {
    int min = 1000001;
    for(int j = 0; j < M; j++) {
        if(coins[j] <= i) {
            int m = dp[i - coins[j]] + 1;
            if(m < min) min = m;
        }
    }
    dp[i] = min;
}

```

10. Convex Hull

```

//Convex Hull
struct point {
    int x, y;
    point(int x, int y): x(x), y(y){}
    point(){}
    bool operator <(const point &p) const {
        return x < p.x || (x == p.x && y < p.y);
    }
}

```

```

    bool operator==(const point &p) const {
        return x == p.x && y == p.y;
    }
};
ll cross(const point &O, const point &A, const point &B) {
    return (A.x - O.x) * (B.y - O.y) - (A.y - O.y) * (B.x - O.x);
}

vector<point> convex_hull(vector<point> &P) {
    int n = P.size(), k = 0;
    vector<point> H(2*n);

    sort(P.begin(), P.end());

    for (int i = 0; i < n; i++) {
        while (k >= 2 && cross(H[k-2], H[k-1], P[i]) <= /*change to < to
            remove equal points */ 0) k--;
        H[k++] = P[i];
    }
    for (int i = n-2, t = k+1; i >= 0; i--) {
        while (k >= t && cross(H[k-2], H[k-1], P[i]) <= /*change to < to
            remove equal points */ 0) k--;
        H[k++] = P[i];
    }
    H.resize(k);
    return H;
}

```

11. Convex Polygon Area

```

//Area de um Poligono Convexo
double area() {
    int N = 4;

    //Points
    int[] x = { 2, -4, 5, 2 };
    int[] y = { 5, 3, 1, 5 };

    double ma = x[N - 1] * y[0], mb = x[0] * y[N - 1];

    for (int i = 0; i < N - 1; i++) {
        ma += (x[i] * y[i + 1]);

```

```

        mb += (x[i + 1] * y[i]);
    }

    double ans = Math.abs((ma - mb) * 0.5);
}

```

12. Count used Digits

```

Int func(int val) {
    int digitCount = (int) log10(val) + 1;
    Int ans = 0LL;
    Int p = 1LL;

    for (int i = 0; i < digitCount - 1; i++) {
        ans += p * 9 * (i + 1);
        p *= 10;
    }

    ans += (val - p + 1) * digitCount;

    return ans;
}

```

13. Cycle Retrieval Algorithm

```

//It only works in graphs without compound cycles
bool inq[MAXN], vis[MAXN];

void dfs(int node, int parent, int len) {
    vis[node] = true;
    cle[node] = len;

    stk[stk_pointer++] = node;
    inq[node] = true;

    for (int i = 0; i < (int) graph[node].size(); i++) {
        int next = graph[node][i].first;
        int cost = graph[node][i].second;

```

```

    if (next == parent) continue;

    if (!vis[next]) {
        dfs(next, node, len + cost);
    } else {
        if (inq[next]) {
            int curr;
            int real_len = len + cost - cle[next];

            while (stk_pointer > 0) {
                curr = stk[--stk_pointer];
                inq[curr] = false;
                cycle_len[curr] = real_len;
                if (curr == next) break;
            }
        }
    }

    if (inq[node]) {
        while (stk_pointer > 0) {
            inq[stk[stk_pointer-1]] = false;
            if (stk[stk_pointer-1] == node) {
                stk_pointer--;
                break;
            }
            stk_pointer--;
        }
    }

    stk_pointer = 0;
    dfs(1, -1, 0);

```

14. Days Counting

```

int meses[] = {0,31,28,31,30,31,30,31,31,30,31,30,31};
int dp[8000][13][34];

for(int i = -3113; i <= 4000; i++){
    for(int j = 1; j <= 12; j++){
        for(int k = 1; k <= meses[j] + (isLeap(i) && j == 2); k++){

```

```

        dp[i + 3113][j][k] = past++;
    }
}

```

15. Dijkstra Algorithm

```

struct MyLess {
    bool operator()(int x, int y) {
        return dist[x] > dist[y];
    }
};

int dijsktra(int source, int destiny) {
    for(int i = 0; i <= 110; i++) {
        dist[i] = INT_MAX;
    }
    priority_queue<int, vector<int>, MyLess> q;
    dist[source] = 0;
    q.push(source);

    while(!q.empty()) {
        int tmp = q.top(); q.pop();
        for(int i = 0; i < graph[tmp].size(); i++) {
            int aux_dist = dist[tmp] + graph[tmp][i].second;
            int actual_dist = dist[graph[tmp][i].first];
            if(aux_dist < actual_dist) {
                dist[graph[tmp][i].first] = aux_dist;
                q.push(graph[tmp][i].first);
            }
        }
    }

    return dist[destiny];
}

// Reconstruo do Caminho
vector<int> path;
int start = destiny;

while(start != -1) {
    path.push_back(start);
    start = prev[start];
}

```

16. Dinic Algorithm

```
//Max Flow dinic O(V^2*E)
const int MAXN = 101010;
const int INF = 101011;

struct edge {
    int to, rev;
    Int cap;
    edge(int to, Int cap, int rev): to(to), cap(cap), rev(rev) {}
};

vector<edge> G[MAXN];
Int level[MAXN];
int iter[MAXN];

void init(int N) {
    for (int i = 0; i < N; i++) {
        G[i].clear();
    }
}

void add_edge(int from, int to, Int cap) {
    G[from].push_back(edge(to, cap, G[to].size()));
    G[to].push_back(edge(from, 0, G[from].size()-1));
}

void bfs(int s) {
    memset(level, -1, sizeof(level));
    queue<int> que;
    level[s] = 0;
    que.push(s);

    while(!que.empty()) {
        int v = que.front();
        que.pop();
        for (int i = 0; i < G[v].size(); i++) {
            edge& e = G[v][i];
            if(e.cap > 0 && level[e.to] < 0) {
                level[e.to] = level[v] + 1;
                que.push(e.to);
            }
        }
    }
}
```

```
}

Int dfs(int v, int t, Int f) {
    if(v == t) return f;
    for(int& i = iter[v]; i < (int) G[v].size(); i++) {
        edge &e = G[v][i];
        if(e.cap > 0 && level[v] < level[e.to]) {
            Int d = dfs(e.to, t, min(f, e.cap));
            if (d > 0) {
                e.cap -= d;
                G[e.to][e.rev].cap += d;
                return d;
            }
        }
    }
    return 0;
}

int max_flow(int s, int t) {
    Int flow = 0;
    for( ; ; ) {
        bfs(s);
        if (level[t] < 0) {
            return flow;
        }
        memset(iter, 0, sizeof(iter));
        int f;
        while ((f=dfs(s,t,INF*INF)) > 0) {
            flow += f;
        }
    }
}
```

17. Euler Phi Function

```
//Memoizing
#include <iostream>
#include <limits.h>
#include <cstdlib>
#include <cmath>
using namespace std;
```

```

const int N1 = 50001, N2 = 5133;
bool isPrime[N1];
int prime[N2], nPrime, totient[N1];

void sieveAndTotient() {
    // reset
    for (int i = 0; i < N1; ++i)
        totient[i] = i;
    isPrime[0] = isPrime[1] = false;
    for (int i = 3; i < N1; i += 2)
        isPrime[i] = true;
    for (int i = 4; i < N1; i += 2)
        isPrime[i] = false;
    nPrime = 0;
    // 2
    // update for 2
    prime[nPrime++] = 2;
    for (int j = 2; j < N1; j += 2) {
        isPrime[j] = false;
        // totient for 2
        totient[j] -= totient[j] / 2;
    }
    isPrime[2] = true;
    // odds
    for (int i = 3; i < N1; i += 2)
        if (isPrime[i]) {
            // update for i
            prime[nPrime++] = i;
            if (i < INT_MAX)
                for (int j = i; j < N1; j += i) {
                    isPrime[j] = false;
                    // totient for i
                    totient[j] -= totient[j] / i;
                }
            isPrime[i] = true;
        }
}

//Direct
int fi(int n) {
    int result = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            result -= result / i;
        }
    }
}

```

```

        while (n % i == 0) {
            n /= i;
        }
    }
    if (n > 1) {
        result -= result / n;
    }
    return result;
}

```

18. Extended GCD

```

//Inverse mod using extended euclid algorithm,

/* This function return the gcd of a and b followed by
the pair x and y of equation ax + by = gcd(a,b)*/
pair<int, pair<int, int> > extendedEuclid(int a, int b) {
    int x = 1, y = 0;
    int xLast = 0, yLast = 1;
    int q, r, m, n;
    while(a != 0) {
        q = b / a;
        r = b % a;
        m = xLast - q * x;
        n = yLast - q * y;
        xLast = x, yLast = y;
        x = m, y = n;
        b = a, a = r;
    }
    return make_pair(b, make_pair(xLast, yLast));
}

int modInverse(int a, int m) {
    return (extendedEuclid(a,m).second.first + m) % m;
}

```

19. Fast Integer Input

```

inline void rd(int &x) {

```

```

register int c = getchar_unlocked();
x = 0;
int neg = 0;

for (; ((c<48 || c>57) && c != '-'); c = getchar_unlocked());

if (c=='-') {
    neg = 1;
    c = getchar_unlocked();
}

for (; c>47 && c<58 ; c = getchar_unlocked()) {
    x = (x<<1) + (x<<3) + c - 48;
}

if (neg) {
    x = -x;
}
}

```

20. FasterSieve

```

//O(n)
const int N = 10000000;
int lp[N+1];
vector<int> pr;

for (int i=2; i<=N; ++i) {
    if (lp[i] == 0) {
        lp[i] = i;
        pr.push_back (i);
    }
    for (int j=0; j<(int)pr.size() && pr[j]<=lp[i] && i*pr[j]<=N; ++j)
        lp[i * pr[j]] = pr[j];
}

```

21. Fenwick Tree 2D

```

const int INF = 1000 * 1000 * 1000;

```

```

int n, m;
vector <vector <int>>> t;

void init(int _n, int _m) {
    n = _n;
    m = _m;
    for(int i = 0; i < n; i++) {
        t.push_back(vector<int>(m, 0));
    }
}

int sum(int x, int y) {
    int result = 0;
    for (int i = x; i>= 0; i = (i & (i + 1)) - 1) {
        for (int j = y; j>= 0; j = (j & (j + 1)) - 1) {
            result += t[i][j];
        }
    }
    return result;
}

void inc (int x, int y, int delta) {
    for (int i = x; i < n; i = (i | (i + 1))) {
        for (int j = y; j < m; j = (j | (j + 1))) {
            t[i][j] += delta;
        }
    }
}

void update(int x, int y, int new_value) {
    for (int i = x; i>= 0; i = (i & (i + 1)) - 1) {
        for (int j = y; j>= 0; j = (j & (j + 1)) - 1) {
            t[i][j] = new_value;
        }
    }
}

// sum[(r1, c1), (r2, c2)]
int sum(int[][] t, int r1, int c1, int r2, int c2) {
    return sum(t, r2, c2) - sum(t, r1 - 1, c2) - sum(t, r2, c1 - 1) +
        sum(t, r1 - 1, c1 - 1);
}

```

22. Fenwick Tree

```
template<typename T = int>
struct FenwickTree {
    int N;
    T *values;

    FenwickTree(int N) {
        this->N = N;
        values = new T[N+5];

        for(int i = 1; i <= N; i++) values[i] = 0;
    }

    void increase(int index, T add) {
        while(index <= N) {
            values[index] += add;
            index += (index & -index);
        }
    }

    void update(int index, T new_value) {
        increase(index, new_value - readSingle(index));
    }

    T read(int index) {
        T sum = 0;

        while(index > 0) {
            sum += values[index];
            index -= (index & -index);
        }

        return sum;
    }

    T readSingle(int index){
        T sum = values[index];
        if(index > 0) {
            int z = index - (index & -index);
            index--;
            while(index != z) {
                sum -= values[index];
                index -= (index & -index);
            }
        }
    }
};
```

```
    }
}

return sum;
}

T read(int low, int high) {
    return read(high) - read(low - 1);
}

void scale(T factor) {
    for(int i = 1; i <= N; i++) {
        values[i] /= factor;
    }
}

void power(T factor) {
    for(int i = 1; i <= N; i++) {
        values[i] *= factor;
    }
}
};
```

23. Fibonnaci - Fast Doubling

```
typedef long long int lli;
typedef pair<lli, lli> ii;

ii fast_doubling(lli n, lli mod) {
    if(n == 1) return ii(1, 1);
    else if(n == 2) return ii(1, 2);

    ii aux = fast_doubling(n/2, mod);
    ii ret;
    ret.first = (aux.first*(aux.second*2 + mod - aux.first))%mod;
    ret.second = ((lli)pow(aux.first, 2)+(lli)pow(aux.second, 2))%mod;

    if(n%2 == 0) {
        return ret;
    } else {
        return ii(ret.second, (ret.first+ret.second)%mod);
    }
}
```

24. First Highest Value to the Left

```
void fillL(void) {
    stack<int> s;

    for (int i = 0; i < N; i++) {
        if (s.empty()) {
            L[i] = i;
        } else {
            while (!s.empty() && P[s.top()] <= P[i]) {
                s.pop();
            }
            if (!s.empty()) {
                L[i] = s.top();
            } else {
                L[i] = i;
            }
        }
        s.push(i);
    }
}
```

25. Floyd Warshall

```
//Floyd-Warshall - O(n^3)
for(int k = 0; k < n; k++) {
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            dist[i][j] = min(dist[i][j], dist[i][k] +
                             dist[k][j]);
        }
    }
}
```

26. Fraction Library

```
struct fraction {
    int num, denom;
    fraction(int num, int denom): num(num), denom(denom){
```

```
    }
    fraction() { num = 0; denom = 0; }
    void reduce(fraction& f) {
        int l = gcd(f.num, f.denom);
        f.num = f.num/l;
        f.denom = f.denom/l;
    }
    fraction operator+(const fraction& f) {
        fraction ans;
        int l = lcm(denom, f.denom);
        ans.num = ((l / denom) * num) + ((l / f.denom) * f.num);
        ans.denom = l;
        reduce(ans);
        return ans;
    }
    fraction operator-(const fraction& f) {
        fraction ans;
        ans.num = num - f.num;
        ans.denom = denom - f.denom;
        reduce(ans);
        return ans;
    }
    fraction operator*(const fraction& f) {
        fraction ans;
        ans.num = num * f.num;
        ans.denom = denom * f.denom;
        reduce(ans);
        return ans;
    }
    fraction operator/(const fraction& f) {
        fraction ans;
        ans.num = num * f.denom;
        ans.denom = denom * f.num;
        reduce(ans);
        return ans;
    }
    bool operator!=(const fraction& f) {
        return num != f.num || denom != f.denom;
    }
    bool operator==(const fraction& f) {
        return num == f.num && denom == f.denom;
    }
    friend ostream &operator<<(ostream &out, fraction f) {
        out << f.num << "/" << f.denom << "\n";
        return out;
    }
}
```

```

    }
    friend istream &operator>>(istream &in, fraction f) {
        in >> f.num >> f.denom;
        return in;
    }
};

```

27. GCD LCM

```

//GCD - Maximo Divisor Comum
int gcd(int a, int b) {
    if(b == 0) return a;
    return gcd(b, a % b);
}
//*****
//LCM - Minimo Multiplo Comum
int lcm(int a, int b) {
    return a * b / gcd(a, b);
}

```

28. Geometry Utils

```

//Point structure
//Piece of code stracted from the hichhikin guide to programming
//start from any initial values.

const double PI = 2.0*acos(0.0);
const double EPS = 1e-9; //too small/big????
struct PT {
    double x,y;
    double length() {
        return sqrt(x*x+y*y);
    }
    int normalize() {
        double l = length();
        if(fabs(l)<EPS) return -1;
        x/=l; y/=l;
        return 0;
    }
}

```

```

PT operator-(PT a) {
    PT r;
    r.x=x-a.x; r.y=y-a.y;
    return r;
}
PT operator+(PT a){
    PT r;
    r.x=x+a.x; r.y=y+a.y;
    return r;
}
PT operator*(double sc) {
    PT r;
    r.x=x*sc; r.y=y*sc;
    return r;
}
};

bool operator<(const PT& a,const PT& b) {
    if(fabs(a.x-b.x)<EPS) return a.y<b.y;
    return a.x<b.x;
}

double dist(PT& a, PT& b){
    return sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}

double dot(PT& a, PT& b) {
    return(a.x*b.x+a.y*b.y);
}

r.x=x*sc; r.y=y*sc;
// Areas
// =====
double trap(PT a, PT b) {
    return (0.5*(b.x - a.x)*(b.y + a.y));
}

double area(vector<PT> &vin) {
    // Area of a simple polygon, not neccessary convex
    int n = vin.size();
    double ret = 0.0;
    for(int i = 0; i < n; i++) {
        ret += trap(vin[i], vin[(i+1)%n]);
    }
    return fabs(ret);
}

double peri(vector<PT> &vin) {
    // Perimeter of a simple polygon, not neccessary convex
    int n = vin.size();
    double ret = 0.0;

```

```

    for(int i = 0; i < n; i++) {
        ret += dist(vin[i], vin[(i+1)%n]);
    }
    return ret;
}
double triarea(PT a, PT b, PT c) {
    //Triangle area
    return fabs(trap(a,b)+trap(b,c)+trap(c,a));
}
double height(PT a, PT b, PT c) {
    // height from a to the line bc
    double s3 = dist(c, b);
    double ar = triarea(a,b,c);
    return (2.0*ar/s3);
}
//*****
//Check wheter a polygon is convex
int sideSign(PT& p1,PT& p2,PT& p3) {
    // which side is p3 to the line p1->p2? returns: 1 left, 0 on, -1
    right
    double sg = (p1.x-p3.x)*(p2.y-p3.y)-(p1.y - p3.y)*(p2.x-p3.x);
    if (fabs(sg)<EPS) return 0;
    if (sg>0) return 1;
    return -1;
}
int isConvex(vector<PT>& v) {
    // test whether a simple polygon is convex
    // return 0 if not convex, 1 if strictly convex,
    // 2 if convex but there are points unnecessary
    // this function does not work if the polycon is self intersecting
    // in that case, compute the convex hull of v, and see if both
    have the same area
    int i,j,k;
    int c1=0; int c2=0; int c0=0;
    int n=v.size();
    for(i = 0;i < n; i++) {
        j= (i+1)%n;
        k= (j+1)%n;
        int s = sideSign(v[i], v[j], v[k]);
        if (s == 0) c0++;
        if (s > 0) c1++;
        if (s < 0) c2++;
    }
    if(c1 && c2) return 0;
    if(c0) return 2;
}

```

```

    return 1;
}
// =====
// Points and Lines
// =====
int intersection( PT p1, PT p2, PT p3, PT p4, PT &r) {
    // two lines given by p1->p2, p3->p4 r is the intersection point
    // return -1 if two lines are parallel
    double d = (p4.y - p3.y)*(p2.x-p1.x) - (p4.x - p3.x)*(p2.y - p1.y);
    if( fabs( d ) < EPS ) return -1;
    // might need to do something special!!!
    double ua, ub;
    ua = (p4.x - p3.x)*(p1.y-p3.y) - (p4.y-p3.y)*(p1.x-p3.x);
    ua /= d;
    // ub = (p2.x - p1.x)*(p1.y-p3.y) - (p2.y-p1.y)*(p1.x-p3.x);
    //ub /= d;
    r = p1 + (p2-p1)*ua;
    return 0;
}

void closestpt( PT p1, PT p2, PT p3, PT &r) {
    // the closest point on the line p1->p2 to p3
    if (fabs( triarea( p1, p2, p3)) < EPS) {
        r = p3;
        return;
    }
    PT v = p2-p1;
    v.normalize();
    double pr; // inner product
    pr = (p3.y-p1.y)*v.y + (p3.x-p1.x)*v.x;
    r = p1+v*pr;
}

int hcenter( PT p1, PT p2, PT p3, PT& r) {
    // point generated by altitudes
    if (triarea( p1, p2, p3 ) < EPS) return -1;
    PT a1, a2;
    closestpt( p2, p3, p1, a1 );
    closestpt( p1, p3, p2, a2 );
    intersection( p1, a1, p2, a2, r );
    return 0;
}

int center( PT p1, PT p2, PT p3, PT& r) {
    // point generated by circumscribed circle
    if (triarea( p1, p2, p3 ) < EPS) return -1;
    PT a1, a2, b1, b2;
}

```

```

a1 = (p2+p3)*0.5;
a2 = (p1+p3)*0.5;
b1.x = a1.x - (p3.y-p2.y);
b1.y = a1.y + (p3.x-p2.x);
b2.x = a2.x - (p3.y-p1.y);
b2.y = a2.y + (p3.x-p1.x);
intersection(a1, b1, a2, b2, r);
return 0;
}

```

29. Hash

```

#include<iostream>
#include<stack>
#include<queue>
#include<cstdio>
#include<algorithm>
#include<vector>
#include<set>
#include<string>
#include<cstring>
#include<map>
#include<numeric>
#include<sstream>
#include<cmath>
using namespace std;

typedef pair<int, int> pii;
typedef long long ll;
typedef long double ld;
typedef unsigned long long Hash;
#define maxn 1000010

Hash CC;
Hash C[maxn];
Hash B;
Hash h[maxn], poww[maxn];
char s[maxn];
int n;

inline int V (char c){
    return c-'a';
}

```

```

}

void pre (){
    h[0] = 0ULL;
    for (int i = 1; i <= n; i++) {
        h[i] = h[i-1]*B+V(s[i-1]);
    }
    poww[0] = 1ULL;
    for (int i = 1; i <= n; i++) {
        poww[i] = poww[i-1]*B;
    }
    C[0] = CC;
    for (int i = 1; i <= n; i++) {
        C[i] = C[i-1]*CC;
    }
}

Hash calcula (int a, int b){
    return h[b]-h[a]*poww[b-a]+C[b-a];
}

int main (){
    CC = 5831ULL;
    B = 33ULL;
    scanf("%s", s);
    n = strlen(s);
    pre();

    while (1){
        int a, b; scanf("%d %d", &a, &b);
        cout << calcula (a, b) << endl;
    }

    return 0;
}

```

30. Heap Sort

```

int n, a[MAXN];

void downheap(int v) {
    int w = 2*v+1;
}

```



```

while (w < n) {
    if(w + 1 < n) {
        if (a[w+1]>a[w]) w++;
    }
    if(a[v] >= a[w]) return;
    swap(a[v], a[w]);
    v = w;
    w = 2*v+1;
}

void buildheap() {
    for (int v = n/2-1; v >= 0; v--) {
        downheap(v);
    }
}

void heapsort() {
    buildheap();
    while (n > 1) {
        n--;
        swap(a[0], a[n]);
        downheap(0);
    }
}

```

31. Heavy Light Decomposition

```

vector<vector<pair<int,int> > > g(MAXN);
int cnt[MAXN], prev[MAXN], chainNode[MAXN], chainHead[MAXN],
    posInChain[MAXN], base[MAXN], level[MAXN], chainIdx, idxSegTree;
int H[MAXN], L[MAXN << 1], E[MAXN << 1], idx;

struct LCA{
    int tree[MAXN * 8];
    LCA(int root, int n){
        build(1, 0, 2*n-1);
    }

    //NlogN build the segtree and minimize the height of the I'th
    visited node
    void build(int node, int l, int r){

```

```

        if(l > r) return;
        if(l == r){
            tree[node] = 1;
        }else{
            int mid = (l+r) >> 1;
            build(node*2, l, mid);
            build(node*2+1, mid+1, r);
            int A = tree[node*2];
            int B = tree[node*2+1];
            if(L[A] <= L[B]){
                tree[node] = A;
            }else{
                tree[node] = B;
            }
        }
    }

    //Get the vertex with the minimum height, then it will be the LCA
    of A and B.
    int rmq(int node, int l, int r, int ra, int rb){
        if(l > rb || r < ra){
            return -1;
        }else if(l >= ra && r <= rb){
            return tree[node];
        }else{
            int mid = (l+r) >> 1;
            int q1 = rmq(node*2, l, mid, ra, rb);
            int q2 = rmq(node*2+1, mid+1, r, ra, rb);
            if(q1 == -1){
                return q2;
            }else if(q2 == -1){
                return q1;
            }else{
                if(L[q1] <= L[q2]){
                    return q1;
                }else{
                    return q2;
                }
            }
        }
    }

    int getLCA(int u, int v, int n){
        int goFrom = H[u];
        int goTo = H[v];

```

```

        if(goFrom > goTo){
            swap(goFrom, goTo);
        }
        return E[rmq(1, 0, 2*n-1, goFrom, goTo)]; //is the LCA of
            A and B;
    }
};

struct SegTree{

    int tree[MAXN*4];

    SegTree(){
        memset(tree,0,sizeof(tree));
    }

    void build(int node, int l, int r){
        if(l > r) return;
        if(l == r){
            tree[node] = 1;
        }else{
            int mid = (l+r) >> 1;
            build(node*2, l, mid);
            build(node*2+1, mid+1, r);
            int A = tree[node*2];
            int B = tree[node*2+1];
            tree[node] = base[A] > base[B] ? A : B;
        }
    }

    int rmq(int node, int l, int r, int ra, int rb){
        if(l > rb || r < ra){
            return -1;
        }else if(l >= ra && r <= rb){
            return tree[node];
        }else{
            int mid = (l+r) >> 1;
            int q1 = rmq(node*2, l, mid, ra, rb);
            int q2 = rmq(node*2+1, mid+1, r, ra, rb);
            if(q1 == -1){
                return q2;
            }else if(q2 == -1){
                return q1;
            }else{

```

```

                return base[q1] > base[q2] ? q1 : q2;
            }
        }
    }

    void update(int node, int l, int r, int pos, int value) {
        if (l > r) return;
        if (l == r) {
            base[pos] = value;
        } else {
            int m = (l + r) >> 1;
            if (pos <= m) {
                update(2 * node, l, m, pos, value);
            } else {
                update(2 * node + 1, m + 1, r, pos, value);
            }
            tree[node] = base[tree[2 * node]] > base[tree[2 *
                node + 1]] ? tree[2 * node] : tree[2 * node +
                1];
        }
    }
};

//Decompose the tree into chains
void HLD(int node, int cost, int parent){
    if(chainHead[chainIdx] == -1){
        chainHead[chainIdx] = node;
    }
    chainNode[node] = chainIdx;
    posInChain[node] = idxSegTree;
    base[idxSegTree++] = cost;
    int nodeHeavy = -1, nextCost;
    //seeking the special child (the one with most childs on the
        subtrees)
    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != parent && (nodeHeavy == -1 || cnt[next] >
            cnt[nodeHeavy])){
            nodeHeavy = next;
            nextCost = g[node][i].second;
        }
    }
    if(nodeHeavy > -1){
        //expanding the current chain
        HLD(nodeHeavy, nextCost, node);
    }
}

```

```

    }

    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != nodeHeavy && next != parent){
            chainIdx++;
            HLD(next, g[node][i].second, node);
        }
    }
}

void dfsCnt(int node, int parent, int depth = 0){
    if(H[node] == -1) H[node] = idx; //mark first time the i'th node is
    visited
    L[idx] = depth; //when you visit a node you should mark the the
    depth you have found it.
    E[idx++] = node; //the i'th recursion, global variable
    level[node] = depth;
    cnt[node] = 1;
    for(int i = 0; i < g[node].size(); i++){
        int next = g[node][i].first;
        if(next != parent){
            prev[next] = node;
            dfsCnt(next, node, depth + 1);
            cnt[node] += cnt[next];
            L[idx] = depth;
            E[idx++] = node;
        }
    }
}

int walkChain(int U, int V, SegTree &q, int n){
    if(U == V) return 0;
    int ans = 0;
    while(chainNode[U] != chainNode[V]){
        int Left = posInChain[chainHead[chainNode[U]]];
        int Right = posInChain[U];
        int val = base[q.rm(1, 0, n-1, Left, Right)];
        if(val > ans) ans = val;
        U = prev[chainHead[chainNode[U]]];
    }
    if(U == V) return ans;
    int val = base[q.rm(1, 0, n-1, posInChain[V]+1, posInChain[U])];
    if(val > ans) ans = val;
}

```

```

    return ans;
}

int getMax(int U, int V, LCA &ref, SegTree &q, int n){
    int lca = ref.getLCA(U, V, n), a=0, b=0;
    if(lca != U)
        a = walkChain(U, lca, q, n);
    if(lca != V)
        b = walkChain(V, lca, q, n);
    return max(a, b);
}

void update(int a, int b, int c, SegTree &q, int n){
    if(level[a] < level[b]){//update b
        q.update(1, 0, n-1, posInChain[b], c);
    }else{//update a
        q.update(1, 0, n-1, posInChain[a], c);
    }
}

void add(int a, int b, int c){
    g[a].push_back(make_pair(b, c));
    g[b].push_back(make_pair(a, c));
}

int n, t, from[MAXN], to[MAXN], cost[MAXN], A, B;
char TYPE[20];

int main(void){
    scanf("%d", &t);
    while(t--){
        scanf("%d", &n);
        chainIdx = idxSegTree = idx = 0;
        for(int i = 0; i <= n; i++){
            cnt[i] = prev[i] = chainNode[i] = base[i] =
            level[i] = 0;
            chainHead[i] = posInChain[i] = H[i] = -1;
            g[i].clear();
        }
        memset(L, 0, sizeof(L));
        memset(E, 0, sizeof(E));
        for(int i = 0; i < n - 1; i++){
            scanf("%d%d%d", &from[i], &to[i], &cost[i]);
            from[i]--;
            to[i]--;
            add(from[i], to[i], cost[i]);
        }
    }
}

```

```

    }
    dfsCnt(0,-1);
    LCA lca(0,n);
    HLD(0,-1, -1);
    SegTree query;
    query.build(1,0,n-1);
    while(1){
        scanf("%s", TYPE);
        if(TYPE[0] == 'D') break;
        scanf("%d%d", &A, &B);
        A--;
        if(TYPE[0] == 'Q'){
            B--;
            printf("%d\n", getMax(A, B, lca, query, n));
        }else if(TYPE[0] == 'C'){
            update(from[A], to[A], B, query, n);
        }
    }
    return 0;
}

```

32. Highly Decomposite Number

```

bool p[MAXN];
vector<int> primes;

void build(void) {
    memset(p, true, sizeof(p));

    for (int i = 2; i <= MAXN; i++) {
        if (p[i]) {
            primes.push_back(i);
            for (int j = i * i; j <= MAXN; j += i) {
                p[j] = false;
            }
        }
    }
}

int func(Int x) {
    int ans = 1;

```

```

        for (int i = 0; i < (int) primes.size() && x > 1; i++) {
            if (x % primes[i] == 0) {
                int curr = 0;
                while (x % primes[i] == 0) {
                    x /= primes[i];
                    curr += 1;
                }
                ans *= (curr + 1);
            }
        }
        return ans;
    }

    set<Int> st;

    void go(int id, Int v, int last) {
        Int base = primes[id];
        if (v > MAXV) return;
        st.insert(v);

        for (int i = 0; i <= last; i++) {
            v *= (Int) base;
            if (v > MAXV) break;
            go(id + 1, v, i);
        }
    }

    vector<Int> ans;

    for (set<Int>::iterator it = st.begin(); it != st.end(); it++) {
        int s = func(*it);
        if (s > curr) {
            ans.push_back(*it);
            curr = s;
        }
    }
}

```

33. KD-Tree

```

struct point {
    Int x, y, z;
    point(Int x=0, Int y=0, Int z=0): x(x), y(y), z(z) {}

```

```

    point operator-(point q) { return point(x-q.x, y-q.y, z-q.z); }
    Int operator*(point q) { return x*q.x + y*q.y + z*q.z; }
};

typedef vector<point> polygon;

struct KDTreeNode {
    point p;
    int level;
    KDTreeNode *below, *above;

    KDTreeNode (const point& q, int lev1) {
        p = q;
        level = lev1;
        below = above = 0;
    }
    ~KDTreeNode() { delete below, above; }

    int diff (const point& pt) {
        switch (level) {
            case 0: return pt.x - p.x;
            case 1: return pt.y - p.y;
            case 2: return pt.z - p.z;
        }
        return 0;
    }

    Int distSq (point& q) { return (p-q)*(p-q); }

    int rangeCount (point& pt, Int K) {
        int count = (distSq(pt) < K*K) ? 1 : 0;
        int d = diff(pt);
        if (-d <= K && above != 0)
            count += above->rangeCount(pt, K);
        if (d <= K && below != 0)
            count += below->rangeCount(pt, K);
        return count;
    }
};

class KDTree {
public:
    polygon P;
    KDTreeNode *root;
    int dimation;
    KDTree() {}
    KDTree(polygon &poly, int D) {

```

```

        P = poly;
        dimation = D;
        root = 0;
        build();
    }
    ~KDTree() { delete root; }

    //count the number of pairs that has a distance less than K
    Int countPairs(Int K) {
        Int count = 0;
        f(i, 0, P.size())
            count += root->rangeCount(P[i], K) - 1;
        return count;
    }

protected:
    void build() {
        random_shuffle(all(P));
        f(i, 0, P.size()) {
            root = insert(root, P[i], -1);
        }
    }

    KDTreeNode *insert(KDTreeNode* t, const point& pt, int parentLevel) {
        if (t == 0) {
            t = new KDTreeNode (pt, (parentLevel+1) % dimation);
            return t;
        } else {
            int d = t->diff(pt);
            if (d <= 0) t->below = insert (t->below, pt, t->level);
            else t->above = insert (t->above, pt, t->level);
        }
        return t;
    }
};

int main() {
    int n, k;
    point e;
    polygon p;
    while (cin >> n >> k && n+k) {
        p.clear();
        f(i, 0, n) {
            cin >> e.x >> e.y >> e.z;
            p.pb(e);
        }
    }
}

```

```

    KDTree tree(p, 3);
    cout << tree.countPairs(k) / 2LL << endl;
}
return 0;
}

```

34. Kadane 2D

```

//Kadane 2D
for (int i = 1; i <= N; i++) {
    for (int j = 1; j <= N; j++) {
        cin >> M[i][j];
    }
    for (int j = 1; j <= N; j++) {
        dp[i][j] = dp[i][j - 1] + M[i][j];
    }
}

int ans = -INT_MAX / 3;
for (int i = 1; i <= N; i++) {
    for (int j = i; j <= N; j++) {
        int sum = 0;
        for (int k = 1; k <= N; k++) {
            sum += dp[k][j] - dp[k][i - 1];
            chmax(ans, sum);
            if (sum < 0) sum = 0;
        }
    }
}

```

35. Knuth Morris Pratt

```

vector<int> KMP(string S, string K) {
    vector<int> T(K.size() + 1, -1);
    vector<int> matches;

    if(K.size() == 0) {
        matches.push_back(0);
        return matches;
    }
}

```

```

}
for(int i = 1; i <= K.size(); i++) {
    int pos = T[i - 1];
    while(pos != -1 && K[pos] != K[i - 1]) pos = T[pos];
    T[i] = pos + 1;
}

int sp = 0;
int kp = 0;
while(sp < S.size()) {
    while(kp != -1 && (kp == K.size() || K[kp] != S[sp])) kp = T[kp];
    kp++;
    sp++;
    if(kp == K.size()) matches.push_back(sp - K.size());
}

return matches;
}

```

36. Kosaraju Algorithm

```

//ga -> Regular Adjacency List
//gb -> Transposed Adjacency List

void dfs1(int x) {
    used[x] = 1;
    for(int b = 0; b < g[x].size(); b++) {
        if(!used[g[x][b]]) dfs1(g[x][b]);
    }
    order.push_back(x);
}

void dfs2(int x) {
    used[x] = 1;
    comonent.insert(x);
    for(int b = 0; b < gr[x].size(); b++) {
        if(!used[gr[x][b]]) dfs2(gr[x][b]);
    }
}

//Topological Sort
for (int i = 1; i <= n; i++) if(!used[i]) dfs1(i);

```

```
//Get components
for(int i = 0; i < order.size(); i++) {
    int v = order[i];
    if(!used[v]) {
        dfs2(v);
        ans++;
        component.clear();
    }
}
```

37. Kruskal Algorithm

```
//Kruskal Algorithm
struct edge {
    int from, to, cost;
    edge() {}
    edge(int from, int to, int cost): from(from), to(to), cost(cost) {};

    bool operator<(const edge& e) const {
        return cost < e.cost;
    }
};

//Sendo 'M' o numero de arestas, 'u' uma implementao do conjunto disjunto
//'UnionFind' e 'ans' o menor custo
vector<edge> edges; //Populado com as arestas
int ans = 0;
UnionFind u(N);
for(i = 0; i < m; i++) {
    if(!u.find(edges[i].from, edges[i].to)) {
        u.unite(edges[i].from, edges[i].to);
        ans += edges[i].cost;
    }
}
```

38. LCA with Segment Tree

```
//LCA using segment tree
int H[MAXN], L[MAXN << 1], E[MAXN << 1], vis[MAXN], tree[MAXN * 8],
    path[MAXN << 1];
```

```
vector<vector<pair<int, int> > > g(MAXN);

void dfs(int x, int depth){
    vis[x] = 1; //visited
    if(H[x] == -1) H[x] = idx; //mark first time the i'th node is
        visited
    L[idx] = depth; //when you visit a node you should mark the the
        depth you have found it.
    E[idx++] = x; //the i'th recursion, global variable
    for(int i = 0; i < g[x].size(); i++){
        int next = g[x][i].first;
        if(!vis[next]){
            path[next] = x;
            dfs(next, depth+1);
            L[idx] = depth;
            E[idx++] = x;
        }
    }
}

//NlogN build the segtree and minimize the height of the I'th visited node
void build(int node, int l, int r){
    if(l > r) return;
    if(l == r){
        tree[node] = l;
    }else{
        int mid = (l+r) >> 1;
        build(node*2, l, mid);
        build(node*2+1, mid+1, r);
        int A = tree[node*2];
        int B = tree[node*2+1];
        if(L[A] <= L[B]){
            tree[node] = A;
        }else{
            tree[node] = B;
        }
    }
}

//Get the vertex with the minimum height, then it will be the LCA of A
//and B.
int rmq(int node, int l, int r, int ra, int rb){
    if(l > rb || r < ra){
        return -1;
    }else if(l >= ra && r <= rb){
```

```

        return tree[node];
    }else{
        int mid = (l+r) >> 1;
        int q1 = rmq(node*2, l, mid, ra, rb);
        int q2 = rmq(node*2+1, mid+1, r, ra, rb);
        if(q1 == -1){
            return q2;
        }else if(q2 == -1){
            return q1;
        }else{
            if(L[q1] <= L[q2]){
                return q1;
            }else{
                return q2;
            }
        }
    }
}

idx = 0;
for(int i = 0; i <= n; i++){
    g[i].clear();
    H[i] = -1;
    L[i] = E[i] = vis[i] = 0;
    path[i] = -1;
}

dfs(0,0);
build(1, 0, 2*n-1);
for(int i = 0; i < k; i++){
    scanf("%d%d", &u, &v);
    u--;
    v--;
    int goFrom = H[u];
    int goTo = H[v];
    if(goFrom > goTo){
        swap(goFrom, goTo);
    }
    int lcaAB = E[rmq(1, 0, 2*n-1, goFrom, goTo)]; //is the LCA of A
    and B;
}

```

39. LCA with Sparse Table

```

//LCA O(<Nlog(N)>, <log(N)>)
int N, Q, A, B;
vector<pair<int, int> > adj[MAXN];
int parent[MAXN], L[MAXN], vis[MAXN];
vector<int> level[MAXN];
int P[MAXN][20];
int dist[MAXN];

void dfs(int pos, int par){
    if(parent[pos] == -1){
        parent[pos] = par;

        for(int i = adj[pos].size() - 1; i >= 0; --i){
            to = adj[pos][i].first;
            if(to != par) {
                dist[to] = dist[pos] + adj[pos][i].second;
                dfs(to, pos);
            }
        }
    }
}

int get_level(int u){
    if(L[u] != -1) return L[u];
    else if(parent[u] == -1) return 0;
    return 1 + get_level(parent[u]);
}

void init() {
    for(int i = 0; i < N; ++i) {
        L[i] = get_level(i);
    }

    for(int i = 0; i < N; ++i) {
        level[L[i]].push_back(i);
    }

    memset(P, -1, sizeof(P));

    for(int i = 0; i < N; ++i) {
        P[i][0] = parent[i];
    }

    for(int j = 1; (1 << j) < N; ++j) {

```



```

        for(int i = 0; i < N; ++i) {
            if(P[i][j-1] != -1) {
                P[i][j] = P[P[i][j-1]][j-1];
            }
        }
    }

int LCA(int p, int q) {
    if(L[p] < L[q]) {
        swap(p,q);
    }

    int log = 1;
    while((1<<log)<=L[p]) ++log;
    --log;

    for(int i = log; i>=0; --i)
        if(L[p] - (1<<i) >= L[q])
            p = P[p][i];

    if (p==q) return p;

    for(int i = log; i>=0; --i){
        if(P[p][i] != -1 && P[q][i] != P[p][i]){
            p = P[p][i];
            q = P[q][i];
        }
    }

    return parent[p];
}

for (i = 0; i <= N; i++) {
    vis[i] = 0;
    L[i] = parent[i] = -1;
    dist[i] = 0LL;
    adj[i].clear();
}

for (i = 1; i < N; i++) {
    scanf("%d%d", &t, &l);
    adj[i].push_back(make_pair(t, l));
    adj[t].push_back(make_pair(i, l));
}

```

```

dfs(0, -2);
parent[0] = -1;
init();

```

40. Line Point Distance

```

//Distance between point - line
double dot(pair<int, int> &A, pair<int, int> &B, pair<int, int> &C) {
    return (double) (B.first - A.first) * (C.first - B.first) + (B.second
        - A.second) * (C.second - B.second);
}

double cross(pair<int, int> &A, pair<int, int> &B, pair<int, int> &C) {
    return (double) (B.first-A.first) * (C.second-A.second) -
        (B.second-A.second) * (C.first-A.first);
}

double _distance(pair<int, int> A, pair<int, int> B) {
    int d1 = A.first - B.first;
    int d2 = A.second - B.second;
    return sqrt(d1*d1+d2*d2);
}

double linePointDist(pair<int, int> A, pair<int, int> B, pair<int, int>
    C, bool isSegment) {
    double dist = cross(A,B,C) / _distance(A,B);
    if(isSegment) {
        int dot1 = dot(A,B,C);
        if(dot1 > 0) return _distance(B,C);
        int dot2 = dot(B,A,C);
        if(dot2 > 0) return _distance(A,C);
    }
    return abs(dist);
}

```

41. Line Point Intesection

```

struct Point
{

```

```

    int x;
    int y;
};

// Given three colinear points p, q, r, the function checks if
// point q lies on line segment 'pr'
bool onSegment(Point p, Point q, Point r) {
    if (q.x <= max(p.x, r.x) && q.x >= min(p.x, r.x) &&
        q.y <= max(p.y, r.y) && q.y >= min(p.y, r.y)) {
        return true;
    }

    return false;
}

// To find orientation of ordered triplet (p, q, r).
// The function returns following values
// 0 --> p, q and r are colinear
// 1 --> Clockwise
// 2 --> Counterclockwise
int orientation(Point p, Point q, Point r) {
    // See 10th slides from following link for derivation of the formula
    // http://www.dcs.gla.ac.uk/~pat/52233/slides/Geometry1x1.pdf
    int val = (q.y - p.y) * (r.x - q.x) -
              (q.x - p.x) * (r.y - q.y);

    if (val == 0) return 0; // colinear

    return (val > 0)? 1: 2; // clock or counterclock wise
}

// The main function that returns true if line segment 'p1q1'
// and 'p2q2' intersect.
bool doIntersect(Point p1, Point q1, Point p2, Point q2)
{
    // Find the four orientations needed for general and
    // special cases
    int o1 = orientation(p1, q1, p2);
    int o2 = orientation(p1, q1, q2);
    int o3 = orientation(p2, q2, p1);
    int o4 = orientation(p2, q2, q1);

    // General case
    if (o1 != o2 && o3 != o4)
        return true;

```

```

    // Special Cases
    // p1, q1 and p2 are colinear and p2 lies on segment p1q1
    if (o1 == 0 && onSegment(p1, p2, q1)) return true;

    // p1, q1 and p2 are colinear and q2 lies on segment p1q1
    if (o2 == 0 && onSegment(p1, q2, q1)) return true;

    // p2, q2 and p1 are colinear and p1 lies on segment p2q2
    if (o3 == 0 && onSegment(p2, p1, q2)) return true;

    // p2, q2 and q1 are colinear and q1 lies on segment p2q2
    if (o4 == 0 && onSegment(p2, q1, q2)) return true;

    return false; // Doesn't fall in any of the above cases
}

```

42. Linha de Paretto - (LIS 2D)

```

#include <stdio.h>
#include <set>
#include <vector>
#include <algorithm>
using namespace std;
#define MAX 100010
#define inf 2000000000
struct no{
    int x,y;
};

no v[MAX];
int n;
set <pair<int,int> > S[MAX];
int topo;
set <pair<int, int> > :: iterator it, it2, ini, fim;
vector <pair<int, int> > aux;

bool cobre (pair <int, int> p, int s){
    it2 = S[s].lower_bound (make_pair (p.first-1, inf));
    if (it2 == S[s].begin()) return false;
    it2--;
    if (p.second > (*it2).second) return true;
}

```

```

    return false;
}

int main (){
    pair <int, int> p;
    topo = 0;
    scanf("%d", &n);
    for (int i = 0; i < n; i++){
        scanf("%d %d", &v[i].x, &v[i].y);
    }
    for (int i = 0; i < n; i++) S[i].clear();
    int ans = 0;

    p = make_pair (v[0].x, v[0].y);
    S[topo++].insert (p);

    for (int i = 1; i < n; i++){
        /*cria o pair do ponto i*/
        p = make_pair (v[i].x, v[i].y);
        /*busca*/
        /*verifica se ele cobre a ultima linha de parreto*/
        if (cobre(p, topo-1)){
            S[topo++].insert (p);
            continue;
        }
        /*faz busca binaria pra descobrir menor linha q ele nao cubra
        ninguem*/
        int u = 0, v = topo-1;
        while (u < v-1){
            int mid = (u+v)/2;
            if (cobre(p, mid)) u = mid;
            else v = mid;
        }
        int quem;
        if (cobre (p, u)) quem = v;
        else quem = u;
        /*insercao*/
        /*insere na linha de parreto, removendo quem for necessario*/
        aux.clear();
        ini = S[quem].lower_bound (make_pair (p.first-1, inf));

        if (ini != S[quem].begin()){
            ini--;
            if ((*ini).second <= p.second) continue;
            ini++;

```

```

        }
        for (it = ini; it != S[quem].end() && (*it).second > p.second;
            it++){
            aux.push_back(*it);
        }
        for (int j = 0; j < aux.size(); j++){
            S[quem].erase(S[quem].find(aux[j]));
        }
        ans++;
        S[quem].insert (p);
    }
    printf("%d\n", topo);
    return 0;
}

```

43. Longest Common Subsequence - Efficient

```

//Longest Common Subsequence - (LCS)  $O(n^2)$  -  $O(n)$  in space
int m[2][1000]; // instead of [1000][1000]
for (i = M; i >= 0; i--) {
    int ii = i&1;
    for (int j = N; j >= 0; j--) {
        if (i == M || j == N) {
            m[ii][j]=0; continue;
        }
        if (s1[i] == s2[j]) {
            m[ii][j] = 1 + m[1-ii][j+1];
        } else {
            m[ii][j] = max(m[ii][j+1], m[1-ii][j]);
        }
    }
}
cout<<m[0][0];

```

44. Longest Common Subsequence

```

//Longest Common Subsequence - (LCS)  $O(N^2)$ 
int lcs(string a, string b) {
    int n = a.size(), m = b.size();

```

```

int[][] dp = new dp[n+1][m+1];

for(int i = 0; i <= max(n, m); i++) {
    dp[i][0] = dp[0][i] = 0;
}
for(int i = 1; i <= n; i++) {
    for(int j = 1; j <= m; j++) {
        if(a[i] == b[j]) {
            dp[i][j] = dp[i - 1][j - 1] + 1;
        } else {
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }
}
return dp[n][m];
}

```

45. Longest Increasing Subsequence $O(n \cdot \log(n))$

```

vector<int> data;

vector<int> A, pos;
vector<int>::iterator it;
A.push_back(data[0]);

pos = vector<int>(data.size(), 0);
int n = data.size(), LIS = 1;

for (int i = 1; i < n; ++i) {
    it = lower_bound(A.begin(), A.end(), data[i]);
    pos[i] = (int)(it - A.begin());
    get_max(LIS, pos[i]);
    if (it == A.end()) {
        A.push_back(data[i]);
    } else {
        *it = data[i];
    }
}

for (int i = n - 1; i >= 0; --i) {
    if (pos[i] == LIS) {
        A[LIS--] = data[i];
    }
}

```

```

}
printf("%d\n", (int)A.size());
for (int i = 0; i < A.size(); ++i) {
    printf("%d\n", A[i]);
}

```

46. Longest Increasing Subsequence $O(n^2)$

```

int lis(int array[], int n) {
    int best[n], prev[n];

    for(int i = 0; i < n; i++) {
        best[i] = 1;
        prev[i] = i;
    }

    for(int i = 1; i < n; i++) {
        for(int j = 0; j < i; j++) {
            if(array[i] > array[j] && best[i] < best[j] + 1) {
                best[i] = best[j] + 1; prev[i] = j;
            }
        }
    }

    int ans = 0; for(int i = 0; i < n; i++) ans = max(ans, best[i]);
    return ans;
}

```

47. Manacher Algorithm

```

//Manacher Algorithm (Longest Palindromic Substring)
string preProcess(string s) {
    int n = s.length();
    if (n == 0) return "^$";
    string ret = "^";
    for (int i = 0; i < n; i++)
        ret += "#" + s.substr(i, 1);

    ret += "#$";
    return ret;
}

```

```

}

vector<int> manacher(string s) {
    string T = preProcess(s);
    int n = T.length();
    vector<int> P(n);

    int C = 0, R = 0;
    for (int i = 1; i < n-1; i++) {
        int i_mirror = 2*C-i;

        P[i] = (R > i) ? min(R-i, P[i_mirror]) : 0;

        while (T[i + 1 + P[i]] == T[i - 1 - P[i]]) {
            P[i]++;
        }

        if (i + P[i] > R) {
            C = i;
            R = i + P[i];
        }
    }

    int maxLen = 0;
    int centerIndex = 0;
    for (int i = 1; i < n-1; i++) {
        if (P[i] > maxLen) {
            maxLen = P[i];
            centerIndex = i;
        }
    }

    //to return actual longest substring
    // return s.substr((centerIndex - 1 - maxLen)/2, maxLen);
    // P[i] is the length of the largest palindrome centered at i
    return P;
}

```

48. Mathematical Expression Solver

```

//Solver for mathematical expressions
void doOp(stack<double> &num, stack<char> &op){
    double A = num.top(); num.pop();

```

```

    double B = num.top(); num.pop();
    char oper = op.top(); op.pop();
    double ans;
    if(oper == '+'){
        ans = A+B;
    }else if(oper == '-'){
        ans = B-A;
    }else if(oper == '*'){
        ans = A*B;
    }else{
        if(A != 0){
            ans = B/A;
        }else{
            //division by 0
            ans = -1;
        }
    }
    num.push(ans);
}

double parse(string s){
    stack<char> op;
    stack<double> num;
    map<char,int> pr;

    //setting the priorities, greater values with higher pr
    pr['+'] = 0;
    pr['-'] = 0;
    pr['*'] = 1;
    pr['/'] = 1;

    for (int i = 0; i < s.size(); i++){
        if (s[i] == '('){
            while(!op.empty() && op.top() != '('){
                doOp(num,op);
            }
            op.pop();
        } else if(s[i] == '('){
            op.push('(');
        } else if(!(s[i] >= '0' && s[i] <= '9')){
            while(!op.empty() && pr[s[i]] <= pr[op.top()]) && op.top() != '('){
                doOp(num,op);
            }
            op.push(s[i]);

```

```

    } else {
        double ans = 0;
        while(i < s.size() && s[i] >= '0' && s[i] <= '9'){
            ans = ans * 10 + (s[i] - '0');
            i++;
        }
        i--;
        num.push(ans);
    }
}
while (op.size()) {
    doOp(num,op);
}
return num.top();
}

```

49. Matrix Multiplication

```

vector<vector<int>> > multiply(vector<vector<int>> > a, vector<vector<int>>
> b) {
    vector<vector<int>> > res(c, vector<int>(c));
    for(int i = 0; i < c; i++) {
        for(int j = 0; j < c; j++) {
            int sum = 0;
            for (int k = 0; k < c; k++) {
                sum += a[i][k] & b[k][j];
            }
            res[i][j] = sum;
        }
    }
    return res;
}

vector<vector<int>> > binPow(vector<vector<int>> > a, int n) {
    if (n == 1) {
        return a;
    } else if ((n & 1) != 0) {
        return multiply(a, binPow(a, n - 1));
    } else {
        vector<vector<int>> > b = binPow(a, n / 2);
        return multiply(b, b);
    }
}

```

```

}

```

50. Maximum Bipartite Matching

```

//Maximum Bipartite Matching (Prefereed implementation)
vector<int> graph[MAXN];

```

```

bool bpm(int u, bool seen[], int matchR[]) {
    for (int i = 0; i < (int) graph[u].size(); i++) {
        int v = graph[u][i];

        if (!seen[v]) {
            seen[v] = true;

            if (matchR[v] < 0 || bpm(matchR[v], seen, matchR)) {
                matchR[v] = u;
                return true;
            }
        }
    }
    return false;
}

int maxBPM() {
    int matchR[MAXN];

    memset(matchR, -1, sizeof(matchR));

    int result = 0;
    for (int u = 1; u <= C; u++) {
        bool seen[MAXN];
        memset(seen, 0, sizeof(seen));

        if (bpm(u, seen, matchR)) {
            result++;
        }
    }
    return result;
}

```

51. Median Online Algorithm

```
//Get median of a sequence in O(log(n))
int median_retrieve(void) {
    if (minHeap.empty() && maxHeap.empty()) return 0;

    if (minHeap.size() == maxHeap.size()) {
        return min(minHeap.top(), maxHeap.top());
    } else {
        if (minHeap.size() > maxHeap.size()) {
            return minHeap.top();
        } else {
            return maxHeap.top();
        }
    }
}

void median_insert(int x) {
    if (x > median_retrieve()) {
        minHeap.push(x);
    } else {
        maxHeap.push(x);
    }

    while (abs((int) (minHeap.size() - maxHeap.size())) > 1) {
        if (minHeap.size() > maxHeap.size()) {
            int tmp = minHeap.top();
            minHeap.pop();
            maxHeap.push(tmp);
        } else {
            int tmp = maxHeap.top();
            maxHeap.pop();
            minHeap.push(tmp);
        }
    }
}
```

52. Merge Sort

```
//Merge-Sort O(N log N)
vector<int> merge(vector<int>& b, vector<int>& c) {
    vector<int> a;
```

```
    while(!b.empty() && !c.empty()) {
        if(*b.begin() < *c.begin()) {
            a.push_back(*b.begin());
            b.erase(b.begin());
        } else if(*b.begin() > *c.begin()) {
            a.push_back(*c.begin());
            c.erase(c.begin());
        } else {
            a.pb(*b.begin());
            a.pb(*c.begin());
            b.erase(b.begin());
            c.erase(c.begin());
        }
    }
    while(!b.empty()) { a.pb(*b.begin()); b.erase(b.begin()); }
    while(!c.empty()) { a.pb(*c.begin()); c.erase(c.begin()); }
    return a;
}

vector<int> mergeSort(vector<int>& a) {
    if(sz(a) <= 1) {
        return a;
    }
    vector<int> b;
    vector<int> c;

    for(int i = 0; i < sz(a) / 2; i++) {
        b.pb(a[i]);
    }
    for(int i = sz(a) / 2; i < sz(a); i++) {
        c.pb(a[i]);
    }
    vector<int> sb = mergeSort(b);
    vector<int> sc = mergeSort(c);
    return merge(sb, sc);
}
```

53. Min Cost Max Flow

```
typedef int Flow;
typedef int Cost;
```

```

const Flow INF = 0x3f3f3f3f;
struct Edge {
    int src, dst;
    Cost cst;
    Flow cap;
    int rev;
};
bool operator<(const Edge a, const Edge b) {
    return a.cst > b.cst;
}

typedef vector<Edge> Edges;
typedef vector<Edges> Graph;

void add_edge(Graph&G, int u, int v, Flow c, Cost l) {
    G[u].push_back((Edge){ u, v, l, c, int(G[v].size()) });
    G[v].push_back((Edge){ v, u, -l, 0, int(G[u].size()-1) });
}

pair<Flow, Cost> flow(Graph&G, int s, int t, int K) {
    int n = G.size();
    Flow flow = 0;
    Cost cost = 0;
    for ( ; ; ) {
        priority_queue<Edge> Q;
        vector<int> prev(n, -1), prev_num(n, -1);
        vector<Cost> length(n, INF);
        Q.push((Edge){-1,s,0,0,0});
        prev[s]=s;
        for (;!Q.empty(); ) {
            Edge e=Q.top();
            Q.pop();
            int v = e.dst;
            for (int i=0; i<(int)G[v].size(); i++) {
                if (G[v][i].cap>0 &&
                    length[G[v][i].dst]>e.cst+G[v][i].cst) {
                    prev[G[v][i].dst]=v;
                    Q.push((Edge){v, G[v][i].dst, e.cst+G[v][i].cst,0,0});
                    prev_num[G[v][i].dst]=i;
                    length[G[v][i].dst]=e.cst+G[v][i].cst;
                }
            }
        }
        if (prev[t]<0) return make_pair(flow, cost);
    }
}

```

```

Flow mi=INF;
Cost cst=0;
for (int v=t; v!=s; v=prev[v]) {
    mi=min(mi, G[prev[v]][prev_num[v]].cap);
    cst+=G[prev[v]][prev_num[v]].cst;
}

K -= cst*mi;
cost+=cst*mi;

for (int v=t; v!=s; v=prev[v]) {
    Edge &e=G[prev[v]][prev_num[v]];
    e.cap-=mi;
    G[e.dst][e.rev].cap+=mi;
}
flow += mi;
}
}

```

54. Minimal Lexicographical Rotation $O(n)$

```

string min_lex (string s){
    int n = s.size();
    s = s + s;
    int mini = 0, p = 1, l = 0;

    while(p < n && mini + l + 1 < n)
        if(s[mini + l] == s[p + l])
            l++;
        else if(s[mini + l] < s[p + l]){
            p = p + l + 1;
            l = 0;
        }
        else if(s[mini + l] > s[p + l]){
            mini = max(mini + l + 1, p);
            p = mini + 1;
            l = 0;
        }
    s = s.substr(mini, n);
    return s;
}

```


55. Mod Pow

```
//modpow(a, n, mod) - calcula a^n % mod de maneira eficiente
int modpow(int a, int n, int mod) {
    int res = 1;
    while (n) {
        if (n&1) {
            res=(res*a)%mod;
        }
        a=(a*1ll*a)%mod;
        n>>=1;
    }
    return res;
}
```

56. Modular Inverse for Primes

```
/* This function calculates (a^b)%MOD */
int pow(int a, int b, int MOD) {
    int x = 1, y = a;
    while(b > 0) {
        if(b%2 == 1) {
            x=(x*y);
            if(x>MOD) x%=MOD;
        }
        y = (y*y);
        if(y>MOD) y%=MOD;
        b /= 2;
    }
    return x;
}

int modInverse(int a, int m) {
    return pow(a,m-2,m);
}
```

57. N-th Palindrome Number

```
//Return the N-th palindromic number
```

```
std::string number_palindrome(int N) {
    if(N < 10){
        return std::string(1, char('0' + N));
    }
    long long sum = 0, digits = 1, v;
    for(; ; digits++){
        if(digits % 2 == 0){
            v = std::pow(10, digits/2-1) * 9;
        }else{
            v = std::pow(10, (digits+1)/2-1) * 9;
        }
        if(v + sum >= N) break;
        sum += v;
    }
    //I have to find the M-th palindromic number with X digits:
    long long Mth = N-sum;
    long long sz = (digits+1) / 2;
    long long pattern = std::pow(10, sz-1);
    pattern += (Mth-1);
    std::vector<int> tmp;
    while(pattern > 0){
        tmp.insert(tmp.begin(), pattern % 10);
        pattern /= 10;
    }
    int idx = digits-tmp.size() - 1;
    std::string ans = "";
    for(int i = 0; i < tmp.size(); i++){
        ans += std::string(1, char('0' + tmp[i]));
    }
    for(;idx >= 0;){
        ans += std::string(1, char('0' + tmp[idx--]));
    }
    return ans;
}
```

58. Next Permutation in Java

```
boolean next_permutation(int[] p) {
    for (int a = p.length - 2; a >= 0; --a)
        if (p[a] < p[a + 1])
            for (int b = p.length - 1; --b)
```

```

        if (p[b] > p[a]) {
            int t = p[a];
            p[a] = p[b];
            p[b] = t;
            for (++a, b = p.length - 1; a < b;
                ++a, --b) {
                t = p[a];
                p[a] = p[b];
                p[b] = t;
            }
            return true;
        }

return false;
}

```

59. Order Statistics Tree - STL

```

//Order statistics tree inside STL
#include<bits/stdc++.h>
#include<ext/pb_ds/assoc_container.hpp>
#include<ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
using namespace std;
template <typename T>
using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

int main(){
    ordered_set<int> s;
    s.insert(1);
    s.insert(3);
    cout << s.order_of_key(2) << endl; // the number of elements in
    the s less than 2
    cout << *s.find_by_order(0) << endl; // print the 0-th smallest
    number in s(0-based)
}

```

60. Palindromic Check with DP

```

//Checa por Palindromos
int T, N, dp[MAXN][MAXN];
char str[MAXN];

for (int i = 0; i < N; i++) {
    dp[i][i] = 1;
    if(i + 1 < N) dp[i][i + 1] = str[i] == str[i + 1];
}
for(int k = 2; k < N; k++) {
    for (int i = 0; i < N - k; i++) {
        dp[i][i + k] = dp[i + 1][i + k - 1] && str[i] == str[i + k];
    }
}

```

61. Point Inside Triangle

```

/* A utility function to calculate area of triangle formed by (x1, y1),
(x2, y2) and (x3, y3) */
float area(int x1, int y1, int x2, int y2, int x3, int y3) {
    return abs((x1*(y2-y3) + x2*(y3-y1)+ x3*(y1-y2))/2.0);
}

/* A function to check whether point P(x, y) lies inside the triangle
formed
by A(x1, y1), B(x2, y2) and C(x3, y3) */
bool isInside(int x1, int y1, int x2, int y2, int x3, int y3, int x, int
y) {
    /* Calculate area of triangle ABC */
    float A = area (x1, y1, x2, y2, x3, y3);

    /* Calculate area of triangle PBC */
    float A1 = area (x, y, x2, y2, x3, y3);

    /* Calculate area of triangle PAC */
    float A2 = area (x1, y1, x, y, x3, y3);

    /* Calculate area of triangle PAB */
    float A3 = area (x1, y1, x2, y2, x, y);

    /* Check if sum of A1, A2 and A3 is same as A */
    return (A == A1 + A2 + A3);
}

```

62. Prim Algorithm

```
int g[MAXN][MAXN], used[MAXN], min_e[MAXN], sel_e[MAXN];
min_e[0] = 0;
for (int i = 0; i < n; ++i) {
    int v = -1;
    for(int j = 0; j < n; ++j) {
        if (!used[j] && (v == -1 || min_e[j] < min_e[v])) {
            v = j;
        }
    }
    used[v] = true;
    if (sel_e[v] != -1) {
        ans += min_e[v];
    }
    for (int to = 0; to < n; ++to) {
        if (g[v][to] < min_e[to]) {
            min_e[to] = g[v][to];
            sel_e[to] = v;
        }
    }
}
```

63. Quicksort

//Worst Case $O(n^2)$ but usually $O(n \log(n))$

```
void quicksort(int lo, int hi) {
    int i=lo, j=hi, h;

    int x=a[(lo+hi)/2];

    do {
        while (a[i]<x) i++;
        while (a[j]>x) j--;
        if (i<=j) {
            swap(a[i], a[j]);
            i++;
            j--;
        }
    } while (i<=j);

    if (lo<j) quicksort(lo, j);
```

```
    if (i<hi) quicksort(i, hi);
}
```

64. Segment Tree - Lazy Propagation

```
void goDown(int node, int l, int r) {
    if (lazy[node]) {
        tree[node] += lazy[node];

        if (l != r) {
            lazy[2 * node] += lazy[node];
            lazy[2 * node + 1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

void build(int node, int l, int r) {
    if (l == r) {
        tree[node] = A[l];
    } else {
        int m = (l + r) / 2;

        build(2 * node, l, m);
        build(2 * node + 1, m + 1, r);

        tree[node] = max(tree[2 * node], tree[2 * node + 1]);
    }
}

int query(int node, int l, int r, int bl, int br) {
    goDown(node, l, r);
    if (l >= bl && r <= br) {
        return tree[node];
    } else if (l > br || r < bl) {
        return -INF;
    } else {
        int m = (l + r) / 2;

        int a = query(2 * node, l, m, bl, br);
        int b = query(2 * node + 1, m + 1, r, bl, br);
```

```

        return max(a, b);
    }
}

void update(int node, int l, int r, int bl, int br, int value) {
    goDown(node, l, r);
    if (l > r) {
        return;
    } else if (l > br || r < bl) {
        return;
    } else if (l >= bl && r <= br) {
        lazy[node] = value;
        goDown(node, l, r);
    } else {
        int m = (l + r) / 2;

        update(2 * node, l, m, bl, br, value);
        update(2 * node + 1, m + 1, r, bl, br, value);

        tree[node] = max(tree[2 * node], tree[2 * node + 1]);
    }
}

```

65. Segment Tree 2D

// Segment Tree 2D

```

pair<int, int> tree[4 * MAXN][4 * MAXN];

void build_y(int nx, int ny, int xl, int xr, int yl, int yr) {
    if (yl == yr) {
        if (xl == xr) {
            tree[nx][ny].first = tree[nx][ny].second =
                P[xl][yl];
        } else {
            tree[nx][ny].first = min(tree[2 * nx][ny].first,
                tree[2 * nx + 1][ny].first);
            tree[nx][ny].second = max(tree[2 * nx][ny].second,
                tree[2 * nx + 1][ny].second);
        }
    } else {

```

```

        int m = (yl + yr) / 2;

        build_y(nx, 2 * ny, xl, xr, yl, m);
        build_y(nx, 2 * ny + 1, xl, xr, m + 1, yr);

        tree[nx][ny].first = min(tree[nx][2 * ny].first,
            tree[nx][2 * ny + 1].first);
        tree[nx][ny].second = max(tree[nx][2 * ny].second,
            tree[nx][2 * ny + 1].second);
    }
}

void build_x(int nx, int xl, int xr) {
    if (xl > xr) {
        return;
    } else if (xl != xr) {
        int m = (xl + xr) / 2;

        build_x(2 * nx, xl, m);
        build_x(2 * nx + 1, m + 1, xr);
    }
    build_y(nx, 1, xl, xr, 0, M - 1);
}

pair<int, int> query_y(int nx, int ny, int xl, int xr, int yl, int yr,
    int bound_lx, int bound_rx, int bound_ly, int bound_ry) {
    if (yl > yr || yl > bound_ry || yr < bound_ly) {
        return make_pair(INF, -INF);
    } else if (yl >= bound_ly && yr <= bound_ry) {
        return tree[nx][ny];
    } else {
        int m = (yl + yr) / 2;

        pair<int, int> q1 = query_y(nx, 2 * ny, xl, xr, yl, m,
            bound_lx, bound_rx, bound_ly, bound_ry);
        pair<int, int> q2 = query_y(nx, 2 * ny + 1, xl, xr, m + 1,
            yr, bound_lx, bound_rx, bound_ly, bound_ry);

        return make_pair(min(q1.first, q2.first), max(q1.second,
            q2.second));
    }
}

pair<int, int> query_x(int nx, int ny, int xl, int xr, int yl, int yr,
    int bound_lx, int bound_rx, int bound_ly, int bound_ry) {

```

```

    if (xl > xr || xl > bound_rx || xr < bound_lx) {
        return make_pair(INF, -INF);
    } else if (xl >= bound_lx && xr <= bound_rx) {
        return query_y(nx, 1, xl, xr, 0, M - 1, bound_lx,
            bound_rx, bound_ly, bound_ry);
    } else {
        int m = (xl + xr) / 2;

        pair<int, int> q1 = query_x(2 * nx, ny, xl, m, yl, yr,
            bound_lx, bound_rx, bound_ly, bound_ry);
        pair<int, int> q2 = query_x(2 * nx + 1, ny, m + 1, xr, yl,
            yr, bound_lx, bound_rx, bound_ly, bound_ry);

        return make_pair(min(q1.first, q2.first), max(q1.second,
            q2.second));
    }
}

pair<int, int> query(int nx, int ny, int xl, int xr, int yl, int yr, int
    bound_lx, int bound_rx, int bound_ly, int bound_ry) {
    return query_x(1, 1, xl, xr, yl, yr, bound_lx, bound_rx, bound_ly,
        bound_ry);
}

void update_y(int nx, int ny, int xl, int xr, int yl, int yr, int posx,
    int posy, int value) {
    if (yl == yr) {
        if (xl == xr) {
            tree[nx][ny].first = tree[nx][ny].second = value;
        } else {
            tree[nx][ny].first = min(tree[2 * nx][ny].first,
                tree[2 * nx + 1][ny].first);
            tree[nx][ny].second = max(tree[2 * nx][ny].second,
                tree[2 * nx + 1][ny].second);
        }
    } else {
        int m = (yl + yr) / 2;

        if (posy <= m) {
            update_y(nx, 2 * ny, xl, xr, yl, m, posx, posy,
                value);
        } else {
            update_y(nx, 2 * ny + 1, xl, xr, m + 1, yr, posx,
                posy, value);
        }
    }
}

```

```

        tree[nx][ny].first = min(tree[nx][2 * ny].first,
            tree[nx][2 * ny + 1].first);
        tree[nx][ny].second = max(tree[nx][2 * ny].second,
            tree[nx][2 * ny + 1].second);
    }
}

void update_x(int nx, int ny, int xl, int xr, int yl, int yr, int posx,
    int posy, int value) {
    if (xl != xr) {
        int m = (xl + xr) / 2;

        if (posx <= m) {
            update_x(2 * nx, ny, xl, m, yl, yr, posx, posy,
                value);
        } else {
            update_x(2 * nx + 1, ny, m + 1, xr, yl, yr, posx,
                posy, value);
        }
    }
    update_y(nx, 1, xl, xr, 0, M - 1, posx, posy, value);
}

void update(int nx, int ny, int xl, int xr, int yl, int yr, int posx, int
    posy, int value) {
    return update_x(1, 1, xl, xr, yl, yr, posx, posy, value);
}

```

66. Sieve

```

//Crivo de Erastotenes Comum - (Todos os numeros primos <= N)
bool sieve(int n) {
    bool prime[n+1];
    fill(prime, prime + n + 1, true);
    prime[0] = false;
    prime[1] = false;

    int m = (int) sqrt(n);

    for(int i = 2; i <= m; i++) {
        if(prime[i]) {

```

```

        for (int k=i*i; k<=n; k+=i) {
            prime[k]=false;
        }
    }
    return prime;
}

```

67. Sliding Window RMQ Faster

//Sliding RMQ in O(N) - Faster (No use of STL)

```

int Q[MAXN];

Int maxSlidingWindow(Int A[], int n, int w, Int B[]) {
    int b = 0, e = 0;
    Int ans = OLL;
    for (int i = 0; i < n; i++) {
        while (!(b == e) && A[i] >= A[Q[e-1]]) {
            e -= 1;
        }
        Q[e++] = i;
    }
    for (int i = w; i < n; i++) {
        B[i-w] = A[Q[b]];
        ans += B[i-w];
        while (!(e == b) && A[i] >= A[Q[e-1]])
            e--;
        while (!(e == b) && Q[b] <= i-w)
            b += 1;
        Q[e++] = i;
    }
    ans += A[Q[b]];

    return ans;
}

```

68. Sliding Window RMQ

```

void maxSlidingWindow(int A[], int n, int w, int B[]) {

```

```

    deque<int> Q;
    for (int i = 0; i < w; i++) {
        while (!Q.empty() && A[i] >= A[Q.back()])
            Q.pop_back();
        Q.push_back(i);
    }
    for (int i = w; i < n; i++) {
        B[i-w] = A[Q.front()];
        while (!Q.empty() && A[i] >= A[Q.back()])
            Q.pop_back();
        while (!Q.empty() && Q.front() <= i-w)
            Q.pop_front();
        Q.push_back(i);
    }
    B[n-w] = A[Q.front()];
}

```

69. Smallest Inclusive String

//Menor string que contem duas strings S1 e S2 como subsequencia

```

char S1[MAXS], S2[MAXS];
int dp[MAXS][MAXS];

memset(dp, 0, sizeof(dp));

for (i = 1; i <= N; i++) {
    for (j = 1; j <= M; j++) {
        if (S1[i - 1] == S2[j - 1]) {
            dp[i][j] = dp[i - 1][j - 1] + 1;
        } else {
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }
}

string track(int i, int j) {
    if (i == 0 && j == 0) {
        return "";
    } else if (i == 0 && j > 0) {
        return track(i, j - 1) + S2[j - 1];
    } else if (i > 0 && j == 0) {

```

```

        return track(i - 1, j) + S1[i - 1];
    } else {
        if (S1[i - 1] == S2[j - 1]) {
            return track(i - 1, j - 1) + S1[i - 1];
        } else {
            if (dp[i][j - 1] > dp[i - 1][j]) {
                return track(i, j - 1) + S2[j - 1];
            } else {
                return track(i - 1, j) + S1[i - 1];
            }
        }
    }
}
}
}

```

70. Splay Tree

```

//Splay Tree
template< typename T, typename Comp = std::less< T > >
class splay_tree {
private:
    Comp comp;
    unsigned long p_size;

    struct node {
        node *left, *right;
        node *parent;
        T key;
        node( const T& init = T() ) : left( 0 ), right( 0 ), parent( 0 ),
            key( init ) { }
    } *root;

    void left_rotate( node *x ) {
        node *y = x->right;
        x->right = y->left;
        if( y->left ) y->left->parent = x;
        y->parent = x->parent;
        if( !x->parent ) root = y;
        else if( x == x->parent->left ) x->parent->left = y;
        else x->parent->right = y;
        y->left = x;
        x->parent = y;
    }
}

```

```

void right_rotate( node *x ) {
    node *y = x->left;
    x->left = y->right;
    if( y->right ) y->right->parent = x;
    y->parent = x->parent;
    if( !x->parent ) root = y;
    else if( x == x->parent->left ) x->parent->left = y;
    else x->parent->right = y;
    y->right = x;
    x->parent = y;
}

void splay( node *x ) {
    while( x->parent ) {
        if( !x->parent->parent ) {
            if( x->parent->left == x ) right_rotate( x->parent );
            else left_rotate( x->parent );
        } else if( x->parent->left == x && x->parent->parent->left ==
            x->parent ) {
            right_rotate( x->parent->parent );
            right_rotate( x->parent );
        } else if( x->parent->right == x && x->parent->parent->right ==
            x->parent ) {
            left_rotate( x->parent->parent );
            left_rotate( x->parent );
        } else if( x->parent->left == x && x->parent->parent->right ==
            x->parent ) {
            right_rotate( x->parent );
            left_rotate( x->parent );
        } else {
            left_rotate( x->parent );
            right_rotate( x->parent );
        }
    }
}

void replace( node *u, node *v ) {
    if( !u->parent ) root = v;
    else if( u == u->parent->left ) u->parent->left = v;
    else u->parent->right = v;
    if( v ) v->parent = u->parent;
}

node* subtree_minimum( node *u ) {

```

```

    while( u->left ) u = u->left;
    return u;
}

node* subtree_maximum( node *u ) {
    while( u->right ) u = u->right;
    return u;
}

public:
    splay_tree( ) : root( 0 ), p_size( 0 ) { }

    void insert( const T &key ) {
        node *z = root;
        node *p = 0;

        while( z ) {
            p = z;
            if( comp( z->key, key ) ) z = z->right;
            else z = z->left;
        }

        z = new node( key );
        z->parent = p;

        if( !p ) root = z;
        else if( comp( p->key, z->key ) ) p->right = z;
        else p->left = z;

        splay( z );
        p_size++;
    }

    node* find( const T &key ) {
        node *z = root;
        while( z ) {
            if( comp( z->key, key ) ) z = z->right;
            else if( comp( key, z->key ) ) z = z->left;
            else return z;
        }
        return 0;
    }

    void erase( const T &key ) {
        node *z = find( key );
        if( !z ) return;

```

```

        splay( z );

        if( !z->left ) replace( z, z->right );
        else if( !z->right ) replace( z, z->left );
        else {
            node *y = subtree_minimum( z->right );
            if( y->parent != z ) {
                replace( y, y->right );
                y->right = z->right;
                y->right->parent = y;
            }
            replace( z, y );
            y->left = z->left;
            y->left->parent = y;
        }

        delete z;
        p_size--;
    }

    const T& minimum( ) { return subtree_minimum( root )->key; }
    const T& maximum( ) { return subtree_maximum( root )->key; }

    bool empty( ) const { return root == 0; }
    unsigned long size( ) const { return p_size; }
};

```

71. Stoer Wagner Algorithm

```

//Global Min-Cut Stoer-Wager  $O(N^3)$ 
int graph[MAXN][MAXN] //Matrix de Adjacencia do grafo.

int minCut(int n) {
    bool a[n];
    int v[n];
    int w[n];
    for(int i = 0; i < n; i++) v[i] = i;
    int best = INF;
    while(n > 1) {
        int maxj = 1;
        a[v[0]] = true;

```



```

for(int i = 1; i < n; ++i) {
    a[v[i]] = false;
    w[i] = graph[v[0]][v[i]];
    if(w[i] > w[maxj]) {
        maxj = i;
    }
}
int prev= 0 ,buf = n;
while(--buf) {
    a[v[maxj]]=true;
    if(buf == 1) {
        best = min(best, w[maxj]);
        for(int k = 0; k < n; k++) {
            graph[v[k]][v[prev]] = (graph[v[prev]][v[k]] +=
            graph[v[maxj]][v[k]]);
        }
        v[maxj] = v[--n];
    }
    prev = maxj;
    maxj = -1;
    for(int j = 1; j < n; ++j) {
        if(!a[v[j]]) {
            w[j] += graph[v[prev]][v[j]];
            if(maxj < 0 || w[j] > w[maxj]) {
                maxj=j;
            }
        }
    }
}
return best;
}

```

72. String Edit Distance

```

int dist(string& s1, string& s2) {
    int N1 = s1.size(), N2 = s2.size();

    for (int i = 0; i <= N1; i++) dp[i][0] = i;
    for (int i = 0; i <= N2; i++) dp[0][i] = i;

    for (int i = 1; i <= N1; i++) {

```

```

        for (int j = 1; j <= N2; j++) {
            if(s1[i-1] == s2[j-1]) {
                dp[i][j] = dp[i-1][j-1];
            } else {
                dp[i][j] = 1 + min(min(dp[i-1][j],
                dp[i][j-1]), dp[i-1][j-1]);
            }
        }
    }
    return dp[N1][N2];
}

```

73. String Period

```

//Find string period
int stringPeriod(string arg) {
    int ori_len = (int) arg.size();
    arg = arg + arg;

    vector<int> prefix = KMP(arg);
    int ans = (int) arg.size();

    for (int i = 0; i < (int) prefix.size(); i++) {
        if (prefix[i] >= ori_len) {
            ans = i - prefix[i];
            break;
        }
    }
    return ans;
}

```

74. Subset Sum

```

//Subset-Sum -> (G = 0 valor total sendo testado, N = numero de valores
disponiveis no array 'values'
int values[n];
bool subsetSum(int n, int g) {
    for(j = 0; j <= g; j++) sub[j] = 0;
    sub[0] = 1;

```

```

for(j = 0; j < n; j++) if(values[j] != g) {
    for(int k = g; k >= values[j]; k--) {
        sub[k] |= sub[k - values[j]];
    }
}
return sub[g];
}

```

75. Suffix Array

//Suffix Array $O(n \log n)$ and LCP in $O(n)$
//Better Implementation

```
const int MAXN = 100005;
```

// Begins Suffix Arrays implementation
// $O(n \log n)$ - Manber and Myers algorithm

//Usage:
// Fill str with the characters of the string.
// Call SuffixSort(n), where n is the length of the string stored in str.
// That's it!

//Output:
// pos = The suffix array. Contains the n suffixes of str sorted in
// lexicographical order.
// Each suffix is represented as a single integer (the position of
// str where it starts).
// rnk = The inverse of the suffix array. rnk[i] = the index of the
// suffix str[i..n)
// in the pos array. (In other words, pos[i] = k \Leftrightarrow rnk[k] = i)
// With this array, you can compare two suffixes in $O(1)$: Suffix
// str[i..n) is smaller
// than str[j..n) if and only if rnk[i] < rnk[j]

```

int str[MAXN]; //input
int rnk[MAXN], pos[MAXN]; //output
int cnt[MAXN], nxt[MAXN]; //internal
bool bh[MAXN], b2h[MAXN];

```

```

bool smaller_first_char(int a, int b){
    return str[a] < str[b];
}

```

```

}

void SuffixSort(int n){
    //sort suffixes according to their first character
    for (int i=0; i<n; ++i){
        pos[i] = i;
    }
    sort(pos, pos + n, smaller_first_char);
    //{pos contains the list of suffixes sorted by their first character}

    for (int i=0; i<n; ++i){
        bh[i] = i == 0 || str[pos[i]] != str[pos[i-1]];
        b2h[i] = false;
    }

    for (int h = 1; h < n; h <= 1){
        //{bh[i] == false if the first h characters of pos[i-1] == the first h
        //characters of pos[i]}
        int buckets = 0;
        for (int i=0, j; i < n; i = j){
            j = i + 1;
            while (j < n && !bh[j]) j++;
            nxt[i] = j;
            buckets++;
        }
        if (buckets == n) break; // We are done! Lucky bastards!
        //{suffixes are separated in buckets containing strings starting with
        //the same h characters}

        for (int i = 0; i < n; i = nxt[i]){
            cnt[i] = 0;
            for (int j = i; j < nxt[i]; ++j){
                rnk[pos[j]] = i;
            }
        }

        cnt[rnk[n - h]]++;
        b2h[rnk[n - h]] = true;
        for (int i = 0; i < n; i = nxt[i]){
            for (int j = i; j < nxt[i]; ++j){
                int s = pos[j] - h;
                if (s >= 0){
                    int head = rnk[s];
                    rnk[s] = head + cnt[head]++;
                    b2h[rnk[s]] = true;
                }
            }
        }
    }
}

```

```

    }
}
for (int j = i; j < nxt[i]; ++j){
    int s = pos[j] - h;
    if (s >= 0 && b2h[rnk[s]]){
        for (int k = rnk[s]+1; !bh[k] && b2h[k]; k++) b2h[k] =
            false;
    }
}
}
for (int i=0; i<n; ++i){
    pos[rnk[i]] = i;
    bh[i] |= b2h[i];
}
}
for (int i=0; i<n; ++i){
    rnk[pos[i]] = i;
}
}
// End of suffix array algorithm

// Begin of the O(n) longest common prefix algorithm
int lcp[MAXN];
// lcp[i] = length of the longest common prefix of suffix pos[i] and
// suffix pos[i-1]
// lcp[0] = 0
void getLcp(int n){
    for (int i=0; i<n; ++i) rnk[pos[i]] = i;
    lcp[0] = 0;
    for (int i=0, h=0; i<n; ++i){
        if (rnk[i] > 0){
            int j = pos[rnk[i]-1];
            while (i + h < n && j + h < n && str[i+h] == str[j+h]) h++;
            lcp[rnk[i]] = h;
            if (h > 0) h--;
        }
    }
}
// End of the longest common prefix algorithm

int N = (int) S.size();

for (int i = 0; i < N; i++) {
    str[i] = S[i];

```

```

}

SuffixSort(N);
getLcp(N);

```

76. Topological Sort - Iterative

```

priority_queue<int, vector<int>, greater<int> > pq;

for (int i = 0; i < N; i++) {
    if(deg[i] == 0) {
        pq.push(i);
    }
}
int on = 0;
while (!pq.empty()) {
    int now = pq.top();
    pq.pop();
    order.push_back(now);
    for (int i = 0; i < (int) graph[now].size(); i++) {
        int next = graph[now][i];
        deg[next] -= 1;

        if(deg[next] == 0) {
            pq.push(next);
        }
    }
}

```

77. Topological Sort - Recursive

```

void dfs(int x) {
    vis[x] = 1;
    for(int u = 0; u < n; u++) {
        if(vis[u] == 1 && graph[x][u] == 1) has = true;
        if(vis[u] == 0 && graph[x][u] == 1) {
            dfs(u);
        }
    }
}

```

```

    vis[x] = 2;
    order.push_back(x);
}

```

78. TriangleArea

```

double area(double a, double b, double c) {
    double s = (a + b + c) / 2.0;

    double area = sqrt(s * (s - a) * (s - b) * (s - c));

    return area;
}

```

79. Trie

```

//Trie
struct Trie {
    Trie *child[MAXN];
    int prefixes;
    int words;

    Trie() {
        int i;
        prefixes = words = 0;
        for(i = 0; i < MAXN; i++) {
            child[i] = NULL;
        }
    }

    void addWord(string s, int pos = 0) {
        if(pos == s.size()) {
            words++;
            return;
        }

        int letter_pos = s[pos] - 'a';

        Trie *t = child[letter_pos];

```

```

        if(child[letter_pos] == NULL) {
            t = child[letter_pos] = new Trie();
            t->prefixes = 1;
        } else {
            t->prefixes = t->prefixes + 1;
        }
        t->addWord(s, pos + 1);
    }

    int count(string s, int pos = 0, int k = 0) {
        if(pos == s.size()) return k;
        Trie *t = child[s[pos] - 'a'];
        if(t == NULL) return 0;
        return t->count(s, pos + 1, (prefixes == t->prefixes) ? k: k + 1);
    }
};

```

80. Union Find

```

//Union Find
struct UnionFind {
    int N, *id, *sz;

    UnionFind(int _N) {
        id = new int[_N];
        sz = new int[_N];
        for(int i = 0; i < _N; i++) {
            id[i] = i;
            sz[i] = 1;
        }
        N = _N;
    }

    int root(int i) {
        while(i != id[i]) {
            id[i] = id[id[i]];
            i = id[i];
        }
        return i;
    }

    bool find(int p, int q) {
        return root(p) == root(q);
    }
};

```

```

    }
    void unite(int p, int q) {
        int i = root(p);
        int j = root(q);
        if(i == j) return;
        if(sz[i] < sz[j]) {
            id[i] = j; sz[j] += sz[i];
        } else {
            id[j] = i; sz[i] += sz[j];
        }
    }
};

```

81. Z Function

```

//Z-Function O(n) => Z[i] = biggest prefix of a substring starting from i
//which is as a prefix of s
vector<int> z_function (string s) {
    int n = (int) s.length();
    vector<int> z (n);
    for (int i=1, l=0, r=0; i<n; ++i) {
        if (i <= r) {
            z[i] = min (r-i+1, z[i-l]);
        }
        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) {
            ++z[i];
        }
        if (i+z[i]-1 > r) {
            l = i;
            r = i+z[i]-1;
        }
    }
    return z;
}

```
