

1. Why does sequence make a large difference when determining semantics of language?
- ☐ It doesn't
 - ☐ Because the order of words doesn't matter
 - ☒ Because the order in which words appear dictate their impact on the meaning of the sentence
 - ☐ Because the order in which words appear dictate their meaning
2. How do Recurrent Neural Networks help you understand the impact of sequence on meaning?
- ☐ They look at the whole sentence at a time
 - ☐ They don't
 - ☒ They carry meaning from one cell to the next
 - ☐ They shuffle the words evenly
3. How does an LSTM help understand meaning when words that qualify each other aren't necessarily beside each other in a sentence?
- ☐ They load all words into a cell state
 - ☐ They don't
 - ☐ They shuffle the words randomly
 - ☒ Values from earlier words can be carried to later ones via a cell state

4. What keras layer type allows LSTMs to look forward and backward in a sentence?

- ☐ Unilateral
- ☐ Bilateral
- ☒ Bidirectional
- ☐ Bothdirection

5. What's the output shape of a bidirectional LSTM layer with 64 units?

- ☒ (None, 128)
- ☐ (128, None)
- ☐ (128, 1)
- ☐ (None, 64)

6. When stacking LSTMs, how do you instruct an LSTM to feed the next one in the sequence?

- ☐ Ensure that return_sequences is set to True on all units
- ☐ Ensure that they have the same number of units
- ☒ Ensure that return_sequences is set to True only on units that feed to another LSTM
- ☐ Do nothing, TensorFlow handles this automatically

7. If a sentence has 120 tokens in it, and a Conv1D with 128 filters with a Kernal size of 5 is passed over it, what's the output shape?

- ☒ (None, 116, 128)
- ☐ (None, 116, 124)
- ☐ (None, 120, 128)
- ☐ (None, 120, 124)

8. What's the best way to avoid overfitting in NLP datasets?

- ☐ Use LSTMs
- ☐ Use GRUs
- ☐ Use Conv1D
- ☒ None of the above