

HOMEWORK ASSIGNMENT # 6

DUE: Friday, November 17, 2017, 5PM

CSCI677: Computer Vision, Prof. Nevatia

Fall Semester, 2017


This is a programming assignment to create, train and test a CNN for the task of object classification. To keep the task manageable, we will use a small dataset and small network.

a) Dataset:

We will use the CIFAR-10 dataset. (<https://www.cs.toronto.edu/~kriz/cifar.html>). It consists of 10 mutually exclusive classes with 50,000 training images and 10000 test images, evenly distributed across the 10 classes. Each image is a 32x32 RGB image. Please use [data_batch_1,data_batch_2,data_batch_3,data_batch_4] for training, and data_batch_5 for validation, and test_batch for test.

b) Architecture:

Construct a LeNet-5 style CNN network, using Tensorflow functions. LeNet-5 is shown graphically below. Additional details of LeNet-5 can be found in <http://yann.lecun.com/exdb/publis/pdf/lecun-01a.pdf>.



Our goal is to not exactly duplicate the architecture of the original LeNet-5 architecture. You may use the following hyper-parameters as a guide to start with.

First layer has six, 5x5 convolution filters, stride =1, each followed by a max pooling layer of 2x2 with stride = 2. Second convolution layer has ten, 5x5 convolution filters, stride =1, each followed by 2x2 max pooling with stride = 2.

Next comes a fully connected layer of dimensions 120 followed by another fully connected layer of dimension 84.

A softmax layer of dimension 10 provides the classification probabilities (note that this is labeled “Gaussian connections” in the diagram but you can ignore this distinction).

All activation units should be ReLU.

c) **Training:**

Train the network using the given training data. We suggest using a mini-batch size of 64, learning rate of 0.001 and the ADAM optimizer, though you are free to experiment with other values. Note that you need not write your own backpropagation algorithm, it is implemented in Tensorflow. However, you will need to write your own sampling program for constructing mini-batches; Python provides a number of “Random” functions that can generate a number in $[0, 1]$ or return a sequence of desired size.

Record the error after each step so you can monitor it and plot it to show results. During training, you should test on the validation set at some regular intervals; say every 0.5 epochs, to check whether the model is overfitting.

d) **Preprocessing:**

You should subtract mean of the images in the test set for pre-processing. An easy way to do this is to compute a mean image (per channel) and subtract from each train and test image. This replaces earlier guidance to use “per_image_standardization” which is more complex.

Initialize network parameters by using the Xavier function.

e) **Augmentation:**

You should augment the training data. A possible way to augment data is: enlarge the image by 10%, crop the 90% of the image in left-top right-top, left-bottom, right-bottom and central, and then flip the image and do this again. You may use “resize” functions in OpenCV or in TensorFlow to enlarge the image.

f) **Test Results:**

Test the trained network on the test data to obtain classification and show the results in the form of confusion matrix and classification accuracy for each class. Additionally, also show accuracy at different ranks (say rank-1 and rank-5).

g) **System Variations:**

Experiment with variations of the network with the aim of improving performance or ease of training the network without losing accuracy. Some suggestions are provided below but these are not requirements nor guaranteed to improve performance. Instead, you should be guided by the results of variations you obtain and also by study of other methods that will have been discussed in class. A suggest list follows.

i) Change the filter size (make them smaller) followed possibly by additional layer.

ii) Change the number of filters in the early layers.

iii) Change the size of the fully connected layers.

iv) Use weight regularizer (weight-decay).

v) For inference, take multiple crops of expanded test image and average the scores.

As the variations can be combined, the number of options to try can be very large, it is not expected that you would try all combinations but, instead, choose a small number of combinations that you expect will result in improved performance.

- h) **You may be able to find pre-trained models for LeNet and CIFAR-10 online. You may not use these and should train the network entirely from your own program.**

SUBMISSION:

You should turn in the following in softcopy:

1. A brief description of the programs you write, including the source listing.
2. In general, show intermediate results that illustrate the workings of your program. No specific list of items to show is provided, general guidance is to show what you would find useful on your own to better understand how your method is working.
3. Show evolution of loss function with multiple steps.
4. A summary and discussion of the results, including effects of parameter choices. Include visualization of results; show some examples of successful and some failure examples.