**DEVHINTS.IO** 

Edit

# docker-compose cheatsheet

### Basic example

#### Commands

```
docker-compose start
docker-compose stop

docker-compose pause
docker-compose unpause

docker-compose ps
docker-compose up
docker-compose down
```

### Reference

```
web:
    # build from Dockerfile
build: .
```

https://devhints.io/docker-compose

```
# build from image
image: ubuntu
image: ubuntu:14.04
image: tutum/influxdb
image: example-registry:4000/postgresql
image: a4bc65fd
ports:
 - "3000"
 - "8000:80" # guest:host
# command to execute
command: bundle exec thin -p 3000
command: [bundle, exec, thin, -p, 3000]
# override the entrypoint
entrypoint: /app/start.sh
entrypoint: [php, -d, vendor/bin/phpunit]
# environment vars
environment:
 RACK_ENV: development
environment:
 - RACK_ENV=development
# environment vars from file
env_file: .env
env_file: [.env, .development.env]
# expose ports to linked services (not to host)
expose: ["3000"]
# make this service extend another
extends:
 file: common.yml # optional
 service: webapp
# makes the `db` service available as the hostname `database`
# (implies depends_on)
links:
  - db:database
 - redis
# make sure `db` is alive before starting
depends_on:
```

- db

#### volumes:

- /var/lib/mysql
- ./\_data:/var/lib/mysql

## Advanced features



O Comments for this cheatsheet. Write yours!

```
devhints.io / Search 368+ cheatsheets
```

https://devhints.io/docker-compose 3/4



https://devhints.io/docker-compose 4/4