

CSS cheatsheet

Selectors

<code>.class { font-weight: bold; }</code>
<code>div</code>
<code>.class</code>
<code>#id</code>
<code>[disabled]</code>
<code>[role="dialog"]</code>

Combinators

<code>.parent .child</code>	
<code>.parent > .child</code>	Direct
<code>.child + .sibling</code>	Adja
<code>.child ~ .sibling</code>	

Pseudo-classes

<code>:target</code>	eg, h2#foo:target
<code>:disabled</code>	
<code>:focus</code>	
<code>:active</code>	
<code>:nth-child(3)</code>	

Attribute selectors

<code>[role="dialog"]</code>
<code>[class~="box"]</code>
<code>[class]="box"]</code>
<code>[href\$=".doc"]</code>

Pseudo-class variations

<code>:first-of-type</code>
<code>:last-of-type</code>
<code>:nth-of-type(2)</code>
<code>:only-of-type</code>

`:nth-child(3n+2)`

2nd child in

`:first-child``:nth-child(-n+4)``:last-child``:nth-last-child(2)``:nth-child(2)``:nth-of-type(2)``:only-child`

Fonts

Properties

Shorthand

`font-family:`

`font: italic 400 14px / 1.5 sans-serif``font-size:`

style

weight

size (required)

line-height

family (required)

`letter-spacing:`

Example

`line-height:``font-weight:``font-style:`

```
font-family: Arial;
font-size: 12pt;
line-height: 1.5;
letter-spacing: 0.02em;
color: #aa3322;
```

`text-decoration:``underline``none``text-transform: capitalize; /* Hello */``text-transform: uppercase; /* HELLO */``text-transform: lowercase; /* hello */``justify``text-align:``capitalize``uppercase`

lowercase

Background

Properties

Shorthand

<code>background:</code>	<code>background: #fff url(bg.jpg) left top / 100px auto no-repeat fixed</code>
<code>background-color:</code>	<code>background: #abc url(bg.png) center center / cover repeat-x local</code>
<code>background-image:</code>	color image positionX positionY size repeat attach
<code>background-position:</code>	left/center/right top/center/bottom
<code>background-size:</code>	background: linear-gradient(to bottom, rgba(0, 0, 0, 0.5), rgba(0, 0, 0, 0.5)) url('background.jpg') center center / cover, #333;
<code>background-clip:</code>	border-box padding-box content-box
<code>background-repeat:</code>	no-repeat repeat-x repeat-y
<code>background-attachment:</code>	scroll fixed local

Animation

Properties

Shorthand

<code>animation:</code>	<code>animation: bounce 300ms linear 100ms infinite alternate-reverse</code>
<code>animation-name:</code>	name duration timing-function delay count direction
<code>animation-delay:</code>	Example 100ms

animation-duration:

animation-direction:

animation-iteration-count:

animation-timing-function:

animation: bounce 300ms linear 0s infinite normal;
animation: bounce 300ms linear infinite;
animation: bounce 300ms linear infinite alternate-reverse;

alternate-reverse
Event
infinite


.one('webkitAnimationEnd oanimationend msAnimationEnd animation

linear
ease-in
ease-out
ease-in-out



0 Comments for this cheatsheet. [Write yours!](#)

devhints.io / Search 368+ cheatsheets



Other CSS cheatsheets

Sass
cheatsheet

CSS flexbox
cheatsheet

Top cheatsheets

Elixir
cheatsheet

ES2015+
cheatsheet

Over 368 curated
cheatsheets, by
developers for developers.

Devhints home

CSS system fonts
cheatsheet

cssnext
cheatsheet

React.js
cheatsheet

Vim
cheatsheet

Stylus
cheatsheet

CSS antialiasing
cheatsheet

Vim scripting
cheatsheet

Capybara
cheatsheet