AIRBUS TECHNICAL DOCUMENTATION / ENGINEERING CHANGE ORDER	**ATA CHAPTER:** ATA 29
DOCUMENT REF: AMM-29-10-00-820-001	**REVISION:** Rev 01 | **DATE:** 15-JAN-2025

AIRCRAFT MAINTENANCE MANUAL — ENGINE DRIVEN HYDRAULIC PUMP

1. COMPONENT IDENTIFICATION & APPLICABILITY

Component Identifier: HYD-001
Component Nomenclature: Engine Driven Hydraulic Pump (EDP)
Aircraft Applicability: Airbus A320-271N / A321-271NX Fleet equipped with CFM LEAP-1A engines.
Purpose: Definition of operational limits, installation torques, part supersession, and maintenance thresholds.

2. TECHNICAL SPECIFICATIONS & TOLERANCES

Parameter Description	Engineering Value	Standard / Remarks
Manufacturer Part Number (P/N)	P/N 9400-A	Aerospace Standard
Rated Operating Delivery Pressure	3000 PSI	Continuous Normal
Maximum Transient System Pressure	3400 PSI	System Safety Limit
Case Drain Return Temperature Limit	105°C	Thermal Threshold
Drive Flange Attachment Bolt Torque	120 in-lbs	Installation Specification
Inspection & Filter Check Interval	500 Flight Hours	Scheduled Line Check
Nominal Delivery Flow Rate	37 GPM	Rated Flow

3. MAINTENANCE & ACCOMPLISHMENT INSTRUCTIONS

Ensure all hydraulic lines are depressurized to 0 PSI prior to commencing removal. Inspect pump casing for signs of hydraulic fluid leakage. Standard elastomeric O-rings (BMS 3-11 Class 4) must be lubricated with Skydrol hydraulic fluid prior to mating. Torque attachment bolts evenly in a cross pattern to 120 in-lbs.

CONFIDENTIAL & PROPRIETARY — FOR USE BY CERTIFIED OPERATOR ENGINEERING PERSONNEL ONLY.