# AskAI command reference

[ ] optional  < > required  a|b pick one  Full detail: askai help <command>

## Start here

```
/askai-cli Codex: $askai-cli
```

1. Start here. Looks at this folder, prepares it, and opens the terminal.

```
/askai-plugins Codex: $askai-plugins
```

2. Then this. Looks at this folder and finishes the plugin setup still left.

## Set up the machine

```
askai install [--dry-run] [--yes]
```

Install the token-saving setup. Skip what is already healthy. Flags below are this command.

```
askai install --profile minimal|code|docs|full|experimental
```

Tool set. Default is lean. code was coding. experimental was max.

```
askai install --target auto|claude|codex|agy|cursor|all
```

Apps to wire. auto is Claude Code plus every app found.

```
askai install --dry-run | --yes
```

Show the plan and change nothing, or skip the confirmation.

```
askai install --only ID,ID | --skip ID,ID | --project DIR
```

Limit components, leave some out, or attach one repository.

```
askai install --lsp ts,py,kotlin,ruby,swift
```

Claude Code language servers. They do not run inside Cursor.

```
askai install --main-model M | --subagent-model M
```

Models when unset. Default main model is claude-haiku-5-5.

```
askai install --add ID
```

Add one tool. graphify, rtk, and context-mode stay off the default set.

```
graphify update .
```

One time per repo: build the code graph. askai install --add graphify. No tokens.

## Set up the machine · continued

```
graphify query "question"
```

Uses the graph from that install. Ask how two parts of the code connect.

```
serena project create --language LANG --index
```

One time per repo: build the symbol index. Profiles code, full, and experimental.

```
askai update | askai upgrade [--dry-run] [--agents]
```

Fetch the latest AskAI from GitHub and re-apply the recorded profile.

```
askai tools update [--target T]
```

Upgrade the tools AskAI installed. This does not update AskAI itself.

```
askai uninstall [--only ID,ID] [--dry-run]
```

Remove only what AskAI added. Backups are kept.

```
askai restore [file]
```

List backups, or put one backed-up file back.

```
askai profiles | askai profiles migrate
```

What each profile installs. migrate renames a recorded max to experimental.

```
askai suggest [dir]
```

Recommend a profile from the files in a folder.

```
askai shell init powershell|bash|zsh | install SHELL --path PROFILE | uninstall
```

Remember the selected project in PowerShell, bash, or zsh.

```
askai version [--all]
```

Print the version. --all adds OS, shell, Node, git, and container.

## See what is set up

```
askai setup [dir] [--yes] [--dry-run]
```

Hosts, check counts, and the file check. --yes installs. A pipe continues.

# AskAI command reference

[ ] optional  < > required  a|b pick one  Full detail: askai help <command>

## See what is set up · continued

```
askai status
```

Per-tool state against your profile, and any reported savings.

```
askai doctor
```

Same rows as askai check.

```
askai check [dir] [--fix] [--json] [--env] [--brief]
```

Audit this machine and a repo. --env prints the platform block only.

```
askai why <finding-id>
```

The message and the fix for one finding. An unknown id is one line.

```
askai next [dir]
```

At most 3 to do now and 2 for later.

```
askai infra [dir] [--json]
```

What is set up. working means called. configured means not yet.

```
askai audit [dir] [--json]
```

Memory, tools, model, hooks, subagents, scheduled work, cache.

```
askai report [days]
```

askai usage --full, plus one line from askai check --brief.

```
askai savings
```

Same as askai usage --plugins. One line per installed plugin.

```
askai todo [dir] [--all] | done <id> | undo <id>
```

Steps only you can do. done marks one after you did it.

```
askai plugins [list | ready [dir] | info <id> | install <id> | decisions]
```

What a tool does, if it is installed, and how to turn it off.

## Project pack

```
askai cli [--prepare] [--launch] [--path DIR] [--about TEXT]
```

From a chat: prepare the project, then open the terminal.

```
tmux attach -t askai
```

Resume the session. tmux is installed by askai install, update, or setup on headless Linux. Or run askai cli here.

```
askai init [dir] [--name NAME] [--path DIR] [--about TEXT] [--type T] [--yes]
[--refresh] [--offline] [--dry-run] [--build CMD] [--test CMD]
```

Scan the repo, write the project pack, and register the path.

```
askai review [status|done] [--project NAME] [--json] [--all]
```

What changed since the review, or record that it is done.

```
askai map [dir] [--dry-run]
```

Rebuild the project map. Keep purposes you edited.

```
askai scaffold [dir] [--dry-run]
```

Write the starter files every agent reads. Never overwrites.

```
askai project [dir] [--print|--remove] | list | show | rename | refresh |
hide-local [--undo]
```

Register a project, refresh its pack, or hide local paths. --undo removes that block.

```
askai set project NAME | project --clear | default NAME | default --clear
```

Select the project for this terminal, or set the fallback.

```
askai docs
[install|architecture|projects|guide|cheatsheet|changelog|preview|check] [--print]
```

Open one AskAI document, or check generated docs for drift.

```
askai graph [dir]
```

Print the architecture diagram and open it in a browser.

# AskAI command reference

[ ] optional  < > required  a|b pick one  Full detail: askai help <command>

## Project pack · continued

```
askai diff [dir]
```

Diff summary and the whitespace check before a handoff.

## Do the work

```
askai go <claude|codex|cursor|agy|task> [--tier lead|build|chore] ["task"] [--dry-run]
```

Start that app. No host uses Claude. Opus only after two failed Sonnet runs.

```
askai route "task"
```

Print the tier and model. Does not launch an agent.

```
askai prompt "ask" [--tier T] [--kind bug|feature|design|risky] [--files a,b] [--done TEXT] [--mode blunt,brutal,assume,counter,contrast] [--copy]
```

Turn a rough ask into goal, files, done-when, and a tier.

```
askai prompt --output-safe "cmd" | --resume
```

Plan a noisy command first, or print the resume prompt.

```
askai models [set <tool>.<tier> <model>[:<effort>] | verify [tool]]
```

Show or set lead, build, and chore. verify lists plan IDs.

```
askai mcp [list | on <name> | off <name>] [--tool claude|codex|cursor|agy] [--dry-run]
```

List MCP servers, or turn one off between sessions.

```
askai start --tool T --task TEXT [--repo DIR]
```

Ledger entry: tool, task, branch, and last commit.

```
askai session init|pause|status|finish|measure|report [--repo DIR]
```

The other ledger actions. pause records a boundary without the break checklist.

```
askai break [--summary TEXT] [--next TEXT] [--repo DIR] [--dry-run]
```

Before a break: checklist, handoff reminder, and the time.

## Do the work · continued

```
askai snapshot [dir] [--include-untracked]
```

Write a git diff. Does not commit or stash.

```
askai run -- <command> | askai run --save NAME -- <command>
```

Keep the log. A successful run offers --save. flash, reboot, and copy_dut need --yes.

```
askai stop [--yes]
```

List running agent CLIs. --yes stops them. Never this process, tmux, sshd, or Cursor.

```
askai resume [--copy] [--repo DIR]
```

Time away, continue or start fresh, and the resume prompt.

```
askai clear [compact] [--tool claude|codex|cursor|agy] [--repo DIR]
```

Whether /clear or /compact is safe, and the command to type.

```
askai context <percent> | --used N --window M
```

What to do at this context level. 60% is a warning.

## Look up, measure, other apps

```
askai chat [claude|chatgpt|gemini|code]
```

Where to paste the short instruction: Claude, ChatGPT, Gemini.

```
askai ask <words>
```

Offline answer: the rule, why, and the command. No model call.

```
askai guide [moment|all]
```

No topic prints the current moment. all prints every moment.

```
askai tips [claude|codex|agy|cursor|session|habits|peak]
```

The short cheat sheet for one app. peak is Claude's peak hours now.

```
askai help [command|all]
```

Command names, one command in detail, or every command.

# AskAI command reference

[ ] optional  < > required  a|b pick one  Full detail: askai help <command>

## Look up, measure, other apps · continued

```
askai usage [days] [--cache] [--plugins] [--full] [--import-cursor FILE.csv]
```

Claude Code and Codex spend. --import-cursor reads tokens, not dollars.

```
askai convert <file|url> | askai convert scan [dir] [--yes] [--ignore-originals]
```

PDF, Office, a web page, or a YouTube URL to Markdown. scan lists them.

```
askai test [--out FILE] [--json]
```

Run each safe command and write one capture. Skips install, update, and agents.

```
askai statusline
```

Claude Code's one line: model, context, and cache.

**Reference notes**

askai usage reads Claude Code and Codex only. Cursor, Claude chat, and ChatGPT show usage in their own settings.
~/.claude/askai is AskAI's folder on every install, including Cursor-only.