AskAI setup & entry points

[ ] optional < > required a|b pick one Full detail: askai help <command>

Start here

```
/askai-cli Codex: $askai-cli
```

1. Start here. Looks at this folder, prepares it, and opens the terminal.

```
/askai-plugins Codex: $askai-plugins
```

2. Then this. Looks at this folder and finishes the plugin setup still left.

```
/askai-gui Codex: $askai-gui
```

3. Prefer a window. Opens the Ask AI desktop app (same as askai desktop open).

Setup (installation & maintenance)

```
askai install [--dry-run] [--yes]
```

Install the token-saving setup. --dry-run changes nothing. --yes skips the confirmation.

```
askai install --profile minimal|code|docs|full|experimental
```

Tool set. Default is lean. code was coding. experimental was max.

```
askai install --target auto|claude|codex|agy|cursor|all
```

Apps to wire. auto is Claude Code plus every app found.

```
askai install --only ID,ID | --skip ID,ID | --project DIR
```

Limit components, leave some out, or attach one repository.

```
askai install --lsp ts,py,kotlin,ruby,swift
```

Claude Code language servers. They do not run inside Cursor.

```
askai install --main-model M | --subagent-model M
```

Models when unset. Default main model is claude-haiku-5-5.

```
askai install --add ID
```

Add one tool. graphify, rtk, and context-mode stay off the default set.

```
askai update [--dry-run] [--check] [--agents]
```

Fetch the latest AskAI from GitHub and re-apply the recorded profile.

Setup (installation & maintenance) · continued

```
askai tools update [--target T]
```

Upgrade the tools AskAI installed. This does not update AskAI itself.

```
askai restore [file]
```

List backups, or put one backed-up file back.

```
askai uninstall [--only ID,ID] [--dry-run]
```

Remove only what AskAI added. Backups are kept.

```
askai profiles | askai profiles migrate
```

What each profile installs. migrate renames a recorded max to experimental.

```
askai suggest [dir]
```

Recommend a profile from the files in a folder.

System (shell, CLI & environment)

```
askai cli [--prepare] [--launch] [--path DIR] [--about TEXT]
```

From a chat: prepare the project, then open the terminal.

```
askai shell init powershell|bash|zsh | install SHELL --path PROFILE | uninstall
```

Remember the selected project in PowerShell, bash, or zsh.

```
askai set project NAME | project --clear | default NAME | default --clear
```

Select the project for this terminal, or set the fallback.

```
askai statusline
```

Claude Code's one line: model, context, and cache.

```
askai version [--all]
```

Print the version. --all adds OS, shell, Node, git, and container.

```
askai help [command|all]
```

Command names, one command in detail, or every command.

AskAI setup & entry points

[ ] optional < > required a|b pick one Full detail: askai help <command>

Reference notes

askai savings reads Claude Code and Codex only. Cursor, Claude chat, and ChatGPT show usage in their own settings.
~/.claude/askai is AskAI's folder on every install, including Cursor-only.