AskAI command reference

[ ] optional < > required a|b pick one Full detail: askai help <command>

Set up the machine

`askai install [--dry-run] [--yes]`
Install the token-saving setup. Skip what is already healthy. Flags below are this command.

`askai install --profile minimal|coding|docs|full|max`
Tool set. Default is coding. max installs every optimiser.

`askai install --target auto|claude|codex|agy|cursor|all`
Apps to wire. auto is Claude Code plus every app found.

`askai install --dry-run | --yes`
Show the plan and change nothing, or skip the confirmation.

`askai install --only ID,ID | --skip ID,ID | --project DIR`
Limit components, leave some out, or attach one repository.

`askai install --lsp ts,py,kotlin,ruby,swift`
Claude Code language servers. They do not run inside Cursor.

`askai install --main-model M | --subagent-model M`
Models when unset. Default main model is claude-sonnet-5-5.

`graphify update .`
One time per repo: build the code graph. askai install --profile max, or --graphify. No tokens.

`graphify query "question"`
Uses the graph from that install. Ask how two parts of the code connect.

`serena project create --language LANG --index`
One time per repo: build the symbol index. askai install --profile coding, full, or max.

`askai upgrade [--dry-run] [--agents] [install options]`
Fetch the latest AskAI and re-apply the recorded profile. Same flags as install.

Set up the machine · continued

`askai update [--target T]`
Upgrade the tools AskAI installed and refresh its rule text.

`askai uninstall [--only ID,ID] [--dry-run]`
Remove only what AskAI added. Backups are kept.

`askai restore [file]`
List backups, or put one backed-up file back.

`askai profiles`
What minimal, coding, docs, full, and max each install.

`askai suggest [dir]`
Recommend a profile from the files in a folder.

`askai shell init powershell|bash|zsh | install SHELL --path PROFILE | uninstall`
Remember the selected project in PowerShell, bash, or zsh.

`askai version`
Print the AskAI version.

See what is set up

`askai setup [dir]`
One check: status, guidelines, infra, plugins, to-dos, files.

`askai status`
Per-tool state against your profile, and any reported savings.

`askai doctor`
Broken JSON, API keys that bypass the plan, proxies, huge files.

`askai check [dir] [--fix] [--json]`
Audit this machine and a repo. Each gap names its fix.

AskAI command reference

[ ] optional < > required a|b pick one Full detail: askai help <command>

See what is set up · continued

```
askai infra [dir] [--json]
```
What is set up. working means called. configured means not yet.

```
askai audit [dir] [--json]
```
Memory, tools, model, hooks, subagents, scheduled work, cache.

```
askai report [hours] [--json]
```
Claude Code status, health, cache, and spend for N hours.

```
askai savings [days] [--repo DIR]
```
Each plugin's own savings report. Compare with askai usage.

```
askai todo [dir] [--all] | done <id> | undo <id>
```
Steps only you can do. done marks one after you did it.

```
askai plugins [list | ready [dir] | info <id> | install <id> | decisions]
```
What a tool does, if it is installed, and how to turn it off.

```
/askai-plugins Codex: $askai-plugins
```
One time. askai install writes this command. Runs the plugin steps still left.

Project pack

```
askai cli [--prepare] [--launch] [--path DIR] [--about TEXT]
```
From a chat: prepare the project, then open the terminal.

```
/askai-cli Codex: $askai-cli
```
The chat form of askai cli. askai install writes this command.

```
tmux attach -t askai
```
Resume the session. tmux is installed by askai install, update, or setup on headless Linux. Or run askai cli here.

Project pack · continued

```
askai init [dir] [--name NAME] [--path DIR] [--about TEXT] [--type T] [--yes]
[--refresh] [--offline] [--dry-run] [--build CMD] [--test CMD]
```
Scan the repo, write the project pack, and register the path.

```
askai review [status|done] [--project NAME] [--json] [--all]
```
What changed since the review, or record that it is done.

```
askai map [dir] [--dry-run]
```
Rebuild the project map. Keep purposes you edited.

```
askai scaffold [dir] [--dry-run]
```
Write the starter files every agent reads. Never overwrites.

```
askai project [dir] [--print|--remove] | list | show | rename OLD NEW | path NAME
NEW_PATH | remove NAME | switch [NAME]
```
Copy Cursor rules, or list, rename, move, or drop a registration.

```
askai set project NAME | project --clear | default NAME | default --clear
```
Select the project for this terminal, or set the fallback.

```
askai docs
[install|architecture|projects|guide|cheatsheet|changelog|preview|check] [--print]
```
Open one AskAI document, or check generated docs for drift.

```
askai graph [dir]
```
Print the architecture diagram and open it in a browser.

```
askai diff [dir]
```
Diff summary and the whitespace check before a handoff.

Do the work

```
askai go <claude|codex|cursor|agy> [--tier lead|build|chore] ["task"] [--files
a,b] [--done TEXT] [--resume] [--dry-run]
```
Start that app with the tier's model fixed for the session.

AskAI command reference

[ ] optional < > required a|b pick one Full detail: askai help <command>

Do the work · continued

```
askai prompt "ask" [--tier T] [--kind bug|feature|design|risky] [--files a,b]
[--done TEXT] [--mode blunt,brutal,assume,counter,contrast] [--copy]
```
Turn a rough ask into goal, files, done-when, and a tier.

```
askai prompt --output-safe "cmd" | --resume
```
Plan a noisy command first, or print the resume prompt.

```
askai models [set <tool>.<tier> <model>[:<effort>] | verify [tool]]
```
Show or set lead, build, and chore. verify lists plan IDs.

```
askai mcp [list | on <name> | off <name>] [--tool claude|codex|cursor|agy]
[--dry-run]
```
List MCP servers, or turn one off between sessions.

```
askai start --tool T --task TEXT [--repo DIR]
```
Ledger entry: tool, task, branch, and last commit.

```
askai session init|pause|status|finish|measure|report [--repo DIR]
```
The other ledger actions. pause records a boundary without the break checklist.

```
askai break [--summary TEXT] [--next TEXT] [--repo DIR] [--dry-run]
```
Before a break: checklist, handoff reminder, and the time.

```
askai resume [--copy] [--repo DIR]
```
Time away, continue or start fresh, and the resume prompt.

```
askai clear [compact] [--tool claude|codex|cursor|agy] [--repo DIR]
```
Whether /clear or /compact is safe, and the command to type.

```
askai context <percent> | --used N --window M
```
What to do at this context level. 60% is a warning.

Look up, measure, other apps

```
askai chat [claude|chatgpt|gemini|code]
```
Where to paste the short instruction: Claude, ChatGPT, Gemini.

```
askai ask <words>
```
Offline answer: the rule, why, and the command. No model call.

```
askai guide [install|start|work|break|resume|clear|compact|cache|models|subagents|
mcp|output|prompts|docs|plugins|peak|all]
```
Etiquette for one moment. work also lists open to-dos. all is every moment.

```
askai tips [claude|codex|agy|cursor|session|habits|peak]
```
The short cheat sheet for one app. peak is Claude's peak hours now.

```
askai help [command|all]
```
Command names, one command in detail, or every command.

```
askai usage [days]
```
What Claude Code and Codex spent. Not Cursor or the chat apps.

```
askai convert <file|url> [--out file.md]
```
PDF, Office, a web page, or a YouTube URL to Markdown.

```
askai hook prompt|session
```
Claude Code runs this itself. You do not type it.

```
askai statusline
```
Claude Code's one line: model, context, and cache.

Reference notes

askai usage reads Claude Code and Codex only. Cursor, Claude chat, and ChatGPT show usage in their own settings.
~/.claude/askai is AskAI's folder on every install, including Cursor-only.