Cloth-Folding Robot Platform

Complete Project Documentation — Every Detail

Revision R1 • 2026-09-09 • Project:
/c/q/RLE_cloth_robot_2026/robot_platform_experiments/08_cloth_folding

Prepared for Aamer Khani. Older revisions are never deleted; each revision is a new file (R1, R2, ...).

1. Project Overview and Goals

The project builds a multi-arm robotic laundry cell in the Genesis physics simulator and uses it as a rigorous testbed for a central scientific question: **can the user's scramble-inversion discrete diffusion method (Zenodo 21970238, 22063663) outperform reinforcement learning on real deformable-object manipulation, and at what cost?** The task ladder grew from towels on a floor to a full laundry loop: crumpled garments in a bucket hanging off a work table are picked one at a time by robot arms, untangled and flattened by two-arm flings, ironed by a third arm with full-coverage guarantees and burn physics, folded into a neat two-fold, and placed on a linen shelf.

Three policy classes compete on identical episode seeds: (1) **Diffusion** — CNN denoisers trained on armless synthetic scramble data, executed as a reverse-process rollout; (2) **RL** — soft actor-critic over manipulation primitives, upgraded to a CNN encoder and behavior-cloning warm starts; (3) **Random** — the control that keeps everyone honest. Verdicts so far: diffusion decisively won towels round 1 (0.76 vs 0.42 coverage at ~50x lower cost), tied a privileged oracle on staged two-folds (metric saturation), and both learned methods tied random on the full laundry loop round 1 — a result traced to solver physics limits and training-data distribution shift, both addressed in the ongoing round 2.

2. Hardware and Software Stack

Component	Detail
Simulator	Genesis 1.3.3, GPU/Warp backend, PBD cloth solver
GPU	RTX 5080 laptop-class, 16 GB VRAM
Robots	3x Franka Emika Panda (MJCF), tabletop-mounted
RL stack	PyTorch SAC (MLP then CNN), parallel worker processes
Diffusion stack	4-conv CNN denoisers, 4 heads (2 grasp + 2 place cells over a 16x16 grid), soft-target CE loss
Env API	Gymnasium; 32x32 heightmap + 6 scalars obs; 8-d action
Version control	git repo rooted at /c/q; every change committed scoped to the project directory

3. Scene Evolution

v0 (towels era): two floor-mounted Frankas facing a 0.4 m PBD towel; tangles spawned by teleported reflection folds; fold/stack zones on the floor.

v1 (garment era): procedural t-shirt and pants meshes; feedback rounds fixed arm facing (both arms now face each other), added a large 2.2 x 1.6 m work table at 0.75 m height with translucent glass enclosure walls, and a third arm holding an iron plate.

v2 (laundry era): a bucket (0.42 m inner, 0.30 m deep) hangs entirely OUTSIDE the left table rim on a mounting bracket, aligned with the left arm and reachable through a 0.55 m gap in the left glass wall; three colored garments crumple-and-drop into it per episode; the ironing arm sits fully on the tabletop; a low linen shelf with a retaining lip occupies the back-right corner as the destination for folded output. PBD bounds extend below the tabletop to contain the bucket volume.

4. Garment Assets

Mesh	Verts	Sim particles	particle_size	Notes

towel_31 (v0)	961	~1,000	0.0133	round-1 towel
tshirt.obj	439	~1,500	0.0133	single-layer, alphabet-T
pants.obj	426	~1,400	0.0133	single-layer
tshirt2/pants2	878/852	~2,900	0.0133	two-layer (front+back panels, seam walls, open hem)
tshirt4.obj	3,330	6,592	0.0072	4x two-layer (current)
pants4.obj	3,306	4,357	0.008	4x two-layer (current)
towel4.obj	3,721	~6,900	0.0072	4x towel (current)

Two-layer construction: front and back panels stitched along boundary seams with the hem left open so the garment reads as real clothing. The PBD sampler resamples meshes into particles by particle_size, so mesh resolution and simulation resolution are tuned jointly.

5. Physics Stability — the Defining Engineering Battle

5.1 The material dilemma. Cotton-look stiffness (bending_compliance 8e-3, air_resistance 0.02) explodes the solver whenever a fold lands on an already-folded stack. The failure is silent: exploded particles clamp at the PBD upper bound instead of going NaN, so isfinite() checks pass. A full day of folded-goal training data (100% of it) was garbage before a heightmap audit (any 16x16 cell > 0.30 m = explosion) exposed it. The validated compromise material is bending 1.4e-2 / air 0.006, which survives the two-fold goal state plus three stacked scramble folds.

5.2 Resolution limits (stress-tested). At 4x mesh resolution, particle_size 0.0072 passes for t-shirt (6,592 particles) and towel; pants need 0.008 (4,357). The 13k-particle regime (psize 0.0067) fails under every dt/substep/material combination tried — a hard boundary of this solver, documented for the planned custom engine.

5.3 Teleport fragility. Teleporting a multi-fold tangle in one shot explodes even with stable material; the tangle spawner applies folds ONE at a time with damped settling between (velocity zeroing near surfaces + 2.5-3 m/s speed clamps). Repeated re-teleports to the folded goal state still explode 64-99% of episodes on 4x two-layer garments — the single biggest data-collection tax, and next-step #1 for the physics rewrite.

5.4 Hard-won primitive rules. Never pin cloth inside gripper collision geometry (hands stop 11.5 cm above grasps); damp near-floor velocities every ~5 steps (PBD boundaries are frictionless); keep two-arm grasps >12 cm apart; PBD bounds are load-bearing containment walls.

6. Manipulation Primitives

Primitive	What it does
grasp	descend, pinch TOP layer only (within one particle size of the highest candidate), pin to hand link; NaN guards; reach-cl
fling	two-arm taut stretch, lift, forward fling, lay flat — the untangle workhorse
fold	two grasps + two placements over a hinge; lift-before-home
carry	two-arm transport of a folded item to a destination
pick_from_bucket	left arm reaches through the glass gap, below table level (special IK clamp zone), grasps the pile top, lifts over the rim, l
iron_pass	third arm rasters the plate over the cloth bbox; row count derives from plate width with 25% overlap (no skipped stripes);
stack/shelf	carry the folded result to the back-right linen shelf with alternating offsets

7. The Ironing Subsystem (full history)

The iron is a plate glued kinematically under the third arm's hand. Pressing flattens particles under the footprint and accumulates per-particle heat; heat beyond a threshold scorches (dark markers, negative reward). Full bug history, each found by validation and fixed with a scoped commit: (1) **rubber-band artifact** — the plate was re-pinned only on primitive steps, so direct scene.step paths let it free-fall then snap back; fixed by wrapping scene.step itself (plate-hand offset now 0.0 mm across all paths). (2) **fixed 2-3 raster rows** left unpressed stripes on wide cloth; rows now tile the cloth width from plate geometry (iron coverage metric went 0.72 -> targeting 0.95+). (3) **repeat-until-covered scorching** — overlapping re-passes re-heated faster than per-step decay cooled (55 burns in one episode); fixed with 55% heat decay between passes. (4) **burn threshold retune** — BURN_HEAT 90 was calibrated for the old raster; correct full-coverage ironing legitimately reaches ~120-150 heat-steps, so proper ironing burned (945 burns in one episode). Threshold now 260: only true loitering scorches. Iron coverage is a first-class eval metric.

8. Metrics — Evolution Toward Honesty

Metric	Status	Lesson
coverage (footprint/flat)	active	great for untangling; saturates once flat
Procrustes goal_err	retired for folding	saturates near 'flat' (~0.15): even a privileged oracle cannot beat flat by much
fold_q (area-ratio + rectangularity + thinness)	active	non-saturating proxy; peaks at the quarter-fold footprint
FoldSSIM (height + gradient SSIM, principal-frame aligned, content-weighted)	active	sees SHAPE: perfect fold 1.0, settled fold 0.40, one-fold 0.21, crumpled blob
iron_coverage	active	fraction of particles pressed; the 'no skipped parts' guarantee made measurab
burns	active	scorched-particle count; safety differentiator

9. The Diffusion Method (scramble-inversion)

Forward process: from a goal state (flat, or canonically folded), apply random reflection folds — cheap, armless, analytic. **Training:** a 4-conv CNN sees the scrambled heightmap and predicts the inverse action as four 16x16 cell distributions (grasp pair + place pair). Refined loss: Gaussian soft targets over cells, coverage-weighted samples, unordered-pair symmetry (min over head swap), fixed torch seeds with best-of-N model selection (training variance at few-hundred-sample scale is large). **Inference:** reverse rollout — repeatedly execute the predicted un-fold through arm primitives until coverage/fold criteria are met.

Distribution shift fix (round 2): round-1 laundry denoisers trained on teleport-scrambles but evaluated on bucket-crumpled, arm-dropped states — and lost to random. The arm-state collector now generates flat-goal data through the REAL pipeline (crumple into bucket, arm pick, then scramble) and folded-goal data at the measured arm-drop position/orientation distribution. It also records env-native (observation, action) pairs for behavior cloning.

10. The RL Method and Its Infrastructure

Policy: SAC; v1 MLP (65-d obs) grew to a CNN actor-critic (32x32 heightmap encoder, 256-d features, twin critics) per the 'more complex model' directive. **Trainer evolution, each stage forced by a real failure:** parallel Genesis workers with crash-respawn -> non-blocking respawn absorption (a fresh laundry worker needs ~10 min to build) -> hang detection with 20-min poll-timeout kills (a worker once spun at 80% CPU for 3+ hours inside one solver step, silently stalling the whole fleet on a blocking pipe read) -> replay-buffer persistence across restarts (three OS-level session restarts each cost the full buffer) -> JSON-safe telemetry (a numpy float32 in history crashed a run at its first checkpoint). **Behavior cloning:** the CNN actor regresses the known-correct inverse actions; validation exposed multimodality (several valid grasp pairs per state), so BC serves as a weak warm start rather than a solution — an honest, documented limitation.

11. Results Compendium (as of this revision)

Towels round 1 (the flagship): diffusion 0.76 coverage / 70% success vs privileged heuristic 0.42 / 30% vs SAC at random level — trained on 4,171 armless pairs in ~40 minutes, roughly 50x cheaper than the RL attempt it beat.

Shirts (flat, round 1): diffusion clean episodes 0.78-0.83 coverage; SAC below random. Caveat: random flinging untangles shirts 83% of the time, so shirts are a weak discriminator.

Staged untangle-to-two-fold: three-way statistical tie at goal_err ~0.14 (diffusion 0.143, oracle 0.142, SAC 0.137-0.141) — the Procrustes metric saturates; fold-execution physics, not policy, is the bottleneck. Pants

separated (oracle 0.115 vs diffusion 0.151) due to place-head data starvation.

Laundry loop round 1: nothing beat random on fold quality (RL 0.328, random 0.334, diffusion 0.283-0.305); the one real difference was burns: structured policies 0, random 108. Causes diagnosed and addressed in round 2 (distribution shift; data starvation; RL cost).

Round 2 (in progress): towels re-enter as the third garment class with 1,187 folded + 172 flat arm-state pairs; towel RL fine-tuned ~380 actions from a BC warm start; three-way towel evals running under the corrected iron physics at the time of writing. Shirts and pants follow, then nine showcase videos (3 garments x 3 policies) under the current scene.

12. Cost Accounting

	RL	Diffusion
training interactions	~1,700 arm actions (laundry v1) + ~380 (towel v2)	0 robot interactions
wall-clock per dataset/run	days, with babysitting	~2 h collect + minutes to train
cost per action/sample	30-100 s (arm execution)	~1-3 s (teleport scramble)
infrastructure required	respawn + hang-watchdog + replay persistence	explosion filtering only
scales with	robot time (expensive)	sim stability (fixable)

13. Engineering Practices

Autonomous long-horizon operation: background jobs with layered monitors (progress lines, failure signatures, liveness watchdogs); every stage validated on real outputs before being called done — a standing lesson from an early incident where a from-scratch training job produced a broken model that was reported as complete. Data audits (explosion heightmap rule) run inline in every collector. Every code change is committed immediately, scoped strictly to the project path (the git root /c/q is shared with unrelated projects); heavy artifacts (videos, checkpoints, datasets) are gitignored. Loud speaker announcements ('It's done') fire when full campaigns complete, timed to waking hours.

14. Requirements for the Planned Custom Cloth Engine

Documented in CLOTH_ENGINE_REQUIREMENTS.md with a validation suite: (1) stability under 8 stacked layers at 5 mm spacing across a silk-to-denim stiffness sweep; (2) teleport-init tolerance (the enabler of cheap diffusion data); (3) plastic crease memory with temperature-dependent set rate (real ironing); (4) real boundary friction; (5) pinned particles as first-class contact citizens; (6) bounded per-step compute + deterministic replay; (7) 10x speed at ~6.6k particles; (8) explicit divergence flags — silent clamp-at-bounds explosions must be impossible.

15. Artifact Inventory

Artifact	Contents
RESULTS_STAGED.md / RESULTS_LAUNDRY.md	full per-round analyses
CLOTH_ENGINE_REQUIREMENTS.md	engine spec from measured pain
40+ videos	from debug clips to full laundry loops; 9-config showcase set in progress under the current scene
Checkpoints	SAC/CNN actors per era; 6 arm-state denoisers; BC actors
Datasets	data_scramble2/4/5, data_laundry_diff, data_armstate (explosion-filtered, BC-annotated)
Envs/trainers	env.py, env_staged.py, env_laundry.py; train_fling/staged/laundry/laundry2; bc_train.py
Eval harnesses	eval_compare, eval_staged, eval_laundry (actor/diffusion/random modes, dual metrics)

16. Current Status and Roadmap

Running now: three-way towel evaluation under corrected iron physics. **Next:** towel showcase videos; shirt RL fine-tune (overnight) and evals; pants RL fine-tune and evals; nine configuration videos; the complete

round-2 comparison report with fold_q + SSIM + iron coverage + burns on identical seeds; speaker announcement on completion. **Beyond:** the custom cloth engine (user's rewrite) unlocks full-resolution folded-goal data, which is the single highest-leverage improvement for the diffusion method; pixel-wise Q-maps remain the untried RL upgrade.

— End of revision R1. Next revision: R2 (this file will not be modified).