

# Computational Bootcamp 4: Data Manipulation and Visualization in R

Ankushi Mitra

Department of Government  
Georgetown University

August 17, 2023

# What We'll Be Covering Overall

- ① Software installation, file management
- ② Basics of R: data structures, writing code, creating objects, packages
- ③ R: working with datasets
- ④ More R: data manipulation, visualization
- ⑤ LaTeX: producing documents with Markdown and Overleaf

# What We'll Be Covering Today

- 1 Basic data manipulation

# What We'll Be Covering Today

- ① Basic data manipulation
- ② Basic data visualization

# Basic Data Manipulation

- The *mutate()* function is used to create new variables or modify existing ones within a dataset.

# Basic Data Manipulation

- The *mutate()* function is used to create new variables or modify existing ones within a dataset.
- The basic syntax of the *mutate()* function is `mutate(data, new column = calculation/transformation)`.

# Basic Data Manipulation

- The *mutate()* function is used to create new variables or modify existing ones within a dataset.
- The basic syntax of the *mutate()* function is `mutate(data, new column = calculation/transformation)`.
- For example, let's say you have a dataset of students' test scores on different subjects and you want to create a column *total* based on columns *math* and *science*: `mutate(data, total = math + science)`

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*



## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*

```
data <- storms
```

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*  

```
data <- storms
```
- *storms* has a column, *category*, which categorizes storms from levels 1-5. Using *mutate()*, create a new variable called *level\_5*

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*  

```
data <- storms
```
- *storms* has a column, *category*, which categorizes storms from levels 1-5. Using *mutate()*, create a new variable called *level\_5*
- *level\_5* should equal 1 if the column *category* equals 5 and 0 for all other categories. *Hint: if\_else()* is useful and works like the IF command in Microsoft Excel.

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*  
`data <- storms`
- *storms* has a column, *category*, which categorizes storms from levels 1-5. Using *mutate()*, create a new variable called *level\_5*
- *level\_5* should equal 1 if the column *category* equals 5 and 0 for all other categories. *Hint: if\_else()* is useful and works like the IF command in Microsoft Excel.

```
data <- data %>%  
  mutate(level_5 = if_else(  
    category == 5, 1, 0))
```

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*  
`data <- storms`
- *storms* has a column, *category*, which categorizes storms from levels 1-5. Using *mutate()*, create a new variable called *level\_5*
- *level\_5* should equal 1 if the column *category* equals 5 and 0 for all other categories. *Hint: if\_else()* is useful and works like the IF command in Microsoft Excel.

```
data <- data %>%  
  mutate(level_5 = if_else(  
    category == 5, 1, 0))
```

- Drop observations with missing (NA) values using function *drop\_na()*

## Basic Data Manipulation: Exercise

- Set your *Math Camp* folder as the working directory and save the script. Assign the built-in R dataset *storms* to an object *data*  
`data <- storms`
- *storms* has a column, *category*, which categorizes storms from levels 1-5. Using *mutate()*, create a new variable called *level\_5*
- *level\_5* should equal 1 if the column *category* equals 5 and 0 for all other categories. *Hint: if\_else()* is useful and works like the IF command in Microsoft Excel.

```
data <- data %>%  
  mutate(level_5 = if_else(  
    category == 5, 1, 0))
```

- Drop observations with missing (NA) values using function *drop\_na()*  
`data <- drop_na(data)`

# Why Data Visualization

## ① Exploratory analysis

# Why Data Visualization

- ① Exploratory analysis
- ② Diagnosis and validation



# Why Data Visualization

- 1 Exploratory analysis
- 2 Diagnosis and validation
- 3 Communication

# Why Data Visualization

- ① Exploratory analysis
- ② Diagnosis and validation
- ③ Communication
- ④ Flexibility, reproducibility, scalability

# Working with ggplot

- *ggplot2* is an R package for data visualization. Install and load the package in R.

# Working with ggplot

- *ggplot2* is an R package for data visualization. Install and load the package in R.
- You build up a plot by adding layers that represent different aspects of your data. Examples of layers include scatter points, lines, labels, titles, and so on.

# Working with ggplot

- *ggplot2* is an R package for data visualization. Install and load the package in R.
- You build up a plot by adding layers that represent different aspects of your data. Examples of layers include scatter points, lines, labels, titles, and so on.
- This layering approach allows you to build complex visualizations step by step while maintaining clarity and customization.

# Working with ggplot

- *ggplot2* is an R package for data visualization. Install and load the package in R.
- You build up a plot by adding layers that represent different aspects of your data. Examples of layers include scatter points, lines, labels, titles, and so on.
- This layering approach allows you to build complex visualizations step by step while maintaining clarity and customization.
- There are eight main ingredients to ggplot visualizations.

# Working with ggplot

- **Data** are the values represented in the visualization.

# Working with ggplot

- **Data** are the values represented in the visualization.

```
ggplot(data = ) or data %>% ggplot()
```



# Working with ggplot

- **Data** are the values represented in the visualization.

`ggplot(data = )` or `data %>% ggplot()`

- **Aesthetic mappings** are directions for how data are mapped in a plot in a way that we can perceive. Aesthetic mappings link variables to the x-position, y-position, color, fill, shape, transparency, and size.

# Working with ggplot

- **Data** are the values represented in the visualization.

```
ggplot(data = ) or data %>% ggplot()
```

- **Aesthetic mappings** are directions for how data are mapped in a plot in a way that we can perceive. Aesthetic mappings link variables to the x-position, y-position, color, fill, shape, transparency, and size.

```
aes(x = , y = , color = )
```

# Working with ggplot

- **Data** are the values represented in the visualization.

```
ggplot(data = ) or data %>% ggplot()
```

- **Aesthetic mappings** are directions for how data are mapped in a plot in a way that we can perceive. Aesthetic mappings link variables to the x-position, y-position, color, fill, shape, transparency, and size.

```
aes(x = , y = , color = )
```

- **Geometric objects** are representations of the data, including points, lines, and polygons.

# Working with ggplot

- **Data** are the values represented in the visualization.

```
ggplot(data = ) or data %>% ggplot()
```

- **Aesthetic mappings** are directions for how data are mapped in a plot in a way that we can perceive. Aesthetic mappings link variables to the x-position, y-position, color, fill, shape, transparency, and size.

```
aes(x = , y = , color = )
```

- **Geometric objects** are representations of the data, including points, lines, and polygons.

```
geom_bar(), geom_col(), geom_line(), geom_point(),  
geom_histogram(), geom_smooth()
```

# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

```
theme_bw(), theme_minimal(), theme_classic()
```

# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

`theme_bw()`, `theme_minimal()`, `theme_classic()`

- **Scales** turn data values into aesthetic values. This includes the x-axis and y-axis, and ranges of sizes, shapes, and colors of aesthetics. Unless otherwise specified, *ggplot()* will use default scales.

# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

`theme_bw()`, `theme_minimal()`, `theme_classic()`

- **Scales** turn data values into aesthetic values. This includes the x-axis and y-axis, and ranges of sizes, shapes, and colors of aesthetics. Unless otherwise specified, *ggplot()* will use default scales.

`scale_x_continuous()`, `scale_x_discrete()`



# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

`theme_bw()`, `theme_minimal()`, `theme_classic()`

- **Scales** turn data values into aesthetic values. This includes the x-axis and y-axis, and ranges of sizes, shapes, and colors of aesthetics. Unless otherwise specified, *ggplot()* will use default scales.

`scale_x_continuous()`, `scale_x_discrete()`

- Other ingredients include coordinate systems, facets, and statistical transformations.

# Working with ggplot

- **Theme** controls the visual style of plot with font types, font sizes, background colors, margins, and positioning.

`theme_bw()`, `theme_minimal()`, `theme_classic()`

- **Scales** turn data values into aesthetic values. This includes the x-axis and y-axis, and ranges of sizes, shapes, and colors of aesthetics. Unless otherwise specified, *ggplot()* will use default scales.

`scale_x_continuous()`, `scale_x_discrete()`

- Other ingredients include coordinate systems, facets, and statistical transformations.
- You use `+` to chain different layers together in *ggplot()*.

# Working with ggplot

- [Exercise](#): A barplot using *storms*

# Working with ggplot

- **Exercise:** A barplot using *storms*
  - Make a barplot of the number of Level 5 storms, *level\_5*, by *year* in *data* using *ggplot2*. Put *year* on the x-axis and *level\_5* on the y-axis.

# Working with ggplot

- **Exercise:** A barplot using *storms*
  - Make a barplot of the number of Level 5 storms, *level\_5*, by *year* in *data* using *ggplot2*. Put *year* on the x-axis and *level\_5* on the y-axis.

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col()
```

# Working with ggplot

- **Exercise:** A barplot using *storms*
  - Make a barplot of the number of Level 5 storms, *level\_5*, by *year* in *data* using *ggplot2*. Put *year* on the x-axis and *level\_5* on the y-axis.  

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col()
```
  - Use *theme\_minimal()*

# Working with ggplot

- **Exercise:** A barplot using *storms*
  - Make a barplot of the number of Level 5 storms, *level\_5*, by *year* in *data* using *ggplot2*. Put *year* on the x-axis and *level\_5* on the y-axis.

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col()
```

- Use *theme\_minimal()*

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col() +  
  theme_minimal()
```

# Working with ggplot

- Clean up the axis labels and add a title using function *labs()*.



# Working with ggplot

- Clean up the axis labels and add a title using function *labs()*.

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col() +  
  theme_minimal() +  
  labs(title = "Level 5 Storms by Year",  
        y = "Number of Level-5 Storms")
```

# Working with ggplot

- You can further clean up the x-axis labels by making them vertical.

## Working with ggplot

- You can further clean up the x-axis labels by making them vertical.

```
data %>%  
  ggplot(aes(x = year, y = level_5)) +  
  geom_col() +  
  theme_minimal() +  
  labs(title = "Level 5 Storms by Year",  
        y = "Number of Level-5 Storms") +  
  theme(axis.text.x =  
    element_text(angle = 90, hjust = 1))
```

# Working with ggplot

- **Exercise:** A scatterplot using the *economics* dataset

# Working with ggplot

- **Exercise:** A scatterplot using the *economics* dataset
  - Make a scatterplot of the median duration of unemployment, *uempmed*, by *date* in *economics* using *ggplot2*. Put *date* on the x-axis and *uempmed* on the y-axis.

# Working with ggplot

- **Exercise:** A scatterplot using the *economics* dataset
  - Make a scatterplot of the median duration of unemployment, *uempmed*, by *date* in *economics* using *ggplot2*. Put *date* on the x-axis and *uempmed* on the y-axis.

```
economics %>%  
ggplot(aes(x = date, y = uempmed)) +  
  geom_point() +  
  labs(title = "Median Unemployment Duration by Date",  
        x = "Date",  
        y = "Median Unemployment Duration") +  
  theme_bw()
```

# Working with ggplot

- Try adding `geom_line()` as another layer.

# Working with ggplot

- Try adding *geom\_line()* as another layer.

```
economics %>%  
ggplot(aes(x = date, y = uempmed)) +  
  geom_point() +  
  geom_line()+  
  labs(title = "Median Unemployment Duration by Date",  
        x = "Date",  
        y = "Median Unemployment Duration") +  
  theme_bw()
```



# Resources for Data Visualization in R

- Elegant graphics for data analysis

# Resources for Data Visualization in R

- Elegant graphics for data analysis
- R graphics cookbook

# Resources for Data Visualization in R

- Elegant graphics for data analysis
- R graphics cookbook
- The complete ggplot tutorial

# Resources for Data Visualization in R

- Elegant graphics for data analysis
- R graphics cookbook
- The complete ggplot tutorial
- R graph gallery