

ICMP Attack Defense Mechanisms

Table of Contents

1. [Linux Kernel Protections](#)
 2. [Network-Level Defenses](#)
 3. [Detection and Monitoring](#)
 4. [Enterprise Security Controls](#)
 5. [Best Practices](#)
 6. [Lab Environment vs Production](#)
-

Overall

In real networks, **ICMP spoofing (especially ICMP Redirect attacks)** is mitigated by a layered set of controls that fall into five broad categories:

1. Host-level hardening

- **Disable or restrict ICMP Redirect processing**

- Linux:

```
sysctl -w net.ipv4.conf.all.accept_redirects=0 sysctl -w  
net.ipv4.conf.all.secure_redirects=0 # only accept redirects to gateways  
already in the local routing table sysctl -w  
net.ipv4.conf.all.send_redirects=0 # stop the host from *issuing* redirects  
These settings are persistent when added to /etc/sysctl.conf.
```

- Windows:

```
netsh interface ipv4 set interface <if> routerdiscovery=disabled
```

- Cisco IOS:

```
no ip redirects on every routed interface .
```

- **Strict source/destination validation**

Enable reverse-path filtering (`rp_filter=1` or `2`) so packets whose source address does *not* match the interface a reply would use are dropped, making blind spoofing far harder .

2. Router & switch security

- **Ingress/egress filtering (BCP-38)** at every edge router drops packets whose source address does not belong to the subnet they arrive from, preventing most forged-source ICMP Redirects .

- **Disable IP redirects on routers** unless absolutely required; OSPF/BGP with cryptographic authentication is preferred for dynamic route updates .

3. Firewall & IDS/IPS

- Stateless filters: block inbound ICMP Type 5 (Redirect) at the perimeter or rate-limit it to near zero.
- Stateful IDS/IPS signatures (Snort, Suricata, Zeek) alarm on any inbound or outbound ICMP Redirect, especially if the gateway address is outside the local subnet .
- Next-gen firewalls and cloud WAF/CDNs automatically drop or tarpit ICMP Redirect packets .

4. Network segmentation & architecture

- Use /30 or /31 point-to-point links where no host should ever need a redirect.
- Place hosts in separate VLANs/subnets so an attacker cannot send a redirect that would “shortcut” through an illegitimate gateway on the same L2 segment.

5. Monitoring & incident response

- Continuous capture (`tcpdump 'icmp[0] == 5'`, Wireshark display filter `icmp.type == 5`) is used to detect any redirect in real time .
- If a rogue redirect slips through, flushing the route cache (`ip route flush cache`) and rebooting (in extreme corner cases) removes the malicious entry, followed by tightening the controls above.

In short, **modern defense is “deny by default”**: disable the feature everywhere, enforce source-address sanity, and rely on logged, rate-limited exceptions only where absolutely required.

Linux Kernel Protections

ICMP Redirect Controls

Linux provides several kernel parameters specifically designed to protect against ICMP redirect attacks. These are the primary defense mechanisms that must be understood and properly configured.

Core Redirect Parameters

```
# Check current settings
sudo sysctl net.ipv4.conf.all.accept_redirects
sudo sysctl net.ipv4.conf.all.secure_redirects
sudo sysctl net.ipv4.conf.all.send_redirects

# Interface-specific settings
sudo sysctl net.ipv4.conf.eth0.accept_redirects
sudo sysctl net.ipv4.conf.eth0.secure_redirects
```

Parameter Explanations

1. `net.ipv4.conf.all.accept_redirects`

- **Default:** 1 (enabled on most distributions)
- **Purpose:** Controls whether the system accepts ICMP redirect messages
- **Security Impact:**
 - 1 = Accept redirects (vulnerable to attacks)
 - 0 = Reject all redirects (secure but may break some networks)

2. `net.ipv4.conf.all.secure_redirects`

- **Default:** 1 (enabled)
- **Purpose:** Only accept redirects from gateways in the default gateway list
- **Security Impact:**
 - 1 = Only accept redirects from known gateways (more secure)

- 0 = Accept redirects from any source (vulnerable)

3. `net.ipv4.conf.all.send_redirects`

- **Default:** 1 (enabled on routers)
- **Purpose:** Controls whether the system sends ICMP redirects
- **Security Impact:**
 - 1 = Send redirects when acting as router (normal)
 - 0 = Never send redirects (prevents being used as attack source)

Interface-Specific Controls

Each network interface can have independent settings:

```
# View all interface settings
for iface in /proc/sys/net/ipv4/conf/*/; do
    echo "=== $(basename $iface) ==="
    echo "Accept redirects: $(cat $iface/accept_redirects)"
    echo "Secure redirects: $(cat $iface/secure_redirects)"
    echo "Send redirects: $(cat $iface/send_redirects)"
done
```

Important: The `all` setting acts as a default, but interface-specific settings take precedence.

Attack Lab Configuration

In your namespace lab, you needed these settings for the attack to work:

```
# Settings required for attack success
sudo ip netns exec victim sysctl -w net.ipv4.conf.all.accept_redirects=1
sudo ip netns exec victim sysctl -w net.ipv4.conf.all.secure_redirects=0
sudo ip netns exec victim sysctl -w net.ipv4.conf.v-veth.accept_redirects=1
sudo ip netns exec victim sysctl -w net.ipv4.conf.v-veth.secure_redirects=0
```

Why These Settings Enable the Attack:

- `accept_redirects=1`: Allows processing of ICMP redirect messages
- `secure_redirects=0`: Disables validation that redirects come from known gateways
- Interface-specific settings ensure the virtual interface accepts redirects

Secure Production Configuration

For production systems, use these hardened settings:

```
# Disable ICMP redirects completely
sudo sysctl -w net.ipv4.conf.all.accept_redirects=0
sudo sysctl -w net.ipv4.conf.default.accept_redirects=0
```

```
# Enable secure redirects if redirects are needed
sudo sysctl -w net.ipv4.conf.all.secure_redirects=1
sudo sysctl -w net.ipv4.conf.default.secure_redirects=1

# Disable sending redirects on end hosts
sudo sysctl -w net.ipv4.conf.all.send_redirects=0
sudo sysctl -w net.ipv4.conf.default.send_redirects=0

# Make settings persistent
echo "net.ipv4.conf.all.accept_redirects = 0" >> /etc/sysctl.conf
echo "net.ipv4.conf.default.accept_redirects = 0" >> /etc/sysctl.conf
echo "net.ipv4.conf.all.secure_redirects = 1" >> /etc/sysctl.conf
echo "net.ipv4.conf.default.secure_redirects = 1" >> /etc/sysctl.conf
echo "net.ipv4.conf.all.send_redirects = 0" >> /etc/sysctl.conf
echo "net.ipv4.conf.default.send_redirects = 0" >> /etc/sysctl.conf

# Apply settings
sudo sysctl -p
```

Additional Kernel Protections

Source Address Validation (rp_filter)

```
# Enable strict reverse path filtering
sudo sysctl -w net.ipv4.conf.all.rp_filter=1
sudo sysctl -w net.ipv4.conf.default.rp_filter=1

# Check current settings
sysctl net.ipv4.conf.all.rp_filter
```

Purpose: Prevents IP spoofing by validating source addresses

- 0 = No source validation
- 1 = Strict mode (recommended)
- 2 = Loose mode

ICMP Rate Limiting

```
# Limit ICMP error message rate
sudo sysctl -w net.ipv4.icmp_ratelimit=1000
sudo sysctl -w net.ipv4.icmp_ratemask=6168

# Disable ICMP timestamp requests
sudo sysctl -w net.ipv4.icmp_echo_ignore_all=0
sudo sysctl -w net.ipv4.icmp_ignore_bogus_error_responses=1
```

Network-Level Defenses

Firewall Rules (iptables/nftables)

Block ICMP Redirects

```
# Block incoming ICMP redirects
sudo iptables -A INPUT -p icmp --icmp-type redirect -j DROP

# Block outgoing ICMP redirects
sudo iptables -A OUTPUT -p icmp --icmp-type redirect -j DROP

# Allow only specific ICMP types
sudo iptables -A INPUT -p icmp --icmp-type echo-request -j ACCEPT
sudo iptables -A INPUT -p icmp --icmp-type echo-reply -j ACCEPT
sudo iptables -A INPUT -p icmp --icmp-type destination-unreachable -j
ACCEPT
sudo iptables -A INPUT -p icmp --icmp-type time-exceeded -j ACCEPT
sudo iptables -A INPUT -p icmp -j DROP
```

Advanced ICMP Filtering

```
# Rate limit ICMP packets
sudo iptables -A INPUT -p icmp -m limit --limit 1/second --limit-burst 1 -j
ACCEPT
sudo iptables -A INPUT -p icmp -j DROP

# Block ICMP from suspicious sources
sudo iptables -A INPUT -s 10.0.0.0/8 -p icmp -j DROP
sudo iptables -A INPUT -s 172.16.0.0/12 -p icmp -j DROP
sudo iptables -A INPUT -s 192.168.0.0/16 -p icmp -j DROP
```

Router and Switch Protections

Access Control Lists (ACLs)

```
# Cisco Router Example
access-list 100 deny icmp any any redirect
access-list 100 permit ip any any
interface GigabitEthernet0/1
ip access-group 100 in
```

Port Security

- Configure port security to prevent MAC address spoofing

- Enable DHCP snooping to prevent IP spoofing
- Use dynamic ARP inspection (DAI)

Network Segmentation

VLANs and Subnets

- Isolate critical systems in separate VLANs
- Implement inter-VLAN routing controls
- Use micro-segmentation for granular control

Zero Trust Architecture

```
# Example: Restrict ICMP between network segments
sudo iptables -A FORWARD -s 192.168.10.0/24 -d 192.168.20.0/24 -p icmp -j DROP
sudo iptables -A FORWARD -s 192.168.20.0/24 -d 192.168.10.0/24 -p icmp -j DROP
```

Detection and Monitoring

Real-time Monitoring Tools

1. tcpdump for ICMP Analysis

```
# Monitor all ICMP traffic
sudo tcpdump -i any icmp -n -v

# Specific redirect detection
sudo tcpdump -i any 'icmp[icmptype] == icmp-redirect' -n -v

# Monitor routing table changes
watch -n 1 'ip route show | grep default'

# Log ICMP redirects to file
sudo tcpdump -i any 'icmp[icmptype] == icmp-redirect' -n -v -w icmp_redirects.pcap
```

2. Wireshark Filters

```
# ICMP redirect messages
icmp.type == 5

# Suspicious ICMP patterns
icmp && ip.src != ip.gw
```

```
# High frequency ICMP from single source
icmp && frame.time_delta < 0.1
```

3. System Monitoring Scripts

```
#!/bin/bash
# monitor_routes.sh - Detect routing table changes

LOGFILE="/var/log/route_monitor.log"
BASELINE="/tmp/routes_baseline"

# Store initial routing table
ip route show > "$BASELINE"

while true; do
    CURRENT="/tmp/routes_current"
    ip route show > "$CURRENT"

    if ! diff -q "$BASELINE" "$CURRENT" > /dev/null; then
        echo "$(date): Routing table changed!" | tee -a "$LOGFILE"
        echo "Old routes:" >> "$LOGFILE"
        cat "$BASELINE" >> "$LOGFILE"
        echo "New routes:" >> "$LOGFILE"
        cat "$CURRENT" >> "$LOGFILE"
        echo "---" >> "$LOGFILE"

        # Update baseline
        cp "$CURRENT" "$BASELINE"

        # Alert mechanism (email, SIEM, etc.)
        # mail -s "Route Change Alert" admin@company.com < "$LOGFILE"
    fi

    sleep 5
done
```

Network Monitoring Tools

1. Nagios/Icinga Checks

```
#!/bin/bash
# check_icmp_redirects.sh

INTERFACE="eth0"
REDIRECT_COUNT=$(netstat -i | grep "$INTERFACE" | awk '{print $4}')

if [ "$REDIRECT_COUNT" -gt 10 ]; then
```

```
    echo "CRITICAL: High ICMP redirect count: $REDIRECT_COUNT"
    exit 2
elif [ "$REDIRECT_COUNT" -gt 5 ]; then
    echo "WARNING: Elevated ICMP redirect count: $REDIRECT_COUNT"
    exit 1
else
    echo "OK: ICMP redirect count normal: $REDIRECT_COUNT"
    exit 0
fi
```

2. SIEM Integration

```
# Rsyslog configuration for ICMP monitoring
# /etc/rsyslog.d/icmp-monitor.conf

# Log kernel messages about ICMP redirects
kern.info /var/log/icmp-redirects.log

# Forward to SIEM
*. * @@siem-server.company.com:514
```

3. Intrusion Detection Systems (IDS)

```
# Suricata rule for ICMP redirect detection
alert icmp any any -> $HOME_NET any (msg:"ICMP Redirect Detected"; itype:5;
icode:1; sid:1000001; rev:1;)

# Snort rule for suspicious ICMP patterns
alert icmp any any -> $HOME_NET any (msg:"Possible ICMP Redirect Attack";
itype:5; threshold:type both, track by_src, count 3, seconds 60;
sid:1000002; rev:1;)
```

Enterprise Security Controls

1. Network Access Control (NAC)

802.1X Authentication

```
# Configure 802.1X on Linux client
# /etc/wpa_supplicant/wpa_supplicant.conf
ctrl_interface=/var/run/wpa_supplicant
eapol_version=1
ap_scan=0
fast_reauth=1
```



```
network={
  key_mgmt=IEEE8021X
  eap=PEAP
  identity="username"
  password="password"
}
```

2. Endpoint Detection and Response (EDR)

Host-based Monitoring

```
# auditd rules for network configuration changes
-w /proc/sys/net/ -p wa -k network_config
-w /etc/sysctl.conf -p wa -k sysctl_changes
-a always,exit -F arch=b64 -S sethostname -S setdomainname -k
network_changes
```

3. Security Information and Event Management (SIEM)

Log Correlation Rules

```
# Example SIEM rule (YAML format)
rule:
  name: "ICMP Redirect Attack Detection"
  description: "Detects potential ICMP redirect attacks"
  conditions:
    - event_type: "icmp_redirect"
    - count: "> 5"
    - timeframe: "60 seconds"
    - source_ip: "not in trusted_gateways"
  actions:
    - alert: "high"
    - notify: "security_team"
    - block_source: true
```

Best Practices

1. Defense in Depth Strategy

Layer 1: Network Perimeter

- Deploy firewalls with ICMP filtering
- Use intrusion prevention systems (IPS)
- Implement DDoS protection

Layer 2: Network Segmentation

- Isolate critical systems
- Implement VLANs and ACLs
- Use micro-segmentation

Layer 3: Host Hardening

- Disable unnecessary ICMP responses
- Configure kernel parameters securely
- Regular security updates

Layer 4: Monitoring and Detection

- Deploy network monitoring tools
- Implement SIEM solutions
- Regular security assessments

2. Configuration Management

Automated Hardening

```
#!/bin/bash
# security_hardening.sh

# ICMP security settings
sysctl -w net.ipv4.conf.all.accept_redirects=0
sysctl -w net.ipv4.conf.default.accept_redirects=0
sysctl -w net.ipv4.conf.all.secure_redirects=1
sysctl -w net.ipv4.conf.default.secure_redirects=1
sysctl -w net.ipv4.conf.all.send_redirects=0
sysctl -w net.ipv4.conf.default.send_redirects=0

# IP spoofing protection
sysctl -w net.ipv4.conf.all.rp_filter=1
sysctl -w net.ipv4.conf.default.rp_filter=1

# ICMP rate limiting
sysctl -w net.ipv4.icmp_ratelimit=1000
sysctl -w net.ipv4.icmp_ignore_bogus_error_responses=1

# Log martian packets
sysctl -w net.ipv4.conf.all.log_martians=1
sysctl -w net.ipv4.conf.default.log_martians=1

echo "Security hardening applied"
```

3. Regular Security Assessments

Vulnerability Scanning

```
# Nmap ICMP discovery scan
nmap -sn -PE 192.168.1.0/24

# Test ICMP redirect acceptance
sudo nmap --script ip-geolocation-* target_ip
```

Penetration Testing

- Regular red team exercises
- Automated security testing
- Vulnerability assessments

Lab Environment vs Production

Lab Environment (Attack Testing)

Required Settings for Attack Success

```
# Enable ICMP redirects (for testing purposes)
sudo sysctl -w net.ipv4.conf.all.accept_redirects=1
sudo sysctl -w net.ipv4.conf.all.secure_redirects=0
sudo sysctl -w net.ipv4.conf.default.accept_redirects=1
sudo sysctl -w net.ipv4.conf.default.secure_redirects=0

# Interface-specific settings
sudo sysctl -w net.ipv4.conf.eth0.accept_redirects=1
sudo sysctl -w net.ipv4.conf.eth0.secure_redirects=0

# Verify settings
sysctl net.ipv4.conf.all.accept_redirects
sysctl net.ipv4.conf.all.secure_redirects
```

Production Environment (Secure Configuration)

Hardened Settings

```
# Disable ICMP redirects completely
sudo sysctl -w net.ipv4.conf.all.accept_redirects=0
sudo sysctl -w net.ipv4.conf.default.accept_redirects=0
sudo sysctl -w net.ipv4.conf.all.send_redirects=0
sudo sysctl -w net.ipv4.conf.default.send_redirects=0

# Enable strict source validation
```

```
sudo sysctl -w net.ipv4.conf.all.rp_filter=1
sudo sysctl -w net.ipv4.conf.default.rp_filter=1

# Make permanent
cat >> /etc/sysctl.conf << EOF
# ICMP Security Settings
net.ipv4.conf.all.accept_redirects = 0
net.ipv4.conf.default.accept_redirects = 0
net.ipv4.conf.all.send_redirects = 0
net.ipv4.conf.default.send_redirects = 0
net.ipv4.conf.all.rp_filter = 1
net.ipv4.conf.default.rp_filter = 1
net.ipv4.icmp_ratelimit = 1000
net.ipv4.icmp_ignore_bogus_error_responses = 1
EOF

sudo sysctl -p
```

Migration Checklist

When moving from lab to production:

1. ☒ **Verify kernel parameters are hardened**
2. ☒ **Configure firewall rules**
3. ☒ **Enable monitoring and alerting**
4. ☒ **Test legitimate network functionality**
5. ☒ **Document configuration changes**
6. ☒ **Train operations team on new settings**

Summary

ICMP redirect attacks can be effectively mitigated through:

1. **Kernel-level protections:** Properly configured sysctl parameters
2. **Network security controls:** Firewalls, ACLs, and segmentation
3. **Monitoring and detection:** Real-time network monitoring
4. **Security best practices:** Defense in depth and regular assessments

The key insight from your lab environment is that modern Linux systems have robust protections against these attacks, but they must be properly configured and maintained. The fact that you needed to disable `secure_redirects` and enable `accept_redirects` demonstrates that the default security posture is quite strong against these attack vectors.

Remember: Security is not just about individual controls, but about implementing multiple layers of protection that work together to provide comprehensive defense against network-based attacks.