DEVHINTS.IO Edit

pm2 cheatsheet

Fork mode

| pm2 start app.jsname my-api | Start and name a process |
|-----------------------------|--------------------------|
| | |

Listing

| pm2 list | Display all processes status |
|----------------|--|
| pm2 jlist | Print process list in raw JSON |
| pm2 prettylist | Print process list in beautified JSON |
| pm2 describe 0 | Display all information about a specific process |
| pm2 monit | Monitor all processes |

Misc

| pm2 reset <pre>cess></pre> | Reset meta data (restarted time) |
|--------------------------------|--|
| pm2 updatePM2 | Update in memory pm2 |
| pm2 ping | Ensure pm2 daemon has been launched |
| pm2 sendSignal SIGUSR2 my-app | Send system signal to script |
| pm2 start app.jsno-daemon | Run pm2 daemon in the foreground if it doesn't exist already |
| pm2 start app.jsno-vizion | Skip vizion features (versioning control) |
| pm2 start app.jsno-autorestart | Do not automatically restart app |

Cluster mode

| pm2 start app.js -i 0 | Will start maximum processes with LB depending on |
|-----------------------|---|
| | available CPUs |

Logs

| pm2 logs [raw] | Display all processes logs in streaming |
|----------------|---|
| pm2 flush | Empty all log files |
| pm2 reloadLogs | Reload all logs |

Actions

| Stop all processes |
|--|
| Restart all processes |
| Will 0s downtime reload (for NETWORKED apps) |
| Stop specific process id |
| Restart specific process id |
| Will remove process from pm2 list |
| Will remove all processes from pm2 list |
| Save processes list to respawn at reboot |
| |