# arc_cellerate Index

KUKA Pre-Engineered Robotic Welding Systems are designed to offer an economical and efficient solution for high-mix/low-volume applications. These systems are available as either single or multi-station setups and come fully equipped to handle various welding tasks. Each complete system includes the following components:

1. **Robot:** A KUKA robot optimized for welding operations, delivering exceptional precision and reliability
2. **Welding Power Source:** A reliable, high-performance welding power source to deliver consistent arc performance and welds
3. **Torch:** A MIG welding torch suitable for GMAW, FCAW, and MCAW welding processes
4. **Controls:** Simple operator control station: push start button(s), hold/access button, and e-stop
5. **Safety:** E-stop(s), locking safety switches for maintenance door and light curtain(s)

| | |
|---|---|
| Standard Configuration | Two station: Indexing |
| Base Frame | Welded steel base with fork pockets, checker plate floor |
| Total size of cell (L x W) | 4.3m long x 2.4 m wide (169" x 96") |
| Robot | KUKA KR 6 R2010-2 arc HW E |
| Controller | KR C5 Controller |
| Input Voltage | 480/575/3/50/60 |

### Options

- Fronius TPS 400i Power Source
- Lincoln Electric Power Wave R450 Power Source
- Fume Hood

For pricing: sales@KUKA.com

### Benefits

- Using the KR 6 R2010-2-arc HW E robot provides a robust and repeatable system that will enhance productivity, ensure consistent quality, and provide the necessary flexibility for various welding applications. This makes KUKA an excellent choice for modern automated welding solutions
- Simple installation, fast commissioning for processing a wide variety of welding applications
- Modular design for plug and play
- Economical for high mix / low volume applications
- Small foot print to conserve floorspace

### Features

- 6-axis robot with programmable teach pendant
- KR C5 Controller
- KUKA.ArcTech Basic and Advanced Software
- KUKA.HMI Easy
- Power Source, MIG torch and torch cleaning station
- Single wire drum feed setup
- Payload Capacity: 350KG (750 lbs) per side
- Side maintenance door for access to robot, wire feeder, and torch cleaning station
- Fully enclosed steel panel guarding
- Welded fixture table(s); working envelope 45" x 30"; a standard hole pattern for mounting tooling
- Weld ground routed to the tooling plate(s)
- Simple operator control station: push start button(s), hold/access button, and e-stop
- Tri-colour operational lights
- Single point electrical power (3-phase 480V, 575V)