

REST API Documentation

Lakshya - Campus Placement Management Platform

Base URL	http://localhost:5000/api/v1
Version	v1
Data Format	JSON
Authentication	JWT Authentication

API Summary

API / Entity	Method	Endpoint	Description
Get All Students	GET	/students	Retrieve all students
Get Student by ID	GET	/students/:id	Retrieve one student
Add Student	POST	/students	Create a new student
Update Student	PUT	/students/:id	Update an existing student
Delete Student	DELETE	/students/:id	Delete an existing student
Get All Recruiters	GET	/recruiters	Retrieve all recruiters
Get Recruiter by ID	GET	/recruiters/:id	Retrieve one recruiter
Add Recruiter	POST	/recruiters	Create a new recruiter
Update Recruiter	PUT	/recruiters/:id	Update an existing recruiter
Delete Recruiter	DELETE	/recruiters/:id	Delete an existing recruiter
Get All Jobs	GET	/jobs	Retrieve all jobs
Get Job by ID	GET	/jobs/:id	Retrieve one job
Add Job	POST	/jobs	Create a new job
Update Job	PUT	/jobs/:id	Update an existing job
Delete Job	DELETE	/jobs/:id	Delete an existing job
Get All Applications	GET	/applications	Retrieve all applications
Get Application by ID	GET	/applications/:id	Retrieve one application
Add Application	POST	/applications	Create a new application
Update Application	PUT	/applications/:id	Update an existing application
Delete Application	DELETE	/applications/:id	Delete an existing application
Get All Placement Drives	GET	/placement-drives	Retrieve all placement drives
Get Placement Drive by ID	GET	/placement-drives/:id	Retrieve one placement drive
Add Placement Drive	POST	/placement-drives	Create a new placement drive
Update Placement Drive	PUT	/placement-drives/:id	Update an existing placement drive
Delete Placement Drive	DELETE	/placement-drives/:id	Delete an existing placement drive
Get All Interviews	GET	/interviews	Retrieve all interviews
Get Interview by ID	GET	/interviews/:id	Retrieve one interview
Add Interview	POST	/interviews	Create a new interview
Update Interview	PUT	/interviews/:id	Update an existing interview

API / Entity	Method	Endpoint	Description
Delete Interview	DELETE	/interviews/:id	Delete an existing interview
Get All Notifications	GET	/notifications	Retrieve all notifications
Get Notification by ID	GET	/notifications/:id	Retrieve one notification
Add Notification	POST	/notifications	Create a new notification
Update Notification	PUT	/notifications/:id	Update an existing notification
Delete Notification	DELETE	/notifications/:id	Delete an existing notification
Get All Reports	GET	/reports	Retrieve all reports
Get Report by ID	GET	/reports/:id	Retrieve one report
Add Report	POST	/reports	Create a new report
Update Report	PUT	/reports/:id	Update an existing report
Delete Report	DELETE	/reports/:id	Delete an existing report

Students API

1. Get All Students

Method	GET
URL	/students
Description	Returns all students.
Request Body	None
Sample Response	[{"id": "STU101", "status": "Active"}]

2. Get Student by ID

Method	GET
URL	/students/:id
Description	Returns one student using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "STU101", "status": "Active"}

3. Add Student

Method	POST
URL	/students
Description	Creates a new student.
Request Body	{"name": "Aarav Bhatt", "enrollmentNo": "24ITU0Z009", "department": "CE", "semester": 5, "cgpa": 8.2, "backlogs": 0}
Sample Response	{"message": "Student added successfully"}

4. Update Student

Method	PUT
URL	/students/:id
Description	Updates an existing student.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Student updated successfully"}

5. Delete Student

Method	DELETE
URL	/students/:id
Description	Deletes an existing student.
Request Body	None
Sample Response	{"message": "Student deleted successfully"}

Recruiters API

1. Get All Recruiters

Method	GET
URL	/recruiters
Description	Returns all recruiters.
Request Body	None
Sample Response	[{"id": "REC101", "status": "Active"}]

2. Get Recruiter by ID

Method	GET
URL	/recruiters/:id
Description	Returns one recruiter using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "REC101", "status": "Active"}

3. Add Recruiter

Method	POST
URL	/recruiters
Description	Creates a new recruiter.
Request Body	{"name": "Riya Shah", "email": "riya@company.com", "designation": "HR Manager", "companyId": "COMP101"}
Sample Response	{"message": "Recruiter added successfully"}

4. Update Recruiter

Method	PUT
URL	/recruiters/:id
Description	Updates an existing recruiter.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Recruiter updated successfully"}

5. Delete Recruiter

Method	DELETE
URL	/recruiters/:id
Description	Deletes an existing recruiter.
Request Body	None
Sample Response	{"message": "Recruiter deleted successfully"}

Jobs API

1. Get All Jobs

Method	GET
URL	/jobs
Description	Returns all jobs.
Request Body	None
Sample Response	[{"id":"JOB101","status":"Active"}]

2. Get Job by ID

Method	GET
URL	/jobs/:id
Description	Returns one job using its ID.
Request Body	URL Parameter: id
Sample Response	{"id":"JOB101","status":"Active"}

3. Add Job

Method	POST
URL	/jobs
Description	Creates a new job.
Request Body	{"title":"Software Developer","companyId":"COMP101","jobType":"Full Time","package":800000,"minCgpa":7.5,"maxBacklogs":0}
Sample Response	{"message":"Job posted successfully"}

4. Update Job

Method	PUT
URL	/jobs/:id
Description	Updates an existing job.
Request Body	{"status":"Updated"}
Sample Response	{"message":"Job updated successfully"}

5. Delete Job

Method	DELETE
URL	/jobs/:id
Description	Deletes an existing job.
Request Body	None
Sample Response	{"message":"Job deleted successfully"}

Applications API

1. Get All Applications

Method	GET
URL	/applications
Description	Returns all applications.
Request Body	None
Sample Response	[{"id": "APP101", "status": "Active"}]

2. Get Application by ID

Method	GET
URL	/applications/:id
Description	Returns one application using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "APP101", "status": "Active"}

3. Add Application

Method	POST
URL	/applications
Description	Creates a new application.
Request Body	{"studentId": "STU101", "jobId": "JOB101", "status": "Applied"}
Sample Response	{"message": "Application submitted successfully"}

4. Update Application

Method	PUT
URL	/applications/:id
Description	Updates an existing application.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Application updated successfully"}

5. Delete Application

Method	DELETE
URL	/applications/:id
Description	Deletes an existing application.
Request Body	None
Sample Response	{"message": "Application deleted successfully"}

Placement Drives API

1. Get All Placement Drives

Method	GET
URL	/placement-drives
Description	Returns all placement drives.
Request Body	None
Sample Response	[{"id": "PLA101", "status": "Active"}]

2. Get Placement Drive by ID

Method	GET
URL	/placement-drives/:id
Description	Returns one placement drive using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "PLA101", "status": "Active"}

3. Add Placement Drive

Method	POST
URL	/placement-drives
Description	Creates a new placement drive.
Request Body	{"driveName": "Campus Drive 2026", "startDate": "2026-09-15", "endDate": "2026-09-16", "status": "Scheduled"}
Sample Response	{"message": "Placement drive created successfully"}

4. Update Placement Drive

Method	PUT
URL	/placement-drives/:id
Description	Updates an existing placement drive.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Placement Drive updated successfully"}

5. Delete Placement Drive

Method	DELETE
URL	/placement-drives/:id
Description	Deletes an existing placement drive.
Request Body	None
Sample Response	{"message": "Placement Drive deleted successfully"}

Interviews API

1. Get All Interviews

Method	GET
URL	/interviews
Description	Returns all interviews.
Request Body	None
Sample Response	[{"id": "INT101", "status": "Active"}]

2. Get Interview by ID

Method	GET
URL	/interviews/:id
Description	Returns one interview using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "INT101", "status": "Active"}

3. Add Interview

Method	POST
URL	/interviews
Description	Creates a new interview.
Request Body	{"applicationId": "APP101", "interviewDate": "2026-09-20", "interviewTime": "10:30", "mode": "Online", "round": "Technical"}
Sample Response	{"message": "Interview scheduled successfully"}

4. Update Interview

Method	PUT
URL	/interviews/:id
Description	Updates an existing interview.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Interview updated successfully"}

5. Delete Interview

Method	DELETE
URL	/interviews/:id
Description	Deletes an existing interview.
Request Body	None
Sample Response	{"message": "Interview deleted successfully"}

Notifications API

1. Get All Notifications

Method	GET
URL	/notifications
Description	Returns all notifications.
Request Body	None
Sample Response	[{"id": "NOT101", "status": "Active"}]

2. Get Notification by ID

Method	GET
URL	/notifications/:id
Description	Returns one notification using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "NOT101", "status": "Active"}

3. Add Notification

Method	POST
URL	/notifications
Description	Creates a new notification.
Request Body	{"userId": "STU101", "message": "You have been shortlisted", "type": "Placement", "isRead": false}
Sample Response	{"message": "Notification created successfully"}

4. Update Notification

Method	PUT
URL	/notifications/:id
Description	Updates an existing notification.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Notification updated successfully"}

5. Delete Notification

Method	DELETE
URL	/notifications/:id
Description	Deletes an existing notification.
Request Body	None
Sample Response	{"message": "Notification deleted successfully"}

Reports API

1. Get All Reports

Method	GET
URL	/reports
Description	Returns all reports.
Request Body	None
Sample Response	[{"id": "REP101", "status": "Active"}]

2. Get Report by ID

Method	GET
URL	/reports/:id
Description	Returns one report using its ID.
Request Body	URL Parameter: id
Sample Response	{"id": "REP101", "status": "Active"}

3. Add Report

Method	POST
URL	/reports
Description	Creates a new report.
Request Body	{"reportType": "Department Placement Report"}
Sample Response	{"message": "Report generated successfully"}

4. Update Report

Method	PUT
URL	/reports/:id
Description	Updates an existing report.
Request Body	{"status": "Updated"}
Sample Response	{"message": "Report updated successfully"}

5. Delete Report

Method	DELETE
URL	/reports/:id
Description	Deletes an existing report.
Request Body	None
Sample Response	{"message": "Report deleted successfully"}

Status Codes

Code	Meaning
200	OK
201	Created
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
500	Internal Server Error

Validation Rules

Entity / Field	Rule
Student - name, email, enrollmentNo	Required; email must be valid and enrollment number unique
Student - cgpa	Range 0-10
Student - backlogs	Must be 0 or greater
Recruiter - name, email, company	Required
Job - title, company, deadline	Required
Job - minCgpa	Range 0-10
Application - studentId, jobId	Required; duplicate application should not be allowed
Placement Drive - driveName, dates	Required; end date must not be before start date
Interview - applicationId, date/time	Required
Notification - userId, message	Required
Report - reportType	Required