From RANS Prediction to Hydrofoil Optimization: A Benchmark of Neural Surrogates

Aarav Dixit
aardixit7@gmail.com

Abstract

Neural flow surrogates are usually compared by field error, although their practical value often lies in the designs they select. We compare a convolutional neural network U-Net (CNN-U-Net), a physics-informed neural network (PINN), a Fourier neural operator (FNO), and a deep operator network (DeepONet) on 381 OpenFOAM computational fluid dynamics (CFD) simulations of hydrofoils in water. Complete families form disjoint training, validation, and final-test sets, and every architecture is trained with three seeds. The models predict Reynolds-averaged Navier–Stokes (RANS) fields, lift, drag, and pressure-based cavitation-inception risk, and then drive the same four-parameter hydrofoil shape-optimization loop. DeepONet gives the lowest mean pressure, C_p, lift, and drag errors on the untouched test families; the PINN is close and has the fastest inference. Inference is 384–665 times faster than OpenFOAM. Across seeds, endpoint solves give mean L/D from 22.10 to 37.47, but a three-level grid study shows that drag remains mesh-sensitive. Field accuracy, force accuracy, search quality, and simulator verification are related but not interchangeable.

1 Introduction

For a hydrofoil operating in water, shape design is an optimization problem wrapped around a flow solver. Each change in camber, thickness, or incidence requires another Reynolds-averaged Navier–Stokes (RANS) solution, so even a modest search can consume hundreds of computational fluid dynamics (CFD) evaluations; neural surrogates move most of that search off the solver by learning the map from geometry and operating conditions to flow and forces [Brunton et al., 2020]. The difficult question is not simply which network minimizes field error, but which one preserves the quantities that determine a useful design.

Convolutional neural network U-Nets (CNN-U-Nets) emphasize local multiscale structure [Ronneberger et al., 2015]. Fourier neural operators (FNOs) mix information globally in Fourier space [Li et al., 2021, Kovachki et al., 2023]. Deep operator networks (DeepONets) separate parameter and coordinate representations [Lu et al., 2021]. Physics-informed neural networks (PINNs) constrain learning with differential equations [Raissi et al., 2019]. Their relative merits may therefore change as the target moves from pressure fields to forces and finally to shape optimization.

Early airfoil-surrogate studies focused on field prediction [Guo et al., 2016, Bhatnagar et al., 2019, Sekar et al., 2019, Thuerey et al., 2020]. More recent benchmarks evaluate surface forces, out-of-distribution accuracy, and computational cost [Bonnet et al., 2022, Li et al., 2023, Yagoubi et al., 2025]. Those metrics establish whether a model approximates CFD, but they do not by themselves establish whether it will make the same design decision. A small, structured force error can be amplified when an optimizer repeatedly queries a narrow region of design space. The missing experiment is therefore a controlled comparison that follows several surrogate families through the same optimizer and then checks the selected geometries with new CFD solutions. High-fidelity endpoint

40th Conference on Neural Information Processing Systems (NeurIPS 2026). Workshop: Sim2Science: ML with Imperfect Scientific Models.

verification is standard in surrogate shape optimization, while a matched direct-CFD search provides a stronger reference when its cost is manageable [Li et al., 2022, Shukla et al., 2023].

That experiment is the contribution of this paper; we do not propose a new architecture. We train four representative model families on the same 381 RANS simulations, reserving two complete families for validation and two more for final testing. We compare fields, total forces, pressure-threshold cavitation screening, and runtime, then give every model the same three-start hydrodynamic shape optimization (HSO) problem. Fresh OpenFOAM solutions check the four surrogate winners, while a direct OpenFOAM search uses the same starts and budget as a reference. Cavitation risk here means inception inferred from C_p, not a multiphase prediction of cavity evolution.

2 Data and CFD reference

2.1 Design space

The dataset contains National Advisory Committee for Aeronautics (NACA) 0006, 0008, 0010, 0012, 0015, 0018, 2412, 2415, 4412, 4415, 4418, and 4421 profiles generated from the standard four-digit parameterization [Abbott and von Doenhoff, 1959]. Its camber, camber-location, and thickness descriptors provide a smooth, low-dimensional design space in which intermediate shapes remain valid four-digit profiles; they do not represent arbitrary hydrofoil topology. For each profile, we simulate angles of attack $\alpha \in \{-4, -2, 0, 2, 4, 6, 8, 10\}^\circ$ and Reynolds numbers $Re \in \{10^5, 2 \times 10^5, 5 \times 10^5, 10^6\}$. All cases use liquid water with density $\rho = 997$ kg/m^3 and kinematic viscosity $\nu = 10^{-6}$ m^2/s. With chord $c = 1$ m, the freestream speed is set by $U_\infty = Re\nu/c$; the far-field absolute pressure p_∞ and vapor pressure p_v are 101325 and 2300 Pa, respectively.

Each case is solved with OpenFOAM `simpleFoam` [Weller et al., 1998]. For steady incompressible flow, the mean velocity $\bar{u}_i$ and pressure $\bar{p}$ satisfy

$$\frac{\partial \bar{u}_i}{\partial x_i} = 0, \tag{1}$$

$$\rho \bar{u}_j \frac{\partial \bar{u}_i}{\partial x_j} = -\frac{\partial \bar{p}}{\partial x_i} + \mu \frac{\partial^2 \bar{u}_i}{\partial x_j \partial x_j} - \rho \frac{\partial \overline{u_i' u_j'}}{\partial x_j}. \tag{2}$$

Here, $\mu = \rho\nu$ is the dynamic viscosity, and $-\rho\overline{u_i' u_j'}$ is the Reynolds-stress tensor formed from velocity fluctuations u_i'. The Reynolds stress is closed with the k–ω shear-stress transport (SST) model [Menter, 1994]. Angled freestream velocity is imposed at the inlet and far boundary, and OpenFOAM's `forceCoeffs` supplies total lift and drag after 300 iterations. Cell-centered fields are interpolated to a common 128×64 Cartesian grid over $x/c \in [-1, 2]$ and $y/c \in [-0.75, 0.75]$. Inputs include coordinates, operating parameters, three NACA descriptors, a fluid mask, and signed distance to the profile.

Three simulations with $|C_L|$ or $|C_D| > 5$ are discarded before splitting, leaving 381 cases. NACA 0015 and 2412 provide 64 validation cases for early stopping; NACA 0018 and 4418 provide an untouched 64-case test set used only for final reporting. The remaining 253 cases from eight families train the models. This fixed partition is identical for every architecture and seed, and no validation or test geometry appears in training at another operating point. All retained solves reach iteration 300. The 95th-percentile maximum initial residual at that iteration is 1.27×10^{-4}; the corresponding late-window spans are 0.0059 in C_L and 2.65×10^{-4} in C_D.

2.2 Targets and cavitation-risk definition

The common output vector contains U_x, U_y, absolute pressure p, eddy viscosity ν_t, k, ω, C_p, cavitation margin, C_L, and C_D. Grid fields use masked normalized mean-squared error, while the case-level force targets use normalized mean-squared error. OpenFOAM's kinematic gauge pressure p_k is converted to absolute pressure as

$$p = p_\infty + \rho p_k, \qquad C_p = \frac{p - p_\infty}{\frac{1}{2}\rho U_\infty^2}. \tag{3}$$

For an ambient-pressure value p_a, the pressure-based inception margin is

$$M(x, y; p_a) = p_a + C_p(x, y)\tfrac{1}{2}\rho U_\infty^2 - p_v. \tag{4}$$

A cell is labeled at risk when $M < 0$. We evaluate this label at $p_a \in \{2500, 3000, 5000, 10000, 25000, 101325\}$ Pa. This sweep creates a useful classification test from the predicted C_p field without representing multiphase physics.

3 Surrogates and optimization

3.1 Model families

The **CNN-U-Net** has three encoder/decoder levels, skip connections, group normalization, Gaussian error linear unit (GELU) activations, and base width 16 [Ronneberger et al., 2015]. The **FNO** has width 32, four operator blocks, and 12 retained Fourier modes per direction [Li et al., 2021]. Its update is

$$h_{l+1} = \sigma\big(W_l h_l + \mathcal{F}^{-1}(R_l \mathcal{F}(h_l))\big)\,. \tag{5}$$

Here, h_l is the layer-l feature field, W_l is a learned local linear map, σ is a nonlinear activation, $\mathcal{F}$ and $\mathcal{F}^{-1}$ are the forward and inverse Fourier transforms, and R_l contains the learned spectral weights on the retained modes. The **DeepONet** uses three-layer, width-64 branch and trunk networks with 64 basis functions. Its output has the form

$$\widehat{y}_q(\mathbf{x}; \boldsymbol{\mu}) = \mathbf{b}_q(\boldsymbol{\mu})^\top \mathbf{t}_q(\mathbf{x})/\sqrt{64} + c_q. \tag{6}$$

Here, $\boldsymbol{\mu}$ contains the operating and geometry parameters, $\mathbf{b}_q$ and $\mathbf{t}_q$ are the branch- and trunk-network outputs for output channel q, $\mathbf{x}$ is the query coordinate, and c_q is a learned bias [Lu et al., 2021]. The **PINN** has three tanh layers of width 64 and uses 1,024 sampled points per case. Its supervised loss is augmented by 10^{-4} times the full steady incompressible RANS continuity and mean-momentum residuals under a Boussinesq eddy-viscosity closure [Raissi et al., 2019]. Appendix B gives the exact implemented objective, including physical-unit denormalization, coordinate scaling, and residual nondimensionalization.

All models use AdamW with learning rate 2×10^{-3}, weight decay 10^{-4}, at most 120 epochs, patience 20, and gradient clipping. Each architecture is trained with seeds 7, 17, and 27 on the same split. Normalization uses training cases only. The best checkpoint is selected by validation loss. Model size ranges from 9,930 to 595,914 parameters (Table 1).

Data, targets, optimizer, stopping rule, and evaluation budget are shared, but parameter counts are reported rather than artificially matched: equal width is not equal capacity across convolutional, spectral, branch–trunk, and pointwise models. These are compact canonical configurations, and no hyperparameter is selected on the test families.

Optimization uses dedicated C_L and C_D output heads supervised by OpenFOAM's total force coefficients. Pressure integration on the coarse common grid is not used for the objective because it omits viscous traction and under-resolves the wall. This choice preserves OpenFOAM's pressure and viscous contributions but makes force prediction dependent on direct supervision and limits transfer beyond the sampled flow and geometry regime.

3.2 Common optimization protocol

At $Re = 5 \times 10^5$, each surrogate drives the same HSO loop. The design vector $\theta = (m, p, t, \alpha)$ contains maximum camber, camber location, thickness, and incidence, with bounds $m \in [0, 0.09]$, $p \in [0.1, 0.9]$, $t \in [0.06, 0.20]$, and $\alpha \in [-4, 10]^\circ$. We launch Nelder–Mead from NACA 0012, 2412, and 4415 and give every run the same 40-iteration budget [Nelder and Mead, 1965]. The objective is

$$J(\theta) = \frac{C_L}{|C_D| + 10^{-6}}. \tag{7}$$

The search calls only the surrogate; OpenFOAM is not used inside the loop, and cavitation margin is retained only as a secondary diagnostic. We return the best design observed within the fixed budget, select the strongest of the three starts for each architecture, and then generate a new mesh and independent OpenFOAM simulation for that winner.

The optimizer is continuous although the training geometries are discrete. It queries intermediate four-digit descriptors (m, p, t) within the stated bounds and can move beyond the convex coverage

Table 1: Final-test RMSE (mean ± sample standard deviation over three seeds), size, and speedup.

Model	p (Pa)	C_p	C_L	C_D	Params. (k)	Speedup
CNN-U-Net	28.3 ± 14.2	$.066 \pm .037$	$.258 \pm .200$	$.0087 \pm .0052$	485	544 ± 13
PINN	11.3 ± 0.4	$.044 \pm .003$	$.036 \pm .005$	$.0035 \pm .0002$	**9.93**	665 ± 4
FNO	27.8 ± 1.1	$.064 \pm .004$	$.248 \pm .020$	$.0103 \pm .0005$	596	464 ± 6
DeepONet	10.7 ± 1.5	$.041 \pm .005$	$.030 \pm .008$	$.0034 \pm .0009$	101	384 ± 2




Figure 1: Absolute-pressure prediction for NACA 4418. The view spans $x/c \in [-0.25, 1.25]$ and $y/c \in [-0.375, 0.375]$.

of the training families near a bound. We retain every query and independently remesh and solve each selected endpoint with CFD; this validates the reported design, not the full learned surface.

The direct-CFD baseline repeats this protocol with the same starts, bounds, objective, tolerances, and 40-iteration budget, but OpenFOAM supplies every objective value. It is distinct from the one-solve endpoint checks of the surrogate winners. Appendix Figure 3 shows the complete best-so-far traces for every start and training seed.

4 Results

4.1 Final-test accuracy and computational cost

Table 1 reports mean and one sample standard deviation over three seeds on the untouched NACA 0018/4418 test set. DeepONet gives the lowest mean pressure, C_p, C_L, and C_D errors. The PINN is consistently second; CNN-U-Net is notably seed-sensitive.

Mean training times are 556, 283, 270, and 47 s for CNN-U-Net, the PINN, FNO, and DeepONet. Complete-field inference yields 384–665× speedups over the measured OpenFOAM cases. The benchmark used an 8-core Apple M2 Mac mini with 16 GB memory; PyTorch ran on CPU and OpenFOAM 9 ran in Docker.

Figure 1 shows a case from the unseen NACA 4418 family. The pointwise models reproduce the leading-edge pressure structure most closely; CNN-U-Net smooths the extrema and FNO introduces spatial texture.

4.2 Cavitation-inception screening

The pressure-threshold labels are highly imbalanced, so we report F1 rather than accuracy. DeepONet obtains 0.900 ± 0.008, the PINN 0.859 ± 0.015, CNN-U-Net 0.758 ± 0.198, and FNO 0.724 ± 0.065. This is a secondary low-C_p diagnostic, not a prediction of cavity dynamics [Brennen, 1995].

4.3 Shape optimization against direct CFD

Figure 2 reports the complete L/D comparison: the OpenFOAM value of the starting foil, the surrogate estimate at its selected design, and the result of remeshing that design and solving it once in OpenFOAM. This one-solve endpoint check is distinct from the direct baseline, which places OpenFOAM inside the matched optimizer.

Across three selected endpoints per architecture, medium-grid OpenFOAM gives $L/D = 24.44 \pm 1.35$ for CNN-U-Net, 36.85 ± 5.09 for the PINN, 22.10 ± 3.46 for FNO, and 37.47 ± 5.95 for




Figure 2: Top: selected shapes against the same dashed NACA 2412 geometric reference. The reference is for visual comparison, not necessarily the optimizer initializer. Bottom: initial-foil OpenFOAM values, surrogate predictions, fresh OpenFOAM endpoint checks, and direct CFD.

DeepONet. The matched direct-CFD search reaches 29.89. These values are not mesh-independent: on the seed-7 winners, medium-to-fine L/D shifts are 16–22%.

5 Discussion

DeepONet is the best final-test predictor, while its optimized endpoints and those of the PINN both vary across seeds. CNN-U-Net is unstable in both force prediction and optimization; FNO is more repeatable but selects lower-performing designs. Accuracy, candidate ranking, and seed robustness are therefore distinct.

All 12 three-level grid-study runs converge iteratively by 1,000 iterations, with maximum final initial residuals below 10^{-5} and force spans below 3×10^{-6} over the final 50 iterations. Lift changes by at most about 4% from medium to fine, but drag changes by 16–26%. Thus, a fresh OpenFOAM endpoint is a standard and useful verification step, yet it is not by itself a grid-independent validation. This is precisely the simulator imperfection exposed by carrying the benchmark through the design loop.

The continuous optimizer also queries descriptors between and near the bounds of twelve discrete families. Endpoint CFD checks the selected shape, not the entire learned surface. All winners remain far from vapor pressure, so cavitation is a secondary diagnostic rather than an active constraint. The rankings are therefore evidence for this controlled benchmark, not for general hydrofoil design: the remaining scope is steady 2D RANS, one compact configuration per architecture, three seeds, and the NACA four-digit space.

6 Conclusion

While standard benchmarks rank neural flow surrogates by field and force errors—where DeepONet excels and the compact PINN dominates in speed—our end-to-end evaluation reveals a critical blind spot. Pushing these models through a multi-start optimization loop demonstrates that isolated test accuracy does not reliably predict downstream design decisions or seed robustness. To truly bridge machine learning and scientific engineering, surrogates must be evaluated on their operational consequences and the numerical uncertainty of the verifying simulator. Future work will advance this paradigm through three-dimensional flows and active cavitation-constrained optimization.

References

Ira H. Abbott and Albert E. von Doenhoff. *Theory of Wing Sections*. Dover Publications, 1959.

Saakaar Bhatnagar, Yaser Afshar, Shaowu Pan, Karthik Duraisamy, and Shailendra Kaushik. Prediction of aerodynamic flow fields using convolutional neural networks. *Computational Mechanics*, 64(2):525–545, 2019. doi: 10.1007/s00466-019-01740-0.

Florent Bonnet, Jocelyn Ahmed Mazari, Paola Cinnella, and Patrick Gallinari. AIRFRANS: High fidelity computational fluid dynamics dataset for approximating reynolds-averaged navier–stokes solutions. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Christopher E. Brennen. *Cavitation and Bubble Dynamics*. Oxford University Press, 1995.

Steven L. Brunton, Bernd R. Noack, and Petros Koumoutsakos. Machine learning for fluid mechanics. *Annual Review of Fluid Mechanics*, 52:477–508, 2020. doi: 10.1146/annurev-fluid-010719-060214.

Xiaoxiao Guo, Wei Li, and Francesco Iorio. Convolutional neural networks for steady flow approximation. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 481–490, 2016. doi: 10.1145/2939672.2939738.

Nikola Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces with applications to PDEs. *Journal of Machine Learning Research*, 24(89):1–97, 2023.

Jichao Li, Xiaosong Du, and Joaquim R. R. A. Martins. Machine learning in aerodynamic shape optimization. *arXiv preprint arXiv:2202.07141*, 2022.

Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. In *International Conference on Learning Representations*, 2021.

Zongyi Li, Nikola Kovachki, Chris Choy, Boyi Li, Jean Kossaifi, Shourya Otta, Mohammad Amin Nabian, Maximilian Stadler, Christian Hundt, Kamyar Azizzadenesheli, and Animashree Anandkumar. Geometry-informed neural operator for large-scale 3d PDEs. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators. *Nature Machine Intelligence*, 3:218–229, 2021. doi: 10.1038/s42256-021-00302-5.

Florian R. Menter. Two-equation eddy-viscosity turbulence models for engineering applications. *AIAA Journal*, 32(8):1598–1605, 1994. doi: 10.2514/3.12149.

John A. Nelder and Roger Mead. A simplex method for function minimization. *The Computer Journal*, 7(4):308–313, 1965. doi: 10.1093/comjnl/7.4.308.

Maziar Raissi, Paris Perdikaris, and George E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. doi: 10.1016/j.jcp.2018.10.045.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical Image Computing and Computer-Assisted Intervention*, pages 234–241, 2015. doi: 10.1007/978-3-319-24574-4_28.

Vinothkumar Sekar, Qinghua Jiang, Chuan Shu, and Boo Cheong Khoo. Fast flow field prediction over airfoils using deep learning approach. *Physics of Fluids*, 31(5):057103, 2019. doi: 10.1063/1.5094943.

Khemraj Shukla, Vivek Oommen, Ahmad Peyvan, Michael Penwarden, Luis Bravo, Anindya Ghoshal, Robert M. Kirby, and George Em Karniadakis. Deep neural operators can serve as accurate surrogates for shape optimization: A case study for airfoils. *arXiv preprint arXiv:2302.00807*, 2023.

Nils Thuerey, Konstantin Weissenow, Lukas Prantl, and Xiangyu Hu. Deep learning methods for reynolds-averaged navier–stokes simulations of airfoil flows. *AIAA Journal*, 58(1):25–36, 2020. doi: 10.2514/1.J058291.

Henry G. Weller, G. Tabor, Hrvoje Jasak, and C. Fureby. A tensorial approach to computational continuum mechanics using object-oriented techniques. *Computers in Physics*, 12(6):620–631, 1998. doi: 10.1063/1.168744.

Mouadh Yagoubi, David Danan, Milad Leyli-Abadi, Jocelyn Mazari, Jean-Patrick Brunet, Abbas Kabalan, Fabien Casenave, Yuxin Ma, Giovanni Catalani, Jean Fesquet, Jacob Helwig, Xuan Zhang, Haiyang Yu, Xavier Bertrand, Frederic Tost, Michael Bauerheim, Joseph Morlier, and Shuiwang Ji. ML4CFD competition: Results and retrospective analysis. In *Advances in Neural Information Processing Systems*, volume 38, 2025.

A Code and data availability

Source code and reproduction instructions are available at `https://github.com/aaravvd/hydrofoil-neural-surrogates`. The CFD dataset and trained checkpoints are archived at `https://doi.org/10.5281/zenodo.21845241`. Code is released under the MIT License; generated data and checkpoints use CC BY 4.0.

B PINN objective

The network predicts normalized outputs, but the residuals are evaluated after velocity and pressure are returned to physical units. For output channel q,

$$q = \sigma_q \widehat{q} + \mu_q, \qquad \frac{\partial q}{\partial x_i} = \frac{\sigma_q}{\sigma_{x_i}} \frac{\partial \widehat{q}}{\partial \widehat{x}_i}, \tag{8}$$

where the means and standard deviations are computed from the training set. Comma subscripts denote partial spatial derivatives. Let $\nu_e = \nu + \max(\nu_t, 0)$. The modeled kinematic stresses are

$$\tau_{xx} = 2\nu_e U_{x,x}, \qquad \tau_{xy} = \nu_e (U_{x,y} + U_{y,x}), \tag{9}$$

$$\tau_{yy} = 2\nu_e U_{y,y}. \tag{10}$$

The sampled-point continuity and momentum residuals are

$$r_c = U_{x,x} + U_{y,y}, \tag{11}$$

$$r_x = U_x U_{x,x} + U_y U_{x,y} + p_{,x}/\rho - \tau_{xx,x} - \tau_{xy,y}, \tag{12}$$

$$r_y = U_x U_{y,x} + U_y U_{y,y} + p_{,y}/\rho - \tau_{xy,x} - \tau_{yy,y}. \tag{13}$$

For chord c and casewise freestream speed U_∞, the combined objective is

$$\mathcal{L} = \mathcal{L}_{\text{sup}} + 10^{-4} \left[\text{MSE}\left(\frac{c r_c}{U_\infty} \right) + \text{MSE}\left(\frac{c r_x}{U_\infty^2} \right) + \text{MSE}\left(\frac{c r_y}{U_\infty^2} \right) \right]. \tag{14}$$

C Complete optimization traces




Figure 3: All three optimization starts and three training seeds per surrogate, with the three direct-CFD starts. Color identifies the NACA 0012, 2412, or 4415 initializer; the three same-color surrogate curves correspond to seeds 7, 17, and 27. Lines show the best-so-far objective, and every raw evaluation is available in the public repository.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract, introduction, and limitations distinguish CFD agreement, physical validation, and pressure-based inception screening.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 5 discusses simulator fidelity, geometry scope, direct force supervision, continuous-shape extrapolation, and the boundary of the cavitation diagnostic.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: The paper presents an empirical benchmark and no theoretical results or proofs.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: Sections 2–3 specify the case matrix, split, CFD setup, model families, losses, hyperparameters, and optimization protocol.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Appendix A links the public code and data releases, which provide three checkpoints per architecture, final-test grids, compact results, licenses, and exact reproduction instructions: `https://github.com/aaravvd/hydrofoil-neural-surrogates` and `https://doi.org/10.5281/zenodo.21845241`.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Sections 2–3 give the fixed train/validation/test families, three seeds, optimizer, learning rate, model sizes, stopping rule, and design bounds.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Every architecture is trained with seeds 7, 17, and 27 on the same split; tables report the mean and one sample standard deviation over those independent training runs.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Section 4 reports CPU hardware, memory, software versions, training time, solver time, inference time, and amortized break-even counts.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The research uses generated CFD data, involves no people or sensitive data, and preserves limitations and exclusions.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: Section 5 discusses computational benefits and the risk that surrogate speed can scale simulator bias or invalid cavitation claims.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The generated hydrofoil models and CFD fields do not present a high-risk dual-use release.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: OpenFOAM and the prior architectures are cited; dependency versions are pinned, source code is MIT licensed, and the generated dataset and checkpoints are CC BY 4.0 licensed in the artifact.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.

- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The public repository and data archive document generation, fixed family partition, training, evaluation, optimization, CFD checks, expected outputs, claim boundaries, and separate code/data licenses.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The work contains no crowdsourcing or human-subject research.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The work contains no human-subject research requiring IRB review.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [N/A]

Justification: LLMs are not part of the scientific method, model architectures, data generation, or evaluation reported in the paper.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.