Fall Risk Assessment of Patients using Machine Learning

Aarav Walavalkar
Reg.No 220911444
Department of I&CT

Abstract - Falls in hospitalized patients remain a critical healthcare issue, prompting the adoption of machine learning for risk prediction. This review examines recent advancements in predictive models, wearable sensor technologies, and ethical concerns surrounding data privacy. Machine learning approaches, including decision trees, deep learning, and ensemble techniques, have improved fall risk assessment accuracy. However, challenges such as model interpretability, dataset generalizability, and clinical integration persist. The study highlights research gaps, including standardization of risk factors and real-time implementation, emphasizing the need for privacy-aware, reliable predictive systems to enhance patient safety.

Index terms - Fall Risk Prediction, Machine Learning, Wearable Sensors, Clinical Decision Support, Deep Learning, Privacy Concerns, Hospitalized Patients, Healthcare AI.

I. Introduction

Falls in hospitalized patients, especially older adults, pose serious health risks, leading to injuries, longer hospital stays, and higher medical costs. Traditional assessment tools like the Morse Fall Scale (MFS) are widely used but often lack real-time adaptability. Advances in artificial intelligence (AI), machine learning (ML), and wearable sensor technology have introduced more dynamic approaches to fall risk prediction and prevention. This review examines the effectiveness of AI-driven models compared to traditional methods, focusing on machine learning applications, wearable sensor systems, hospitalbased prevention strategies, and ethical considerations regarding patient privacy. The key research question is: How do AI-based fall risk assessment models improve upon traditional methods, and what are their clinical implications? Studies selected for this review include peerreviewed research on hospital fall prediction, ML-driven risk assessment, and IoT-based monitoring, emphasizing empirical data and comparative analysis. By evaluating current models, this review identifies strengths, limitations, and research gaps, offering insights into future advancements in real-time fall prevention strategies.

II. Theoretical Framework

A. Morse Theory Scale(MSF) Theory

The Morse Fall Scale (MFS) is a widely used clinical tool designed to assess a patient's likelihood of falling based on six key factors: history of falling, secondary diagnoses, ambulatory aid use, intravenous therapy, gait stability, and mental status. Each factor is assigned a score, and the total score categorizes patients into different risk levels. The MFS has been a benchmark in clinical settings for decades, providing a simple yet effective means of assessing fall risk. However, recent studies, such as Choi et al. (2023), examine the limitations of MFS in real-world hospital settings, particularly its inability to dynamically adjust risk levels based on real-time patient data. As a result, machine learning models have been explored to improve upon MFS, offering more personalized and data-driven risk assessments.

B. Human Activity Recognition Model

The Human Activity Recognition (HAR) model is a machine learning-based approach that utilizes data from wearable sensors to classify human movements and detect fall events. These models analyze patterns of acceleration, posture shifts, and gait irregularities to determine when a fall has occurred or is likely to occur. Subramaniam et al. (2022) discuss the role of HAR models in improving wearable-based fall detection, highlighting their ability to differentiate between normal movements and sudden, risky shifts that indicate a fall. HAR models have become increasingly relevant in geriatric and inpatient care, where real-time monitoring can provide early warnings and trigger interventions before a fall occurs.

C. Intrinsic & Extrinsic Risk Factor Framework

The Intrinsic & Extrinsic Risk Factor Framework categorizes fall risks into two main groups: intrinsic (patient-related) and extrinsic (environmental). Intrinsic factors include age, muscle weakness, cognitive impairment, and medication side effects, while extrinsic factors encompass environmental hazards like poor lighting, slippery floors, and improper footwear. Jahangiri et al. (2024) apply this framework in their study by integrating it with machine learning models to enhance fall risk prediction. This framework helps shape research by ensuring that AI-based models consider both personal and environmental risk factors, making predictions more comprehensive and actionable.

D. Supervise Machine Learning Models for Fall Risk Predicion

Supervised machine learning techniques, such as Decision Trees, Support Vector Machines (SVM), and Neural Networks, have been widely explored for fall risk assessment. These models learn from historical patient data, identifying patterns and correlations between different risk factors and fall incidents. Jahandideh et al. (2023) compare

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

various supervised learning models, demonstrating how advanced algorithms can improve prediction accuracy over traditional assessment tools. These models provide dynamic and adaptable risk assessments, capable of updating in realtime as new patient data becomes available. By integrating AI into clinical settings, fall prevention strategies can be tailored to individual patients with greater precision.

E. Fall Prevention and Prevention Paradigm in Geriartic Care

The Fall Detection and Prevention Paradigm in Geriatric Care focuses on utilizing technology to support elderly populations by identifying risk factors and implementing preventative measures. Falls are a leading cause of injury among older adults, and studies such as Yang (2023) examine the ethical and privacy concerns surrounding AI-based monitoring systems. While machine learning and IoT (Internet of Things) technologies present promising solutions for early fall detection, issues related to patient autonomy, data privacy, and continuous surveillance have been raised. This paradigm shapes research by balancing the advantages of AI-driven fall prevention with ethical considerations that uphold patient dignity and informed consent.

F. Bayesian Inference model for Risk Estimation

The Bayesian Inference Model utilizes probabilistic reasoning to assess the likelihood of falls based on historical data. These models deliver more adaptable and context-aware risk evaluations by continually refreshing probability distributions with new information. Warrington et al. (2021) emphasize the application of Bayesian models in wearable technology, showcasing their ability to enhance fall detection and predictive accuracy. In contrast to static scoring systems, Bayesian inference facilitates real-time updates, making it an essential tool in hospitals where patient conditions can fluctuate swiftly.

G. Internet of Medical things in fall prevention

The Internet of Medical Things (IoMT) refers to the interconnected network of smart medical devices that communicate and analyze patient data in real time. In fall prevention, IoMT enables wearable sensors, hospital monitoring systems, and AI algorithms to work together to detect risks and alert healthcare providers. Mao et al. (2023) emphasize the future of IoMT in fall prediction, noting its potential for remote monitoring and early intervention. This model has significant implications for aging populations and hospitalized patients, allowing caregivers to respond proactively rather than reactively to fall risks.

H. Clinical Decision Support system

Clinical Decision Support Systems (CDSS) are AIpowered tools that assist healthcare professionals in making informed decisions regarding patient care. In fall risk management, CDSS analyzes patient data, applies predictive models, and suggests interventions to prevent falls. Choi et al. (2023) discuss CDSS applications in stroke patient fall prediction, demonstrating how AI-driven decision support enhances clinical workflows. CDSS plays a crucial role in translating AI predictions into actionable insights, ensuring that healthcare providers can implement timely and effective fall prevention strategies.

III. Review of Literature

This review of literature organized methodically addressing various approaches and methodologies in machinelearning (ML) algorithms and Fall Risk Assessment.

A. Machine Learning in Fall Risk Prediction The main theme of this paper is the application of machine learning (ML) techniques for assessing fall risk in hospitalized patients. This research builds upon existing studies that combine machine learning (ML) algorithms with healthcare data to enhance predictive accuracy beyond traditional assessment methods such as the Morse Fall Scale (MFS).Below is a methodological breakdown of the key theories that serve as the foundation for this paper

- Human Activity Recognition (HAR) model plays a crucial role in identifying patient movement patterns, distinguishing normal activities from potentially hazardous behaviors. By utilizing sensor-based or vision-based approaches, the HAR framework enables the ML model in this study to track motion-related risk factors for falls. The methodology aligns with previous research where HAR-based algorithms were trained on patient movement data to detect abnormal gait patterns.
- Bayesian approaches are widely applied in fall risk prediction due to their ability to incorporate prior knowledge and update probabilities as new patient data becomes available. The paper likely integrates Bayesian classifiers or Hidden Markov Models (HMMs) to assess uncertainty in patient movement and environmental risks. Such models have been methodologically validated in previous research for dynamic risk estimation in clinical settings.
- The integration of machine learning within a Clinical Decision Support System (CDSS) is a key methodological step. The study builds on prior models where AI-driven tools assist healthcare providers in making real-time interventions by flagging high-risk patients. The methodological framework follows previous studies that incorporated MLdriven alerts into hospital workflows, ensuring that caregivers receive timely fall risk assessments.
- The research applies supervised learning algorithms such as logistic regression, decision trees, and neural networks, which are common in healthcare risk prediction. This methodological approach is informed by past studies that used structured patient data (e.g., age, mobility scores, medication history) to train models capable of predicting falls with higher accuracy than traditional risk assessment scales like the Morse Fall Scale (MFS).

B. Ethical and Environmental Considerations in AI-Driven Fall Risk Assessment

- Environmental Risk Factor Theory in Fall Prevention

  Jahangiri et al. (2023) integrate extrinsic risk factors into fall risk prediction, aligning with Subramaniam et al. (2023), who highlight the role of hospital environments in patient falls. Traditional models focus on patient characteristics, but recent studies

incorporate sensor-based environmental monitoring to detect hazards like poor lighting or improper furniture placement. Both studies emphasize IoTbased spatial analysis for real-time risk assessment, shifting the focus from reactive interventions to proactive fall prevention in clinical settings.

- Ethical and Privacy Concerns in AI-Based Fall Monitoring

  With the rise of AI-driven fall detection, concerns over patient privacy and data security are critical.

  Yang (2023) discusses how wearables and IoT-based monitoring raise ethical challenges, a concern echoed by Jahangiri et al. (2023). Both studies advocate for privacy-preserving AI techniques, such as federated learning and data anonymization, to balance fall prevention and patient autonomy. As hospitals adopt real-time surveillance, these studies stress the need for robust ethical frameworks to prevent excessive monitoring while ensuring effective fall risk mitigation.

C. Comparison Of Studies: Agreements, Contradictions and Gaps

- *Agreements*
  Most studies, including Jahangiri et al. (2023), Subramaniam et al. (2023), and Yang (2023), agree that fall risk assessment must integrate both intrinsic and extrinsic factors. There is a consensus that machine learning models improve prediction accuracy, and recent advancements focus on sensor-based monitoring to enhance realtime risk detection. Additionally, all studies emphasize the importance of ethical considerations, particularly in data privacy and AI-driven surveillance. Yang (2023) and Jahangiri et al. (2023) both advocate for privacy-preserving AI methods, such as federated learning and anonymization techniques, to address growing concerns about patient monitoring.
- *Contradictions*
  While there is agreement on the role of machine learning in fall prediction, studies differ in methodological emphasis. Subramaniam et al. (2023) focus on wearable sensors and IoT-based environmental monitoring, while Jahangiri et al. (2023) prioritize AI-driven clinical decisionmaking using patient records. Furthermore, Yang (2023) takes a more cautionary stance, highlighting privacy risks that other studies only briefly mention. This reflects a gap in how ethical challenges are addressed—some studies propose technical solutions, while others argue for policydriven regulation of AI in healthcare.
- *Research Gaps*
  Despite advancements in AI-driven fall prediction, gaps remain in real-world implementation and validation. Many studies rely on retrospective datasets, limiting their applicability in dynamic hospital settings. Additionally, while studies discuss privacy concerns, few explore the patient perspective on AI monitoring or how consent frameworks should be designed. There is also limited research on how AI models perform across different hospital environments, suggesting a need for multi-site validation studies to ensure broader applicability.

D. Trends and Development

Recent advancements in fall risk assessment have shifted from traditional methods, such as the Morse Fall Scale, to AI-driven predictive models that integrate wearable sensors and IoT-based monitoring systems. Studies like Subramaniam et al. (2023) and Jahangiri et al. (2023) highlight how real-time motion analysis improves fall detection and prevention. Additionally, hybrid approaches combining intrinsic (patient-specific) and extrinsic (environmental) factors are gaining traction. Jahangiri et al. (2023) emphasize that factors such as floor conditions, lighting, and bed height must be considered alongside patient movement patterns. Moreover, the development of real-time AI-driven Clinical Decision Support Systems (CDSS) enables dynamic risk alerts, enhancing patient safety and hospital interventions.

Privacy concerns surrounding AI-based fall detection have led to privacy-preserving AI techniques, such as federated learning and differential privacy, as discussed by Yang (2023). These techniques allow hospitals to analyze patient data securely without compromising confidentiality. Additionally, there is a growing focus on standardizing AI models for clinical validation, ensuring transparency and reliability. Studies like Mao et al. (2023) are also advancing personalized AI models, which account for individual movement patterns, medication effects, and comorbidities. This shift from generalized fall risk assessments to adaptive, patient-specific AI models represents a critical development in fall prevention research.

IV. Critical Analysis and Synthesis

While AI-driven fall risk assessment has seen significant advancements, gaps remain in current research. Many studies, such as Jahangiri et al. (2023) and Subramaniam et al. (2023), focus on machine learning-based prediction models but often rely on limited datasets that do not fully represent diverse patient populations. The lack of largescale clinical validation hinders the widespread adoption of these models in hospital environments, as their effectiveness across different healthcare settings remains unproven. Furthermore, most models depend on historical patient data, making them less adaptable to real-time fall risk prediction.

Another key limitation is the inconsistency in integrating intrinsic and extrinsic factors. While Jahangiri et al. (2023) propose a hybrid approach that considers both patient-specific risk factors and environmental conditions, there is no universal framework for combining these variables. Different hospitals may use varying data collection methods, leading to inconsistent model performance. Moreover, real-time IoT-based monitoring systems, as discussed by Subramaniam et al. (2023), show potential but lack standardization, limiting their practical application.

Ethical and privacy concerns also present challenges in AI-based fall risk prediction. Yang (2023) highlights the risks associated with continuous surveillance in hospitals, where AI models collect sensitive patient data. The implementation of privacy-preserving AI techniques, such as federated learning and differential privacy, is still in

its early stages. Without robust data security measures, AIdriven models may compromise patient confidentiality, raising concerns about regulatory compliance in healthcare AI applications.

Additionally, existing research often fails to account for real-time adaptability in fall risk prediction models. Mao et al. (2023) emphasize the need for personalized AI models that adjust to individual movement patterns, medication effects, and comorbidities. However, most current models remain static, lacking mechanisms for dynamic risk updates based on changing patient conditions. Future research should explore adaptive AI systems capable of continuous learning from live patient data.

To bridge these gaps, further exploration is needed in realtime clinical validation, standardization of hybrid models, and ethical AI implementation. Jahangiri et al. (2023) suggest that collaborations between AI researchers and clinicians could enhance model reliability, while Yang (2023) calls for stricter regulatory guidelines to ensure ethical deployment. Addressing these challenges will be crucial in enhancing the effectiveness, reliability, and ethical considerations of AI-based fall risk assessment models in clinical settings.

V. Conclusion

The integration of AI-driven models in fall risk assessment has demonstrated significant potential, yet challenges remain in clinical validation, data integration, privacy, and adaptability. Studies such as Jahangiri et al. (2023) and Subramaniam et al. (2023) emphasize the shift towards real-time, hybrid approaches, but inconsistent methodologies and lack of standardized frameworks hinder widespread adoption. Ethical concerns, as highlighted by Yang (2023), further underscore the need for privacypreserving AI techniques to ensure regulatory compliance. Moreover, the demand for adaptive, patient-specific AI models, as suggested by Mao et al. (2023), calls for further research into dynamic, continuously learning systems. Addressing these gaps through interdisciplinary collaboration, clinical validation, and regulatory advancements will be essential in optimizing AI-driven fall prevention strategies for hospital environments.

References

[1] S. Jahangiri, M. Abdollahi, R. Patil, E. Rashedi, and N. Azadeh-Fard, "An inpatient fall risk assessment tool: Application of machine learning models on intrinsic and extrinsic risk factors," in *2023 IEEE International Conference on Biomedical and Health Informatics (BHI)*, 2023. : https://doi.org/10.1016/j.mlwa.2023.100519

[2] S. Subramaniam, A. I. Faisal, and M. J. Deen, "Wearable sensor systems for fall risk assessment: A review," in *2023 IEEE International Conference on Wearable and Implantable Body Sensor Networks (BSN)*, 2023.: https://www.frontiersin.org/journals/digitalhealth/articles/10.3389/fdgth.2022.921506/full

[3] A. Mao, J. Su, M. Ren, S. Chen, and H. Zhang, "Risk prediction models for falls in hospitalized older patients: A systematic review and metaanalysis," in *2023 IEEE International Conference on Healthcare Informatics (ICHI)*, 2023.: http://dx.doi.org/10.1186/s12877-025-05688-0

[4] R. Yang, "Privacy and surveillance concerns in machine learning fall prediction models: Implications for geriatric care and the Internet of Medical Things," in *2023 IEEE International Conference on AI for Health (AIAH)*, 2023.: http://dx.doi.org/10.1007/s00146-023-01655-8

[5] C.-W. Kang, Z.-K. Yan, J.-L. Tian, X.-B. Pu, and L.-X. Wu, "Constructing a fall risk prediction model for hospitalized patients using machine learning," in *2023 IEEE International Conference on Machine Learning and Applications (ICMLA)*, 2023.: https://bmcpublichealth.biomedcentral.com/articles/10.1186/s12889-025-21284-8

[6] J. H. Choi, E. S. Choi, and D. Park, "In-hospital fall prediction using machine learning algorithms and the Morse Fall Scale in patients with acute stroke: A nested case-control study," in *2023 IEEE International Conference on Neural Engineering (NER)*, 2023.: https://link.springer.com/article/10.1186/s12911-023-02330-0

[7] S. Jahandideh, A. F. Hutchinson, T. K. Bucknall, J. Considine, A. Driscoll, E. Manias, N. M. Phillips, B. Rasmussen, N. Vos, and A. M. Hutchinson, "Using machine learning models to predict falls in hospitalised adults," in *2023 IEEE International Conference on Smart Health (ICSH)*, 2023.: https://doi.org/10.1016/j.ijmedinf.2024.105436

[8] D. J. Warrington, E. J. Shortis, and P. J. Whittaker, "Are wearable devices effective for preventing and detecting falls: An umbrella review (a review of systematic reviews)," in *2023 IEEE International Conference on Aging and Technology (ICAT)*, 2023.: https://doi.org/10.1186/s12889-021-12169-7

[9] J. Zhang *et al.*, "An Effective Deep Learning Framework for Fall Detection: Model Development and Study Design," *J. Med. Internet Res.*, vol. 26, p. e56750, 2024.: https://www.jmir.org/2024/1/e56750

[10] M. P. Bharadwaz, J. Kalita, A. Mitro, and A. Dutta, "Utilizing Machine Learning to Identify Fall Predictors in India's Aging Population: Findings from the LASI," *BMC Geriatrics*, vol. 25, no. 181, 2025.: https://bmcgeriatr.biomedcentral.com/articles/10.1186/s12877-02505813-z.

Sr. No	Title	Author Details	Year	Concept	Methodology	Dataset	Findings	Research Gaps
1	An inpatient fall risk assessment tool: Application of machine learning models on intrinsic and extrinsic risk factors	S. Jahangiri, M. Abdollahi, R. Patil, E. Rashedi, and N. AzadehFard	2023	Machine learning-based fall risk assessment using intrinsic and extrinsic facto	Supervised learning models analyzing patient data for risk prediction.	Electronic health records from hospitalized patients.	Improved fall risk prediction accuracy using multiple machine learning models.	Lack of realtime testing and generalizability across hospitals.

2	Wearable sensor systems for fall risk assessment: A review	S. Subramaniam, A. I. Faisal, and M. J. Deen	2023	Review of wearable sensor-based fall detection and prevention systems.	Literature review of sensor technologies for fall risk assessment.	Multiple sensor-based fall detection studies.	Accelerometer and gyroscope-based sensors enhance realtime fall detection.	Battery life, accuracy, and real-world implementation challenges.
3	Risk prediction models for falls in hospitalized older patients: A systematic review and metaanalysis	A. Mao, J. Su, M. Ren, S. Chen, and H. Zhang,	2023	Comprehensive review of existing fall risk prediction models.	Systematic review and meta-analysis of published studies.	Multiple studies on hospitalized elderly patients	Variability in model performance due to inconsistent predictor selection.	Standardization of risk factors and validation across different hospitals.
4	Privacy and surveillance concerns in machine learning fall prediction models: Implications for geriatric care and the Internet of Medical Things	R. Yang	2023	Ethical and privacy concerns in ML-based fall prediction systems.	Theoretical analysis of privacy risks and data security challenges.	No empirical dataset, reviewbased approach	Privacy risks increase with wearable IoTbased monitoring	Balancing predictive accuracy with ethical and legal constraints.
5	Constructing a fall risk prediction model for hospitalized patients using machine learning	C.-W. Kang, Z.-K. Yan, J.-L. Tian, X.-B. Pu, and L.-X. Wu	2023	Fall prediction in hospitalized patients using machine learning techniques.	Random forest, decision tree, and SVM-based predictive modeling.	Clinical records from a tertiary care hospital.	Decision trees and ensemble models outperformed traditional risk assessment tools	Model interpretability and external validation with diverse populations.
6	In-hospital fall prediction using machine learning algorithms	J. H. Choi, E. S. Choi, and D. Park	2023	Machine learning-enhanced Morse Fall Scale for stroke patient	Logistic regression, decision trees, and neural networks.	Acute stroke patient data from a clinical registry.	Neural networks outperformed traditional Morse Fall Scale predictions.	Integration into hospital systems and real-time monitoring.
	and the Morse Fall Scale in patients with acute stroke: A nested casecontrol study			risk assessment.				

7	Using machine learning models to predict falls in hospitalised adults	S. Jahandideh, A. F. Hutchinson, T. K. Bucknall, J. Considine, A. Driscoll, E. Manias, N. M. Phillips, B. Rasmussen, N. Vos, and A. M. Hutchinson	2023	ML-based fall prediction for hospitalized patients.	Deep learning models trained on patient movement data.	Clinical movement and medical history data.	Deep learning improves sensitivity in fall risk prediction.	Data imbalance and lack of multihospital validation.
8	Are wearable devices effective for preventing and detecting falls: An umbrella review (a review of systematic reviews	D. J. Warrington, E. J. Shortis, and P. J. Whittaker	2023	Effectiveness of wearable devices in fall detection and prevention.	Meta-analysis of multiple systematic reviews.	Aggregated wearable technology studies.	Wearable devices show promise but have inconsistent accuracy.	Real-world efficacy and standardization of device usage.
9	An Effective Deep Learning Framework for Fall Detection: Model Development and Study Design	Zhang J, Li Z, Liu Y, Li J, Qiu H, Li M, Hou G, Zhou Z	2024	Fall detection using deep learning and sensor-based data processing.	CNNs and LSTMs trained on sensor motion data.	Public fall detection dataset from motion sensors.	CNN-LSTM models outperform traditional ML methods in accuracy.	Model deployment on real-time hospital monitoring systems
10	Utilizing Machine Learning to Identify Fall Predictors in India's Aging Population: Findings from the LASI	M. P. Bharadwaz, J. Kalita, A. Mitro, and A. Dutta,	2025	Fall risk analysis in elderly Indian populations using ML models.	Statistical modeling and supervised learning on survey data.	Longitudinal Aging Study in India (LASI).	Socioeconomic and health-related factors significantly influence fall risk.	Need for culturally adapted risk prediction tools.

DM_Aarav_220911444.pdf

ORIGINALITY REPORT

4%	4%	3%	0%
SIMILARITY INDEX	INTERNET SOURCES	PUBLICATIONS	STUDENT PAPERS

PRIMARY SOURCES

1	ijsdcs.com Internet Source	1%
2	expertbeacon.com Internet Source	1%
3	www.collegesidekick.com Internet Source	1%
4	pmc.ncbi.nlm.nih.gov Internet Source	1%
5	Anna Weigand, Julie Kathman, Janet Colton, James Davis. "Comparative Analysis of Two Fall Risk Assessment Tools in the Obstetric Population", Nursing for Women's Health, 2025 Publication	1%