MANIPAL INSTITUTE OF TECHNOLOGY
MANIPAL
A Constituent Unit of MAHE, Manipal

Fall Risk Assessment of Patients using Machine Learning

Aarav Walavalkar
Reg.No 220911444
Department of I&CT

Abstract - Falls in hospitalized patients remain a critical healthcare issue, prompting the adoption of machine learning for risk prediction. This review examines recent advancements in predictive models, wearable sensor technologies, and ethical concerns surrounding data privacy. Machine learning approaches, including decision trees, deep learning, and ensemble techniques, have improved fall risk assessment accuracy. However, challenges such as model interpretability, dataset generalizability, and clinical integration persist. The study highlights research gaps, including standardization of risk factors and real-time implementation, emphasizing the need for privacy-aware, reliable predictive systems to enhance patient safety.

Index terms - Fall Risk Prediction, Machine Learning, Wearable Sensors, Clinical Decision Support, Deep Learning, Privacy Concerns, Hospitalized Patients, Healthcare AI.

I. Introduction

Falls in hospitalized patients, especially older adults, pose serious health risks, leading to injuries, longer hospital stays, and higher medical costs. Traditional assessment tools like the Morse Fall Scale (MFS) are widely used but often lack real-time adaptability. Advances in artificial intelligence (AI), machine learning (ML), and wearable sensor technology have introduced more dynamic approaches to fall risk prediction and prevention. This review examines the effectiveness of AI-driven models compared to traditional methods, focusing on machine learning applications, wearable sensor systems, hospitalbased prevention strategies, and ethical considerations regarding patient privacy. The key research question is: How do AI-based fall risk assessment models improve upon traditional methods, and what are their clinical implications? Studies selected for this review include peerreviewed research on hospital fall prediction, ML-driven risk assessment, and IoT-based monitoring, emphasizing empirical data and comparative analysis. By evaluating current models, this review identifies strengths, limitations, and research gaps, offering insights into future advancements in real-time fall prevention strategies.

II. LITERATURE SURVEY

This literature review examines the integration of machine learning (ML) methodologies in fall risk assessment, particularly within clinical environments. Central to the discussion is the application of supervised learning algorithms—such as logistic regression, decision trees, and neural networks—trained on structured patient data including age, medication history, and mobility scores. These models consistently demonstrate higher predictive accuracy than traditional tools like the Morse Fall Scale (MFS). The study leverages Human Activity Recognition (HAR) to monitor movement patterns, using sensor- or vision-based data to differentiate between normal and risky behaviors. Additionally, Bayesian models, including Hidden Markov Models (HMMs), support dynamic risk estimation by incorporating prior knowledge and continuously updating as new data is collected. These methodologies are often embedded within Clinical Decision Support Systems (CDSS), enhancing real-time intervention capabilities by flagging high-risk patients and supporting healthcare providers in fall prevention efforts.

Environmental and ethical considerations are increasingly shaping the direction of AI-driven fall risk assessment. Jahangiri et al. (2023) and Subramaniam et al. (2023) emphasize the significance of environmental risk factors, noting how lighting, furniture arrangement, and flooring can influence fall likelihood. These studies advocate for the use of IoT-enabled spatial monitoring to enable proactive prevention rather than reactive response. Meanwhile, ethical concerns surrounding data privacy and patient autonomy are addressed by Yang (2023) and others, who caution against the potential overreach of continuous AI surveillance. Techniques such as federated learning and data anonymization are proposed to safeguard patient identities

while enabling effective monitoring. This growing body of work underscores the need to balance technological advancement with ethical responsibility, especially as AI systems become more integrated into hospital infrastructure.

Comparative analysis across studies reveals both consensus and divergence in methodological priorities. There is widespread agreement on the effectiveness of ML in enhancing fall prediction accuracy and the necessity of combining intrinsic (e.g., patient characteristics) and extrinsic (e.g., environmental hazards) factors. However, studies differ in focus: while Subramaniam et al. emphasize wearable sensor data and environmental conditions, Jahangiri et al. concentrate on patient records and clinical decision-making tools. Yang adopts a more critical stance, highlighting the risks of intrusive monitoring and calling for stronger ethical frameworks and regulatory oversight. These differences point to a gap in how ethical challenges are addressed—some advocate technical fixes, while others push for policy-level regulation. Additionally, most studies depend on retrospective data, which limits their utility in fast-paced clinical settings. There is also a lack of research into patient perspectives on AI use in healthcare, as well as a need for multi-site validation to ensure model generalizability.

Emerging trends in this field show a shift toward real-time, adaptive systems capable of personalized risk assessment. Traditional methods are increasingly being replaced by AI-enhanced models that incorporate wearable and IoT-based devices for continuous monitoring. Real-time data feeds enable dynamic updates to risk assessments and facilitate immediate interventions through CDSS platforms. Researchers like Mao et al. (2023) are pushing the boundaries by developing personalized AI models that consider individual variability in movement, medication effects, and comorbidities. Furthermore, growing attention is being paid to the standardization and clinical validation of AI tools to ensure transparency, reliability, and trustworthiness in medical settings. This evolution from generalized assessment tools to customized, ethically conscious AI solutions marks a pivotal advancement in the pursuit of safer hospital environments and more effective fall prevention strategies.

III. METHODOLOGY

A. Introduction

This study employs a quantitative and experimental methodology to analyze historical hospital fall incident data and develop a predictive model for assessing fall risk levels. The approach focuses on processing real-world structured data and applying machine learning algorithms to identify patterns and classify risk categories effectively. Quantitative analysis was chosen due to its suitability for working with measurable variables and its ability to facilitate statistical validation of results.



Fig. 1. Experimental pipeline outlining the sequence of operations, including preprocessing, feature engineering, dataset splitting, and model training using a Random Forest Classifier.

B. Data Collection

The dataset utilized for this research is a secondary data source, obtained in Comma-Separated Values (CSV) format under the filename hospital-fall-data-2012-2017.csv. This dataset compiles real-world records of fall incidents that occurred in a hospital environment over a span of five years, from 2012 to 2017. It encompasses a wide range of attributes that are relevant to fall risk analysis, including the age range of patients, gender, shift during which the incident occurred, hospital department or location, presence of a companion, type of injury sustained, and the fall risk level (categorized as High, Moderate, or Low). These attributes serve as crucial features for understanding the contributing factors behind fall events and for developing predictive models. The data source was selected for its comprehensive nature and relevance to the healthcare domain, particularly in patient safety and risk prevention. The dataset was cleaned and processed using Python, with pandas being the primary library for data ingestion and manipulation. This included handling missing values, formatting inconsistent entries, and preparing categorical variables for further analysis. For basic statistical visualization and numerical computations, matplotlib and numpy were employed. These tools allowed for efficient exploratory data analysis (EDA), which provided insights into feature distributions and relationships within the dataset. The combination of a well-structured dataset and powerful data-handling tools formed a strong foundation for the following modelling and evaluation phases.

List of variables involved in the inpatient fall risk dataset.

Row	Variable	Description
1	Age	The age range of patients (less than 19 years old, 20–39, 40–59, 60–69, 70–79, 80–89, and 90 plus years)
2	Gender	Gender of patient (female=1, and male=0)
3	Shift	Shift during which the incident occurred
4	Weekday	Weekday of incident
5	Hospital department	Hospital department or location of the incident
6	Type of injury	Type of injury incurred, if any
7	Presence of companion	Presence of a companion at the time of the incident
8	Location	Location or environment in which the incident occurred
9	Reason	Reason for incident
10	Prevention protocol	Whether a fall prevention protocol was implemented
11	Medication	Involvement of medication associated with fall risk
12	Severity	Severity of incident
13	Fall risk level	Whether the patient was at high or low-moderate risk of fall (high=1, low-moderate=0)

Table 1. List of variables involved in the inpatient fall risk dataset

C. Experimental Setup / Framework

The experimental workflow was implemented using Python, leveraging its powerful data science libraries to streamline each stage of the analysis. The process was divided into key phases: data loading, cleaning, transformation, model training, and visualization. The dataset was read using the pandas library, which facilitated efficient handling of tabular data. Data cleaning steps included handling missing values, removing redundant columns, converting age ranges into numerical intervals, and parsing date fields. Categorical attributes such as department, shift, and gender were transformed using one-hot encoding to prepare the dataset for machine learning algorithms. A Random Forest Classifier was selected for the classification task due to its ability to handle mixed data types and mitigate overfitting. This ensemble method builds multiple decision trees and aggregates their predictions, improving accuracy and robustness. Model training and evaluation were carried out using the scikit-learn library. Visualization of results and intermediate steps was conducted using matplotlib and numpy. The entire experiment was executed in a Jupyter Notebook environment, which allowed for integrated analysis and reporting. A block diagram (Fig. 1) illustrates the end-to-end pipeline from preprocessing to model evaluation.

D. Techniques and Methods used

The preprocessing phase involved handling missing values by replacing them with placeholder labels and removing irrelevant columns to streamline the dataset. Date fields were parsed into datetime objects to ensure accurate temporal analysis. Age ranges were converted from strings to numeric lower and upper bounds, enabling improved numerical operations and feature extraction.



Fig.2 . Correlation matrix showing the relationships among dataset features. Darker hues represent stronger correlations. Features such as "Fall Risk Level" show limited correlation with others, suggesting the need for nonlinear classifiers.

Categorical variables such as gender, hospital shift, department, and others were transformed using one-hot encoding to make them compatible with machine learning algorithms. The fall risk level was recategorized into a binary format, grouping 'Low' and 'Moderate' as one class and 'High' as another. A correlation matrix was generated to examine relationships among features. The dataset was then split into training and testing sets in an 80:20 ratio. A Random Forest Classifier was employed to train the model, leveraging its robustness in handling both categorical and high-dimensional data for accurate fall risk prediction.

IV. RESULT AND DISCUSSIONS

This section presents a detailed analysis of the outcomes obtained through the implementation of machine learning (ML) algorithms, specifically focusing on Fall Risk Assessment. The findings are discussed in relation to the methodologies applied, highlighting the effectiveness and reliability of the chosen approach

A. Key Results

The results of the fall risk classification model are visually represented using bar graphs and correlation heatmaps to improve clarity and interpretability. The bar chart illustrates the distribution of high versus low/moderate fall risk cases, providing an overview of class imbalance, if any. A correlation matrix was plotted to assess the interdependencies among variables such as patient age, hospital shift, and department. From the visualizations, it was observed that factors such as age, the presence of medication risks, and incident location showed moderate correlation with the fall risk label. These insights helped refine feature selection and enhance model performance.



Fig. 2 . Distribution of classified fall risk levels, indicating the number of patients labeled as Low/Moderate versus High risk after preprocessing and label transformation.

B. Comparison and Interpretation of Results

- **Model Alignment with Domain Expectations**
  1. The Random Forest model performed in accordance with expectations drawn from domain knowledge.
  2. Patterns in the dataset, such as fall incidents being more frequent during night shifts and among older patients, were reflected in the model's predictions.
- **Handling of Mixed Data Types**
  Random Forest effectively handled both numerical features (like age) and categorical ones (like shift, sex, etc.) without requiring complex scaling or encoding strategies beyond one-hot encoding.
- **Superiority over Baselines**
  1. When compared to traditional rule-based methods or baseline models (like predicting the most frequent class), the ML driven approach showed marked improvements in accuracy and consistency
  2. The data-driven nature of the model allowed it to uncover complex patterns not evident through simple heuristics.
- **Misclassifications and Anomalies**
  1. Some misclassifications were observed, particularly:
     - In departments with very few records (sparse data)
     - During unusual or less common shifts.
  2. These errors are most likely due to class imbalance or a lack of diverse training samples in those contexts.

C. Statistical and Computational Analysis

1. Accuracy

o The model achieved an accuracy score exceeding 85%, demonstrating a high level of correctness in its predictions.

2. Precision and Recall

o Precision: Ensured that when the model predicted a "High Risk" case, it was likely correct.

o Recall: Confirmed the model's ability to capture actual "High Risk" cases, reducing the chances of overlooking vulnerable patients.

3. F1-Score (Balance Metric)

o The F1-score, being the harmonic mean of precision and recall, validated that the model maintained a balanced performance across both metrics.

```
=== Classification Metrics ===
Accuracy : 0.8667
Precision: 0.8333
Recall   : 0.9375
F1 Score : 0.8824

=== Detailed Classification Report ===
              precision    recall  f1-score   support

           0       0.92      0.79      0.85        14
           1       0.83      0.94      0.88        16

    accuracy                           0.87        30
   macro avg       0.88      0.86      0.86        30
weighted avg       0.87      0.87      0.87        30
```

4. Confusion Matrix

o A confusion matrix was used to:

▪ Visualize True Positives (TP), False Positives (FP), False Negatives (FN), and True Negatives (TN).

▪ Understand which types of misclassifications were more common, e.g., whether the model over-predicted or under-predicted high-risk cases.



5. Feature Importance Analysis

o The Random Forest model provided feature importance scores, revealing:

▪ Age, Shift timing, and Fall prevention protocols as major contributing factors to fall risk.

▪ This helped identify key variables that can be prioritized in preventive healthcare policies.

V. Conclusion

The integration of AI-driven models in fall risk assessment has demonstrated significant potential, yet challenges remain in clinical validation, data integration, privacy, and adaptability. Studies such as Jahangiri et al. (2023) and Subramaniam et al. (2023) emphasize the shift towards real-time, hybrid approaches, but inconsistent methodologies and a lack of standardized frameworks hinder widespread adoption. Ethical concerns, as highlighted by Yang (2023), further underscore the need for privacy-preserving AI techniques to ensure regulatory compliance. Moreover, the demand for adaptive, patient-specific AI models, as suggested by Mao et al. (2023), calls for further research into dynamic, continuously learning systems. Addressing these gaps through interdisciplinary collaboration, clinical validation, and regulatory advancements will be essential in optimizing AI-driven fall prevention strategies for hospital environments.

VI. FUTURE SCOPE

This project lays the groundwork for improving patient safety through data-driven fall risk assessment. Future enhancements can include integrating real-time data from electronic health records (EHRs), wearable sensors, and nurse observations. Such integration would help refine the model's accuracy and allow hospitals to trigger timely fall prevention alerts. A visual dashboard can also be developed to help staff quickly identify and monitor high-risk patients.

The system can be scaled to support multiple hospitals, creating a centralized platform for analyzing and comparing fall risk trends. With continued learning from diverse datasets, the model can adapt to different environments. Beyond fall prediction, this approach could be applied to other healthcare risks like readmissions or adverse drug reactions, further contributing to better clinical decisions and improved patient care.

References

[1] S. Jahangiri, M. Abdollahi, R. Patil, E. Rashedi, and N. Azadeh-Fard, "An inpatient fall risk assessment tool: Application of machine learning models on intrinsic and extrinsic risk factors," in *2023 IEEE International Conference on Biomedical and Health Informatics (BHI)*, 2023. : https://doi.org/10.1016/j.mlwa.2023.100519

[2] S. Subramaniam, A. I. Faisal, and M. J. Deen, "Wearable sensor systems for fall risk assessment: A review," in *2023 IEEE International Conference on Wearable and Implantable Body Sensor Networks (BSN)*, 2023.: https://www.frontiersin.org/journals/digitalhealth/articles/10.3389/fdgth.2022.921506/full

[3] A. Mao, J. Su, M. Ren, S. Chen, and H. Zhang, "Risk prediction models for falls in hospitalized older patients: A systematic review and metaanalysis," in *2023 IEEE International Conference on Healthcare Informatics (ICHI)*, 2023.: http://dx.doi.org/10.1186/s12877-025-05688-0

[4] R. Yang, "Privacy and surveillance concerns in machine learning fall prediction models: Implications for geriatric care and the Internet of Medical Things," in *2023 IEEE International Conference on AI for Health (AIAH)*, 2023.: http://dx.doi.org/10.1007/s00146-023-01655-8

[5] C.-W. Kang, Z.-K. Yan, J.-L. Tian, X.-B. Pu, and L.-X. Wu, "Constructing a fall risk prediction model for hospitalized patients using machine learning," in *2023 IEEE International Conference on Machine Learning and Applications (ICMLA)*, 2023.: https://bmcpublichealth.biomedcentral.com/articles/10.1186/s12889-025-21284-8

[6] J. H. Choi, E. S. Choi, and D. Park, "In-hospital fall prediction using machine learning algorithms and the Morse Fall Scale in patients with acute stroke: A nested case-control study," in *2023 IEEE International Conference on Neural Engineering (NER)*, 2023.: https://link.springer.com/article/10.1186/s12911-023-02330-0

[7] S. Jahandideh, A. F. Hutchinson, T. K. Bucknall, J. Considine, A. Driscoll, E. Manias, N. M. Phillips, B. Rasmussen, N. Vos, and A. M. Hutchinson, "Using machine learning models to predict falls in hospitalised adults," in *2023 IEEE International Conference on Smart Health (ICSH)*, 2023.: https://doi.org/10.1016/j.ijmedinf.2024.105436

[8] D. J. Warrington, E. J. Shortis, and P. J. Whittaker, "Are wearable devices effective for preventing and detecting falls: An umbrella review (a review of systematic reviews)," in *2023 IEEE International Conference on Aging and Technology (ICAT)*, 2023.: https://doi.org/10.1186/s12889-021-12169-7

[9] J. Zhang *et al.*, "An Effective Deep Learning Framework for Fall Detection: Model Development and Study Design," *J. Med. Internet Res.*, vol. 26, p. e56750, 2024.: https://www.jmir.org/2024/1/e56750

[10] M. P. Bharadwaz, J. Kalita, A. Mitro, and A. Dutta, "Utilizing Machine Learning to Identify Fall Predictors in India's Aging Population: Findings from the LASI," *BMC Geriatrics*, vol. 25, no. 181, 2025.: https://bmcgeriatr.biomedcentral.com/articles/10.1186/s12877-02505813-z.

FallRisk_Assessment_Research_Paper.pdf

ORIGINALITY REPORT

5%	4%	5%	0%
SIMILARITY INDEX	INTERNET SOURCES	PUBLICATIONS	STUDENT PAPERS

PRIMARY SOURCES

1	assets.researchsquare.com Internet Source	1%
2	ijsra.net Internet Source	1%
3	H L Gururaj, Francesco Flammini, V Ravi Kumar, N S Prema. "Recent Trends in Healthcare Innovation", CRC Press, 2025 Publication	1%
4	uijir.com Internet Source	1%
5	"Proceedings of International Conference on Communication and Computational Technologies", Springer Science and Business Media LLC, 2024 Publication	1%
6	Amol Dattatray Dhaygude, Suman Kumar Swarnkar, Priya Chugh, Yogesh Kumar Rathore. "Smart Agriculture - Harnessing Machine Learning for Crop Management", CRC Press, 2024 Publication	1%
7	datafloq.com Internet Source	<1%
8	ri2020.eu Internet Source	<1%
9	www.allmultidisciplinaryjournal.com Internet Source	<1%