DIGITAL BATTERY PASSPORT

DBP-CALCE-CS2_35

Battery CS2_35 · Status waste

VERIFIED: all 22 events pass the six checks

Access tier: public. Schema aligned with Regulation (EU) 2023/1542, Article 77 and Annex XIII.

Scan to open the live record and check that it matches this copy.

General information

model	CS2_35
manufacturer	Unknown (CALCE CS2 test cells)
manufacture date	2010-07-17
chemistry	LiCoO2 (LCO) prismatic
form factor	Prismatic
rated capacity ah	1.1
nominal voltage v	3.7
manufacturing site	not disclosed (laboratory test cell)

Carbon footprint

kgco2e per kwh	75
total kgco2e	0.3053
basis	assumed mid value of published 61-106 kg CO2e/kWh (IVL)

Performance and durability

rated capacity ah	1.1
initial capacity ah	1.128
initial resistance ohm	0.0875
expected cycle life	not recorded
cut off voltage v	not recorded

Battery status

status	waste
events	22
last event	SENT_TO_RECYCLING

Signed event chain (6 public events)

#	Date	Event	Signed by	Hash
0	2010-07-17	Manufactured	MFR-01	02c31d4b7e3dd8bed589…
1	2010-07-18	Carbon Footprint Declared	MFR-01	ac232a35b43e55d9dfbf…
2	2010-08-16	First Life Start	OEM-01	7d89d1d2c2a310d13992…
13	2010-12-14	First Life Retired	OEM-01	b136339cf6f5b3677e8e…
17	2010-12-14	Repurposed	REP-01	d6dcf40d7b85492092bf…
21	2011-01-19	Sent To Recycling	REP-01	3f5ae1d274db2cde1157…

Head hash (fingerprint of the whole chain)

3f5ae1d274db2cde11571271af6ed1959bb4638afe7092bcb598c24469f955db

Each event stores the SHA-256 hash of the event before it and an Ed25519 signature from the actor who issued it. Changing, deleting or re-ordering any event changes the head hash and fails verification. This printed copy is a snapshot; the live record is authoritative.