

Fundamentals

SFWRENG 2CO3: Data Structures and Algorithms

Jelle Hellings

Department of Computing and Software
McMaster University



Winter 2024

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

- ▶ Analysis of algorithms and data structures: *correctness* and *complexity*.
- ▶ Common design strategies for algorithms and data structures.
- ▶ A useful toolbox of standard fundamental algorithms and data structures.
- ▶ Graph representations and fundamental graph algorithms.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

- ▶ Analysis of algorithms and data structures: *correctness* and *complexity*.
- ▶ Common design strategies for algorithms and data structures.
- ▶ A useful toolbox of standard fundamental algorithms and data structures.
- ▶ Graph representations and fundamental graph algorithms.

This course is *not* about learning how to program (basic programming is prior knowledge).

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

An algorithm takes one-or-more values as input
and produces an output via a *well-defined computational procedure*.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

An algorithm takes one-or-more values as input and produces an output via a *well-defined computational procedure*.

Definition (Data structure)

Scheme to store and organize data in order to facilitate *efficient* access and modification.

About Programming Languages

We all have our own favorites.

About Programming Languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

About Programming Languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

For *optimal* implementations, we sometimes need a lower-level toolbox.
E.g., references or pointers when implementing data structures.

About Programming Languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

For *optimal* implementations, we sometimes need a lower-level toolbox.
E.g., references or pointers when implementing data structures.

Many programming languages suffice, e.g.,

- ▶ the book has many examples in Java;
- ▶ I will provide some examples in C++.

Feel free to experiment in your programming language of choice.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Result: return true if $v \in L$ and false otherwise.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

Input: L is an *array*, v a value.

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Result: return true if $v \in L$ and false otherwise.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm EVILCONTAINS(L, v):

Input: L is an *array*, v a value.

1: $L := []$.

2: **return** false.

Result: return true if $v \in L$ and false otherwise.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}.$   
  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}.$   
5:      $i := i + 1.$   
6:   else  
7:      $i := i + 1.$   
  
8: return  $r.$ 
```

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
   /*  $L$  is an array,  $v$  a value,  $i = 0$ , and  $r = \text{false}$ . */  
  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
   /*  $r$  is true if  $v \in L$  and false otherwise. */  
8: return  $r$ .
```

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
   /*  $L$  is an array,  $v$  a value,  $i = 0$ , and  $r = \text{false}$ . */  
   /* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
   /*  $r$  is true if  $v \in L$  and false otherwise. */  
8: return  $r$ .
```

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Proof by induction

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Proof by induction

Base case Prove **invariant** holds before the loop.

Hypothesis The **invariant** holds after the j -th, $j < m$, repetition of the loop.

Step Assume **invariant** holds when we start the m -th repetition of the loop.
Prove **invariant** holds again when we reach the end of the m -th repetition.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove **invariant** holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove invariant holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove invariant holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.
2. $L[0, 0)$ is empty, hence $v \notin L[0, 0)$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove **invariant** holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.
2. $L[0, 0)$ is empty, hence $v \notin L[0, 0)$.
3. Hence, $r = \text{false}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repitition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repitition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repetition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

If-statement: Case distinction.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.
3. Hence, $r_{\text{new}} = \text{true}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.
3. Hence, $r = \text{true}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{false}$. Hence, $v \notin L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$ and $L[i] \neq v$, hence, $v \notin L[0, i_{\text{new}})$.
3. Hence, $r = \text{false}$ must hold (which is the case).

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */
```

```
6: while  $i \neq |L|$  do ... end while
```

```
/* Invariant and  $\neg(i \neq |L|)$ . */
```

```
/*  $r$  is true if  $v \in L$  and false otherwise. */
```

```
7: return  $r$ .
```

Questions

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */  
6: while  $i \neq |L|$  do ... end while  
   /* Invariant and  $\neg(i \neq |L|)$ . */  
   /*  $r$  is true if  $v \in L$  and false otherwise. */  
7: return  $r$ .
```

Questions

1. Do we reach the end of the loop?

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */  
6: while  $i \neq |L|$  do ... end while  
   /* Invariant and  $\neg(i \neq |L|)$ . */  
   /*  $r$  is true if  $v \in L$  and false otherwise. */  
7: return  $r$ .
```

Questions

1. Do we reach the end of the loop?
2. Assuming /* **Invariant** and $\neg(i \neq |L|)$ */,
Do we have /* r is true if $v \in L$ and false otherwise */?