

Fundamentals

SFWRENG 2CO3: Data Structures and Algorithms

Jelle Hellings

Department of Computing and Software
McMaster University



Winter 2024

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

- ▶ Analysis of algorithms and data structures: *correctness* and *complexity*.
- ▶ Common design strategies for algorithms and data structures.
- ▶ A useful toolbox of standard fundamental algorithms and data structures.
- ▶ Graph representations and fundamental graph algorithms.

Focus of this course: From hacking to engineering

Engineering is the application of science and mathematics to solve practical problems.

Software engineering requires

- ▶ a deep understanding of *what software (programs) do*;
- ▶ mastery of a toolbox of *fundamental tools* to tackle programming challenges;
- ▶ capability to *analyze* software in depth.

This course introduces the analysis of software by studying and analyzing fundamental tools.

- ▶ Analysis of algorithms and data structures: *correctness* and *complexity*.
- ▶ Common design strategies for algorithms and data structures.
- ▶ A useful toolbox of standard fundamental algorithms and data structures.
- ▶ Graph representations and fundamental graph algorithms.

This course is *not* about learning how to program (basic programming is prior knowledge).

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

An algorithm takes one-or-more values as input
and produces an output via a *well-defined computational procedure*.

Algorithms and data structures

The basic building blocks of any problem that can be solved by a computer program.

Definition (Algorithm)

Procedures for solving problems that are suited for computer implementation.

An algorithm takes one-or-more values as input and produces an output via a *well-defined computational procedure*.

Definition (Data structure)

Scheme to store and organize data in order to facilitate *efficient* access and modification.

About programming languages

We all have our own favorites.

About programming languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

About programming languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

For *optimal* implementations, we sometimes need a lower-level toolbox.
E.g., references or pointers when implementing data structures.

About programming languages

We all have our own favorites.

For the study of data structures and algorithms:

Choice of programming language does *not really* matter (mostly).

For *optimal* implementations, we sometimes need a lower-level toolbox.
E.g., references or pointers when implementing data structures.

Many programming languages suffice, e.g.,

- ▶ the book has many examples in Java;
- ▶ I will provide some examples in C++.

Feel free to experiment in your programming language of choice.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```


A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Is CONTAINS correct?

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Result: return true if $v \in L$ and false otherwise.

Is CONTAINS correct?

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

Input: L is an *array*, v a value.

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Result: return true if $v \in L$ and false otherwise.

Is CONTAINS correct?

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm EVILCONTAINS(L, v):

Input: L is an *array*, v a value.

1: $L := []$.

2: **return** false.

Result: return true if $v \in L$ and false otherwise.

Is EVILCONTAINS correct?

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}$.

2: **while** $i \neq |L|$ **do**

3: **if** $L[i] = v$ **then**

4: $r := \text{true}$.

5: $i := i + 1$.

6: **else**

7: $i := i + 1$.

8: **return** r .

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
   /*  $L$  is an array,  $v$  a value,  $i = 0$ , and  $r = \text{false}$ . */  
  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
   /*  $r$  is true if  $v \in L$  and false otherwise. */  
8: return  $r$ .
```

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}$.

/ L is an array, v a value, $i = 0$, and $r = \text{false}$. */*

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

2: **while** $i \neq |L|$ **do**

3: **if** $L[i] = v$ **then**

4: $r := \text{true}$.

5: $i := i + 1$.

6: **else**

7: $i := i + 1$.

/ r is true if $v \in L$ and false otherwise. */*

8: **return** r .

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Proof by induction

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

`/* inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */`

Proof by induction

Base case Prove invariant holds before the loop.

Hypothesis The invariant holds after the j -th, $j < m$, repetition of the loop.

Step Assume invariant holds when we start the m -th repetition of the loop.
Prove invariant holds again when we reach the end of the m -th repetition.

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove invariant holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

Intermezzo: The invariant of CONTAINS holds

Prove the invariant holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove invariant holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove **invariant** holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.

2. $L[0, 0)$ is empty, hence $v \notin L[0, 0)$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Base case: Prove **invariant** holds before the loop

Input: L is an *array*, v a value.

1: $i, r := 0, \text{false}$.

/ L is an *array*, v a value, $i = 0$, and $r = \text{false}$. */*

2: **while**

Argument

1. $L[0, i)$ with $i = 0$ is $L[0, 0)$.
2. $L[0, 0)$ is empty, hence $v \notin L[0, 0)$.
3. Hence, $r = \text{false}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repetition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repetition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Step: Prove **invariant** holds again when we reach the end of the m -th repetition.

```
2: while  $i \neq |L|$  do  
    /* Invariant and  $i \neq |L|$ . */  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
    /* Invariant. */
```

Argument

If-statement: Case distinction.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $L[i] = v$, hence, $v \in L[0, i]$.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.
3. Hence, $r_{\text{new}} = \text{true}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: If-case ($L[i] = v$ holds).

3: **if** $L[i] = v$ **then**

/ Invariant, $i \neq |L|$, and $L[i] = v$ */*

4: $r := \text{true}$.

5: $i := i + 1$.

/ Invariant. */*

Argument

After Line 5: prove that **Invariant** holds for the *updated* values r_{new} , i_{new} of r and i .

1. $0 \leq i \leq |L|$ and $i \neq |L|$ implies $0 \leq i < |L|$.
2. $i_{\text{new}} = i + 1$, hence, $0 < i_{\text{new}} \leq |L|$.
3. $0 < i_{\text{new}} \leq |L|$ implies $0 \leq i_{\text{new}} \leq |L|$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{true}$. Hence, $v \in L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$, hence, $v \in L[0, i_{\text{new}})$.
3. Hence, $r = \text{true}$ must hold (which is the case).

Intermezzo: The **invariant** of CONTAINS holds

Prove the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

Case distinction: Else-case ($L[i] \neq v$ holds).

6: **if** $L[i] = v$ **then** ... **else**

/ Invariant, $i \neq |L|$, and $L[i] \neq v$ */*

7: $i := i + 1$.

/ Invariant. */*

Argument

After Line 7: prove that **Invariant** holds for the *updated* value i_{new} of i .

1. Assume $r = \text{false}$. Hence, $v \notin L[0, i)$ by the **invariant**.
2. $i_{\text{new}} = i + 1$ and $L[i] \neq v$, hence, $v \notin L[0, i_{\text{new}})$.
3. Hence, $r = \text{false}$ must hold (which is the case).

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */?*

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */?*

Argument

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */*?

Argument

1. $\neg(i \neq |L|)$ implies $i = |L|$.

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */?*

Argument

1. $\neg(i \neq |L|)$ implies $i = |L|$.
2. $L[0, i)$ with $i = |L|$ is equivalent to L .

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */?*

Argument

1. $\neg(i \neq |L|)$ implies $i = |L|$.
2. $L[0, i)$ with $i = |L|$ is equivalent to L .
3. Hence, $v \in L$ implies $r = \text{true}$, $v \notin L$ implies $r = \text{false}$.

Intermezzo: The correctness of CONTAINS

We have proven the **invariant** holds

/ inv: $0 \leq i \leq |L|$, $v \in L[0, i)$ implies $r = \text{true}$, $v \notin L[0, i)$ implies $r = \text{false}$. */*

6: **while** $i \neq |L|$ **do** ... **end while**

/ Invariant and $\neg(i \neq |L|)$. */*

/ r is true if $v \in L$ and false otherwise. */*

7: **return** r .

Are we done?

- ▶ *Assuming* */* Invariant and $\neg(i \neq |L|)$ */*,
Do we have */* r is true if $v \in L$ and false otherwise */?* \longrightarrow *Yes!*
- ▶ Do we reach the end of the loop?

Intermezzo: The correctness of CONTAINS

Are we done?

► Do we reach the end of the loop?

2: $i, r := 0, \text{false}.$

3: **while** $i \neq |L|$ **do**

4: **if** $L[i] = v$ **then**

5: $r := \text{true}.$

6: $i := i + 1.$

7: **else**

8: $i := i + 1.$

Intermezzo: The correctness of CONTAINS

Are we done?

► Do we reach the end of the loop? \longrightarrow *Yes—obviously i will only be $0, \dots, |L|$.*

2: $i, r := 0, \text{false}$.

3: **while** $i \neq |L|$ **do**

4: **if** $L[i] = v$ **then**

5: $r := \text{true}$.

6: $i := i + 1$.

7: **else**

8: $i := i + 1$.

Intermezzo: The correctness of CONTAINS

Are we done?

- Do we reach the end of the loop? \longrightarrow *Yes—obviously i will only be $0, \dots, |L|$.*

2: $i, r := 0, \text{false}.$

3: **while** $i \neq |L|$ **do**

4: **if** $L[i] = v$ **then**

5: $r := \text{true}.$

6: $i := i + 1.$

7: **else**

8: $i := i + 1.$

Formal argument: prove a bound function

Define a *bound function* f on the state of the algorithm such that the output of f :

- is a *natural number* $(0, 1, 2, \dots)$.
- *strictly decreases* after each iteration of the loop body.

Intermezzo: The correctness of CONTAINS

Are we done?

► Do we reach the end of the loop? \longrightarrow *Yes—obviously i will only be $0, \dots, |L|$.*

2: $i, r := 0, \text{false}$.

3: **while** $i \neq |L|$ **do** /* bound function: $|L| - i$ */

4: **if** $L[i] = v$ **then**

5: $r := \text{true}$.

6: $i := i + 1$.

7: **else**

8: $i := i + 1$.

Formal argument: prove a bound function

Define a *bound function* f on the state of the algorithm such that the output of f :

► is a *natural number* $(0, 1, 2, \dots)$.

► *strictly decreases* after each iteration of the loop body.

Intermezzo: The correctness of CONTAINS

Are we done?

► Do we reach the end of the loop? \longrightarrow *Yes—obviously i will only be $0, \dots, |L|$.*

2: $i, r := 0, \text{false}.$ $\longleftarrow |L| - i \text{ starts at } |L|, |L| \geq 0.$

3: **while** $i \neq |L|$ **do** /* bound function: $|L| - i$ */ $\longleftarrow |L| - i \text{ stops at } 0.$

4: **if** $L[i] = v$ **then**

5: $r := \text{true}.$

6: $i := i + 1.$ $\longleftarrow |L| - i \text{ strictly decreases}.$

7: **else**

8: $i := i + 1.$ $\longleftarrow |L| - i \text{ strictly decreases}.$

Formal argument: prove a bound function

Define a *bound function* f on the state of the algorithm such that the output of f :

- is a *natural number* $(0, 1, 2, \dots)$.
- *strictly decreases* after each iteration of the loop body.

Intermezzo: How to prove correctness

Summary

- ▶ Define a *pre-condition*: What restrictions do we require on the input?
- ▶ Define a *post-condition*: What should the output be?
- ▶ Prove that *running the program* turns the pre-condition into the post-condition.

Intermezzo: How to prove correctness

Summary

- ▶ Define a *pre-condition*: What restrictions do we require on the input?
- ▶ Define a *post-condition*: What should the output be?
- ▶ Prove that *running the program* turns the pre-condition into the post-condition.

Hard parts: loops \longrightarrow invariants (induction proofs) and bound functions.

Intermezzo: How to prove correctness

Hard parts: loops \longrightarrow invariants (induction proofs) and bound functions.

On finding invariants

Most induction proofs are *easy* if you have the correct *induction hypothesis*.

Finding the induction hypothesis (invariant) is the *hard part* \longrightarrow trial and error.

Intermezzo: How to prove correctness

Hard parts: loops \longrightarrow invariants (induction proofs) and bound functions.

On finding invariants

Most induction proofs are *easy* if you have the correct *induction hypothesis*.

Finding the induction hypothesis (invariant) is the *hard part* \longrightarrow trial and error.

Take inspiration from what should hold *after the loop* and *what is changed during the loop*.

Example: CONTAINS

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */
```

```
3: while  $i \neq |L|$  ... end while
```

```
/*  $r$  is true if  $v \in L$  and false otherwise. */
```

Intermezzo: How to prove correctness

Hard parts: loops \longrightarrow invariants (induction proofs) and bound functions.

On finding invariants

Most induction proofs are *easy* if you have the correct *induction hypothesis*.

Finding the induction hypothesis (invariant) is the *hard part* \longrightarrow trial and error.

Take inspiration from what should hold *after the loop* and *what is changed during the loop*.

Example: CONTAINS

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */
```

```
3: while  $i \neq |L|$  ... end while
```

```
/*  $r$  is true if  $v \in L$  and false otherwise. */
```

Intermezzo: How to prove correctness

Hard parts: loops \longrightarrow invariants (induction proofs) and bound functions.

On finding invariants

Most induction proofs are *easy* if you have the correct *induction hypothesis*.

Finding the induction hypothesis (invariant) is the *hard part* \longrightarrow trial and error.

Take inspiration from what should hold *after the loop* and *what is changed during the loop*.

Example: CONTAINS

```
/* inv:  $0 \leq i \leq |L|$ ,  $v \in L[0, i)$  implies  $r = \text{true}$ ,  $v \notin L[0, i)$  implies  $r = \text{false}$ . */
```

```
3: while  $i \neq |L|$  ... end while
```

```
/*  $r$  is true if  $v \in L$  and false otherwise. */
```

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

What is the complexity of CONTAINS?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}.$   
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}.$   
5:      $i := i + 1.$   
6:   else  
7:      $i := i + 1.$   
8: return  $r.$ 
```

We need a *scientific model* of the work done by CONTAINS

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}.$	$\leftarrow 2 \text{ instruction}(s).$
2: while $i \neq L $ do	$\leftarrow 2 \text{ instruction}(s).$
3: if $L[i] = v$ then	$\leftarrow 3 \text{ instruction}(s).$
4: $r := \text{true}.$	$\leftarrow 1 \text{ instruction}(s).$
5: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$
6: else	
7: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$
8: return $r.$	$\leftarrow 1 \text{ instruction}(s).$

We need a *scientific model* of the work done by CONTAINS

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}.$	$\leftarrow 2 \text{ instruction}(s).$
2: while $i \neq L $ do	$\leftarrow 2 \text{ instruction}(s).$
3: if $L[i] = v$ then	$\leftarrow 3 \text{ instruction}(s).$
4: $r := \text{true}.$	$\leftarrow 1 \text{ instruction}(s).$
5: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$
6: else	
7: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$
8: return $r.$	$\leftarrow 1 \text{ instruction}(s).$

We need a *scientific model* of the work done by CONTAINS

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}.$	$\leftarrow 2 \text{ instruction}(s).$	
2: while $i \neq L $ do	$\leftarrow 2 \text{ instruction}(s).$	} $ L + 1 \text{ times}.$
3: if $L[i] = v$ then	$\leftarrow 3 \text{ instruction}(s).$	
4: $r := \text{true}.$	$\leftarrow 1 \text{ instruction}(s).$	} $ L \text{ times}.$
5: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
6: else		
7: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
8: return $r.$	$\leftarrow 1 \text{ instruction}(s).$	

We need a *scientific model* of the work done by CONTAINS

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}.$	$\leftarrow 2 \text{ instruction}(s).$	
2: while $i \neq L $ do	$\leftarrow 2 \text{ instruction}(s).$	} $ L + 1 \text{ times}.$
3: if $L[i] = v$ then	$\leftarrow 3 \text{ instruction}(s).$	
4: $r := \text{true}.$	$\leftarrow 1 \text{ instruction}(s).$	} $ L \text{ times}.$
5: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
6: else		
7: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
8: return $r.$	$\leftarrow 1 \text{ instruction}(s).$	

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

Algorithm CONTAINS(L, v):

1: $i, r := 0, \text{false}.$	$\leftarrow 2 \text{ instruction}(s).$	
2: while $i \neq L $ do	$\leftarrow 2 \text{ instruction}(s).$	
3: if $L[i] = v$ then	$\leftarrow 3 \text{ instruction}(s).$	
4: $r := \text{true}.$	$\leftarrow 1 \text{ instruction}(s).$	} $m \text{ times}.$
5: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
6: else		
7: $i := i + 1.$	$\leftarrow 2 \text{ instruction}(s).$	
8: return $r.$	$\leftarrow 1 \text{ instruction}(s).$	

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstr}(N) = 5 + 7N + m \text{ with } N = |L|.$$

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12\mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values?

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values?

Argument

1. $\text{NumInstrOnlyElse}(1000) = 7005$ instructions $\longrightarrow 12 \mu\text{s}$.
2. $\text{NumInstrOnlyElse}(2000) = 14\,005$ instructions \longrightarrow

$$\frac{14005}{7005} \cdot 12 \mu\text{s} \approx 2 \cdot 12 \mu\text{s} = 24 \mu\text{s}.$$

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values? $\rightarrow 24 \mu\text{s}$.

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values? $\longrightarrow 24 \mu\text{s}$.

Useful models are *simple* and make *correct* predictions

- Are our predictions correct?
- Is our model simple?

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.


Predict: How long does CONTAINS take with a list of 2000 values? $\rightarrow 24 \mu\text{s}$.

Useful models are *simple* and make *correct* predictions

- ▶ Are our predictions correct? \rightarrow *Lets implement CONTAINS and measure.*
- ▶ Is our model simple?


Intermezzo: The complexity of CONTAINS

First Attempt




Intermezzo: The complexity of CONTAINS

Second Attempt




Intermezzo: The complexity of CONTAINS

Second Attempt



Intermezzo: The complexity of CONTAINS

Second Attempt



Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values? $\rightarrow 24 \mu\text{s}$.

Useful models are *simple* and make *correct* predictions

- ▶ Are our predictions correct? \rightarrow *Yes*.
- ▶ Is our model simple? \rightarrow *No: Runtime(N) = N predicts the same!*

Intermezzo: The complexity of CONTAINS

What is the complexity of CONTAINS if $v \notin L$?

Interested in *scalability*: How do the costs of CONTAINS *increase* when increasing $|L|$?

We need a *scientific model* of the work done by CONTAINS

$$\text{NumInstrOnlyElse}(N) = 5 + 7N \text{ with } N = |L|.$$

A *scientific model* allows predictions

Assume: CONTAINS with a list L , $|L| = 1000$, takes $12 \mu\text{s}$.

Predict: How long does CONTAINS take with a list of 2000 values? $\rightarrow 24 \mu\text{s}$.

Useful models are *simple* and make *correct* predictions

- ▶ Are our predictions correct? \rightarrow *Yes*.
- ▶ Is our model simple? \rightarrow *No: Runtime(N) = N predicts the same!*
Also: Our instruction counting is mostly fiction!

A simple algorithm: CONTAINS

Problem

Given a list L and value v , return $v \in L$.

Algorithm CONTAINS(L, v):

```
1:  $i, r := 0, \text{false}$ .  
2: while  $i \neq |L|$  do  
3:   if  $L[i] = v$  then  
4:      $r := \text{true}$ .  
5:      $i := i + 1$ .  
6:   else  
7:      $i := i + 1$ .  
8: return  $r$ .
```

Theorem

*CONTAINS is **correct**, its **runtime complexity** is modelled by $\text{ContainsRuntime}(|L|) = |L|$, and its **memory complexity** is modelled by $\text{ContainsMemory}(|L|) = 1$.*

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALTC with $AltCRuntime(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest?

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALTC with $AltCRuntime(|L|) = |L|^2$.

Which one is *faster*?

Input size	1000	
Runtime CONTAINS	12 μ s	
Runtime ALTC	3 μ s	
<i>Speed up of ALTC</i>	4×	

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.\text{Runtime}(|L|) = |L|$.
- ▶ ALTC with $\text{AltCRuntime}(|L|) = |L|^2$.

Which one is *faster*?

Input size	1000	2000
Runtime CONTAINS	12 μs	24 μs
Runtime ALTC	3 μs	12 μs
<i>Speed up of ALTC</i>	4 \times	2 \times

Argument

- ▶ $C.\text{Runtime}(2000) = 2000 = 2 \cdot 1000 = 2 \cdot C.\text{Runtime}(1000)$.
- ▶ $\text{AltCRuntime}(2000) = 2000^2 = 2^2 \cdot 1000^2 = 2^2 \cdot \text{AltCRuntime}(1000)$.

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.\text{Runtime}(|L|) = |L|$.
- ▶ ALTC with $\text{AltCRuntime}(|L|) = |L|^2$.

Which one is *faster*?

Input size	1000	2000	4000
Runtime CONTAINS	12 μs	24 μs	48 μs
Runtime ALTC	3 μs	12 μs	48 μs
<i>Speed up of ALTC</i>	4 \times	2 \times	1 \times

Argument

- ▶ $C.\text{Runtime}(4000) = 4000 = 4 \cdot 1000 = 4 \cdot C.\text{Runtime}(1000)$.
- ▶ $\text{AltCRuntime}(4000) = 4000^2 = 4^2 \cdot 1000^2 = 4^2 \cdot \text{AltCRuntime}(1000)$.

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.\text{Runtime}(|L|) = |L|$.
- ▶ ALTC with $\text{AltCRuntime}(|L|) = |L|^2$.

Which one is *faster*?

Input size	1000	2000	4000	8000
Runtime CONTAINS	12 μs	24 μs	48 μs	96 μs
Runtime ALTC	3 μs	12 μs	48 μs	192 μs
<i>Speed up of ALTC</i>	4 \times	2 \times	1 \times	0.5 \times

Argument

- ▶ $C.\text{Runtime}(8000) = 8000 = 8 \cdot 1000 = 8 \cdot C.\text{Runtime}(1000)$.
- ▶ $\text{AltCRuntime}(8000) = 8000^2 = 8^2 \cdot 1000^2 = 8^2 \cdot \text{AltCRuntime}(1000)$.

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALT C with $AltC Runtime(|L|) = |L|^2$.



Which one is *faster*?

Input size	1000	2000	4000	8000	1 000 000
Runtime CONTAINS	12 μ s	24 μ s	48 μ s	96 μ s	12 ms
Runtime ALT C	3 μ s	12 μ s	48 μ s	192 μ s	3000 ms
<i>Speed up of ALT C</i>	4 \times	2 \times	1 \times	0.5 \times	0.004 \times

Argument

- ▶ $C.Runtime(1\,000\,000) = 1\,000\,000 = 1000 \cdot 1000 = 1000 \cdot C.Runtime(1000)$.
- ▶ $AltC Runtime(1\,000\,000) = 1\,000\,000^2 = 1000^2 \cdot 1000^2 = 1000^2 \cdot AltC Runtime(1000)$.

Comparing algorithm: Runtime complexity



Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALTC with $AltCRuntime(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest? \longrightarrow *No!*

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALTC with $AltCRuntime(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest? \longrightarrow *No!*

Our models are simplifications!

Exact performance influenced by details of the compiler, memory, CPU architecture,

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.Runtime(|L|) = |L|$.
- ▶ ALTC with $AltCRuntime(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest? \longrightarrow *No!*

Our models are simplifications!

Exact performance influenced by details of the compiler, memory, CPU architecture,

Are our models meaningless?

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.\text{Runtime}(|L|) = |L|$.
- ▶ ALTC with $\text{AltCRuntime}(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest? \longrightarrow *No!*

Our models are simplifications!

Exact performance influenced by details of the compiler, memory, CPU architecture,

Are our models meaningless?

No: our comparisons shows *differences in growth rates*: $|L|$ versus $|L|^2 \longrightarrow$
for large-enough inputs, ALTC should always be *much slower* than CONTAINS.

Comparing algorithm: Runtime complexity

Say we have two algorithms for the *contains* problem

- ▶ CONTAINS with $C.\text{Runtime}(|L|) = |L|$.
- ▶ ALTC with $\text{AltCRuntime}(|L|) = |L|^2$.

Which one is *faster*?

Can we conclude that CONTAINS is always fastest, ALTC is slowest? \longrightarrow *No!*

Our models are simplifications!

Exact performance influenced by details of the compiler, memory, CPU architecture,

Remember: We are interested in *scalability* of algorithms

For large-enough inputs, CONTAINS will always be much faster than ALTC *because* the *order of growth* of $C.\text{Runtime}$ is *lower* than the *order of growth* of AltCRuntime .

Comparing algorithm: Runtime complexity

Remember: We are interested in *scalability* of algorithms

For large-enough inputs, CONTAINS will always be much faster than ALT C *because* the *order of growth* of C.Runtime is *lower* than the *order of growth* of AltC Runtime.

Runtime complexity (size of input: N)		Which is faster? (for large-enough N)
ALGORITHM 1	ALGORITHM 2	
$5 + 7N$	$3N + 100$	
$5 + 7N$	$100 \log_2(N) + 2$	
$5 + 7N$	$N(N - 1)/2$	
$5 + 7N$	$1000N^{\frac{1}{2}} - 120$	
$2N^3 + 1000$	$2^N - 1$	

Comparing algorithm: Runtime complexity

Remember: We are interested in *scalability* of algorithms

For large-enough inputs, CONTAINS will always be much faster than ALT C *because* the *order of growth* of C.Runtime is *lower* than the *order of growth* of AltC Runtime.

Runtime complexity (size of input: N)		Which is faster? (for large-enough N)
ALGORITHM 1	ALGORITHM 2	
$5 + 7N$	$3N + 100$	Similar
$5 + 7N$	$100 \log_2(N) + 2$	Algorithm 2
$5 + 7N$	$N(N - 1)/2$	Algorithm 1
$5 + 7N$	$1000N^{\frac{1}{2}} - 120$	Algorithm 2
$2N^3 + 1000$	$2^N - 1$	Algorithm 1

Comparing algorithm: Runtime complexity

Remember: We are interested in *scalability* of algorithms


For large-enough inputs, CONTAINS will always be much faster than ALT C *because* the *order of growth* of C.Runtime is *lower* than the *order of growth* of AltC Runtime.

Runtime complexity (size of input: N)		Which is faster? (for large-enough N)
ALGORITHM 1	ALGORITHM 2	
N	N	Similar
N	$\ln(N)$	Algorithm 2
N	N^2	Algorithm 1
N	\sqrt{N}	Algorithm 2
N^3	2^N	Algorithm 1

Simpler models are easier to compare!

Comparing algorithm: Runtime complexity

Some very common functions $f(n)$ —(increasing order of growth)



Comparing functions: Order of growth

Definition (informal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ denotes f “scales better” than $g(n)$.

The order of growth of f is *upper bounded* by g : any increase in the runtime predicted by f as a consequence of increasing n is *at-most* the increase predicted by $g(n)$.

2. $f(n) = \Omega(g(n))$ denotes f “scales worse” than $g(n)$.

The order of growth of f is *lower bounded* by g : any increase in the runtime predicted by f as a consequence of increasing n is *at-least* the increase predicted by $g(n)$.

3. $f(n) = \Theta(g(n))$ denotes f “scales the same” as $g(n)$.

The order of growth of f is *equivalent* to g : any increase in the runtime predicted by f as a consequence of increasing n is *equivalent to* the increase predicted by $g(n)$.

In this case, we also say that $f(n)$ is *strictly bounded by* $g(n)$.

The book uses the notation $f(n) \sim (g(n))$ instead of $f(n) = \Theta(g(n))$.

Comparing functions: Order of growth

Definition (formal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ if there exists constants $n_0, c > 0$ such that

$$0 \leq f(n) \leq c \cdot g(n) \text{ for all } n \geq n_0.$$

2. $f(n) = \Omega(g(n))$ if there exists constants $n_0, c > 0$ such that,

$$0 \leq c \cdot g(n) \leq f(n) \text{ for all } n \geq n_0.$$

3. $f(n) = \Theta(g(n))$ if there exists constants $n_0, c_{lb}, c_{ub} > 0$ such that,

$$0 \leq c_{lb} \cdot g(n) \leq f(n) \leq c_{ub} \cdot g(n) \text{ for all } n \geq n_0.$$

Comparing functions: Order of growth

Definition (formal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ if there exists constants $n_0, c > 0$ such that

$$0 \leq f(n) \leq c \cdot g(n) \text{ for all } n \geq n_0.$$

Constants n_0 ? c ?

Comparing functions: Order of growth

Definition (formal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ if there exists constants $n_0, c > 0$ such that

$$0 \leq f(n) \leq c \cdot g(n) \text{ for all } n \geq n_0.$$

Constants n_0 ? c ?

- *Constant n_0* allows us to *only* look at large inputs (larger than n_0).
Example, $n^2 > n$ *only when* inputs are large enough!

Comparing functions: Order of growth

Definition (formal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ if there exists constants $n_0, c > 0$ such that

$$0 \leq f(n) \leq c \cdot g(n) \text{ for all } n \geq n_0.$$

Constants n_0 ? c ?

- ▶ *Constant n_0* allows us to *only* look at large inputs (larger than n_0).
Example, $n^2 > n$ *only when* inputs are large enough!
- ▶ *Constant c* hides “irrelevant details”.
Example, $3 + 7 \cdot n$ and n *model* the same behavior!

Comparing functions: Order of growth

Definition (formal)

Let f and g be functions of size of input n :

1. $f(n) = O(g(n))$ if there exists constants $n_0, c > 0$ such that

$$0 \leq f(n) \leq c \cdot g(n) \text{ for all } n \geq n_0.$$

Show that $3 + 7 \cdot n = O(n)$


- $3 + 7 \cdot n = O(n)$. Choose $n_0 = 3$ and $c = 8$. The statement

$$\text{for all } n \geq 3, 0 \leq 3 + 7 \cdot n \leq 8 \cdot n$$

is true, completing the proof.

Comparing functions: Order of growth

Show that $3 + 7 \cdot n = \Theta(n)$



Comparing functions: Order of growth

Theorem

- ▶ *The runtime complexity of CONTAINS is $\Theta(|L|)$.*
- ▶ *The memory complexity of CONTAINS is $\Theta(1)$.*

How to compare the order of growth of functions?

How to compare the order of growth of functions?

Limits: A mathematical power tool

Let f and g be functions of n with non-negative ranges. If

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} \text{ is defined and is } \begin{cases} \infty & \text{then } f(n) = \Omega(g(n)); \\ c, \text{ with } c > 0 \text{ a constant} & \text{then } f(n) = \Theta(g(n)); \\ 0 & \text{then } f(n) = O(g(n)). \end{cases}$$

How to compare the order of growth of functions?

Limits: A mathematical power tool

Let f and g be functions of n with non-negative ranges. If

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} \text{ is defined and is } \begin{cases} \infty & \text{then } f(n) = \Omega(g(n)); \\ c, \text{ with } c > 0 \text{ a constant} & \text{then } f(n) = \Theta(g(n)); \\ 0 & \text{then } f(n) = O(g(n)). \end{cases}$$

Example

$$\lim_{n \rightarrow \infty} \frac{c \cdot f(n)}{f(n)} = c \cdot \left(\lim_{n \rightarrow \infty} \frac{f(n)}{f(n)} \right) = c$$

How to compare the order of growth of functions?

Limits: A mathematical power tool

Let f and g be functions of n with non-negative ranges. If

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} \text{ is defined and is } \begin{cases} \infty & \text{then } f(n) = \Omega(g(n)); \\ c, \text{ with } c > 0 \text{ a constant} & \text{then } f(n) = \Theta(g(n)); \\ 0 & \text{then } f(n) = O(g(n)). \end{cases}$$

Example

$$\lim_{n \rightarrow \infty} \frac{c \cdot f(n)}{f(n)} = c \cdot \left(\lim_{n \rightarrow \infty} \frac{f(n)}{f(n)} \right) = c \quad \longrightarrow \quad c \cdot f(n) = \Theta(f(n))$$

How to compare the order of growth of functions?

Limits: A mathematical power tool

Let f and g be functions of n with non-negative ranges. If

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} \text{ is defined and is } \begin{cases} \infty & \text{then } f(n) = \Omega(g(n)); \\ c, \text{ with } c > 0 \text{ a constant} & \text{then } f(n) = \Theta(g(n)); \\ 0 & \text{then } f(n) = O(g(n)). \end{cases}$$

Example

$$\lim_{n \rightarrow \infty} \frac{c \cdot f(n)}{f(n)} = c \cdot \left(\lim_{n \rightarrow \infty} \frac{f(n)}{f(n)} \right) = c \quad \longrightarrow \quad c \cdot f(n) = \Theta(f(n))$$

$$\lim_{n \rightarrow \infty} \frac{n^c}{n^{c+d}} = \lim_{n \rightarrow \infty} \frac{1}{n^d} = 0 \quad \longrightarrow \quad n^c = O(n^{c+d})$$

How to compare the order of growth of functions?

Limits: A mathematical power tool

Let f and g be functions of n with non-negative ranges. If

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} \text{ is defined and is } \begin{cases} \infty & \text{then } f(n) = \Omega(g(n)); \\ c, \text{ with } c > 0 \text{ a constant} & \text{then } f(n) = \Theta(g(n)); \\ 0 & \text{then } f(n) = O(g(n)). \end{cases}$$

Example

$$\lim_{n \rightarrow \infty} \frac{c \cdot f(n)}{f(n)} = c \cdot \left(\lim_{n \rightarrow \infty} \frac{f(n)}{f(n)} \right) = c \quad \longrightarrow \quad c \cdot f(n) = \Theta(f(n))$$

$$\lim_{n \rightarrow \infty} \frac{n^c}{n^{c+d}} = \lim_{n \rightarrow \infty} \frac{1}{n^d} = 0 \quad \longrightarrow \quad n^c = O(n^{c+d})$$

$$\lim_{n \rightarrow \infty} \frac{n^c}{d^n} = 0 \quad \longrightarrow \quad n^c = O(d^n)$$

How to compare the order of growth of functions?

Example (See Example 3.26 in the course notes for details)

$$\log_a(n) = \frac{\log_b(n)}{\log_b(a)} = \frac{1}{\log_b(a)} \cdot \log_b(n) \quad \longrightarrow \quad \log_a(n) = \Theta(\log_b(n))$$

$$\lim_{n \rightarrow \infty} \frac{\log_2(n)^c}{n^d} = 0 \quad \longrightarrow \quad \log_2(n)^c = O(n^d)$$

$$\lim_{n \rightarrow \infty} \frac{d^{n/u}}{c^{n/v}} = 0 \text{ (if } c \geq d \geq 1, u \geq v \geq 1) \quad \longrightarrow \quad d^{n/u} = O(c^{n/v})$$

$$\lim_{n \rightarrow \infty} \frac{c_1 n^{d_1} + \dots + c_m n^{d_m}}{n^{d_i}} = c_i \text{ (if } d_i = \max(d_1, \dots, d_m)) \quad \longrightarrow \quad c_1 n^{d_1} + \dots + c_m n^{d_m} = \Theta(n^{d_i})$$

$$\lim_{n \rightarrow \infty} \frac{f(n) + g(n)}{g(n)} = 1 \text{ (if } f(n) = O(g(n))) \quad \longrightarrow \quad f(n) + g(n) = \Theta(g(n))$$

$$\lim_{n \rightarrow \infty} \frac{h(n) \cdot f(n)}{h(n) \cdot g(n)} = 0 \text{ (if } f(n) = O(g(n))) \quad \longrightarrow \quad h(n) \cdot f(n) = O(h(n) \cdot g(n))$$

Reflection on CONTAINS

Is CONTAINS a *good* algorithm?

CONTAINS is correct and has a runtime complexity of $\Theta(|L|)$ \longrightarrow Sounds good to me!

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: " $o \leq r \leq |L|$ and $v \notin L[o, r)$ ", bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

Reflection on CONTAINS

Is CONTAINS a *good* algorithm?

CONTAINS is correct and has a runtime complexity of $\Theta(|L|)$ \longrightarrow Sounds good to me!

Critique: CONTAINS is *too specialized* \longrightarrow .

We cannot use CONTAINS for anything else than the contains problem!

Example

- ▶ Searching in only *part* of the list?
- ▶ Finding where v is in the list?

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: " $o \leq r \leq |L|$ and $v \notin L[o, r]$ ", bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

Reflection on CONTAINS

Critique: CONTAINS is *too specialized* \longrightarrow .

We cannot use CONTAINS for anything else than the contains problem!

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: " $o \leq r \leq |L|$ and $v \notin L[o, r]$ ", bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

Reflection on CONTAINS

Critique: CONTAINS is *too specialized* \longrightarrow .

We cannot use CONTAINS for anything else than the contains problem!

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

Algorithm LSCONTAINS(L, v):

1: **return** LINEARSEARCH($L, v, 0$) $\neq |L|$.

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

- With respect to worst-case inputs ($v \notin L$): $\Theta(|L|)$.

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

- ▶ With respect to worst-case inputs ($v \notin L$): $\Theta(|L|)$.
- ▶ With respect to best-case inputs ($v = L[o]$): $\Theta(1)$.

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

- ▶ With respect to worst-case inputs ($v \notin L$): $\Theta(|L|)$.
- ▶ With respect to best-case inputs ($v = L[o]$): $\Theta(1)$.

Problem: Modeling runtime complexity in terms of *only the input* limits us!

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

Problem: Modeling runtime complexity in terms of *only the input* limits us!

Assume: $L[i] = v$ and i is the *first* offset after o equivalent to v .

The runtime complexity of LINEARSEARCH is $\Theta(i - o)$.

Reflection on CONTAINS

Algorithm LINEARSEARCH(L, v, o):

Input: L is an *array*, v a value, $0 \leq o \leq |L|$.

1: $r := o$.

/* invariant: “ $o \leq r \leq |L|$ and $v \notin L[o, r)$ ”, bound function: $|L| - r$ */

2: **while** $r \neq |L|$ **and also** $L[r] \neq v$ **do**

3: $r := r + 1$.

4: **return** r .

Result: return the first offset r , $o \leq r < |L|$, with $L[r] = v$ or,
if no such offset exists, $r = |L|$.

What is the runtime complexity of LINEARSEARCH?

Problem: Modeling runtime complexity in terms of *only the input* limits us!

Assume: $L[i] = v$ and i is the *first* offset after o equivalent to v .

The runtime complexity of LINEARSEARCH is $\Theta(i - o)$ with $i = \text{LINEARSEARCH}(L, v, o)$.