

Question Description	Answer Choice 1	Answer Choice 2	Answer Choice 3	Answer Choice 4	Correct Answer Choice	
<pre>public static void main(String[] args) { int x = 5; System.out.println(x++ + ++x); }</pre>	11	12	13	14	2	
<pre>public static void main(String[] args) { int x = 10; int y = x > 5 ? (x < 20 ? 15 : 25) : 5; System.out.println(y); }</pre>	5	10	15	25	3	
<pre>public static void main(String[] args) { int number = 2; switch (number) { case 1: System.out.println("One"); case 2: System.out.println("Two"); case 3: System.out.println("Three"); default: System.out.println("Default"); } }</pre>	Two	Two Three Default	Three	Default	2	
<pre>public static void main(String[] args) { int arr[] = new int[5]; System.out.println(Arrays.toString(arr)); }</pre>	null, null, null, null, null	[1, 1, 1, 1, 1]	[0, 0, 0, 0, 0]	Compilation Error	3	
<pre>public static void main(String[] args) { int arr[][] = {{1, 2, 3}, {4, 5}}; System.out.println(arr[1].length); }</pre>	2	3	Compilation Error	5	1	
<pre>public static void main(String[] args) { int[][] arr = {{1,2,3},{4,5,6},{7,8,9}}; System.out.println(arr.length + arr[1].length); }</pre>	4	5	6	8	3	
<pre>public static void main(String[] args) {int arr[] = {1, 2, 3, 4}; System.out.println(arr[arr[1]]);}</pre>	1	2	3	4	3	
<pre>public static void main(String[] args) { int arr[] = {1, 2, 3, 4, 5}; System.out.println(arr[arr.length - arr[2]]); }</pre>	1	2	3	4	3	
<pre>public static void main(String[] args) { int arr[] = new int[3]; for (int i : arr){ i = 10; } System.out.println(arr[0]); }</pre>	0	10	3	Compilation Error	1	
Which keyword is used to create a package in Java?	import	package	namespace	module	2	
What is the default access modifier for classes in a package if not explicitly declared?	private	public	package-private	protected	3	

How do you access a class from a user-defined package?	package.*; then use Class	Just use ClassName	ude package.ClassName	using package.ClassName	1	
What is the correct way to import all classes from a package `myPack`?	import myPackage;	include myPackage.*;	import myPackage.*;	using myPackage.*;	3	
What happens if a class is declared public but placed in a file with a different name?	Compiles successfully	Runtime error	Compilation error	Runs with warning	3	
Which of the following allows interfaces to have method bodies (from Java 8)?	static methods	private methods	default methods	All of the above	4	
Can an interface inherit another interface?	No	Yes, only one	Yes, multiple	Only abstract classes can	3	
What is the output of the `javac` command?	Class file	JAR file	Source code	None	1	
Which loop executes at least once?	`for`	`while`	`do-while`	None	3	
What is a jagged array in Java?	An array with unequal columns	A 3D array	A sparse array	None	1	
What is the size of a char in Java?	1 byte	4 byte	3 byte	2 byte	4	
What is passed to the `main()` method in Java as arguments?	Array of Strings	Integer values	Boolean values	Array of Objects	1	
Which operator is used to concatenate strings in Java?	+	concatenate()	cat()		1	
Which of these is a checked exception?	NullPointerException	IOException	ArithmeticException	IndexOutOfBoundsException	2	
Which method gets the current time in Java 8 Date-Time API?	LocalTime.now()	Date.now()	Clock.time()	Time.now()	1	
Which class is used to read characters from a file?	FileReader	FileWriter	File	InputStream	1	
How to write text using character streams?	FileWriter writer = new FileWriter("out.txt"); writer.write("Hello");	FileReader reader = new FileReader("out.txt");	File out = new File("out.txt"); Files.write(out, "Hello".getBytes());		1	
Which stream should be used to write binary data?	FileWriter	BufferedReader	FileOutputStream	FileReader	3	
What is required for a class to be serializable?	Implements Serializable	Extends Thread	Implements Closeable	Extends File	1	
What does the `StringTokenizer` class do?	Sorts strings	Joins strings	Splits strings using delimiters	Deletes strings	3	
<pre>public static void main(String[] args) { StringBuilder sb1 = new StringBuilder("abc"); StringBuilder sb2 = new StringBuilder("abc"); System.out.println(sb1.equals(sb2)); }</pre>	1	TRUE	FALSE	0	3	
<pre>public static void main(String[] args) { StringBuilder sb = new StringBuilder("abcdef"); sb.delete(2, 5); System.out.println(sb); }</pre>	ab	abcdef	abc	abf	4	
<pre>public static void main(String[] args) { StringBuffer sb = new StringBuffer("Coding"); sb.setLength(2); System.out.println(sb); }</pre>	Co	Coding	Cod	error	1	
<pre>public static void main(String[] args) { StringTokenizer st = new StringTokenizer("a:b:c", ":"); System.out.println(st.nextToken() + st.nextToken()); }</pre>	aa	a:b	abc	ab	4	
<pre>public static void main(String[] args) { String s1 = "hello"; String s2 = "hello"; System.out.println(s1 == s2); }</pre>	TRUE	FALSE	Compilation error	Runtime error	1	

<pre> public static void main(String[] args) { String s = "Java"; s += " DSA"; System.out.println(s); } </pre>	Java	DSA	Error	Java DSA	4	
<pre> public static void main(String[] args) { String s1 = "abc"; String s2 = "a" + "b" + "c"; System.out.println(s1.equals(s2)); } </pre>	FALSE	TRUE	Compilation error	Runtime error	2	
<pre> public static void main(String[] args) { StringTokenizer st = new StringTokenizer("a:b:c"); while (st.hasMoreTokens()) { System.out.println(st.nextToken()); } } </pre>	a:b:c	a b c	a	error	1	
<pre> public static void main(String[] args) { StringBuffer sb1 = new StringBuffer("abc"); StringBuffer sb2 = new StringBuffer("abc"); System.out.println(sb1.equals(sb2)); } </pre>	1	TRUE	FALSE	0	3	
<pre> public static void main(String[] args) { StringBuilder sb = new StringBuilder("abcdef"); sb.replace(2, 3, "xyz"); System.out.println(sb); } </pre>	abwdef	abwxyzef	abwxyz	abwxyzdef	4	
<pre> public static void main(String[] args) { String s1 = "Java"; String s2 = "Java"; String s3 = new String("Java"); System.out.println(s1 == s3); } </pre>	TRUE	FALSE	Compilation Error	Runtime Error	2	
<pre> public static void main(String[] args) { StringTokenizer st = new StringTokenizer("A,B,C", ","); System.out.println(st.countTokens()); } </pre>	2	3	5	4	2	
<pre> public class Main { Main(int x) {} public static void main(String[] args) { Main t = new Main(); } } </pre>	ompile and run succe	Compilation Error	Run-time error	alls default construct	2	

<pre> class test{ private test(){ System.out.println("Constructor called"); } } public class Main { public static void main(String[] args) { test m = new test(); } } </pre>	Compilation error	Constructor Called	runtime error	No Output	1	
<pre> class test{ void display(double a) { System.out.println("Double: " + a); } } public class Main { public static void main(String[] args) { test t = new test(); t.display(5); } } </pre>	Compilation error	Double: 5.0	runtime error	no Output	2	
<pre> public class Main { private Main(){ System.out.println("Constructor Called"); } public static void main(String[] args) { Main m = new Main(); } } </pre>	Constructor Called	Compilation error	runtime error	No Output	1	
<pre> public static void main(String[] args) { Integer x = new Integer(50); Integer y = 50; System.out.println(x == y); } </pre>	Compilation error	TRUE	FALSE	runtime error	3	
<pre> public class Main { static void print(){ System.out.println("Print called"); } public static void main(String[] args) { print(); } } </pre>	runtime error	compilation error	no output	Print called	4	
<pre> public class Main { static int x = 10; Main(){ x += 5; } public static void main(String[] args) { Main m1 = new Main(); Main m2 = new Main(); System.out.println(Main.x); } } </pre>	10	15	20	Error	3	

<pre> class test{ void display(){ System.out.println("Display"); } } public class Main { public static void main(String[] args) { test m = null; m.display(); } } </pre>	Display	compilation error	Error	IOException Exception	4
<pre> public class Main { void print(){ System.out.println("Hello World"); } public static void main(String[] args) { print(); } } </pre>	Hello World	compilation error	runtime error	no output	2
<pre> public static void main(String args[]) { for (byte b = 0; b < 128; b++) { System.out.println(b); } } </pre>	Output will be numbers 0 to 127	Compilation Error	Infinite Loop	None of these	3
What will be the result of (7 >> 2) in Java?	3	2	1	0	3
What is the output? <pre> try { int arr[] = new int[5]; arr[5] = 100; } catch(ArrayIndexOutOfBoundsException e) { System.out.println(</pre>	100	Error	Compile error	Runtime error	2
What is the purpose of 'finally' block?	Handle runtime errors	Execute code after catch	Clean up resources	Declare exceptions	3
What will be the output? <pre> try { System.out.println("A"); } finally { System.out.println("B"); } </pre>	A	A B	B	Compile error	2
Which is faster for single-threaded operations?	StringBuffer	StringTokenizer	StringBuilder	String	3
Which of these declarations will cause a compilation error?	int[][] arr = new int[3][];	int[] arr[] = new int[3][3];	int[][] arr = new int[][3];	int arr[][] = new int[3][3];	3
Which is true about multiple catch blocks?	Only one is executed	All are executed	They are optional	Must be followed by finally	1
<pre> public static void main(String args[]) { int a =10; String b = "10+10"; System.out.println(a+b); } </pre>	30	1020	10+10+10	1010+10	4
Can interfaces have variables? <pre> interface A { int x = 5; } </pre>	public static final by default	No	Only static	Only private	1

<pre> public class Main { static int function(){ return 10; } static String function(){ return "20"; } public static void main(String[] args) { int a = function(); System.out.println(a); } } </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>
	compilation error	runtime error	10	20	1	
<pre> class parent{ final void display(){ System.out.println("parent"); } } class child extends parent{ void display(){ System.out.println("child"); } } public class Main { public static void main(String[] args) { child c = new child(); c.display(); } } </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>
	parent	child	compilation error	runtime error	3	
<pre> abstract class test{ int a; } public class Main { public static void main(String[] args) { test t = new test(); t.a = 10; System.out.println(t.a); } } </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>	<pre> </pre>
	compilation error	10	runtime error	0	1	

<pre> class parent{ void display(){ System.out.println("parent class"); } } class child extends parent{ int display(){ System.out.println("child class"); return 10; } } public class Main { public static void main(String[] args) { child c = new child(); c.display(); } } </pre>	parent class	child class	compilation error	runtime error	3	
<pre> public class Main { int x; Main(){ x = 10; } public static void main(String[] args) { Main m1 = new Main(); Main m2 = new Main(m1); m1.x = 20; System.out.println(m2.x); } } </pre>	20	10	30	Compilation error	4	
<pre> final class test{ int a; int b; } class exam extends test{ int x; } public class Main { public static void main(String[] args) { test t = new test(); t.a = 10; t.b = 20; t = new test(); } } </pre> which is not a valid syntax in above code	<pre> class exam extends test{ int x; } </pre>	test t = new test();	<pre> t.a = 10; t.b = 20; </pre>	t = new test();	1	

<pre> class parent{ void display(){ System.out.println("parent class"); } } class child extends parent{ void display(){ System.out.println("child class"); } } public class Main { public static void main(String[] args) { child c = new child(); c.display(); } } </pre>	parent class	child class	compilation error	runtime error	2	
<pre> public class Main { int x; Main(){ x = 10; } public static void main(String[] args) { Main m1 = new Main(); Main m2 = m1; m1.x = 20; System.out.println(m2.x); } } </pre>	20	10	30	Compilation error	1	
<pre> class parent{ int a; parent(int a){ this.a = a; } } class test extends parent{ int b; test(int b){ this.b = b; } } public class Main { public static void main(String[] args) { test t = new test(10); t.a = 20; System.out.println(t.a); } } </pre>	20	10	compilation error	runtime error	3	
<pre> What is the output? Random rand = new Random(); System.out.println(rand.nextInt(10)); </pre>	Compile-time error	A random int between 0 and 9	Always prints 10	Runtime error	2	

What does the following code do? File file = new File("data.txt"); file.createNewFile();	Creates a new file	Deletes the file	Reads file content	Renames the file	1	
What is the output of: System.out.println(new File("test.txt").exists()); when the file doesn't exist?	TRUE	FALSE	Error	null	2	
class test{ int a; test(){ a = 5; } } public class Main { public static void main(String[] args) { final test t = new test(); t.a = 10; t = new test(); System.out.println(t.a); } }	5	10	compilation error	No Output	3	
abstract class A{ int a; abstract void display(); } class test extends A{ int b; } public class Main { public static void main(String[] args) { test t = new test(); t.a = 10; System.out.println(t.a); } }	10	compilation error	null	runtime error	2	
abstract class test{ private abstract void display(); } public class Main { public static void main(String[] args) { System.out.println("Test"); } }	Test	runtime error	no output	compilation error	4	

<pre> class A{ protected void display(){ System.out.println("Parent class"); } } class test extends A{ void display(){ System.out.println("Child class"); } } public class Main { public static void main(String[] args) { test t = new test(); t.display(); } </pre>						
	Parent Class	Child Class	compilation error	runtime error	3	
<pre> final class test{ int b; test(int b){ this.b = b; } } public class Main { public static void main(String[] args) { test t = new test(10); System.out.println(t.b); } } </pre>						
	10	20	compilation error	runtime error	1	
which of the following is correct statement regarding Multiple Inheritance?	support multiple inheritance	allowed on Classes	allowed on abstract classes	allowed on interfaces	4	
<pre> interface A { void show(); } class Main implements A { public void show() { System.out.println("Hello"); } public static void main(String[] args) { new Main().show(); } } </pre>						
	interface can't be implemented	Hello	No output	Runtime Exception	2	
Which of the following correctly implements an interface?						
<pre> interface MyInterface { void doStuff(); } class MyClass _____ MyInterface { public void doStuff() { System.out.println("Done"); } } </pre>	extends	implements	inherits	uses	2	

What is the output? interface X { int A = 10; } class Y implements X { public static void main(String args[]) { System.out.println(A); } }	0	10	compile error	runtime error	2	
interface A { default void print() { System.out.println("A"); } } class B implements A { public static void main(String[] args) { new B().print(); } }	A	B	Compile Error	Runtime Error	1	
Which of the following is correct for interface inheritance? interface A { void show(); } interface B extends A { void display(); }	interfaces can't extend	Only one interface allowed	Valid syntax	class must be abstract	3	
What happens here? interface A { void show(); } class B implements A { // method show() not implemented	method show() not implemented	No error	Runtime error	Abstract method error	1	
Choose the correct implementation. interface Printable { void print(); } class Doc implements Printable { public void print() { System.out.println("Printing"); } }	Correct	incorrect: class must be abstract	interface must be abstract	Incorrect syntax	1	
What is the output? interface A { static void print() { System.out.println("Hello"); } } class B { public static void main(String[] args) { A.print(); } }	Compile error	Hello	Nothing	Runtime error	2	
interface A { void display(); } class B implements A { public void display() { System.out.print("B"); } } class C extends B { public void display() { System.out.print("C"); } public static void main(String args[]) { new C().display(); } }	B	C	BC	Compile Error	2	

<pre> public class Test { public static void main(String args[]) { try { int data = 50/0; } catch(ArithmeticException e) { System.out.println("Exception caught"); } } } </pre>	Exception caught	Compile error	0	Runtime error	1	
What will be the output? <pre> Pattern p = Pattern.compile("a*b"); Matcher m = p.matcher("aaab"); System.out.println(m.matches()); </pre>	TRUE	FALSE	compile error	runtime error	1	
What does the following print? <pre> LocalDate date = LocalDate.of(2023, 4, 19); System.out.println(date.getYear()); </pre>	2022	2023	2024	Compile Error	2	