1 Procedure A: Download PhishNet

Use one of the two methods below. Method 1 is recommended.

Method 1: Download from the Releases page

1. Open the Releases page:
   `https://github.com/aaron-c-s-ramos/PhishNet-v2-Public-Release/releases`
2. Find the newest release at the top of the page.
   Result: At the date of this manual, the newest release is **PhishNet v2.3.0**.
3. Under **Assets**, click `phishnet-2.3.0.zip` to download it.
   Result: The browser downloads a file of approximately 4.4 MB.
4. Do not download **Source code (zip)** or **Source code (tar.gz)**. These files contain the repository, not the extension folder.

Method 2: Download from the file list

1. Open the repository page:
   `https://github.com/aaron-c-s-ramos/PhishNet-v2-Public-Release`
2. In the file list, click `phishnet-2.3.0.zip`.
3. Click **Download raw file**. This button is at the top right of the file view.
   Result: The browser downloads a file of approximately 4.4 MB.

Extract the ZIP file

1. Make a folder for the extension in a location that you will keep. For example:
   - Windows: `C:\PhishNet`
   - macOS or Linux: `~/PhishNet`
2. Extract the contents of `phishnet-2.3.0.zip` into that folder.
   - Windows: right-click the file, click **Extract All**, then select the folder.
   - macOS: double-click the file, then move the contents into the folder.
   - Linux: use your archive manager or the `unzip` command.
3. Open the folder. Make sure that `manifest.json` is directly in the folder.
   Result: The folder contains `assets`, `block.html`, `fonts`, `icons`, `manifest.json`, `model`, `options.html`, `ort`, `popup.html`, and `rules`.

> **CAUTION**
> Do not move, rename, or delete this folder after the installation. The browser loads the extension from this folder each time it starts. If the folder is not there, PhishNet stops.

2 Procedure B: Load the extension in the browser

The steps are the same in all Chromium browsers. Only the address of the extensions page is different.

Browser	Extensions page address
Google Chrome	`chrome://extensions`
Microsoft Edge	`edge://extensions`
Brave	`brave://extensions`
Opera	`opera://extensions`
Vivaldi	`vivaldi://extensions`

1. Open the browser.
2. Type the extensions page address in the address bar, then push Enter.

3. Set **Developer mode** to on.
   - Chrome, Brave, Opera, and Vivaldi: the switch is at the top right of the page.
   - Edge: the switch is in the left panel.

   Result: The **Load unpacked** button shows.
4. Click **Load unpacked**.
5. Select the folder that you made in Procedure A, for example `C:\PhishNet`. Do not select a file in the folder.
   Result: The **PhishNet** card shows version **2.3.0** and no error.
6. Click the extensions icon in the browser toolbar. In Chrome and Edge, this icon is a puzzle piece.
7. Click the pin icon next to **PhishNet**.
   Result: The PhishNet icon stays in the toolbar.

> **NOTE**
> The browser can show a message about extensions in developer mode. This message is usual for an extension that you load from a folder.

> **NOTE**
> PhishNet uses permissions to examine each address before the page loads. Appendix A gives each permission and its purpose.

3 Procedure C: Turn on protection in private windows

> **CAUTION**
> Set the private-window switch to on. If the switch is off, PhishNet does not examine the pages that you open in private windows.

The browser keeps PhishNet off in private windows by default. Only you can change this setting. PhishNet cannot change it.

1. Open the extensions page of the browser.
2. On the **PhishNet** card, click **Details**.
3. Set the private-window switch to on:
   - Chrome: **Allow in Incognito**
   - Edge: **Allow in InPrivate**
   - Brave, Opera, and Vivaldi: the switch for private windows. The label can be different in each browser.
4. Open the PhishNet settings. Click the PhishNet icon, then click the gear icon.
   Result: Under **Private browsing**, the setting shows `granted`. Figure 3 shows this setting before the switch is on.

> **NOTE**
> In a private window, PhishNet keeps its data in session storage. The browser deletes this data when the private session closes.

4 Procedure E: Install PhishNet in Firefox

Firefox 140 or later uses a separate package. Mozilla signed this package, thus Firefox keeps PhishNet after a restart.

1. Open the Releases page:
   ```
   https://github.com/aaron-c-s-ramos/PhishNet-v2-Public-Release/releases
   ```
2. Under **Assets**, click `phishnet-2.3.0-firefox.xpi` to download it.
   Result: The browser downloads a file of approximately 4.4 MB.
3. In Firefox, type this address in the address bar, then push Enter:
   ```
   about:addons
   ```

4. Click the gear icon, then click **Install Add-on From File**.
5. Select the file `phishnet-2.3.0-firefox.xpi`.
   Result: Firefox asks if you want to add PhishNet.
6. Click **Add**.
   Result: PhishNet shows in the list of extensions.
7. Click **PhishNet**, then click the **Details** tab.
8. Set **Run in Private Windows** to **Allow**.
9. Click the extensions icon in the toolbar. Click the gear next to **PhishNet**, then click **Pin to Toolbar**.
10. Do Procedure D.

> **NOTE**
> Browsers that use the Firefox engine, for example LibreWolf, Waterfox, Floorp, and Zen, can read the same package. The project team did not do a test of these browsers.

> **NOTE**
> Firefox asks for your consent before the first community report. Without a gateway, PhishNet sends nothing (section 9).