

ACCESSING AND ANALYZING MLB PITCH TRACKING DATA IN R

Applying the Scientific Method

March 28, 2017

Aaron R. Baggett, Ph.D.

University of Mary Hardin-Baylor

[Department of Psychology](#)

RESOURCES

- Slides, data, and R code are available at:

bit.ly/austin_r

MAJOR LEAGUE BASEBALL (MLB) PITCH TRACKING DATA

MLB PITCH TRACKING DATA

- Since 2007, MLB has tracked pitch location and play-by-play data for all games
- Source: Sportvision PITCHf/x system
- PITCHf/x data are fed real time to mobile and desktop apps
- All data are stored in XML format on MLB servers

MLB PITCH TRACKING DATA

- Location: <http://gd2.mlb.com/components/game/mlb/>

ACCESSING MLB PITCH TRACKING DATA

ACCESSING MLB PITCH TRACKING DATA

- R packages:
 1. `pitchRx`: Data collection
 2. `dplyr`: Data analysis

- Prior to 2013, researchers had to scrape PITCHf/x data manually
- In 2013, Carson Sievert created the **pitchRx** R package
- **pitchRx** contains tools for accessing play-by-play data

PITCHRX

- Prior to 2013, researchers had to scrape PITCHf/x data manually
- In 2013, Carson Sievert created the **pitchRx** R package
- **pitchRx** contains tools for accessing play-by-play data

```
pfx_db <- src_sqlite("pfx_db.sqlite3", create = TRUE)
files <- c("inning/inning_all.xml", "players.xml", "miniscoreboard.xml")
scrape(start = "YYY-MM-DD", end = "YYY-MM-DD", suffix = files,
        connect = pfx_db$con)
pfx_db <- src_sqlite("~/your/working/directory/pfx_db.sqlite3")
src_tbls(pfx_16)
```

- Once we set up a PITCHf/x database, we have access to all MLB pitch and gameplay data
- Best to use a small date range for initial setup
- 10 primary tables in the data

PITCHF/X DATA TABLES

Table Name	Description
action	Ball/strike count, result of pitch, ...
atbat	Pitcher/batter names, handedness, heights, at bat result, ...
coach	Names of manager and staff, ...
game	Venue, start time, time zone, TV, win-loss records, ...
media	Mobile/TV media assets, ...
pitch	Umpire's decision/outcome, strike zone parameters, x-y coordinates, ...
player	Players' stats, position, number, ...
po	Details about put out attempts (e.g., pickoffs and stolen bases), ...
runner	Details about base runner(s) and at bat events, ...
umpire	Umpire names and positions, ...

PITCHF/X DATA TABLES

For most analyses, we usually work with:

Table Name	Description
action	Ball/strike count, result of pitch, ...
atbat	Pitcher/batter names, handedness, heights, at bat result, ...
coach	Names of manager and staff, ...
game	Venue, start time, time zone, TV, win-loss records, ...
media	Mobile/TV media assets, ...
pitch	Umpire's decision/outcome, strike zone parameters, x-y coordinates, ...
player	Players' stats, position, number, ...
po	Details about put out attempts (e.g., pickoffs and stolen bases), ...
runner	Details about base runner(s) and at bat events, ...
umpire	Umpire names and positions, ...

- Wickham and Francois (2016)
- A grammar of data manipulation
- Provides a set of verbs for lots of tasks
 - **select()**: Selects columns
 - **filter()**: Filters rows (e.g., ==, !=, <=, etc.)
 - **arrange()**: Re-orders and sorts rows
 - **mutate()**: Creates new variables/columns
 - **summarise()**: Summarizes values/output
 - **group_by()**: Allows for by-group operations

ACCESSING MLB PITCH TRACKING DATA

- R packages:
 1. `pitchRx`: Data collection
 2. `dplyr`: Data analysis

ANALYZING MLB PITCH TRACKING DATA

TONIGHT

- There are several ways to analyze PITCHf/x data
 - Ex.: Pitching/batting outcomes, predictive models, et al.
- Tonight though, let's concentrate on home plate umpire decisions
- Specifically:
 1. How many pitches do umpires see during games? Of those, how many require a decision?
 2. How accurate are *all* umpires over the season? How accurate are *individual* umpires over the season?

1. PITCHES SEEN VS. DECISIONS MADE

- How many pitches do umpires see during games? Of those, how many require an umpire decision?
 - Pitches seen: Total number of recorded pitches thrown during game
 - Decisions made: Total number of called strikes and called balls during game

1. PITCHES SEEN VS. DECISIONS MADE

- We'll use the **pitch** table to answer these questions
- Steps:
 1. Create data frame for pitches seen, **observed**
 2. Create data frame for decisions made, **decisions**
 3. Join **observed** and **decisions**
 4. Calculate proportion of pitches requiring decision
 5. Calculate simple descriptive statistics

1. PITCHES SEEN VS. DECISIONS MADE

- Step 1. Create data frame for pitches seen

```
observed <- pitch %>%  
  group_by(gameday_link) %>%  
  summarize(seen = n())
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 1. Create data frame for pitches seen
- R code:
 - `pitch`: Current data frame
 - `group_by()`, `summarize()`, `n()`: `dplyr` verbs
 - `gameday_link`: Unique date/team label
 - `seen`: New name for variable `n()`
 - `observed`: Name of new data frame

```
observed <- pitch %>%  
  group_by(gameday_link) %>%  
  summarize(seen = n())
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 1. Create data frame for pitches seen

```
(observed <- pitch %>%  
  group_by(gameday_link) %>%  
  summarize(seen = n()))
```

```
## # A tibble: 2,468 × 2  
##           gameday_link  seen  
##           <chr>    <int>  
## 1 gid_2016_04_03_chnmlb_anamlb_1    252  
## 2 gid_2016_04_03_nynmlb_kcamlb_1    291  
## 3 gid_2016_04_03_slnmlb_pitmlb_1    285  
## 4 gid_2016_04_03_tormlb_tbamlb_1    276  
## 5 gid_2016_04_04_chamlb_oakmlb_1    292  
## 6 gid_2016_04_04_chnmlb_anamlb_1    297  
## 7 gid_2016_04_04_colmlb_arimlb_1    362  
## 8 gid_2016_04_04_lanmlb_sdnmlb_1    319  
## 9 gid_2016_04_04_milmlb_indmlb_1    270
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 2. Create data frame for decisions made
- We need to omit all pitches/outcomes except for called strikes and called balls

```
decisions <- pitch %>%  
  group_by(gameday_link) %>%  
  filter(des == "Called Strike" | des == "Ball") %>%  
  summarize(decisions = n())
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 2. Create data frame for decisions made
- We need to omit all pitches/outcomes except for called strikes and called balls
- R code:
 - `filter()`: Returns rows with matching conditions

```
decisions <- pitch %>%  
  group_by(gameday_link) %>%  
  filter(des == "Called strike" | des == "Ball") %>%  
  summarize(decisions = n())
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 2. Create data frame for decisions made

```
(decisions <- pitch %>%  
  group_by(gameday_link) %>%  
  filter(des == "called strike" | des == "ball") %>%  
  summarize(decisions = n()))
```

```
## # A tibble: 2,468 × 2  
##           gameday_link decisions  
##           <chr>         <int>  
## 1 gid_2016_04_03_chnmlb_anamlb_1      124  
## 2 gid_2016_04_03_nynmlb_kcamlb_1      150  
## 3 gid_2016_04_03_slnmlb_pitmlb_1      145  
## 4 gid_2016_04_03_tormlb_tbamlb_1      136  
## 5 gid_2016_04_04_chamlb_oakmlb_1      153  
## 6 gid_2016_04_04_chnmlb_anamlb_1      135  
## 7 gid_2016_04_04_colmlb_arimlb_1      158  
## 8 gid_2016_04_04_milmlb_miamlb_1      165
```


1. PITCHES SEEN VS. DECISIONS MADE

- Step 3. Join **observed** and **decisions** by **gameday_link**

```
pitches <- inner_join(observed, decisions, by = "gameday_link")
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 3. Join `observed` and `decisions` by `gameday_link`
- R code:
 - `inner_join()`: Returns observations that match in both x and y

```
pitches <- inner_join(observed, decisions, by = "gameday_link")
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 3. Join **observed** and **decisions** by **gameday_link**

```
(pitches <- inner_join(observed, decisions, by = "gameday_link"))
```

```
## # A tibble: 2,468 × 3
```

##		gameday_link	seen	decisions
##		<chr>	<int>	<int>
## 1	gid_2016_04_03_chnmlb_anamlb_1		252	124
## 2	gid_2016_04_03_nynmlb_kcamlb_1		291	150
## 3	gid_2016_04_03_slmlb_pitmlb_1		285	145
## 4	gid_2016_04_03_tormlb_tbamlb_1		276	136
## 5	gid_2016_04_04_chamlb_oakmlb_1		292	153
## 6	gid_2016_04_04_chnmlb_anamlb_1		297	135
## 7	gid_2016_04_04_colmlb_arimlb_1		362	158
## 8	gid_2016_04_04_lanmlb_sdnmlb_1		319	165
## 9	gid_2016_04_04_minmlb_bamlb_1		278	136

1. PITCHES SEEN VS. DECISIONS MADE

- Step 4. Calculate proportion of pitches requiring decision

```
pitches <- pitches %>%  
  mutate(prop = decisions/seen)
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 4. Calculate proportion of pitches requiring decision
- R code:
 - `mutate()`: Adds new variable

```
pitches <- pitches %>%  
  mutate(prop = decisions/seen)
```

1. PITCHES SEEN VS. DECISIONS MADE

- Step 4. Calculate proportion of pitches requiring decision

```
(pitches <- pitches %>%  
  mutate(prop = decisions/seen))
```

```
## # A tibble: 2,468 × 4
```

##		gameday_link	seen	decisions	prop
##		<chr>	<int>	<int>	<dbl>
## 1		gid_2016_04_03_chnmlb_anamlb_1	252	124	0.4920635
## 2		gid_2016_04_03_nynmlb_kcamlb_1	291	150	0.5154639
## 3		gid_2016_04_03_slnmlb_pitmlb_1	285	145	0.5087719
## 4		gid_2016_04_03_tormlb_tbamlb_1	276	136	0.4927536
## 5		gid_2016_04_04_chamlb_oakmlb_1	292	153	0.5239726
## 6		gid_2016_04_04_chnmlb_anamlb_1	297	135	0.4545455
## 7		gid_2016_04_04_colmlb_arimlb_1	362	158	0.4364641
## 8		gid_2016_04_04_lanmlb_sdnmlb_1	319	165	0.5172414
## 9		gid_2016_04_04_minmlb_bamlb_1	278	136	0.4892086

1. PITCHES SEEN VS. DECISIONS MADE

- Step 5. Calculate simple descriptive statistics

```
(pitch_summs <- pitches %>%  
  summarize(m_pitches = mean(seen),  
            sd_pitches = sd(seen),  
            m_calls = mean(decisions),  
            sd_calls = sd(decisions),  
            m_prop = mean(prop),  
            sd_prop = sd(prop)))
```

```
## # A tibble: 1 × 6  
##   m_pitches sd_pitches m_calls sd_calls m_prop sd_prop  
##   <dbl>      <dbl>    <dbl>    <dbl>    <dbl>    <dbl>  
## 1    294.485    40.32311 148.1896    22.9948 0.5028475 0.03240739
```

UMPIRE ACCURACY

- Check out `umpire_accuracy.R` in my GitHub Repo for this talk
- Overall, umpires are quite accurate

<i>M</i>	<i>SD</i>	<i>SEM</i>	95% CI
0.94	0.24	0.05	[0.84, 0.98]

UMPIRE ACCURACY

- Here's a plot of the cumulative accuracy for MLB umpires over the season


QUESTIONS?


CONTACT DETAILS

Aaron R. Baggett, Ph.D.

Assistant Professor of Psychology
University of Mary Hardin-Baylor

 **abaggett@umhb.edu**

 (254) 295-4553

 @aaron_baggett