

Machine Learning Engineer Nanodegree

Capstone Proposal

Aaron Balson Caroltin J
August 2019

Proposal

Domain Background

Imagine being able to detect blindness before it happened.

Millions of people suffer from [diabetic retinopathy](#), the leading cause of blindness among working aged adults. Aravind Eye Hospital in India hopes to detect and prevent this disease among people living in rural areas where medical screening is difficult to conduct. Successful entries in this [Kaggle](#) competition will improve the hospital's ability to identify potential patients. Further, the solutions will be spread to other Ophthalmologists through the [4th Asia Pacific Tele-Ophthalmology Society \(APTOS\) Symposium](#).

My personal motivation for investigating this problem domain is double fold – to get a taste of these competitions to increase my knowledge which may also contribute a local hospital to serve the community better. The symposium is planned on Sept 22-23 at my city Chennai, which is a good opportunity to meet and discuss with winners/experts.

Problem Statement

Currently, Aravind technicians travel to these rural areas to capture images and then rely on highly trained doctors to review the images and provide diagnosis. The accuracy of such screenings by interns and juniors can vary significantly with one study found a 49 percent error rate¹.

Their goal is to scale their efforts through technology; to gain the ability to automatically screen images for disease and provide information on how severe the condition may be, as accurately as possible. Here the problem is quantified as classifying the correct stage of Retinopathy and one relevant solution is to use image classification model to predict and assist humans with high accuracy.

Datasets and Inputs

We will use the datasets provided by Aravind Hospital itself at Kaggle's competition [data page](#), so they are highly relevant to our problem. It was collected over an extended period of time from different clinics and classified by doctors.

- train.csv - the training labels (has id_code, diagnosis)
 - test.csv - the test set (has id_code)
 - sample_submission.csv - (has id_code, diagnosis)
 - train.zip - the training set images
 - test.zip - the public test set images
- train=3662, test=1928 entries in total

Images are known to have noise, variance in resolution, size & scale, over/under exposed which are challenges to be taken care during pre-processing.

Solution Statement

Using Convolutional Neural Network Image classification model with DenseNet Architecture² we can create high precision models required for medical domain to quickly train and accurately identify the 5 classes of diagnosis

0 - No DR

1 - Mild

2 - Moderate

3 - Severe


4 - Proliferative DR

We will be using the free kernel from Kaggle workspace to experiment. We will use transfer learning to expediate training with DenseNet (over Standard ConvNet or ResNet) because the network can be thinner and compact as a result which also has a higher computational and memory efficiency (to run within time limits).

Benchmark Model

Doctor/manual intervention for screening can be costly and junior/intern classification results only around 50-60% accuracy. Competition is scored based on *quadratic weighted kappa* and our first aim is to achieve a public score matching or exceeding 60% on complete test data (given dataset + secret dataset). A similar competition³ on retinopathy was run 4 years ago in Kaggle which had the winning score of 84%. Since

this year competition spans from June-Sept and the highest score in leaderboard is already around 84% (as on today), it will be reasonable to *aim between 60-70%* in limited time (which is also the [median rank](#) for this year, as shown below).



Evaluation Metrics

Submissions are scored based on the *quadratic weighted kappa*, which measures the agreement between two ratings. This metric typically varies from 0 (random agreement between raters) to 1 (complete agreement between raters). In the event that there is less agreement between the raters than expected by chance, this metric may go below 0. The quadratic weighted kappa is calculated between the scores assigned by the human rater and the predicted scores.

Images have five possible ratings, 0,1,2,3,4. Each image is characterized by a tuple (e,e) , which corresponds to its scores by *Rater A* (human) and *Rater B* (predicted). The quadratic weighted kappa is calculated as follows. First, an $N \times N$ histogram matrix O is constructed, such that O corresponds to the number of images that received a rating i by A and a rating j by B . An N -by- N matrix of weights, w , is calculated based on the difference between raters' scores:

An N -by- N histogram matrix of expected ratings, E , is calculated, assuming that there is no correlation between rating scores. This is calculated as the outer product between each rater's histogram vector of ratings, normalized such that E and O have the same sum.

Project Design

1. Setup kernel and download/import required packages.
 2. Load given dataset and understand its format.
 3. Exploratory data analysis on csv and images.
 4. Perform pre-processing, resizing/rescaling to match that of ImageNet (224x224) as we intend to use DenseNet (which was trained on ImageNet) for transfer learning.
 5. Perform data augmentation using Data Generator since training set is small.
 6. Use Multilabel instead of multiclass classification. Eg: represent class 3 as [1,1,1,0,0] instead of [0,0,1,0,0] by encompassing all previous classes (better kappa scoring)
 7. Adopt DenseNet-121 Architecture and append our dense and output layers at end their conv layers.
 8. Plot training vs validation loss to inspect overfitting
 9. Kappa scoring, fine tune hyperparameters and optimizers
 10. Test the model with given data set.
 11. Create submission file with results and submit to Kaggle.
 12. Wait for public score and aim to improve.
-

Citations & References

- 1 <https://www.sciencedaily.com/releases/2019/03/190318141135.htm>
 - 2 <https://towardsdatascience.com/review-densenet-image-classification-b6631a8ef803>
 - 3 <https://www.kaggle.com/c/diabetic-retinopathy-detection/leaderboard>
- <http://2019.asiateleophth.org/>
- <https://aravind.org/vision-mission/>