

Data

- int
- float
- double
- char
- string

Expressions

- I/O expressions
- Arithmetic expressions

Control Flow

- Sequential

Data

- int
- float
- double
- char
- string
- bool

Expressions

- I/O expressions
- Arithmetic expressions

Control Flow

- Sequential

The `bool` Data Type

Boolean values are used to represent true or false conditions.

Boolean values are `True` and `False`.

Boolean values are case-sensitive.

Boolean values are used in conditional statements.

Boolean values are used in loops.

Boolean values are used in functions.

Boolean values are used in expressions.

Boolean values are used in comparisons.

The `bool` Data Type

Kind of data:

The `bool` Data Type

Kind of data: Truth value (True/False)

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals:

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators:

Not

Not

p	not p
True	False
False	True

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: `!`

Not

p	not p
True	False
False	True

```
int main() {  
    bool b1, b2, b3;  
  
    return 0;  
}
```


Not

p	not p
True	False
False	True

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
  
    return 0;  
}
```

Not

p	not p
True	False
False	True

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
    b2 = !b1;  
  
    return 0;  
}
```

Not

p	not p
True	False
False	True

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
    b2 = !b1;  
    b3 = !false;  
  
    return 0;  
}
```

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: !

And

And

p	q	p and q
True	True	True
True	False	False
False	True	False
False	False	False

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: `!`, `&&`

And

p	q	p and q
True	True	True
True	False	False
False	True	False
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    return 0;  
}
```


And

p	q	p and q
True	True	True
True	False	False
False	True	False
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
    b2 = false;  
  
    return 0;  
}
```

And

p	q	p and q
True	True	True
True	False	False
False	True	False
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
    b2 = false;  
    b3 = b1 && b2;  
  
    return 0;  
}
```

And

p	q	p and q
True	True	True
True	False	False
False	True	False
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = true;  
    b2 = false;  
    b3 = b1 && b2;  
    b3 = b1 && !b2;  
  
    return 0;  
}
```

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: `!`, `&&`

Or

Or

p	q	p or q
True	True	True
True	False	True
False	True	True
False	False	False

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: `!`, `&&`, `||`

Or

p	q	p or q
True	True	True
True	False	True
False	True	True
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = false;  
  
    return 0;  
}
```


Or

p	q	p or q
True	True	True
True	False	True
False	True	True
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = false;  
    b2 = b1 || !b1;  
  
    return 0;  
}
```

Or

p	q	p or q
True	True	True
True	False	True
False	True	True
False	False	False

```
int main() {  
    bool b1, b2, b3;  
  
    b1 = false;  
    b2 = b1 || !b1;  
    b3 = b2 && (b1 || true);  
  
    return 0;  
}
```

The `bool` Data Type

Kind of data: Truth value (True/False)

Inner representation:

- Each `bool` data uses 1 byte (8 bits)
- False is represented by a byte of 0s
True is any non-zero value

C++ literals: `true`, `false`

Boolean Operators: `!`, `&&`, `||`

Data

- int
- float
- double
- char
- string
- bool

Expressions

- I/O expressions
- Arithmetic expressions

Control Flow

- Sequential

Data

- int
- float
- double
- char
- string
- bool

Expressions

- I/O expressions
- Arithmetic expressions
- Boolean expressions

Control Flow

- Sequential

Boolean Expressions

Boolean Expressions

Atomic Boolean Expressions:

Compound Boolean Expressions:

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`

Compound Boolean Expressions:

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

```
int main() {
    bool b;

    return 0;
}
```

```
int main() {  
    bool b;  
  
    b = true;  
  
    return 0;  
}
```

```
int main() {  
    bool b;  
  
    b = true;  
    b = (true && !b) ;  
  
    return 0;  
}
```

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`
- Arithmetic expressions compared with relational operators (`<`, `>`, `<=`, `>=`, `==`, `!=`)

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

```
int main() {  
    bool b;  
  
    b = true;  
    b = (true && !b) ;  
  
    return 0;  
}
```

```
int main() {  
    bool b;  
    int x;  
  
    b = true;  
    b = (true && !b) ;  
  
    x = 3;  
  
    return 0;  
}
```



```
int main() {  
    bool b;  
    int x;  
  
    b = true;  
    b = (true && !b) ;  
  
    x = 3;  
    b = (x < 5) ;  
  
    return 0;  
}
```

```
int main() {  
    bool b;  
    int x;  
  
    b = true;  
    b = (true && !b) ;  
  
    x = 3;  
    b = (x < 5) ;  
    b = (x >= 0) && (x < 5) ;  
  
    return 0;  
}
```

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`
- Arithmetic expressions compared with relational operators (`<`, `>`, `<=`, `>=`)

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`
- Arithmetic expressions compared with relational operators (`<`, `>`, `<=`, `>=`, `==`)

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

Boolean Expressions

Atomic Boolean Expressions:

- The `bool` literals – `true`, `false`
- Arithmetic expressions compared with relational operators (`<`, `>`, `<=`, `>=`, `==`, `!=`)

Compound Boolean Expressions:

Simple boolean expressions combined with boolean operators (`!`, `&&`, `||`)

```
int main() {  
    bool b;  
    int x;  
  
    b = true;  
    b = (true && !b) ;  
  
    x = 3;  
    b = (x < 5) ;  
    b = (x >= 0) && (x < 5) ;  
  
    return 0;  
}
```

```
int main() {  
    bool b;  
    int x;  
  
    b = true;  
    b = (true && !b) ;  
  
    x = 3;  
    b = (x < 5) ;  
    b = (x >= 0) && (x < 5) ;  
    b = (x == 3) || (x == 4) ;  
  
    return 0;  
}
```