Hazard Analysis The Nursery Poject

Team #, Team Name Student 1 name Student 2 name Student 3 name Student 4 name

Table 1: Revision History

Date	$\mathbf{Developer(s)}$	Change
	Name(s) Name(s)	Description of changes Description of changes
•••	•••	•••

Contents

1	Introduction	1
2	Scope and Purpose of Hazard Analysis	1
3	System Boundaries and Components	1
4	Critical Assumptions	2
5	Failure Mode and Effect Analysis	3
6	Safety and Security Requirements	5
7	Roadmap	5

1 Introduction

This document is the hazard analysis of the Pot-Pulator. This machine will be built for Sheridan Nurseries, filling trays with pots, preparing them to be populated with soil and seeds, to reduce the manual labour of the workers at the farm. The hazard analysis will consider each part of the Pot-Pulator, including the respective tray and pot droppers, the sensor verification section, and the conveyer belt.

The definition of a hazard used in this document is any issue or property in the Pot-Pulator that will cause a risk to the ideal result of the system. In this system, most hazards will be concerning safety of the workers collecting the trays at the end of the conveyer, and the effectiveness of the verification system.

This document will include the Scope and Purpose of Hazard Analysis, System Boundaries and Components, Failure Mode and Effect Analysis, and Safety & Security Requirements.

2 Scope and Purpose of Hazard Analysis

The scope of this document is to identify the components of the Pot-Pulator that could have harmful consequences to the users or the results and reduce each risk to a level where the overall system will be safe and acceptable.

Hazards will be analyzed based on research of similar systems, and any specific hazards occurring throughout the development process of the machine.

3 System Boundaries and Components

The hazard analysis will be conducted based on the Pot-Pulator, which is restricted to the components below.

- 1. Conveyer belt
- 2. Tray allocation
- 3. Pot dropping
- 4. Verification system

The hazard analysis will be based on these critical elements of the system. The system boundary includes a conveyer belt moving the system along, tray allocation to place the trays on the conveyer, a pot dropper to place the pots into the trays, and a verification system to confirm the correct placement of the components.

The conveyer belt will be controlled by a sensor based on the other components. At the end of the process, the conveyer belt will bring the completed trays to the end of the line, to be collected by a worker. This will all be accounted for in the hazard analysis.

4 Critical Assumptions

There are no critical assumptions for this system.

5 Failure Mode and Effect Analysis

Component	Failure Mode	Effect of Failure	Cause of failure	Recomended action	SR	Ref
Tray Dispensing	Tray is not dispensed	Machine is unable to continue operation, tray may be damaged	 (a) Tray stack software/hardware failure (b) Tray dispenser software/hardware failure (c) Parts failure 	 (a) Sensor will recognize if tray has not been dispensed, error message will be displayed and operator will be notified. (b) Refer to H1-1a (c) Refer to H1-1a 		H1-1
	Trays placed incorrectly on conveyor	Tray is unable to move forward on conveyor, pot dispenser is unable to place pots correctly. May damage pots/trays	Tray dispenser soft- ware/hardware failure	Guiding rods will be placed on the conveyor to centre trays into correct position. If trays are unable to move forward, error message will be displayed and operator will be notified.		H1-2

		Trays dispensed are stacked, 2+ trays dispensed at once	Tray storage becomes out of sync with pot storage, may damage pots/trays	 Parts failure Trays loaded incorrectly 	1. Sensor will recognize if multiple trays have been dispensed, error message will be displayed and operator will be notified	H1-3
					2. Operator will be trained to properly load trays into ma- chine"	
4		Tray dispenser damages tray	Tray is unable to hold pots and be sent for distribu- tion (will depend on sever- ity of damage to tray)	Quality issue in trays	Operator will be trained to perform 60 second vi- sual check of Pot-pulator, trays, and pots before each refill to note and eliminate trays with any noticeable defects	H1-4
	Pot Dispenser	Pots are not dispensed	Tray will be dispensed empty	Software/hardware failure	Sensor post pot dispensing will sense that the tray has not been populated, error message will be displayed and operator will be notified	H2-1

6 Safety and Security Requirements

[Newly discovered requirements. These should also be added to the SRS. (A rationale design process how and why to fake it.) —SS]

7 Roadmap

There were some new non-functional requirements (safety and security) discovered, after performing hazard analysis on the system. The safety and security requirements that will be implemented in the future beyond the timeline of the capstone are SR7, SR10, and SR12. These requirements will be apart of a future implementation due to time-related and financial reasons. The remaining non-functional requirements related to safety and security will be implemented within the timeline the capstone project.