LAB WORKSHEET

Tera Term Console

A Tera Term-style serial console on the lab PC. Pick the Router or the Switch tab and configure it from scratch with the full emulated IOS command set. The two devices are cabled Gi0/0/0 ↔ Gi1/0/1.

Getting started

1. Choose the **Router (R1)** or **Switch (SW1)** tab — each opens its own console inside the monitor.
2. Type `?` for help in the current mode and press **Tab** to complete commands.
3. **Power cycle** reboots the device; **Erase & restart** wipes its configuration.

Router (R1) — bring the link up

```
enable
configure terminal
 hostname R1
 interface g0/0/0
  ip address 10.0.0.1 255.255.255.252
  no shutdown
 end
show ip interface brief
```

Switch (SW1) — basics & a VLAN

```
enable
configure terminal
 hostname SW1
 vlan 10
  name STAFF
 interface g1/0/2
  switchport mode access
  switchport access vlan 10
 interface vlan 1
  ip address 10.0.0.2 255.255.255.252
  no shutdown
 end
show vlan brief
```

Save & verify

```
copy running-config startup-config
show running-config
show version
```

Try: set an `enable secret`, a `banner motd`, and `no ip domain-lookup` on both devices. Use ↑/↓ to recall previous commands and Ctrl+Z to jump back to privileged mode.