

Samsung SL-45A for Industrial & General Manufacturing

Heavy CNC lathe purpose-built for forged blanks, rough shafts, drive mandrels, and structural stock. This paper covers what the machine does, the industrial & general manufacturing parts we produce with it, the alloys we run, the tolerances and finishes industrial & general manufacturing buyers expect, and the documentation package.

14" OD × 96" L max turning
ENVELOPE

±0.0005" routine after roughing
TOLERANCE

1994
SINCE

Same-week / rig-down direct
RESPONSE



Hammer of Forge · 14" OD × 96" L max turning · heavy-duty CNC lathe for rough stock

PUBLISHED

January 15, 2026

LAST UPDATED

2026-01-15

FORMAT

Web + PDF

READ TIME

~6 min

Executive summary

Machine: Samsung SL-45A/2200 (shop nickname: *Hammer of Forge*). heavy-duty CNC lathe for rough stock at B&R Productions, running from our New Waverly, Texas shop.

Application: Heavy CNC lathe purpose-built for forged blanks, rough shafts, drive mandrels, and structural stock for Industrial & General Manufacturing customers — Industrial equipment OEMs, custom machinery builders, pump and valve manufacturers outside oilfield, food and pharma equipment suppliers, mining and heavy-equipment operators, reverse-engineering customers, sustainment for out-of-production industrial equipment.

Envelope: 14" OD × 96" L max turning. **Tolerance:** ±0.0005" routine on critical features. **Traceability:** Material by heat and lot on every job.

The machine, in context

Hammer of Forge is the machine that takes ugly starting material and makes it round, straight, and to size. Forged blanks with scale and skin, rough saw-cut billets, oversized bar stock — this machine has the rigidity and horsepower to get through the roughing pass without chatter and without walking the part. Most of what our other lathes finish, this one starts.

Why Hammer of Forge for Industrial work

Industrial work arrives as whatever the customer has — saw-cut billet, oversized bar, castings, forgings with scale. Hammer of Forge is built to get through that stage without drama: 14" OD × 96", 6.5" bar capacity, torque at the low end of a 3-speed gearbox.

What this looks like on a real part

A cast iron or steel casting is an interrupted cut into a surface with sand inclusions and a hard skin, and the first pass is genuinely abusive to tooling. The same rule applies as with forgings: get under the skin in one deep pass rather than skimming it, because the skin is where the abrasive inclusions live. A tool traversing that layer wears far faster than one cutting the clean material underneath.

When this is the wrong machine

Roughing machine. Industrial parts with tight finish requirements get finished on a Hi-Eco cell afterwards.

Full specifications

Model	Samsung SL-45A/2200 ("Hammer of Forge")
Type	Heavy-duty CNC turning center — Samsung SL-45A platform
Max turning capacity	14" OD × 96" L (B&R working spec)
Platform max swing	29.72" over bed; 24.8" swing over cross slide
Platform max machining Ø	26.7"
Platform max length	118" between centers
Bar capacity	6.5" through spindle
Spindle speed	2,000 RPM max (3-speed gearbox)
Main motor	50 HP continuous / 40 HP rated
Tailstock	Programmable #5 MT (full-length support for slender parts)
Turret	12-position
Tolerance capability	±0.0005" routine after roughing; excellent for finish passes
Materials	Forgings, castings, bar stock — 4140/4340, stainless, Inconel, Duplex, 17-4 PH

Values marked "platform" reflect the machine manufacturer's published spec range for this platform family; B&R's working spec is what we quote on this specific unit.

Who this serves in Industrial & General Manufacturing

Typical buyer: Industrial equipment OEMs, custom machinery builders, pump and valve manufacturers outside oilfield, food and pharma equipment suppliers, mining and heavy-equipment operators, reverse-engineering customers, sustainment for out-of-production industrial equipment.

What's hard about industrial & general manufacturing work: Legacy parts with no OEM support, one-off replacement components, small-lot production runs, materials that don't fit standard shop capabilities, and tight lead times on repair work where a down-machine is losing money by the day.

Typical Industrial & General Manufacturing parts we produce on Hammer of Forge

- Rough-turning of industrial forgings and castings
- Large-diameter industrial shaft roughing
- Structural round parts starting from forgings
- Pump body blanks and roughing pass
- Roughing to prep parts for finish on precision machines

Above list is representative; if your part isn't shown, call and ask — most oilfield / aerospace / defense / industrial turned or milled work fits somewhere in the shop.

Alloys we run for Industrial & General Manufacturing

Standard range: Stainless (304, 316, 17-4 PH) · Tool steels · 4140 / 4340 · Brass · Bronze · Aluminum · Cast iron · Specialty alloys per customer requirement.

Industrial work covers the widest alloy range because the applications are the widest. Food and pharma often specify 316L or 17-4 PH; mining and heavy equipment specify tool steels and 4140/4340; pump manufacturers outside oilfield use everything from bronze bushings to stainless impellers. We work with the customer's spec sheet — if you tell us the alloy, we'll tell you honestly whether we can machine it and how quickly.

What "we run these weekly" means: we stock or reliably source the common alloys in the industry's typical spec range. Sharp tooling, proven feeds and speeds, and process control specific to each alloy family. Your part is not the one we're experimenting on.

How we machine it — our 5-step process

This is the process B&R runs on every job, industrial & general manufacturing or otherwise. The specifics of feeds, speeds, and tooling shift by alloy and machine; the discipline is universal.

- 1 Material verification.** Every job starts with material traceability. Heat and lot numbers documented against the mill test report. For customer-supplied material, we verify against the CofC before touching the stock.
- 2 First-article layout.** Stock is measured and laid out before any cutting starts. Concentricity, roundness, and squareness of the starting material established; if the stock is out of tolerance we call the customer before wasting time on a bad blank.
- 3 Roughing with process control for the alloy.** Feeds, speeds, and coolant strategy set for the specific alloy family — sharp coated carbide (or PCD for high-volume Ti Grade 5), positive rake, high-pressure through-tool coolant on 2507 and Inconel to control cutting temperature. Interrupted cuts get extra attention because they cycle heat into the workpiece.
- 4 Finish pass to spec.** Finish pass with a fresh insert, controlled DOC, and measured surface-finish targets. Critical features (bore concentricity, seat grooves, sealing surfaces) are held tighter than most job-shop lathes can offer.
- 5 CMM verification + documentation.** Every critical dimension CMM-verified. First-article report generated. Certificate of conformance issued with delivery. If your quality group needs a documentation package beyond that, tell us with the RFQ and we'll be straight about what we can and can't produce in-house.

Tolerance and finish expectations in Industrial & General Manufacturing

± 0.0005 " routine on critical features. Industrial applications range from precision (pump seal areas, close-fit bushings) to structural (mining and heavy-equipment brackets); we adjust the inspection plan to what the part actually needs. Surface finish measured on parts where finish drives function.

Documentation and quality workflow

Documentation calibrated to customer requirement. Material traceability standard for critical parts. Certificates of conformance issued with delivery. NDAs on request for proprietary designs or reverse-engineered legacy parts.

Response time and emergency work

Down-machine and production-critical work prioritized. Lead times honestly quoted — no false promises. For legacy reverse-engineering, we typically confirm feasibility on the first phone call. Call (936) 291-7827.

How we compare

Compared to sourcing a new OEM part: we're often faster and cheaper for one-offs and small runs, and for legacy parts where the OEM has moved on we're often the only realistic option. Compared to a cheapest-bidder job shop: we hold tolerance, document material, and don't ruin the part.

Working with B&R Productions

New customer or existing, the process starts the same way: call (936) 291-7827 or send a print through the quote form. Prints are accepted as PDF, STEP, IGES, DWG, or DXF; if you only have a sample part, we reverse-engineer routinely. NDAs on request, and prints stay in-shop rather than going out to third-party vendors. Note for defense and aerospace buyers: B&R is not ITAR- or AS9100-registered, so export-controlled prints and AS9100 flow-down programs need a registered shop — we'll tell you that on the first call, not after the PO.

Quotes typically come back within 24 hours for standard work, same-day for repeat customers on stocked materials, and near-immediately by phone for emergency and rig-down situations. Lead times are quoted honestly — we don't promise Wednesday and deliver next month.

Frequently asked questions

8 questions covering the Samsung SL-45A platform and Industrial & General Manufacturing work. Also indexed as FAQ schema for AI answer engines.

What's the Samsung SL-45A designed for?

Heavy roughing. Forged blanks with scale and skin, rough saw-cut billets, oversized bar stock — this machine has the rigidity and horsepower (50 HP continuous / 40 HP rated, 3-speed gearbox) to get through the roughing pass without chatter or walking the part.

What's the max envelope on the SL-45A?

14" OD × 96" L is B&R's working spec. Platform max is 26.7" machining diameter × 118" between centers with 29.72" swing over bed. Bar capacity: 6.5" through spindle.

What tailstock does the SL-45A carry?

Programmable #5 MT tailstock — full-length support for slender long parts. 12-position turret.

What kind of industrial customers does B&R work with?

Industrial equipment OEMs, custom machinery builders, non-oilfield pump and valve manufacturers, food and pharma equipment suppliers, mining and heavy-equipment operators, and any customer who needs a legacy or reverse-engineered part made right.

Do you machine one-off replacement parts?

Yes — a lot of our industrial work is exactly this. Send the sample or drawing; if the material is on the shelf, we're often faster than the OEM. Reverse-engineered legacy parts across almost every sector.

What materials do you run for industrial work?

Full range — stainless (304, 316, 17-4 PH), tool steels, 4140/4340, brass, bronze, aluminum, cast iron, and specialty alloys per customer requirement. If you need something unusual, ask.

Do you offer emergency turnaround on down-machine parts?

Yes for repeat customers with material on the shelf. Same-day and next-day realistic when we already have the alloy. Call (936) 291-7827 and describe what's down.

Can you do small-batch production or is B&R just one-offs?

Both. Prototype and small-batch through repeat production. Small production runs where a big shop's minimum order would kill the economics are exactly where we fit.

Related white papers

[See all machine × industry white papers →](#)

Ready to talk about your Industrial & General Manufacturing work?

Send us a print or a sample photo and specs. Emergencies: call direct and say "rig-down."

Published by B&R Productions — a precision CNC machining shop in New Waverly, Texas, in business since 1994. Serving oil & gas, aerospace, defense, and industrial customers across Texas and the Gulf Coast.

Written by the B&R Productions team. Machine specs verified against manufacturer data. Alloy and process notes reflect shop practice as of 2026-01-15.

[Samsung SL-45A/2200 overview](#) · [All white papers](#) · [Industrial & General Manufacturing industry page](#)