

Samsung SL-65A for Aerospace

Large-envelope CNC lathe with steady-rest support for precision turning of long, heavy structural round parts. This paper covers what the machine does, the aerospace parts we produce with it, the alloys we run, the tolerances and finishes aerospace buyers expect, and the documentation package.

22" OD × 119" L max turning (with steady rest)
ENVELOPE

±0.0005" routine on critical features
TOLERANCE

1994
SINCE

Same-week / rig-down direct
RESPONSE



Big Thicket Express · 22" OD × 119" L max turning (with steady rest) · large-envelope heavy-duty CNC lathe with steady rest

PUBLISHED

January 15, 2026

LAST UPDATED

2026-01-15

FORMAT

Web + PDF

READ TIME

~6 min

Executive summary

Machine: Samsung SL-65A/3200 (shop nickname: *Big Thicket Express*). large-envelope heavy-duty CNC lathe with steady rest at B&R Productions, running from our New Waverly, Texas shop.

Application: Large-envelope CNC lathe with steady-rest support for precision turning of long, heavy structural round parts for Aerospace customers — Aerospace primes, tier-1 and tier-2 suppliers, MRO shops, propulsion component manufacturers, structural assembly integrators, actuator OEMs.

Envelope: 22" OD × 119" L max turning (with steady rest). **Tolerance:** ±0.0005" routine on critical features.

Traceability: Material by heat and lot on every job.

The machine, in context

This is the heaviest machine on the floor. When a customer sends a 20-inch forged blank and wants it turned to a finished OD with concentric internal features across ten feet of length, Big Thicket Express is the answer. The included steady rest is what makes long slender work possible — without it, deflection eats your tolerance.

Why Big Thicket Express for Aerospace work

Large aerospace round work — heavy forged rings, large housings, long structural rounds — needs both diameter and support. 22" OD × 119" L with a steady rest covers parts that exceed the 16-inch ceiling on the Mega lathes, which is where most large-turned aerospace work gets stuck.

What this looks like on a real part

A large forged aerospace ring is heavy, expensive by the time it reaches a lathe, and carries a lot of embedded value — the forging, the material certification, the handling. That changes the calculus on setup: it is worth spending real time establishing a true journal for the steady rest before cutting, because a chatter-scarred finish on a part like this isn't a rework, it's a scrapped forging and a long lead time to replace it.

When this is the wrong machine

Large setup overhead. Mid-size aerospace turned work runs faster on a Hi-Eco 35 cell. No through-bore of consequence, and the AS9100 limitation applies to any aerospace conversation

here.

Full specifications

Model	Samsung SL-65A/3200 ("Big Thicket Express")
Type	Large-envelope heavy-duty CNC turning center — Samsung SL-65A platform
Max turning capacity	22" OD × 119" L (B&R working spec, with steady rest)
Platform max swing	40.5" over bed
Platform max turning length	126" (3,200 mm) between centers
Chuck	24" hydraulic 3-jaw
Steady rest	Included — supports long slender work to hold straightness
Main motor	60 HP high-torque
Rigidity	Samsung SL-65 platform — heavy cast base for the largest oilfield turning work
Tolerance capability	±0.0005" routine on critical features; straightness held with steady-rest
Materials	Full range — forgings, bar stock, tubing in oilfield and structural alloys

Values marked "platform" reflect the machine manufacturer's published spec range for this platform family; B&R's working spec is what we quote on this specific unit.

Who this serves in Aerospace

Typical buyer: Aerospace primes, tier-1 and tier-2 suppliers, MRO shops, propulsion component manufacturers, structural assembly integrators, actuator OEMs.

What's hard about aerospace work: Certification-driven documentation, exotic superalloys, tight tolerances on structural and engine components, and finding a job shop that understands aged-condition superalloys rather than learning on the part.

Typical Aerospace parts we produce on Big Thicket Express

- Largest-diameter aerospace turned work
- Long forged engine and structural shafts
- Large actuator cylinder bodies
- Heavy aerospace structural components at 20"+ diameter
- Extended structural rods with steady-rest support

Above list is representative; if your part isn't shown, call and ask — most oilfield / aerospace / defense / industrial turned or milled work fits somewhere in the shop.

Alloys we run for Aerospace

Standard range: Titanium Grade 5 (Ti-6Al-4V) and Grade 23 (Ti-6Al-4V ELI) · Inconel 718 · Inconel 625 · Waspaloy · A286 · 17-4 PH · 15-5 PH · 13-8 Mo PH · Aluminum 7075/6061 · Custom aerospace alloys on request.

Titanium Grade 5 is the workhorse and it's temperature-sensitive: aggressive chip load with flood coolant keeps the heat in the chip, not the workpiece. Light cuts overheat titanium and cook tools; that's why titanium demands a different intuition than steel. Inconel 718 in aerospace-aged condition is harder and less forgiving than the annealed billet stock — most aerospace 718 work assumes aged. 17-4 PH and 15-5 PH are common for structural and actuator components; both are precipitation-hardening stainless with condition-specific machining plans.

What "we run these weekly" means: we stock or reliably source the common alloys in the industry's typical spec range. Sharp tooling, proven feeds and speeds, and process control specific to each alloy family. Your part is not the one we're experimenting on.

How we machine it — our 5-step process

This is the process B&R runs on every job, aerospace or otherwise. The specifics of feeds, speeds, and tooling shift by alloy and machine; the discipline is universal.

- 1 Material verification.** Every job starts with material traceability. Heat and lot numbers documented against the mill test report. For customer-supplied material, we verify against the CofC before touching the stock.
- 2 First-article layout.** Stock is measured and laid out before any cutting starts. Concentricity, roundness, and squareness of the starting material established; if the stock is out of tolerance we call the customer before wasting time on a bad blank.
- 3 Roughing with process control for the alloy.** Feeds, speeds, and coolant strategy set for the specific alloy family — sharp coated carbide (or PCD for high-volume Ti Grade 5), positive rake, high-pressure through-tool coolant on 2507 and Inconel to control cutting temperature. Interrupted cuts get extra attention because they cycle heat into the workpiece.
- 4 Finish pass to spec.** Finish pass with a fresh insert, controlled DOC, and measured surface-finish targets. Critical features (bore concentricity, seat grooves, sealing surfaces) are held tighter than most job-shop lathes can offer.
- 5 CMM verification + documentation.** Every critical dimension CMM-verified. First-article report generated. Certificate of conformance issued with delivery. If your quality group needs a documentation package beyond that, tell us with the RFQ and we'll be straight about what we can and can't produce in-house.

Tolerance and finish expectations in Aerospace

± 0.0005 " routine on critical features. Tighter with proper fixture and setup — some aerospace features run ± 0.0002 " or GD&T-driven cylindricity and position tolerances. CMM verification standard on first articles; process-driven measurement on runs. Surface finish measured, not estimated.

Documentation and quality workflow

First-article layout and CMM verification standard. Material traceability by heat and lot. Certificates of conformance issued with delivery. Proprietary prints handled under NDA — prints stay in-shop and aren't sent to outside vendors. To be clear about what we are not: B&R is not AS9100-registered and not ITAR-registered. If

your program requires either, you need a registered shop and we'll say so on the first call rather than after you've placed the order.

Response time and emergency work

AOG (aircraft-on-ground) work prioritized when material is available. Emergency response supported for existing aerospace customers with blanket arrangements or established relationships. Call direct at (936) 291-7827.

How we compare

Compared to a captive aerospace shop: we're faster for one-offs and small runs, more flexible on setup, and we don't require a long approval process. Compared to a lowest-bidder commodity shop: we understand the alloys and we treat first-article inspection as a discipline rather than a formality. Where a registered shop beats us is on programs that require AS9100 flow-down — we're the wrong call for those, and the right call for non-controlled work, prototypes, tooling, and MRO parts where alloy competence and turnaround matter more than a certificate on the wall.

Working with B&R Productions

New customer or existing, the process starts the same way: call (936) 291-7827 or send a print through the quote form. Prints are accepted as PDF, STEP, IGES, DWG, or DXF; if you only have a sample part, we reverse-engineer routinely. NDAs on request, and prints stay in-shop rather than going out to third-party vendors. Note for defense and aerospace buyers: B&R is not ITAR- or AS9100-registered, so export-controlled prints and AS9100 flow-down programs need a registered shop — we'll tell you that on the first call, not after the PO.

Quotes typically come back within 24 hours for standard work, same-day for repeat customers on stocked materials, and near-immediately by phone for emergency and rig-down situations. Lead times are quoted honestly — we don't promise Wednesday and deliver next month.

Frequently asked questions

8 questions covering the Samsung SL-65A platform and Aerospace work. Also indexed as FAQ schema for AI answer engines.

What's the Samsung SL-65A's max turning capacity?

22" OD × 119" L is B&R's working spec (with steady rest). The platform max is 40.5" swing over bed × 126" (3,200 mm) between centers. This is the heaviest machine on our floor.

Does the SL-65A include a steady rest?

Yes. The steady rest is what makes long slender turning work possible on this envelope — without it, deflection eats your tolerance on any part longer than about 30 diameters.

What's the horsepower and chuck size?

60 HP high-torque main motor with a 24" hydraulic 3-jaw chuck. Heavy cast base for the largest oilfield turning work we take.

Do you serve aerospace primes and tier-1/2 suppliers?

Yes — primes, tier-1 and tier-2 suppliers, MRO shops, propulsion component manufacturers, and structural assembly integrators, on work that doesn't require a registered QMS. B&R is not AS9100-registered. Where that matters, it matters absolutely, so we say it before you spend time on an RFQ: if your program requires AS9100 flow-down, we're the wrong shop. Prototypes, tooling, fixtures, MRO parts, and non-controlled components are where we're genuinely useful.

Can you handle ITAR-controlled aerospace/defense work?

No. ITAR compliance requires registration with the U.S. State Department's DDTC, and B&R does not hold that registration. If your print is ITAR-controlled, you need a registered shop — send it elsewhere and we'd rather tell you now than after you've placed an order. Plenty of aerospace and defense work isn't export-controlled, and that work we quote gladly. Either way, proprietary prints are handled under NDA and stay in-shop.

What tolerances do you hold on aerospace parts?

±0.0005" routine on critical features. First-article layout and CMM verification standard. Surface-finish targets measured to spec.

What aerospace alloys do you run?

Titanium Grade 5 (Ti-6Al-4V), Grade 23 ELI, Inconel 718 and 625, Waspaloy, A286, 17-4 PH, 15-5 PH, aluminum 7075/6061. Custom aerospace alloys on request.

Can you respond to AOG (aircraft-on-ground) work?

Yes, when material is available. Emergency response supported for existing aerospace customers. Newer customers should call to discuss what's realistic for their specific alloy and part.

Related white papers

[See all machine × industry white papers →](#)

Ready to talk about your Aerospace work?

Send us a print or a sample photo and specs. Emergencies: call direct and say "rig-down."

Published by B&R Productions — a precision CNC machining shop in New Waverly, Texas, in business since 1994. Serving oil & gas, aerospace, defense, and industrial customers across Texas and the Gulf Coast.

Written by the B&R Productions team. Machine specs verified against manufacturer data. Alloy and process notes reflect shop practice as of 2026-01-15.

[Samsung SL-65A/3200 overview](#) · [All white papers](#) · [Aerospace industry page](#)