

Math 210

Aaron Graybill

Problem Set 6

4/8/21

```
In [2]: import numpy as np
        from scipy.optimize import linprog
        import pandas as pd
```

Problem 1.

a.

I convert the problem to a single source problem:

Edges: $\mathcal{E} = \{(0, 1), (0, 2), (0, 4), (1, 2), (1, 3), (2, 3), (2, 4), (2, 5), (3, 4), (3, 5), (4, 5), (4, 6), (5, 4), (5, 6)\}$.

Fix the flow on $(0, 1), (0, 2), (0, 4)$ to 30, 6, and 4 respectively.

Let the currently unspecified constraint set be \mathcal{C} .

Maximize the flow into vertex 6, so $\max_{x \in \mathcal{C}} \{x_{46} + x_{56}\}$

We have the following constraint set:

$$\begin{aligned} x_{12} + x_{13} &= x_{01} \\ x_{23} + x_{24} + x_{25} &= x_{02} + x_{12} \\ x_{34} + x_{35} &= x_{13} + x_{23} \\ x_{45} + x_{46} &= x_{24} + x_{34} + x_{54} \\ x_{54} + x_{56} &= x_{25} + x_{35} + x_{45} \end{aligned}$$

```
In [3]: a_eq=np.array([
        [1,0,-1,-1,-1,0,0,0,0,0,0],
        [0,1,1,0,0,-1,-1,0,0,0,0],
        [0,0,0,1,0,1,0,-1,-1,1,0],
        [0,0,0,0,1,0,1,1,0,-1,-1]])
        print(a_eq)


        b_eq=np.zeros((4))
        print(b_eq)
        a_leq=np.identity(11)
        b_leq=[14,16,9,3,8,10,6,5,16,4,15]

        c=[0,0,0,0,0,0,0,0,-1,0,-1]

        linprog(c,A_ub=a_leq,b_ub=b_leq,A_eq=a_eq,b_eq=b_eq,method="simplex")
```

```
[[ 1  0 -1 -1 -1  0  0  0  0  0  0]
 [ 0  1  1  0  0 -1 -1  0  0  0  0]
 [ 0  0  0  1  0  1  0 -1 -1  1  0]
 [ 0  0  0  0  1  0  1  1  0 -1 -1]]
[0.  0.  0.  0.]
```

```
Out[3]: con: array([0., 0., 0., 0.])
        fun: -27.0
        message: 'Optimization terminated successfully.'
        nit: 15
        slack: array([3., 0., 9., 0., 0., 0., 0., 4., 0., 0., 4.])
        status: 0
        success: True
        x: array([11., 16., 0., 3., 8., 10., 6., 1., 16., 4., 11.])
```





$$q_1 = 10, q_2 = 8, q_3 = 6, q_4 = 3, x^*$$

$$\text{max flow} = 27$$

Problem 2.

The optimal flows are in the first chart and the process is in the second:



$$q_1 = 2, q_2 = 2, q_3 = 2, q_4 = 2, q_5 = 1, q_6 = 1$$

Problem 3.

```
In [4]: #used to make label names:
#source: geeksforgeeks.org/python-insert-the-string-at-the-beginning-of-all-items-in-a-list/
def prepend(list, str):

    # Using '% s'
    str += '% s'
    list = [str % i for i in list]
    return(list)
```

```

In [5]: import itertools

def create_eq_matrix(nvert,edgemat):

    A=np.zeros((nvert,(nvert**2))) #too large will shrink later,
                                     #but makes for easy indexing
    c=np.zeros(nvert**2) # ditto

    #loop over the edgemat, taking each path as an iterand
    for count, value in enumerate(edgemat[:,0:2]):

        col_num=(nvert)*(value[0])+(value[1]) # n columns from each vertex

        if (value[0]==0): #coming from source
            #Don't have to worry about constraint on sources
            A[value[1],col_num]=1
        elif (value[1]==(nvert-1)): #going to sink
            #dont have to worry about constraint on sink
            A[value[0],col_num]=-1
            c[col_num]=-1#Hey this is an important column, but it in the objective
        else: #intermediate
            A[value[1],col_num]=1
            A[value[0],col_num]=-1

    A=np.append(A,np.array([c]),axis=0) #add the row of cs

    #Name appropriately
    col_names=[] #create vector of names
    for i in itertools.product(np.arange(nvert),repeat=2): #all combos of indexes
        col_names += [str(i[0])+"",str(i[1])]
    row_names=prepend(np.arange(nvert),"V")
    row_names+="c" #add one final row name

    A=pd.DataFrame(A,index=row_names,columns=col_names)# put things into pd data

    # Remove unused rows and columns
    A=A.loc[(A != 0).any(axis=1), (A != 0).any(axis=0)]

    #separate A and c again
    c=A.iloc[-1:,:]
    A=A.iloc[:-1,:]

    #create easy matrices and vectors
    b_eq=np.zeros(A.shape[0])
    A_leq=np.identity(edgemat.shape[0])
    b_leq=edgemat[:,2]

    #do optimization
    optimal=linprog(c,A_eq=A,A_ub=A_leq,b_eq=b_eq,b_ub=b_leq,method="simplex")
    flows=np.array(np.array([optimal.x]))

    #generate output
    summary=pd.DataFrame(flows,index=["flow"],columns=A.columns)
    max="The maximum is: " +str(-optimal.fun)

    #print output and return
    print(max)
    return (summary,A)

```

Problem 1 Confirmation

```

In [6]: create_eq_matrix(6,edgemat=np.array([
                                                [0,1,14],
                                                [0,2,16],
                                                [1,2,9],
                                                [1,3,3],
                                                [1,4,8],
                                                [2,3,10],
                                                [2,4,6],
                                                [3,4,5],
                                                [3,5,16],
                                                [4,3,4],
                                                [4,5,15]])) [0]

```

The maximum is: 27.0

```

Out[6]:
    0,1  0,2  1,2  1,3  1,4  2,3  2,4  3,4  3,5  4,3  4,5
flow 11.0 16.0 0.0 3.0 8.0 10.0 6.0 1.0 16.0 4.0 11.0

```

Problem 2 Confirmation.

```
In [7]: create_eq_matrix(10,
        np.array([
            [0,1,6],
            [0,5,6],
            [0,8,2],
            [1,2,3],
            [1,5,3],
            [2,3,2],
            [2,5,6],
            [2,7,3],
            [3,4,4],
            [4,7,4],
            [4,9,7],
            [5,6,3],
            [5,8,2],
            [6,7,2],
            [6,8,1],
            [7,9,3],
            [8,9,6]
        ]))

The maximum is: 10.0
```

| | 0,1 | 0,5 | 0,8 | 1,2 | 1,5 | 2,3 | 2,5 | 2,7 | 3,4 | 4,7 | 4,9 | 5,6 | 5,8 | 6,7 | 6,8 | 7,9 | 8,9 |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| flow | 6.0 | 2.0 | 2.0 | 3.0 | 3.0 | 2.0 | 0.0 | 1.0 | 2.0 | 0.0 | 2.0 | 3.0 | 2.0 | 2.0 | 1.0 | 3.0 | 5.0 |

Problem 4.

a.

```
In [8]: A_leq=np.identity(9)
        A_eq=np.array([
            [1,0,-1,-1,0,0,0,0,0],
            [0,0,1,0,-1,-1,1,0,0],
            [0,1,0,1,0,0,-1,-1,0],
            [0,0,0,0,1,0,0,1,-1]
        ])

        b_eq=np.zeros(4)
        b_leq=[5,6,4,1,2,4,3,3,6]

        tab=np.concatenate((A_eq,A_leq),axis=0)
        b_full=np.transpose(np.array([np.append(b_eq,b_leq)]))

        c=np.array([[0,0,0,0,0,1,0,0,1]])

        tab=np.concatenate((tab,b_full),axis=1)
        tab=np.concatenate((tab,c),axis=0)

        print(tab)

        indep_names=["x01","x03","x12","x13","x24","x25","x32","x34","x45"]
        dep_names=["0","0","0","0","c01","c03","c12","c13","c24","c25","c32","c34","c45"]

        indep_names_dual=["mu1","mu2","mu3","mu4","y01","y03","y12","y13","y24","y25","y32","y34","y45"]
        dep_names_dual=["s01","s03","s12","s13","s24","s25","s32","s34","s45"]

[[ 1.  0. -1. -1.  0.  0.  0.  0.  0.]
 [ 0.  0.  1.  0. -1. -1.  1.  0.  0.]
 [ 0.  1.  0.  1.  0.  0. -1. -1.  0.]
 [ 0.  0.  0.  0.  1.  0.  0.  1. -1.]
 [ 1.  0.  0.  0.  0.  0.  0.  0.  5.]
 [ 0.  1.  0.  0.  0.  0.  0.  0.  6.]
 [ 0.  0.  1.  0.  0.  0.  0.  0.  4.]
 [ 0.  0.  0.  1.  0.  0.  0.  0.  1.]
 [ 0.  0.  0.  0.  1.  0.  0.  0.  2.]
 [ 0.  0.  0.  0.  0.  1.  0.  0.  4.]
 [ 0.  0.  0.  0.  0.  0.  1.  0.  3.]
 [ 0.  0.  0.  0.  0.  0.  0.  1.  3.]
 [ 0.  0.  0.  0.  0.  0.  0.  0.  1.]
 [ 0.  0.  0.  0.  0.  1.  0.  0.  1.]]

In [9]: def print_tableau(a,indep_names,dep_names,indep_names_dual,dep_names_dual):
        #
        # Given matrix "a" and lists of variables names "indep_names" and "dep_names",
        # and (for the dual) "indep_names_dual" and "dep_names_dual",
        # this function prints the matrix and labels in standard tableau format
        # (including adding the -1, the minus signs in the last column, and labeling the lower-right as obj)
```

```

#
# First, check the inputs: indep_names and dep_names_dual should be one shorter than the number of columns of A
# dep_names and indep_names_dual should be one shorter than the number of rows of A
#
nrows = a.shape[0] # use the shape function to determine number of rows and cols in A
ncols = a.shape[1]
nindep = len(indep_names)
nindep_dual = len(indep_names_dual)
ndep = len(dep_names)
ndep_dual = len(dep_names_dual)
if nindep != ncols-1:
    print("WARNING: # of indep vbles should be one fewer than # columns of matrix")
if ndep != nrows-1:
    print("WARNING: # of dep vbles should be one fewer than # rows of matrix")
if nindep_dual != nrows-1:
    print("WARNING: # of indep dual vbles should be one fewer than # rows of matrix")
if ndep_dual != ncols-1:
    print("WARNING: # of dep dual vbles should be one fewer than # columns of matrix")
# Now do the printing (uses a variety of formatting techniques in Python)
print(" ",end="") # On first line, leave blank space so we can fit in dual labels lower down
for j in range(ncols-1): # Print the independent variables in the first row
    print(indep_names[j].rjust(10),end="") # rjust(10) makes fields 10 wide and right-justifies;
    # the end command prevents newline)
print(" ",end="") # Tack on the -1 at the end of the first row
for i in range(nrows-1):
    print(indep_names_dual[i].rjust(10),end="")
    for j in range(ncols): # Print all but the last row of the matrix
        print("%10.3f" % a[i][j],end="") # The syntax prints in a field 10 wide, showing 3 decimal point
    lab = "-" + dep_names[i]
    print(lab.rjust(10))
print(" ",end="")
for j in range(ncols):
    print("%10.3f" % a[nrows-1][j],end="") # Print the last row of the matrix, with label "obj" at end
lab = "- obj"
print(lab.rjust(10))
print(" ",end="")
for j in range(ncols-1):
    lab = "-" + dep_names_dual[j]
    print(lab.rjust(10),end="")
print(" -dualobj")
print(" ") # Put blank line at bottom

```

```

In [10]: def pivot(a,pivrow,pivcol,indep_names,dep_names,indep_names_dual,dep_names_dual) :
#
# Given matrix "a", a row number "pivrow" and column number "pivcol",
# and lists of variable names "indep_names" and "dep_names", this
# function does three things:
# (1) outputs the new version of the matrix after a pivot,
# (2) updates the lists of variable names post-pivot
# (3) prints the new matrix, including labels showing the variable names
#
# First, check the inputs: indep_names should be one shorter than the number of columns of A
# dep_names should be one shorter than the number of rows of A
# you should not be pivoting on the last row or last column
#
nrows = a.shape[0] # use the shape function to determine number of rows and cols in A
ncols = a.shape[1]
nindep = len(indep_names)
nindep_dual = len(indep_names_dual)
ndep = len(dep_names)
ndep_dual = len(dep_names_dual)
if nindep != ncols-1:
    print("WARNING: # of indep vbles should be one fewer than # columns of matrix")
if ndep != nrows-1:
    print("WARNING: # of dep vbles should be one fewer than # rows of matrix")
if nindep_dual != nrows-1:
    print("WARNING: # of indep dual vbles should be one fewer than # rows of matrix")
if ndep_dual != ncols-1:
    print("WARNING: # of dep dual vbles should be one fewer than # columns of matrix")
if pivrow > nrows-1 or pivcol > ncols-1:
    print("WARNING: should not pivot on last row or column")
newa = a.copy() # make a copy of A, to be filled in below with result of pivot
p = a[pivrow-1][pivcol-1] # identify pivot element
newa[pivrow-1][pivcol-1] = 1/p # set new value of pivot element
# Set entries in p's row
for j in range(ncols):
    if j != pivcol-1:
        newa[pivrow-1][j] = a[pivrow-1][j]/p;
# Set entries in p's column
for i in range(nrows):
    if i != pivrow-1:

```

```

        newa[i][pivcol-1] = -a[i][pivcol-1]/p;
# Set all other entries
for i in range(nrows):
    for j in range(ncols):
        if i != pivrow-1 and j != pivcol-1:
            r = a[i][pivcol-1]
            q = a[pivrow-1][j]
            s = a[i][j]
            newa[i][j] = (p*s-q*r)/p
# Now transfer the new tableau into a
for i in range(nrows):
    for j in range(ncols):
        a[i][j] = newa[i][j]
# Now swap the variable names
temp = indep_names[pivcol-1]
indep_names[pivcol-1] = dep_names[pivrow-1]
dep_names[pivrow-1] = temp
temp = indep_names_dual[pivrow-1]
indep_names_dual[pivrow-1] = dep_names_dual[pivcol-1]
dep_names_dual[pivcol-1] = temp
print_tableau(newa, indep_names, dep_names, indep_names_dual, dep_names_dual) # Print the matrix with updated labels
return 0;

```

```

In [11]: def column_delete(a, col_to_remove, indep_names, dep_names, indep_names_dual, dep_names_dual) :
import numpy as np
anew = np.delete(a, col_to_remove-1, axis=1)
del indep_names[col_to_remove-1]
del dep_names_dual[col_to_remove-1]
print_tableau(anew, indep_names, dep_names, indep_names_dual, dep_names_dual)
return anew

```

```

In [12]: def row_delete(a, row_to_remove, indep_names, dep_names, indep_names_dual, dep_names_dual) :
import numpy as np
anew = np.delete(a, row_to_remove-1, axis=0)
del dep_names[row_to_remove-1]
del indep_names_dual[row_to_remove-1]
print_tableau(anew, indep_names, dep_names, indep_names_dual, dep_names_dual)
return anew

```

```

In [13]: def target(a) :
nrows = a.shape[0] # use the shape function to determine number of rows and cols in "a"
ncols = a.shape[1]
import numpy as np
v = np.empty(ncols-1)
for i in range(ncols-1):
    v[i] = a[nrows-1, i]
biggest_c = np.max(v)
where_is_biggest_c = np.argmax(v)+1
if biggest_c > 0 :
    return where_is_biggest_c
else :
    return -1

```

```

In [14]: def select(a, pivcolnum) :
nrows = a.shape[0] # use the shape function to determine number of rows and cols in A
ncols = a.shape[1]
# First task: work down the column and record the b/a ratios in a vector v
# except record -1 if a is negative or zero
import numpy as np
v = np.zeros(nrows-1)
for i in range(nrows-1):
    if a[i, pivcolnum-1] > 0 :
        v[i] = a[i, ncols-1]/a[i, pivcolnum-1]
    else :
        v[i] = -1
# Second task: if max b/a > -1, find min b/a by hand (ignoring zero entries in v)
if np.max(v) > -1 :
    min_so_far = np.max(v)+1 # Initialize min to be for-sure bigger than the min
    for i in range(nrows-1):
        if v[i] > -1 and v[i] < min_so_far :
            min_so_far = v[i]
            where_is_min = i+1 # Add 1 to use human numbering
    return where_is_min # Once we've scanned v for min, we can return result
else :
    # Otherwise, we find the m
    return -1

```

```

In [15]: def simplexbf(a, indep_names, dep_names, dual_indep_names, dual_dep_names):
# Run the simplexbf algorithm

```

```

# Inputs: np.array "a" (assumed to be basic feasible)
#         lists of variable names indep_names and dep_names (pivot will catch if they're wrong size)
# Output: -1 if we stop because problem is unbounded, 0 if we continue to a solution
#         -9 if we take too many steps
nrows = a.shape[0] # use shape to find # of rows and cols in A
ncols = a.shape[1]
print("Starting SimplexBF (will do nothing if solution can already be determined)")
pivcol = target(a)
nsteps = 0
while pivcol > -1 and nsteps < 50: # Repeat until either solution found or 50 pivots completed
    pivrow = select(a,pivcol)
    if pivrow == -1 :
        return -1 # If select reports -1, problem is unbounded, so exit this function
    else :
        pivot(a,pivrow,pivcol,indep_names,dep_names,dual_indep_names,dual_dep_names)
        nsteps=nsteps+1
        pivcol = target(a)
if nsteps >= 50:
    return -9 # we took too many pivots
else:
    return 0

```

```

In [16]: def targetnbf(a):
nrows = a.shape[0]
ncols = a.shape[1]
import numpy as np
checkrow = nrows-2
while a[checkrow,ncols-1] >= -0.00000001 :
    if checkrow == 0 : # if still in the "while" and at the top,
        return -1 # all the b's were >= 0, so return -1
    else :
        checkrow = checkrow-1
return checkrow+1 # if we exit the "while", we found a negative
# b, so return current row # (in human numbering)

```

```

In [17]: def selectnbf(a,targetrow) :
# Given inputs "a" (tableau as an np.array, numbers only, no labels)
#         and "targetrow" (a row that has a negative b; start-at-1 numbering assumed),
# computes a pivot that could be chosen by SimplexNBF and
# outputs "pivrow" and "pivcol", the row and column (start-at-1 numbering) of that pivot
# If the targeted row has no negative aij, returns -2 for both pivrow and pivcol
nrows = a.shape[0]
ncols = a.shape[1]
import numpy as np
targetrow = targetrow-1 # convert to start-at-0
pivcol = ncols-2 # column index of last aij
while a[targetrow,pivcol] >= 0 :
    if pivcol == 0 : # if pivcol makes it to zero, all aij
        return [-2,-2] # in this row were >= 0, so problem infeasible
    else :
        pivcol = pivcol-1
minsofar = a[targetrow,ncols-1]/a[targetrow,pivcol] # we found a negative aij
pivrow = targetrow
for i in range(targetrow+1,nrows-2): # now check below it for a smaller bi/aij with aij>0
    if a[i,pivcol]>0 and a[i,ncols-1]/a[i,pivcol] < minsofar :
        minsofar = a[i,ncols-1]/a[i,pivcol]
        pivrow = i
return [pivrow+1,pivcol+1] # Return result (shifted to start-at-1 numbering)

```

```

In [18]: def simplexnbf(a,indep_names,dep_names,dual_indep_names,dual_dep_names):
# Run the simplexnbf algorithm
# Inputs: np.array "a"
#         lists of variable names indep_names and dep_names (pivot will catch if they're wrong size)
# Output: -2 if we stop because problem is infeasible, 0 if we stop at a basic feasible tableau
#         -9 if we take too many pivots
# (Also, the tableau "a" and variable-lists are updated with each pivot)
nrows = a.shape[0]
ncols = a.shape[1]
print("Starting SimplexNBF (will do nothing if already basic feasible)")
nsteps = 0
targetrow = targetnbf(a)
while targetrow > -1 and nsteps < 50: # Repeat until either basic feasible tableau produced or 50 pivots completed
    [pivrow,pivcol] = selectnbf(a,targetrow)
    if pivrow == -2 :
        return -2 # If selectnbf reports -2, problem is infeasible, so exit this function
    else :
        pivot(a,pivrow,pivcol,indep_names,dep_names,dual_indep_names,dual_dep_names)
        nsteps=nsteps+1
        targetrow = targetnbf(a)
if nsteps >= 50:

```



```

        return -9    # took too many pivots
    else:
        return 0

```

```

In [19]: def simplex(a,indep_names,dep_names,dual_indep_names,dual_dep_names) :
# Runs the simplex algorithm (doing NBF if needed, then BF)
# Inputs: np.array "a"
#         lists of variable names indep_names and dep_names (pivot will catch if they're wrong size)
# Output: -2 if problem is infeasible
#         -1 if problem is unbounded
#         0 if problem has a solution
#         (Also, the tableau "a" and variable-lists are updated with each pivot)
nrows = a.shape[0]
ncols = a.shape[1]
print("Initial tableau")
print_tableau(a,indep_names,dep_names,dual_indep_names,dual_dep_names)
code = simplexnbf(a,indep_names,dep_names,dual_indep_names,dual_dep_names)
if code == -2 :
    print("Problem is infeasible")
    return -2
elif code == -9 :
    print("SimplexNBF took too many pivots")
else :
    code = simplexbf(a,indep_names,dep_names,dual_indep_names,dual_dep_names)
    if code == -1 :
        print("Problem is unbounded")
        return -1
    elif code == -9 :
        print("SimplexBF took too many pivots")
    else :
        print("Problem has solution, final tableau is shown above")
        return 0

```

```

In [20]: def simplexeq(a,k,indep_names,dep_names,dual_indep_names,dual_dep_names) :
# Specialized function to do the "pre-simplex" step to handle tableaus where the
# first k rows correspond to equality constraints.
nrows = a.shape[0]
ncols = a.shape[1]
print_tableau(a,indep_names,dep_names,dual_indep_names,dual_dep_names)
for i in range(k) :
    j=0
    pivcol=-1
    for j in range(ncols-1) :
        if abs(a[i,j]) > 0.000001 :
            pivrow=i+1
            pivcol=j+1
            break
    if pivcol == -1 :
        return -3
    else :
        pivot(a,pivrow,pivcol,indep_names,dep_names,dual_indep_names,dual_dep_names)
        a=column_delete(a,pivcol,indep_names,dep_names,dual_indep_names,dual_dep_names)
        ncols=ncols-1
code = simplex(a,indep_names,dep_names,dual_indep_names,dual_dep_names)
return code

```

```

In [21]: tab,4,indep_names,dep_names,indep_names_dual,dep_names_dual

```

```

Out[21]: (array([[ 1.,  0., -1., -1.,  0.,  0.,  0.,  0.,  0.,  0.],
 [ 0.,  0.,  1.,  0., -1., -1.,  1.,  0.,  0.,  0.],
 [ 0.,  1.,  0.,  1.,  0.,  0., -1., -1.,  0.,  0.],
 [ 0.,  0.,  0.,  0.,  1.,  0.,  0.,  1., -1.,  0.],
 [ 1.,  0.,  0.,  0.,  0.,  0.,  0.,  0.,  0.,  5.],
 [ 0.,  1.,  0.,  0.,  0.,  0.,  0.,  0.,  0.,  6.],
 [ 0.,  0.,  1.,  0.,  0.,  0.,  0.,  0.,  0.,  4.],
 [ 0.,  0.,  0.,  1.,  0.,  0.,  0.,  0.,  0.,  1.],
 [ 0.,  0.,  0.,  0.,  1.,  0.,  0.,  0.,  0.,  2.],
 [ 0.,  0.,  0.,  0.,  0.,  1.,  0.,  0.,  0.,  4.],
 [ 0.,  0.,  0.,  0.,  0.,  0.,  1.,  0.,  0.,  3.],
 [ 0.,  0.,  0.,  0.,  0.,  0.,  0.,  1.,  0.,  3.],
 [ 0.,  0.,  0.,  0.,  0.,  0.,  0.,  0.,  1.,  6.],
 [ 0.,  0.,  0.,  0.,  0.,  1.,  0.,  0.,  1.,  0.]]),
4,
['x01', 'x03', 'x12', 'x13', 'x24', 'x25', 'x32', 'x34', 'x45'],
['0',
 '0',
 '0',
 '0',
 'c01',
 'c03',
 'c12',
 'c13',

```

```

'c24',
'c25',
'c32',
'c34',
'c45'],
['mu1',
'mu2',
'mu3',
'mu4',
'y01',
'y03',
'y12',
'y13',
'y24',
'y25',
'y32',
'y34',
'y45'],
['s01', 's03', 's12', 's13', 's24', 's25', 's32', 's34', 's45'])

```

```
In [22]: simplexeq(tab,4,indep_names,dep_names,indep_names_dual,dep_names_dual)
```

| | | x01 | x03 | x12 | x13 | x24 | x25 | x32 | x34 | x45 | -1 |
|--------|------|--------|-------|--------|--------|--------|--------|--------|--------|----------|--------|
| = -0 | mu1 | 1.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 |
| = -0 | mu2 | 0.000 | 0.000 | 1.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 |
| = -0 | mu3 | 0.000 | 1.000 | 0.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 |
| = -0 | mu4 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 |
| = -c01 | y01 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 5.000 |
| = -c03 | y03 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 6.000 |
| = -c12 | y12 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 4.000 |
| = -c13 | y13 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 |
| = -c24 | y24 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 |
| = -c25 | y25 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 |
| = -c32 | y32 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 |
| = -c34 | y34 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 |
| = -c45 | y45 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 |
| = obj | -1 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 |
| | =s01 | =s03 | =s12 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | |
| | s01 | 0 | x03 | x12 | x13 | x24 | x25 | x32 | x34 | x45 | -1 |
| = -x01 | s01 | 1.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 |
| = -0 | mu2 | -0.000 | 0.000 | 1.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 |
| = -0 | mu3 | -0.000 | 1.000 | 0.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 |
| = -0 | mu4 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 |
| = -c01 | y01 | -1.000 | 0.000 | 1.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 5.000 |
| = -c03 | y03 | -0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 6.000 |
| = -c12 | y12 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 4.000 |
| = -c13 | y13 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 |
| = -c24 | y24 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 |
| = -c25 | y25 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 |
| = -c32 | y32 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 |
| = -c34 | y34 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 |
| = -c45 | y45 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 |
| = obj | -1 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 |
| | =mu1 | =s03 | =s12 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | |
| | s01 | 0.000 | x12 | x13 | x24 | x25 | x32 | x34 | x45 | -1 | = -x01 |
| | mu2 | 0.000 | 1.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -0 |

| | | | | | | | | | | |
|-----|--------|--------|--------|--------|--------|--------|----------|----------|----------|--------|
| mu3 | 1.000 | 0.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -0 |
| mu4 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -0 |
| y01 | 0.000 | 1.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 5.000 | = -c01 |
| y03 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 6.000 | = -c03 |
| y12 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c12 |
| y13 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 | = -c24 |
| y25 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 |
| y32 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj |
| | =s03 | =s12 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | |
| | x03 | 0 | x13 | x24 | x25 | x32 | x34 | x45 | -1 | |
| s01 | 0.000 | 1.000 | -1.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x01 |
| s12 | 0.000 | 1.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x12 |
| mu3 | 1.000 | -0.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -0 |
| mu4 | 0.000 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -0 |
| y01 | 0.000 | -1.000 | 1.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 5.000 | = -c01 |
| y03 | 1.000 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 6.000 | = -c03 |
| y12 | 0.000 | -1.000 | 0.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 4.000 | = -c12 |
| y13 | 0.000 | -0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 | = -c24 |
| y25 | 0.000 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 |
| y32 | 0.000 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj |
| | =s03 | =mu2 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | |
| | x03 | x13 | x24 | x25 | x32 | x34 | x45 | -1 | | |
| s01 | 0.000 | -1.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x01 | |
| s12 | 0.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x12 | |
| mu3 | 1.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -0 | |
| mu4 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -0 | |
| y01 | 0.000 | 1.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 5.000 | = -c01 | |
| y03 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 6.000 | = -c03 | |
| y12 | 0.000 | 0.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 4.000 | = -c12 | |
| y13 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 | |
| y24 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 | = -c24 | |
| y25 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 | |
| y32 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 | |
| y34 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 | |
| y45 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 | |
| -1 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj | |
| | =s03 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | | |
| | 0 | x13 | x24 | x25 | x32 | x34 | x45 | -1 | | |
| s01 | -0.000 | -1.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x01 | |
| s12 | -0.000 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x12 | |
| s03 | 1.000 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 | |
| mu4 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -0 | |
| y01 | -0.000 | 1.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 5.000 | = -c01 | |
| y03 | -1.000 | -1.000 | 0.000 | 0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 | |
| y12 | -0.000 | 0.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 4.000 | = -c12 | |
| y13 | -0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 | |
| y24 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 | = -c24 | |
| y25 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 | |
| y32 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 | |
| y34 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 | |
| y45 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 | |
| -1 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj | |
| | =mu3 | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | | |
| | x13 | x24 | x25 | x32 | x34 | x45 | -1 | | | |
| s01 | -1.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x01 | | |
| s12 | 0.000 | -1.000 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | = -x12 | | |
| s03 | 1.000 | 0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 | | |
| mu4 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -0 | | |
| y01 | 1.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 5.000 | = -c01 | | |
| y03 | -1.000 | 0.000 | 0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 | | |
| y12 | 0.000 | 1.000 | 1.000 | -1.000 | 0.000 | 0.000 | 4.000 | = -c12 | | |
| y13 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 | | |
| y24 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 2.000 | = -c24 | | |
| y25 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 | | |
| y32 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 | | |
| y34 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 | | |
| y45 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 | | |
| -1 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj | | |
| | =s13 | =s24 | =s25 | =s32 | =s34 | =s45 | =dualobj | | | |
| | x13 | 0 | x25 | x32 | x34 | x45 | -1 | | | |
| s01 | -1.000 | 1.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x01 | | |
| s12 | 0.000 | 1.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x12 | | |
| s03 | 1.000 | -0.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 | | |
| s24 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -x24 | | |

| | | | | | | | | |
|-----|--------|--------|-------|--------|--------|-------|----------|--------|
| y01 | 1.000 | -1.000 | 1.000 | -1.000 | -1.000 | 1.000 | 5.000 | = -c01 |
| y03 | -1.000 | -0.000 | 0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 |
| y12 | 0.000 | -1.000 | 1.000 | -1.000 | -1.000 | 1.000 | 4.000 | = -c12 |
| y13 | 1.000 | -0.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | -1.000 | 0.000 | 0.000 | -1.000 | 1.000 | 2.000 | = -c24 |
| y25 | 0.000 | -0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 |
| y32 | 0.000 | -0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | -0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | -0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj |
| | =s13 | =mu4 | =s25 | =s32 | =s34 | =s45 | =dualobj | |

| | | | | | | | |
|-----|--------|--------|--------|--------|--------|----------|--------|
| | x13 | x25 | x32 | x34 | x45 | -1 | |
| s01 | -1.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x01 |
| s12 | 0.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x12 |
| s03 | 1.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 |
| s24 | 0.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -x24 |
| y01 | 1.000 | 1.000 | -1.000 | -1.000 | 1.000 | 5.000 | = -c01 |
| y03 | -1.000 | 0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 |
| y12 | 0.000 | 1.000 | -1.000 | -1.000 | 1.000 | 4.000 | = -c12 |
| y13 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | 0.000 | 0.000 | -1.000 | 1.000 | 2.000 | = -c24 |
| y25 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 |
| y32 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj |
| | =s13 | =s25 | =s32 | =s34 | =s45 | =dualobj | |

Initial tableau

| | | | | | | | |
|-----|--------|--------|--------|--------|--------|----------|--------|
| | x13 | x25 | x32 | x34 | x45 | -1 | |
| s01 | -1.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x01 |
| s12 | 0.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x12 |
| s03 | 1.000 | 0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 |
| s24 | 0.000 | 0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -x24 |
| y01 | 1.000 | 1.000 | -1.000 | -1.000 | 1.000 | 5.000 | = -c01 |
| y03 | -1.000 | 0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 |
| y12 | 0.000 | 1.000 | -1.000 | -1.000 | 1.000 | 4.000 | = -c12 |
| y13 | 1.000 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | 0.000 | 0.000 | -1.000 | 1.000 | 2.000 | = -c24 |
| y25 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -c25 |
| y32 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | 0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | 0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | 1.000 | 0.000 | 0.000 | 1.000 | 0.000 | = obj |
| | =s13 | =s25 | =s32 | =s34 | =s45 | =dualobj | |

Starting SimplexNBF (will do nothing if already basic feasible)

Starting SimplexBF (will do nothing if solution can already be determined)

| | | | | | | | |
|-----|--------|--------|--------|--------|--------|----------|--------|
| | x13 | c12 | x32 | x34 | x45 | -1 | |
| s01 | -1.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -x01 |
| s12 | 0.000 | 1.000 | 0.000 | 0.000 | 0.000 | 4.000 | = -x12 |
| s03 | 1.000 | -0.000 | -1.000 | -1.000 | 0.000 | 0.000 | = -x03 |
| s24 | 0.000 | -0.000 | 0.000 | 1.000 | -1.000 | 0.000 | = -x24 |
| y01 | 1.000 | -1.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c01 |
| y03 | -1.000 | -0.000 | 1.000 | 1.000 | 0.000 | 6.000 | = -c03 |
| s25 | 0.000 | 1.000 | -1.000 | -1.000 | 1.000 | 4.000 | = -x25 |
| y13 | 1.000 | -0.000 | 0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | -0.000 | 0.000 | -1.000 | 1.000 | 2.000 | = -c24 |
| y25 | 0.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -c25 |
| y32 | 0.000 | -0.000 | 1.000 | 0.000 | 0.000 | 3.000 | = -c32 |
| y34 | 0.000 | -0.000 | 0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | -0.000 | 0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | -1.000 | 1.000 | 1.000 | 0.000 | -4.000 | = obj |
| | =s13 | =y12 | =s32 | =s34 | =s45 | =dualobj | |

| | | | | | | | |
|-----|--------|--------|--------|--------|--------|----------|--------|
| | x13 | c12 | c25 | x34 | x45 | -1 | |
| s01 | -1.000 | 1.000 | -0.000 | 0.000 | 0.000 | 4.000 | = -x01 |
| s12 | 0.000 | 1.000 | -0.000 | 0.000 | 0.000 | 4.000 | = -x12 |
| s03 | 1.000 | -1.000 | 1.000 | 0.000 | -1.000 | 0.000 | = -x03 |
| s24 | 0.000 | 0.000 | -0.000 | 1.000 | -1.000 | 0.000 | = -x24 |
| y01 | 1.000 | -1.000 | -0.000 | 0.000 | 0.000 | 1.000 | = -c01 |
| y03 | -1.000 | 1.000 | -1.000 | 0.000 | 1.000 | 6.000 | = -c03 |
| s25 | 0.000 | 0.000 | 1.000 | 0.000 | 0.000 | 4.000 | = -x25 |
| y13 | 1.000 | 0.000 | -0.000 | 0.000 | 0.000 | 1.000 | = -c13 |
| y24 | 0.000 | 0.000 | -0.000 | -1.000 | 1.000 | 2.000 | = -c24 |
| s32 | 0.000 | -1.000 | 1.000 | 1.000 | -1.000 | 0.000 | = -x32 |
| y32 | 0.000 | 1.000 | -1.000 | -1.000 | 1.000 | 3.000 | = -c32 |
| y34 | 0.000 | 0.000 | -0.000 | 1.000 | 0.000 | 3.000 | = -c34 |
| y45 | 0.000 | 0.000 | -0.000 | 0.000 | 1.000 | 6.000 | = -c45 |
| -1 | 0.000 | 0.000 | -1.000 | 0.000 | 1.000 | -4.000 | = obj |
| | =s13 | =y12 | =y25 | =s34 | =s45 | =dualobj | |

| | | | | | | | |
|-----|--------|--------|-------|--------|--------|-------|--------|
| | x13 | c12 | c25 | x34 | c24 | -1 | |
| s01 | -1.000 | 1.000 | 0.000 | 0.000 | -0.000 | 4.000 | = -x01 |
| s12 | 0.000 | 1.000 | 0.000 | 0.000 | -0.000 | 4.000 | = -x12 |
| s03 | 1.000 | -1.000 | 1.000 | -1.000 | 1.000 | 2.000 | = -x03 |

| | | | | | | | |
|-----|--------|--------|--------|--------|--------|----------|--------|
| s24 | 0.000 | 0.000 | -0.000 | 0.000 | 1.000 | 2.000 | = -x24 |
| y01 | 1.000 | -1.000 | 0.000 | 0.000 | -0.000 | 1.000 | = -c01 |
| y03 | -1.000 | 1.000 | -1.000 | 1.000 | -1.000 | 4.000 | = -c03 |
| s25 | 0.000 | 0.000 | 1.000 | 0.000 | -0.000 | 4.000 | = -x25 |
| y13 | 1.000 | 0.000 | 0.000 | 0.000 | -0.000 | 1.000 | = -c13 |
| s45 | 0.000 | 0.000 | -0.000 | -1.000 | 1.000 | 2.000 | = -x45 |
| s32 | 0.000 | -1.000 | 1.000 | 0.000 | 1.000 | 2.000 | = -x32 |
| y32 | 0.000 | 1.000 | -1.000 | 0.000 | -1.000 | 1.000 | = -c32 |
| y34 | 0.000 | 0.000 | 0.000 | 1.000 | -0.000 | 3.000 | = -c34 |
| y45 | 0.000 | 0.000 | 0.000 | 1.000 | -1.000 | 4.000 | = -c45 |
| -1 | 0.000 | 0.000 | -1.000 | 1.000 | -1.000 | -6.000 | = obj |
| | =s13 | =y12 | =y25 | =s34 | =y24 | =dualobj | |
| | x13 | c12 | c25 | c34 | c24 | -1 | |
| s01 | -1.000 | 1.000 | 0.000 | -0.000 | 0.000 | 4.000 | = -x01 |
| s12 | 0.000 | 1.000 | 0.000 | -0.000 | 0.000 | 4.000 | = -x12 |
| s03 | 1.000 | -1.000 | 1.000 | 1.000 | 1.000 | 5.000 | = -x03 |
| s24 | 0.000 | 0.000 | -0.000 | -0.000 | 1.000 | 2.000 | = -x24 |
| y01 | 1.000 | -1.000 | 0.000 | -0.000 | 0.000 | 1.000 | = -c01 |
| y03 | -1.000 | 1.000 | -1.000 | -1.000 | -1.000 | 1.000 | = -c03 |
| s25 | 0.000 | 0.000 | 1.000 | -0.000 | 0.000 | 4.000 | = -x25 |
| y13 | 1.000 | 0.000 | 0.000 | -0.000 | 0.000 | 1.000 | = -c13 |
| s45 | 0.000 | 0.000 | 0.000 | 1.000 | 1.000 | 5.000 | = -x45 |
| s32 | 0.000 | -1.000 | 1.000 | -0.000 | 1.000 | 2.000 | = -x32 |
| y32 | 0.000 | 1.000 | -1.000 | -0.000 | -1.000 | 1.000 | = -c32 |
| s34 | 0.000 | 0.000 | 0.000 | 1.000 | -0.000 | 3.000 | = -x34 |
| y45 | 0.000 | 0.000 | 0.000 | -1.000 | -1.000 | 1.000 | = -c45 |
| -1 | 0.000 | 0.000 | -1.000 | -1.000 | -1.000 | -9.000 | = obj |
| | =s13 | =y12 | =y25 | =y34 | =y24 | =dualobj | |

Problem has solution, final tableau is shown above

Out[22]: 0

Reading off of the output above, the maximum flow is nine. With flow as indicated in the table. They are:

$$\begin{aligned}
 x_{01} &= 4 \\
 x_{03} &= 5 \\
 x_{12} &= 4 \\
 x_{13} &= 0 \\
 x_{24} &= 2 \\
 x_{25} &= 4 \\
 x_{32} &= 2 \\
 x_{34} &= 3 \\
 x_{45} &= 5
 \end{aligned}$$

We can tell that there is an edge between cuts between $(1, 2)$, $(2, 5)$, $(3, 4)$, & $(2, 4)$. This implies that $V_1 = 0, 1, 2, 3$ and $V_2 = 4, 5$.