


CUDA C: The Basics

- Terminology
 - Host The CPU and its memory (host memory)
 - Device The GPU and its memory (device memory)

Host Device





Note: Figure Not to Scale

Hello, World!

```
int main( void ) {
    printf( "Hello, World!\n" );
    return 0;
}
```

- This basic program is just standard C that runs on the *host*
- NVIDIA's compiler (nvcc) will not complain about CUDA programs with no device code
- At its simplest, CUDA C is just C!

Hello, World! with Device Code

```
__global__ void kernel( void ) {
}
int main( void ) {
   kernel<<<1,1>>>();
   printf( "Hello, World!\n" );
   return 0;
}
```

■ Two notable additions to the original "Hello, World!"

Hello, World! with Device Code

```
__global___ void kernel( void ) {
}
```

- CUDA C keyword global indicates that a function
 - Runs on the device
 - Called from host code
- nvcc splits source file into host and device components
 - NVIDIA's compiler handles device functions like kernel ()
 - Standard host compiler handles host functions like main ()
 - qcc
 - Microsoft Visual C

Hello, World! with Device Code

```
int main( void ) {
    kernel <<< 1, 1 >>>();
    printf( "Hello, World!\n" );
    return 0;
}
```

- Triple angle brackets mark a call from host code to device code
 - Sometimes called a "kernel launch"
 - We'll discuss the parameters inside the angle brackets later
- This is all that's required to execute a function on the GPU!
- The function kernel() does nothing, so this is fairly anticlimactic...

A More Complex Example

A simple kernel to add two integers:

```
__global___ void add( int *a, int *b, int *c ) {
    *c = *a + *b;
}
```

- As before, __global__ is a CUDA C keyword meaning
 - add() will execute on the device
 - add() will be called from the host

A More Complex Example

Notice that we use pointers for our variables:


```
__global__ void add( int *a, int *b, int *c ) {
    *c = *a + *b;
}
```

add() runs on the device...so a, b, and c must point to device memory

How do we allocate memory on the GPU?


Memory Management

- Host and device memory are distinct entities
 - Device pointers point to GPU memory
 - May be passed to and from host code
 - May not be dereferenced from host code



- May be passed to and from device code
- May not be dereferenced from device code





- Basic CUDA API for dealing with device memory
 - cudaMalloc(), cudaFree(), cudaMemcpy()
 - Similar to their C equivalents, malloc(), free(), memcpy()

A More Complex Example: add()

Using our add () kernel:

```
__global___ void add( int *a, int *b, int *c ) {
    *c = *a + *b;
}
```

Let's take a look at main()...

A More Complex Example: main()

```
int main( void ) {
   int a, b, c;
                                  // host copies of a, b, c
   int *dev a, *dev b, *dev c; // device copies of a, b, c
   int size = sizeof( int );  // we need space for an integer
    // allocate device copies of a, b, c
    cudaMalloc( (void**) &dev a, size );
    cudaMalloc( (void**)&dev b, size );
    cudaMalloc( (void**)&dev c, size );
   a = 2;
   b = 7;
```

A More Complex Example: main() (cont)

```
// copy inputs to device
cudaMemcpy( dev a, &a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, &b, size, cudaMemcpyHostToDevice );
// launch add() kernel on GPU, passing parameters
add <<< 1, 1 >>> ( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( &c, dev c, size, cudaMemcpyDeviceToHost );
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Parallel Programming in CUDA C

- But wait...GPU computing is about massive parallelism
- So how do we run code in parallel on the device?
- Solution lies in the parameters between the triple angle brackets:

```
add<<< 1, 1 >>>( dev_a, dev_b, dev_c );

ded<<< N, 1 >>>( dev_a, dev_b, dev_c );
```

• Instead of executing add() once, add() executed N times in parallel

Parallel Programming in CUDA C

- With add() running in parallel...let's do vector addition
- Terminology: Each parallel invocation of add() referred to as a block
- Kernel can refer to its block's index with the variable blockIdx.x
- Each block adds a value from a[] and b[], storing the result in c[]:

```
__global__ void add( int *a, int *b, int *c ) {
    c[blockIdx.x] = a[blockIdx.x] + b[blockIdx.x];
}
```

By using blockIdx.x to index arrays, each block handles different indices

Parallel Programming in CUDA C

We write this code:

```
__global__ void add( int *a, int *b, int *c ) {
    c[blockIdx.x] = a[blockIdx.x] + b[blockIdx.x];
}
```

This is what runs in parallel on the device:

Block 0

$$c[0] = a[0] + b[0];$$

Block 2

$$c[2] = a[2] + b[2];$$

Block 1

$$c[1] = a[1] + b[1];$$

Block 3

$$c[3] = a[3] + b[3];$$

Parallel Addition: add()

Using our newly parallelized add() kernel:

```
__global__ void add( int *a, int *b, int *c ) {
    c[blockIdx.x] = a[blockIdx.x] + b[blockIdx.x];
}
```

Let's take a look at main()...

Parallel Addition: main()

```
#define N 512
int main( void ) {
   int *a, *b, *c;
                                    // host copies of a, b, c
   int *dev a, *dev b, *dev c; // device copies of a, b, c
   int size = N * sizeof(int); // we need space for 512 integers
   // allocate device copies of a, b, c
    cudaMalloc( (void**) &dev a, size );
    cudaMalloc( (void**)&dev b, size );
    cudaMalloc( (void**)&dev c, size );
   a = (int*)malloc( size );
   b = (int*)malloc( size );
    c = (int*) malloc(size);
    random ints( a, N );
    random ints( b, N );
```

Parallel Addition: main() (cont)

```
// copy inputs to device
cudaMemcpy( dev a, a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, b, size, cudaMemcpyHostToDevice );
// launch add() kernel with N parallel blocks
add<<< N, 1 >>>( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( c, dev c, size, cudaMemcpyDeviceToHost );
free( a ); free( b ); free( c );
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Review

- Difference between "host" and "device"
 - Host = CPU
 - Device = GPU

- Using global to declare a function as device code
 - Runs on device
 - Called from host

Passing parameters from host code to a device function

Review (cont)

- Basic device memory management
 - cudaMalloc()
 - cudaMemcpy()
 - cudaFree()

- Launching parallel kernels
 - Launch N copies of add() with: add<<< N, 1 >>>();
 - Used blockIdx.x to access block's index

Threads

- Terminology: A block can be split into parallel threads
- Let's change vector addition to use parallel threads instead of parallel blocks:

```
__global___void add(int *a, int *b, int *c) {

c[threakIdx.x] = a[threakIdx.x] + b[threakIdx.x];
}
```

- We use threadIdx.x instead of blockIdx.x in add()
- main() will require one change as well...

Parallel Addition (Threads): main()

```
#define N
        512
int main( void ) {
   int *a, *b, *c;
                                  //host copies of a, b, c
   int *dev a, *dev b, *dev c;
                                 //device copies of a, b, c
   // allocate device copies of a, b, c
   cudaMalloc( (void**) &dev a, size );
   cudaMalloc( (void**)&dev b, size );
   cudaMalloc( (void**)&dev c, size );
   a = (int*)malloc( size );
   b = (int*)malloc(size);
   c = (int*) malloc(size);
   random ints( a, N );
   random ints( b, N );
```

Parallel Addition (Threads): main() (cont)

```
// copy inputs to device
cudaMemcpy( dev a, a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, b, size, cudaMemcpyHostToDevice );
// launch add() kernel with N bhoekds
add<<< \mathbb{N}, \mathbb{N} >>>( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( c, dev c, size, cudaMemcpyDeviceToHost );
free( a ); free( b ); free( c );
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Using Threads <u>And</u> Blocks

- We've seen parallel vector addition using
 - Many blocks with 1 thread apiece
 - 1 block with many threads

- Let's adapt vector addition to use lots of both blocks and threads
- After using threads and blocks together, we'll talk about why threads

First let's discuss data indexing...

Indexing Arrays With Threads And Blocks

- No longer as simple as just using threadIdx.x or blockIdx.x as indices
- To index array with 1 thread per entry (using 8 threads/block)




■ If we have M threads/block, a unique array index for each entry given by

```
int index = threadIdx.x + blockIdx.x * M;
int index = x + y * width;
```

Indexing Arrays: Example

■ In this example, the red entry would have an index of 21:



Addition with Threads and Blocks

■ The blockDim.x is a built-in variable for threads per block:

```
int index= threadIdx.x + blockIdx.x * blockDim.x;
```

A combined version of our vector addition kernel to use blocks and threads:

```
__global__ void add( int *a, int *b, int *c ) {
   int index = threadIdx.x + blockIdx.x * blockDim.x;
   c[index] = a[index] + b[index];
}
```

So what changes in main() when we use both blocks and threads?

Parallel Addition (Blocks/Threads): main()

```
#define N
        (2048 \times 2048)
#define THREADS PER BLOCK 512
int main( void ) {
   int *a, *b, *c;
                           // host copies of a, b, c
   int *dev a, *dev b, *dev c;  // device copies of a, b, c
   // allocate device copies of a, b, c
   cudaMalloc( (void**)&dev a, size );
   cudaMalloc( (void**)&dev b, size );
   cudaMalloc( (void**)&dev c, size );
   a = (int*)malloc( size );
   b = (int*)malloc( size );
   c = (int*)malloc( size );
   random ints( a, N );
   random ints(b, N);
```

Parallel Addition (Blocks/Threads): main()

```
// copy inputs to device
cudaMemcpy( dev a, a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, b, size, cudaMemcpyHostToDevice );
// launch add() kernel with blocks and threads
add<<< N/THREADS PER BLOCK, THREADS PER BLOCK >>> ( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( c, dev c, size, cudaMemcpyDeviceToHost );
free(a); free(b); free(c);
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Why Bother With Threads?


- Threads seem unnecessary
 - Added a level of abstraction and complexity
 - What did we gain?

- Unlike parallel blocks, parallel threads have mechanisms to
 - Communicate
 - Synchronize

Let's see how...

Dot Product

Unlike vector addition, dot product is a reduction from vectors to a scalar




$$c = \vec{\mathbf{a}} \cdot \vec{\mathbf{b}}$$

$$= (a_0, a_1, a_2, a_3) \cdot (b_0, b_1, b_2, b_3)$$

$$= a_0 b_0 + a_1 b_1 + a_2 b_2 + a_3 b_3$$

Dot Product

Parallel threads have no problem computing the pairwise products:




So we can start a dot product CUDA kernel by doing just that:

```
__global__ void dot( int *a, int *b, int *c) {
    // Each thread computes a pairwise product
    int temp = a[threadIdx.x] *b[threadIdx.x];
```

Dot Product

But we need to share data between threads to compute the final sum:




```
global__ void dot( int *a, int *b, int *c ) {
    // Each thread computes a pairwise product
    int temp = a[threadIdx.x] * b[threadIdx.x];


    // Can't compute the final sum
    // Each thread's copy of 'temp' is private
}
```


Sharing Data Between Threads

- Terminology: A block of threads shares memory called...shared memory
- Extremely fast, on-chip memory (user-managed cache)
- Declared with the shared CUDA keyword

Not visible to threads in other blocks running in parallel







Parallel Dot Product: dot()

We perform parallel multiplication, serial addition:

```
#define N 512
 global void dot( int *a, int *b, int *c ) {
     // Shared memory for results of multiplication
       shared int temp[N];
     temp[threadIdx.x] = a[threadIdx.x] * b[threadIdx.x];
      // Thread 0 sums the pairwise products
     if(0) == threadIdx.x) {
         int sum = 0;
         for ( int i = 0; i < N; i++ )
             sum += temp[i];
         *c = sum;
```

Parallel Dot Product Recap

We perform parallel, pairwise multiplications


Shared memory stores each thread's result

We sum these pairwise products from a single thread


Sounds good...but we've made a huge mistake

Faulty Dot Product Exposed!

Step 1: In parallel, each thread writes a pairwise product




Step 2: Thread 0 reads and sums the products




But there's an assumption hidden in Step 1...

Read-Before-Write Hazard

Suppose thread 0 finishes its write in step 1



■ Then thread 0 reads index 12 in step 2



Before thread 12 writes to index 12 in step 1?



Synchronization

■ We need threads to wait between the sections of dot():

```
global void dot( int *a, int *b, int *c ) {
      shared int temp[N];
    temp[threadIdx.x] = a[threadIdx.x] * b[threadIdx.x];
       * NEED THREADS TO SYNCHRONIZE HERE *
     // No thread can advance until all threads
     // have reached this point in the code
     // Thread 0 sums the pairwise products
    if(0) == threadIdx.x) {
        int sum = 0;
        for ( int i = 0; i < N; i++ )
            sum += temp[i];
        *c = sum;
```

syncthreads()

- We can synchronize threads with the function syncthreads()
- Threads in the block wait until all threads have hit the __syncthreads()

Threads are only synchronized within a block

Parallel Dot Product: dot()

```
global void dot(int *a, int *b, int *c) {
     shared int temp[N];
   temp[threadIdx.x] = a[threadIdx.x] * b[threadIdx.x];
     syncthreads();
   if(0) == threadIdx.x) {
       int sum = 0;
       for ( int i = 0; i < N; i++ )
            sum += temp[i];
       *c = sum;
```

■ With a properly synchronized dot() routine, let's look at main()

Parallel Dot Product: main()

```
#define N 512
int main( void ) {
   int *a, *b, *c;
                      // copies of a, b, c
   int *dev a, *dev b, *dev c;  // device copies of a, b, c
   // allocate device copies of a, b, c
   cudaMalloc( (void**)&dev a, size );
   cudaMalloc( (void**)&dev b, size );
   cudaMalloc( (void**)&dev c, sizeof( int ) );
   a = (int *)malloc( size );
   b = (int *)malloc( size );
   c = (int *)malloc( sizeof( int ) );
   random ints( a, N );
   random ints( b, N );
```

Parallel Dot Product: main()

```
// copy inputs to device
cudaMemcpy( dev a, a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, b, size, cudaMemcpyHostToDevice );
// launch dot() kernel with 1 block and N threads
dot<<< 1, N >>>( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( c, dev c, sizeof( int ) , cudaMemcpyDeviceToHost );
free( a ); free( b ); free( c );
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Review

- Launching kernels with parallel threads
 - Launch add() with N threads: add<<< 1, N >>>();
 - Used threadIdx.x to access thread's index

- Using both blocks and threads
 - Used (threadIdx.x + blockIdx.x * blockDim.x) to index input/output
 - N/THREADS_PER_BLOCK blocks and THREADS_PER_BLOCK threads gave us N threads total

Review (cont)

- Using __shared__ to declare memory as shared memory
 - Data shared among threads in a block
 - Not visible to threads in other parallel blocks

- Using syncthreads() as a barrier
 - No thread executes instructions after __syncthreads() until all threads have reached the syncthreads()
 - Needs to be used to prevent data hazards

Multiblock Dot Product

Recall our dot product launch:


```
// launch dot() kernel with 1 block and N threads
dot<<< 1, N >>>( dev_a, dev_b, dev_c );
```


Launching with one block will not utilize much of the GPU

Let's write a multiblock version of dot product

Multiblock Dot Product: Algorithm


Each block computes a sum of its pairwise products like before:





Multiblock Dot Product: Algorithm

• And then contributes its sum to the final result:



Multiblock Dot Product: dot()

```
\#define N (2048*2048)
#define THREADS PER BLOCK 512
 global void dot( int *a, int *b, int *c ) {
     shared int temp[THREADS PER BLOCK];
   int index = threadIdx.x + blockIdx.x * blockDim.x;
   temp[threadIdx.x] = a[index] * b[index];
    syncthreads();
   if(0) == threadIdx.x) {
       int sum = 0;
        for( int i = 0; i < THREADS PER BLOCK; i++ )</pre>
            sum += temp[i];
        atomicAdm ( c , sum );
```

- But we have a race condition...
- We can fix it with one of CUDA's atomic operations

Race Conditions

- Terminology: A race condition occurs when program behavior depends upon relative timing of two (or more) event sequences
- What actually takes place to execute the line in question: *c += sum;
 - Read value at address c
 - Add sum to value
 - Write result to address c

Terminology: Read-Modify-Write

- What if two threads are trying to do this at the same time?
 - Thread 0, Block 0
 - Read value at address c
 Read value at address c
 - Add sum to value
 - Write result to address c

- Thread 0, Block 1


 - Add sum to value
 - Write result to address c


Global Memory Contention

Block 0 sum = 3


*c += sum

Block 1 sum = 4





Global Memory Contention



Atomic Operations

Terminology: Read-modify-write uninterruptible when atomic

Many atomic operations on memory available with CUDA C

```
atomicAdd()
atomicInc()
atomicSub()
atomicDec()
atomicExch()
atomicMax()
atomicCAS()
```

- Predictable result when simultaneous access to memory required
- We need to atomically add sum to c in our multiblock dot product

Multiblock Dot Product: dot()

```
global void dot(int *a, int *b, int *c) {
    shared int temp[THREADS PER BLOCK];
   int index = threadIdx.x + blockIdx.x * blockDim.x;
   temp[threadIdx.x] = a[index] * b[index];
    syncthreads();
  if(0) == threadIdx.x) {
      int sum = 0;
       for( int i = 0; i < THREADS PER BLOCK; i++ )</pre>
           sum += temp[i];
       atomicAdd( c , sum );
```

Now let's fix up main() to handle a multiblock dot product

Parallel Dot Product: main()

```
#define N (2048*2048)
#define THREADS PER BLOCK 512
int main( void ) {
   int *a, *b, *c;
                                   // host copies of a, b, c
   int *dev a, *dev b, *dev c;  // device copies of a, b, c
   // allocate device copies of a, b, c
   cudaMalloc( (void**)&dev a, size );
   cudaMalloc( (void**)&dev b, size );
   cudaMalloc( (void**)&dev c, sizeof( int ) );
   a = (int *)malloc( size );
   b = (int *)malloc( size );
   c = (int *)malloc( sizeof( int ) );
   random ints( a, N );
   random ints( b, N );
```

Parallel Dot Product: main()

```
// copy inputs to device
cudaMemcpy( dev a, a, size, cudaMemcpyHostToDevice );
cudaMemcpy( dev b, b, size, cudaMemcpyHostToDevice );
// launch dot() kernel
dot<<< N/THREADS PER BLOCK, THREADS PER BLOCK >>> ( dev a, dev b, dev c );
// copy device result back to host copy of c
cudaMemcpy( c, dev c, sizeof( int ) , cudaMemcpyDeviceToHost );
free( a ); free( b ); free( c );
cudaFree( dev a );
cudaFree( dev b );
cudaFree( dev c );
return 0;
```

Review

Race conditions


- Behavior depends upon relative timing of multiple event sequences
- Can occur when an implied read-modify-write is interruptible

Atomic operations

- CUDA provides read-modify-write operations guaranteed to be atomic
- Atomics ensure correct results when multiple threads modify memory

To Learn More CUDA C

- Check out CUDA by Example
 - Parallel Programming in CUDA C
 - Thread Cooperation
 - Constant Memory and Events
 - Texture Memory
 - Graphics Interoperability
 - Atomics
 - Streams
 - CUDA C on Multiple GPUs
 - Other CUDA Resources



http://developer.nvidia.com/object/cuda-by-example.html