

The Lunar Geometric Power Link

Infrastructure Proposal for Zone II Quarantine & Energy Transmission

Aaron M. Schutza

Institute for Geometric Physics
Austin, Texas

January 22, 2026

Abstract

The engineering specifications and economic governance framework are outlined for the **Fano-Daedalus Complex**, a centralized Geometric Stiffness Reactor (GSR) facility located on the lunar far side. This project aims to decouple high-risk vacuum engineering from the terrestrial biosphere. By relocating the Associative Recycler technology to the Daedalus Crater, we utilize the lunar mass as a physical shield against Sedenion Slag fallout and exploit the radio-quiet environment for the Mark III Listening Post. We define the transmission architecture via Earth-Moon L2 relays and establish the **Lunar DCS Tariff** to regulate the importation of low-stiffness energy into the Earth's homeostatic zone.

1 Introduction

The development of the Geometric Stiffness Reactor (GSR) has unlocked the latent binding energy of baryonic matter via vacuum modulation ($\beta \rightarrow 0$). However, the generation of Sedenion Slag—radioactive topological defects—presents an unacceptable radiological risk for consumer-grade or terrestrial municipal deployment.

To safely harness this energy, we propose moving the Engine Room of civilization to a Zone II Quarantine environment. The lunar far side offers three critical advantages: **Geometric Shielding**: 3,000 km of silicate rock permanently isolates the Earth from potential vacuum collapse events. **Thermodynamic Efficiency**: Radiative heat rejection into the 3 K cosmic background is optimal for high-yield Fano Septet arrays. **Signal Clarity**: It provides the necessary radio silence for the detection of the 1.811 GHz Silent Geometer signal.

2 Site Specification: The Fano-Daedalus Complex

2.1 Location

The facility will be sited in the **Daedalus Crater** on the lunar far side. This location ensures that the reactor core never has a direct line-of-sight to the Earth, mitigating the risk of direct beam transmission of vacuum instability.

2.2 Reactor Architecture

Unlike the consumer-grade Associative Recycler which requires Chiral Scrambling for safety, the lunar facility will utilize **Open-Fano Mark V** cores. **Core Design**: Unshielded stiffness mod-

ulation allows for higher energy density. **Cooling:** Active liquid-sodium loops rejecting heat via vertical radiator fins. **Safety:** The entire crater is designated as a Soft Vacuum exclusion zone.

3 Transmission Architecture: The Lagrange Lens

Direct cable transmission is impossible. We propose a wireless power transmission (WPT) network utilizing the Earth-Moon Lagrange Point 2 (L2).

$$P_{received} = P_{emitted} \cdot \eta_{relay} \cdot \exp(-\alpha_{atm}h) \quad (1)$$

Emitter: Phased-array microwave masers located at the complex. **Relay:** A passive dielectric mirror satellite stationed at L2 to reflect the beam around the lunar curvature. **Receiver:** Rectenna farms located in terrestrial Zone I deserts (e.g., Mojave, Sahara).

4 Economic Governance: The Lunar DCS Tariff

In accordance with the Distributed Consensus Stiffness (DCS) Protocol, energy generated in a low-stiffness environment (Moon) creates an economic imbalance when imported to a high-stiffness environment (Earth). To prevent Geometric Inflation, we impose a physics-based tariff. The cost of importation is governed by the DCS Tariff Equation:

$$Cost_{import} = P_{lunar} \cdot \left(\frac{\beta_{Earth}}{\beta_{Moon}} \right)^{\gamma_{coupling}} + \mathcal{S}_{sink} \quad (2)$$

Where: $\beta_{Earth} \approx 1.91$: The homeostatic stiffness of Earth. β_{Moon} : The reduced stiffness of the lunar vacuum. $\gamma_{coupling} \approx 1/137$: The vacuum coupling constant. $\mathcal{S}_{sink}$: The Sedenion Surcharge utilized to fund waste sequestration.

5 Waste Management: Regolith Sequestration

The primary hazard of GSR operation is the saturation of Borated Graphite sinks with vacuum defects. Transporting this waste back to Earth is strictly prohibited. Saturated graphite cartridges will be disposed of via deep-borehole sequestration: **Depth:** > 5 km beneath the crater floor. **Stability:** The lunar geology is tectonically inert and lacks groundwater, preventing the migration of topological defects. **Capacity:** The lunar regolith offers effectively infinite volume for the disposal of Geometric Sickness.

6 Safety Protocols: The Light-Speed Cutoff

The transmission system provides an inherent fail-safe mechanism superior to any physical containment. **Zero Inertia:** The transmission medium (photons) has no mass. **Immediate Cessation:** In the event of a Koide Interlock breach ($\Delta Q > 10^{-5}$), the maser array is instantly de-energized. **Result:** Power delivery to Earth ceases within 1.3 seconds. No physical radiation or debris can traverse the vacuum gap.

7 Conclusion

Project Daedalus solves the trilemma of energy abundance, planetary safety, and vacuum hygiene. By establishing the Moon as the Engine Room of the solar system, we adhere to the principles of Axiomatic Physical Homeostasis: keeping the Earth Stiff and safe, while allowing the Soft zones to bear the thermodynamic load of civilization.