From classical energy estimates to a certified ground state: a modular Stetcu–Baroni filter pipeline and its cost for the J_1–J_2 chain

Authors to be added
(Dated: October 23, 2026)

Classical methods such as the density-matrix renormalization group (DMRG) supply accurate ground-state energies, a gap estimate and a compact trial state, but a shallow circuit for that trial state keeps some weight on excited states. The projection filter of Stetcu, Baroni and Carlson removes it with one ancilla, controlled time evolution and post-selection. We give a generic, modular pipeline that takes energy estimates and an ansatz for any Hamiltonian written as a sum of Pauli strings, designs a cosine filter with a certified suppression ratio, chooses first- or second-order Trotter step counts from commutator bounds, and returns an a-priori bound on the infidelity of the prepared state together with a transparent gate count. The bound is a theorem conditional on the inputs (an interval for the ground energy, a lower bound on the gap and on the trial overlap), and every one of these conditions is an explicit input. We apply it to the open spin-$\frac{1}{2}$ J_1–J_2 chain with DMRG inputs and bond-dimension-χ matrix-product trial states, $N = 8$–48. In all 96 of 96 simulated circuits ($N \leq 14$) the certified bound held; it overestimates the measured infidelity by a median factor of 17, mostly through its Trotter term. A second-order product formula is a median $92\times$ cheaper than first order, and an optimized filter a median $2.9\times$ cheaper than a closed-form halving ("dyadic") schedule, which however is the only design that stays feasible for small overlaps. Near the critical coupling at $N = 48$, a $\chi = 4$ trial state is refined to infidelity 10^{-2} for 8.8×10^6 CNOTs per success. Overestimating the gap by 50% is the one input error that broke the target; a conservative gap costs at most $2.8\times$. For this one-dimensional model at $\epsilon = 10^{-2}$, however, a $\chi = 8$ matrix-product circuit alone already meets the target with about 10^3–10^4 CNOTs, so the value of the pipeline lies in its certificate and in models where compact trial states are not available.

I. INTRODUCTION

A common route to a ground state on a quantum computer starts classically: an approximate method produces a trial state that can be compiled into a short circuit, and a quantum subroutine removes its residual excited-state weight. For one-dimensional and quasi-one-dimensional systems the natural classical engine is DMRG [3, 4], which yields the ground-state energy E_0, excited-state energies and a matrix-product state (MPS) whose low-bond-dimension truncations compile exactly into staircase circuits [5]. The quantum step can be phase estimation [6], a polynomial filter implemented by quantum singular-value transformation [7–9], or a product of cosine filters implemented with a single ancilla [1, 10]. The last option, the projection algorithm of Stetcu, Baroni and Carlson (SBC) [1], is attractive for early fault-tolerant hardware: each step is one controlled time evolution sandwiched between ancilla rotations and a measurement, the filter is designed classically, and the success probability is known in advance.

To use such a filter one has to answer three practical questions: which times and phases, how many Trotter steps, and how good the result is. SBC optimize the times and phases numerically for a model spectrum with a given gap; they do not give a bound on the error of the prepared state, and the Trotter error is treated separately [1]. This paper packages the full chain as a pipeline with typed inputs and a certificate:

1. *Inputs*: a Pauli-sum Hamiltonian H, energy estimates (an interval for E_0, a lower bound on the first excited energy E_1, optionally an upper bound on the spectrum) and an ansatz (its estimated ground-space weight γ and the gate cost of its circuit). Any classical method can supply them.
2. *Filter design*: three schedules, from the naive repeated cosine to an optimized design, each with a rigorous interval bound on its suppression ratio.
3. *Trotterization*: first- and second-order commutator-scaling bounds [2], evaluated exactly on the support of each local commutator.
4. *Certificate*: an a-priori bound on the trace distance between the prepared state and the ground space, valid whenever the inputs are valid.
5. *Resources*: qubits, CNOTs, arbitrary rotations, a T-count estimate and the expected cost per successful preparation.

We then apply it to the open J_1–J_2 Heisenberg chain using DMRG, validate the certificate by statevector simulation for $N \leq 14$, and report resources for $N \leq 48$. The code is the `sbpipe` package in the accompanying repository; every number below is produced by the scripts named in Appendix B.

The contribution is methodological and quantitative rather than algorithmic: the filter is SBC's, the Trotter bounds are those of Childs *et al.* [2], and the certificate follows the standard triangle-inequality argument. What is new is a generic interface whose guarantees are stated in terms of the inputs, a closed-form "dyadic" energy schedule with $O(\Delta^{-1} \log \eta^{-1})$ total time, and a calibrated account of what this costs and where the bound is loose for a concrete, physically relevant model.




FIG. 1. The pipeline. Blue: inputs, which any classical method can supply. Grey: the stages of `refine()`. Green: the optional statevector check used in Sec. III B.

II. THE PIPELINE

A. Inputs and the spectral window

The Hamiltonian is $H = \sum_a c_a P_a$ with real c_a and Pauli strings P_a, in a fixed order that is also the Trotter order, and with an optional grouping of terms (here: one group per bond). The pipeline assumes

$$\begin{aligned} E_0 &\in [E_0^{\text{est}} - \delta E_0,\ E_0^{\text{est}} + \delta E_0], \\ E_1 &\ge E_1^{\text{est}} - \delta E_1, \qquad E_{\text{top}} \le E_{\max}, \end{aligned} \tag{1}$$

where E_1 is the lowest level above the ground space that the trial state can overlap with. If no $E_{\max}$ is given, the Weyl bound $E_{\max} = \sum_g \lambda_{\max}(h_g)$ over the term groups h_g is used; it is rigorous and, for the antiferromagnetic J_1–J_2 chain, attained by the ferromagnetic state. With $s = E_0^{\text{est}} - \delta E_0$ and $W = E_{\max} - s$, the scaled Hamiltonian $H_s = (H - s)/W$ has its ground energy in the *pass band* $[0, w_0]$, $w_0 = 2\delta E_0/W$, and every other relevant level in the *stop band* $[\Delta, 1]$, $\Delta = (E_1^{\text{est}} - \delta E_1 - s)/W$.

The ansatz enters through γ, a lower estimate of its weight on the ground space, and through the gate cost of the circuit that prepares it. A statevector is needed only for validation.

B. The filter and three schedules

One SBC pulse [1] applies $\mathsf{H}_a\, e^{-itH_s \otimes Z_a}\, R_z^{(a)}(2\phi)\, \mathsf{H}_a$ to the system and an ancilla in $|0\rangle$; the ancilla-$|0\rangle$ block of this unitary is $\cos(H_s t + \phi)$. (SBC write the same block with $e^{-i(tH+\delta)\otimes Y_a}$.) Keeping outcome 0 after m pulses applies

$$F(H_s) = \prod_{i=1}^{m} \cos(H_s t_i + \phi_i), \qquad T = \sum_i |t_i|. \tag{2}$$

Two numbers characterize a filter: the pass-band floor $F_{\text{pass}} \le \min_{[0,w_0]} |F|$ and the suppression ratio $\eta = \sup_{[\Delta,1]} |F|/F_{\text{pass}}$. Both are certified, not sampled: since $|F'| \le L := \sum_i |t_i|$ and $|F''| \le L^2$, an interval branch-and-bound gives a rigorous upper bound on $\sup |F|$ over the stop band, and $F_{\text{pass}} = |F(0)| - Lw_0$ (the certifier is `floor.certify` of the repository; it is used for the optimized schedule, the other two have closed-form certificates). Given a target leakage ϵ_ℓ and γ, the design target is $\eta^2 \le \gamma\epsilon_\ell/[(1-\epsilon_\ell)(1-\gamma)]$ (Lemma 1). We provide three schedules:

Uniform: m equal pulses $t = \pi/(1+\Delta)$, $\phi = 0$, so $F = \cos^m(Et)$ and $\sup_{[\Delta,1]} |\cos Et| = \cos\theta$, $\theta = \pi\Delta/(1+\Delta)$. Then $m \approx 2\ln(1/\eta)/\theta^2$ and $T \approx 2\ln(1/\eta)/(\pi\Delta^2)$: quadratic in the inverse gap. It is the baseline that any design should beat.

Dyadic: r repetitions of the halving ladder $t = \tau, 2\tau, \ldots, 2^{K-1}\tau$, $\tau = \pi/(1+\Delta)$, $\phi = 0$. This is the schedule SBC use for quantum-number projection [1], here applied to the energy. One block is a Dirichlet kernel,

$$\prod_{k=0}^{K-1} \cos(2^k E\tau) = \frac{\sin(2^K E\tau)}{2^K \sin(E\tau)}, \tag{3}$$

which equals 1 at $E = 0$ and is at most $\eta_b = 1/(2^K \sin\theta)$ on $[\Delta, 1]$ because $\sin(E\tau) \ge \sin\theta$ there. With $r = \lceil \ln\eta / \ln\eta_b \rceil$ blocks, $T = r\tau(2^K - 1)$; choosing $2^K \sin\theta \approx e$ gives

$$T_{\text{dyadic}} \approx \frac{e\,\tau}{\sin\theta} \ln\frac{1}{\eta} \ \approx\ \frac{e}{\Delta} \ln\frac{1}{\eta}, \tag{4}$$

the optimal $O(\Delta^{-1} \log\eta^{-1})$ scaling [7] with an explicit constant and no optimization. The pipeline searches K and r for the smallest T. Both closed-form schedules are certified by the inequalities just given (with $F_{\text{pass}} = \cos^m(w_0 t)$ and $1 - Lw_0$, respectively), which avoids interval arithmetic on filters with $L \sim 10^3$–10^5; the test suite checks them against a 2×10^6-point grid.

Optimized: times and phases chosen to maximize $F(0)^2$ subject to the certified constraint on η at fixed (T, m), over a grid of $x = T\Delta/\pi$ and $m \in \{4, 6, 8\}$, picking the pair with the smallest $T^2/F(0)^2$. This is SBC's recipe for energy filters [1] with a certified constraint in place of a grid objective; it uses the SLSQP designer `floor.py` of the repository. Nonzero phases trade success probability ($F(0) < 1$) for a shorter T.

For each schedule the leakage share $\epsilon_\ell/\epsilon \in \{0.5, 0.25, 0.1, 0.05\}$ is scanned and the plan with the smallest expected CNOT count per success is kept. An "auto" mode does the same over the dyadic and optimized schedules together.

C. Trotterization

Each controlled evolution $e^{-it_i H_s \otimes Z_a}$ is approximated by k_i steps of the first-order (Lie) or second-order (Strang) product formula over the non-identity terms; the identity term of H_s becomes a single ancilla R_z per pulse and is exact. For $B_a = \sum_{b>a} H_b$ the bounds of Childs *et al.* [2, Props. 15–16] are

$$\|S_1(t) - e^{-itH}\| \le \tfrac{t^2}{2}\alpha_1, \quad \alpha_1 = \textstyle\sum_a \|[B_a, H_a]\|, \tag{5}$$

$$\|S_2(t) - e^{-itH}\| \le t^3\beta_2, \quad \beta_2 = \tfrac{1}{12}\textstyle\sum_a \|[B_a,[B_a,H_a]]\| + \tfrac{1}{24}\textstyle\sum_a \|[H_a,[H_a,B_a]]\|, \tag{6}$$

so k steps over time t cost $\alpha_1 t^2/(2k)$ or $\beta_2 t^3/k^2$. Tensoring every term with Z_a leaves α_1 and β_2 unchanged because $Z_a^2 = 1$. For Pauli strings $[P_b, P_a] = 2P_bP_a$ when they anticommute and 0 otherwise, so each commutator is a short Pauli sum supported on a few qubits around term a; we evaluate its norm exactly on that support (dense for ≤ 8 qubits, Lanczos up to 12, triangle inequality beyond, which never occurred here). The constants are maximized over the forward and reversed term order, so they hold for either convention. A common step size, $k_i = \lceil t_i/\delta t \rceil$, minimizes $\sum_i k_i$ for both orders at a given error budget (a Lagrange argument), and leaves the certified times untouched.

D. The certificate

Theorem 1. *Assume (1) and that the trial state has ground-space weight at least γ. Let the designed filter have certified η and F_{pass}, let ϵ_U bound the operator-norm error of the implementation (Trotter error $\sum_i \epsilon_i$ plus $R\delta$ for the R arbitrary rotations of the trial and filter circuits, each synthesized to accuracy δ), and let*

$$\ell = \frac{(1-\gamma)\eta^2}{\gamma + (1-\gamma)\eta^2}, \qquad p_g = \gamma F_{\text{pass}}^2. \tag{7}$$

Then, conditioned on the ancilla outcomes 0, the prepared state $\tilde{\rho}$ satisfies

$$D(\tilde{\rho}, \Pi_0) \le \sqrt{\ell} + \frac{\epsilon_U}{\sqrt{p_g}}, \qquad 1 - F \le D^2, \tag{8}$$

where D is the trace distance to the normalized projection of the trial state on the ground space, $\langle H\rangle - E_0 \le (E_{\text{top}} - E_0)D^2$, and the success probability is at least $(\sqrt{p_g} - \epsilon_U)^2$.

The proof (Appendix A) combines a leakage lemma for the exact filter with the observation that a vector error ϵ_U on an unnormalized vector of norm at least $\sqrt{p_g}$ moves its direction by at most $\epsilon_U/\sqrt{p_g}$. The pipeline sets the budget $\epsilon_U \le (\sqrt{\epsilon} - \sqrt{\ell})\sqrt{p_g}$, gives 90% of it to the product formula and the rest to rotation synthesis. If the trial state already satisfies $1 - \gamma \le \epsilon$, the pipeline also offers the empty filter ($\eta = 1$, no post-selection, $\ell = 1-\gamma$) and keeps whichever plan is cheaper.

E. Resource model

All-to-all connectivity and the Clifford+R_z gate set are assumed. A term $cP \otimes Z_a$ with $|P| = w$ is a weight-$(w+1)$ Pauli rotation: $2w$ CNOTs in a ladder and one R_z. A Lie step costs one rotation per term; k Strang steps cost $k(2\Gamma - 2) + 1$ rotations for Γ terms because the two middle half-steps and the outer half-steps of adjacent steps merge. Each pulse adds one ancilla R_z. An arbitrary rotation at accuracy δ costs $3\log_2(1/\delta)$ T gates, the leading term of Ross–Selinger synthesis [11]. The cost of one attempt is the trial circuit plus the filter, and the expected cost per success is the attempt cost divided by the success probability, which we bound below by p_g (repeat-until-success; an early-abort protocol that measures after each pulse would be cheaper and is not modeled). The ladder CNOT count is an upper bound: qiskit's synthesis shares CNOTs between the XX, YY, ZZ terms of a bond and needs 8 instead of 12 per controlled bond per Lie step (checked in the test suite), so CNOT numbers below can be read as upper bounds that a compiler lowers by about one third.

III. APPLICATION: J_1–J_2 CHAIN WITH DMRG

A. Model and front end

We study the open spin-$\frac{1}{2}$ chain

$$H = J_1 \sum_{i=1}^{N-1} \mathbf{S}_i \cdot \mathbf{S}_{i+1} + J_2 \sum_{i=1}^{N-2} \mathbf{S}_i \cdot \mathbf{S}_{i+2}, \tag{9}$$

$J_1 = 1$, at $J_2 = 0$ (Heisenberg), $J_2 = 0.2411$ (close to the critical point of the gapless-to-dimerized transition [13, 14]) and $J_2 = 0.4$ (dimerized), for $N = 8$ to 48. Its Pauli form has $3(2N-3)$ terms of weight 2. Terms are ordered by bond: nearest-neighbor bonds with even then odd left site, then next-nearest-neighbor bonds likewise.

The front end (`sbpipe/frontends/dmrg_quimb.py`) builds the MPO from the Pauli sum and runs two-site DMRG (quimb [15]) with bond dimensions up to 256 ($N \le 24$) or 128 ($N > 24$) and truncation cutoff 10^{-12}. E_1 is the lowest state of $H + \mu(S^z_{\text{tot}} - 1)^2$, $\mu = 2$, i.e. the lowest triplet. The error bars $\delta E_0, \delta E_1$ are the energy change between the last two bond dimensions, floored at 10^{-10}; they are convergence heuristics, not bounds. The trial state is the variationally optimal MPS at fixed bond dimension $\chi \in \{1, 2, 4, 8\}$, and γ is its overlap with the reference MPS. An MPS of bond dimension 2^b is exactly a staircase of $N - b$ unitaries on $b + 1$ qubits; we cost each with the quantum Shannon decomposition bound $\frac{23}{48}4^n - \frac{3}{2}2^n + \frac{4}{3}$ CNOTs (3, 20, 100 for $n = 2, 3, 4$) [12] and $4^n - 1$ rotations.

For $N \le 14$ we compare with exact diagonalization (ED). DMRG reproduces E_0 to 2.3×10^{-11}, the first excited level of any symmetry to 2.4×10^{-11} (so the first

TABLE I. DMRG inputs: ground energy, gap $E_1 - E_0$ and trial overlap γ of the optimal bond-dimension-χ MPS. Source: `results/inputs.json`.

N	J_2	E_0	gap	$\gamma_{\chi=1}$	γ_2	γ_4	γ_8
8	0	-3.374933	0.3927	0.134	0.775	0.999	1.0000
12	0	-5.142091	0.2809	0.060	0.591	0.994	1.0000
16	0	-6.911737	0.2193	0.028	0.475	0.984	0.9999
24	0	-10.453786	0.1530	0.006	0.328	0.954	0.9994
32	0	-13.997316	0.1177	0.001	0.234	0.913	0.9978
48	0	-21.085956	0.0809	0.000	0.125	0.817	0.9902
8	0.2411	-3.135001	0.3859	0.113	0.904	1.000	1.0000
12	0.2411	-4.738077	0.2720	0.046	0.806	1.000	1.0000
16	0.2411	-6.343316	0.2100	0.019	0.703	0.998	1.0000
24	0.2411	-9.556221	0.1443	0.003	0.517	0.989	0.9997
32	0.2411	-12.770432	0.1099	0.001	0.373	0.972	0.9989
48	0.2411	-19.200243	0.0744	0.000	0.191	0.920	0.9946
8	0.4	-3.025191	0.4037	0.036	0.976	1.000	1.0000
12	0.4	-4.545626	0.2956	0.003	0.945	1.000	1.0000
16	0.4	-6.066666	0.2371	0.000	0.911	0.999	1.0000
24	0.4	-9.109325	0.1748	0.000	0.839	0.995	0.9998
32	0.4	-12.152237	0.1418	0.000	0.768	0.990	0.9995
48	0.4	-18.238247	0.1075	0.000	0.640	0.976	0.9981

excitation is the triplet in every ED case, as also found for $N \leq 16$ in Ref. [17]), and the trial overlaps to 4.0×10^{-8} (largest difference, for a $\chi = 1$ trial). The Weyl bound equals the exact top of the spectrum to 1.2×10^{-14}. Table I lists the inputs. The trial overlap decays roughly exponentially with N at fixed χ, the familiar orthogonality catastrophe, so the filter has more to do at larger N.

B. Validation of the certificate ($N \leq 14$)

For $N \in \{8, 10, 12, 14\}$, the three couplings, $\epsilon \in \{10^{-2}, 10^{-3}\}$, the three schedules and both Trotter orders we plan a circuit for the $\chi = 2$ trial state and, when its size permits, simulate it exactly: the ancilla-0 block of the Trotterized circuit is $\frac{1}{2}(e^{-i\phi}S(t) + e^{i\phi}S(-t))$ per pulse, applied to the trial statevector and compared with the ED ground state. Of 144 plans, 96 were simulated (the others, mostly uniform or first-order plans with 10^4–10^8 steps, exceed our simulation budget), and the certificate held in all 96 (Fig. 2).

The bound is conservative by a median factor 17 (range 2–4.0×10^5) in infidelity. Splitting it shows where: the leakage term ℓ overestimates the exact filter's infidelity by a median 4.5× (range 1.1–134063). By schedule the medians are 1.4 (optimized), 4 (uniform) and 56 (dyadic): the optimized design pushes $|F|$ to ηF_{pass} across the band, whereas the closed-form dyadic bound $1/(2^K \sin\theta)$




FIG. 2. All simulated plans. (a) Measured infidelity of the planned circuit divided by the target ϵ (the certified bound is $\leq \epsilon$ by construction); points are offset horizontally by schedule and order. (b) Measured distance between the Trotterized and the exact filtered state against its certified bound. Points below the dashed lines respect the bound. Filled circles: second order; open squares: first order.




FIG. 3. $|F(E)|$ of the three schedules for $N = 12$, $J_2 = 0.2411$, $\epsilon = 10^{-2}$, second order. Dotted lines: certified ηF_{pass}. Grey: the gap region. The horizontal axis is linear below Δ and logarithmic above.

is reached only near the band edge. More generally, η is a worst case over the whole stop band while the trial state's excited weight sits mostly low in the band. The Trotter term overestimates the measured Trotter distance by a median 188× (range 26–4.5×10^3), consistent with earlier findings for this model [17]: commutator bounds are worst-case over all states, while the filtered state lives in the low-energy subspace, where Trotter errors are much smaller [16]. The measured success probability equals p_g to two digits in every case, because after filtering almost all of the surviving norm is ground-state weight.

Table II compares the schedules for one case. The uniform filter needs a total time an order of magnitude larger than the others, as its Δ^{-2} scaling predicts. The optimized filter is shortest; its nonzero phases lower p_g (0.58 against 0.81 here), which the cost criterion accounts for. Second order cuts the step count by one to two orders of magnitude at these sizes. Figure 3 shows the three filter functions.

How much of the remaining gap could a better bound

TABLE II. Plans for $N = 12$, $J_2 = 0.2411$, $\chi = 2$ trial. $T_{\rm phys} = T/W$ in units of $1/J_1$; CNOT and T counts per attempt (filter) and expected per success (trial + filter, divided by p_g). "meas.": simulated infidelity of the planned circuit. Source: `results/validate.json`.

ϵ	schedule	order	m	$T_{\rm phys}$	p_g	steps	CNOT (filter)	CNOT/success	T/success	meas. $1-F$
1×10^{-2}	uniform	1	437	164.2	0.81	4,136,205	1.0×10^{9}	1.3×10^{9}	3.5×10^{10}	–
1×10^{-2}	uniform	2	437	164.2	0.81	17,043	8.5×10^{6}	1.0×10^{7}	2.3×10^{8}	7.6×10^{-4}
1×10^{-2}	dyadic	1	10	23.3	0.81	77,308	1.9×10^{7}	2.4×10^{7}	5.4×10^{8}	–
1×10^{-2}	dyadic	2	10	23.3	0.81	884	4.4×10^{5}	5.4×10^{5}	9.9×10^{6}	8.5×10^{-7}
1×10^{-2}	optimized	1	6	8.7	0.58	13,384	3.4×10^{6}	5.8×10^{6}	1.2×10^{8}	1.1×10^{-3}
1×10^{-2}	optimized	2	6	8.7	0.58	226	1.1×10^{5}	1.9×10^{5}	3.3×10^{6}	1.1×10^{-3}
1×10^{-3}	uniform	1	745	279.9	0.81	27,817,555	7.0×10^{9}	8.7×10^{9}	2.6×10^{11}	–
1×10^{-3}	uniform	2	658	247.2	0.81	55,930	2.8×10^{7}	3.4×10^{7}	8.3×10^{8}	–
1×10^{-3}	dyadic	1	15	34.9	0.81	536,160	1.4×10^{8}	1.7×10^{8}	4.3×10^{9}	–
1×10^{-3}	dyadic	2	15	34.9	0.81	2,835	1.4×10^{6}	1.7×10^{6}	3.6×10^{7}	2.5×10^{-9}
1×10^{-3}	optimized	1	8	14.4	0.67	80,421	2.0×10^{7}	3.0×10^{7}	7.1×10^{8}	–
1×10^{-3}	optimized	2	8	14.4	0.67	709	3.5×10^{5}	5.2×10^{5}	1.0×10^{7}	6.2×10^{-5}

TABLE III. Certified over oracle step count (second order, $\chi = 2$). Columns: $N = 8, 10, 12$ for each J_2. Source: `results/oracle.json`.

		$J_2=0$			$J_2=0.2411$			$J_2=0.4$		
ϵ	schedule	8	10	12	8	10	12	8	10	12
1×10^{-2}	dyadic	14	22	30	24	24	34	18	15	28
1×10^{-2}	optimized	9	12	13	14	15	21	11	12	12
1×10^{-3}	dyadic	22	24	39	31	36	39	20	27	28
1×10^{-3}	optimized	12	17	21	24	22	27	14	16	17

recover? For $N \le 12$ we bisect a common scale factor on the certified k_i until the simulated infidelity just meets ϵ. The certified step count is 8.7–39× (median 21) larger than this oracle value (Table III). The oracle uses the exact ground state and is not a usable rule; it measures the price of certification at second order.

C. Resources up to $N = 48$

Without simulation the pipeline only needs DMRG, so we plan for N up to 48 with the same $\chi = 2$ trial family (Fig. 4, Table IV). Over all sizes, couplings and targets the second-order plan is 16–661× (median 92) cheaper than the first-order plan of the same schedule. The optimized schedule is 0.7–3.7× (median 2.9) cheaper than the dyadic one at second order, and more expensive in 1 of 29 comparable cases. Its numerical design, however, failed in 14 of 144 plans, all at $N \ge 32$ where $\gamma \lesssim 0.4$ or $\epsilon = 10^{-3}$ demand a suppression η the SLSQP search with $F(0)^2 \ge 10^{-3}$ did not reach; the dyadic schedule is feasible everywhere, which is why the pipeline offers an automatic choice between the two. For $N = 16$–48 the expected CNOT count of the dyadic second-order plan grows as $N^{4.8}$, $N^{5.0}$ and $N^{3.5}$ for $J_2 = 0, 0.2411, 0.4$, and its step count as $N^{2.6}$, $N^{2.7}$, $N^{2.1}$. These exponents combine the shrinking gap ($T \propto 1/\Delta$, and $\Delta = g/W$ with $W \propto N$), the growing commutator constant, the number of terms per step and the decaying overlap ($1/p_g$); they are fits over $N = 16$–48, not asymptotic statements. At $N = 48$, $J_2 = 0.2411$ the best $\chi = 2$ plan (dyadic) needs 4.8×10^{8} CNOTs per success, which the next section reduces by choosing a better trial.

D. What if the energy estimates are wrong?

The certificate is only as good as its inputs, so we perturb them for $N = 12$, $J_2 = 0.2411$, $\epsilon = 10^{-2}$ (optimized, second order) and simulate the resulting circuit on the true trial state (Fig. 5).

Gap. A gap assumed larger than the true one moves the stop-band edge above the first excitation, which then sits in the filter's transition region. The target was missed in 3 cases, $f \ge 1.5$, with infidelity up to 5.1×10^{-2} at $f = 3$; at $f = 1.1$ and 1.25 the looseness of the certificate still covered the error. Underestimating the gap is safe and cheap: even $f = 0.5$ costs only 2.8×. Since DMRG gives an *upper* bound on E_1, an explicit margin δE_1 is the natural safeguard.

Ground energy. An error bar δE_0 widens the pass band and lowers $F_{\rm pass}$; the cost stays flat until δE_0 is a sizeable fraction of the gap (14.1× at $\delta E_0 = 0.1$ gap). DMRG energies are far more accurate than this, so E_0 is never the limiting input here.

Overlap. Underestimating γ is safe (a stricter η); the




FIG. 4. Expected CNOTs per successful preparation versus N (trial $\chi = 2$, $\epsilon = 10^{-2}$), including the trial circuit and the $1/p_g$ repetitions. Solid: second order; dashed: first order. Missing optimized points: no feasible design (see text). Source: `results/scaling.json`.

TABLE IV. Cheapest second-order plan ("sch.": dyadic or optimized) for $\epsilon = 10^{-2}$, trial $\chi = 2$. Δ is the scaled gap, $T_{\text{phys}} = T/W$ in $1/J_1$. Steps for first (1st) and second (2nd) order with the same schedule; CNOT and T counts for second order. Source: `results/scaling.json`.

N	J_2	γ	Δ	sch.	T_{phys}	p_g	steps (1st)	steps (2nd)	CNOT/attempt	CNOT/success	T/success
16	0	0.475	0.0206	opt.	14.3	0.38	38,020	464	1.6×10^5	4.2×10^5	7.5×10^6
16	0.2411	0.703	0.0192	opt.	15.0	0.58	41,572	521	3.6×10^5	6.2×10^5	1.1×10^7
16	0.4	0.911	0.0211	opt.	7.9	0.64	19,266	266	1.8×10^5	2.8×10^5	5.0×10^6
24	0	0.328	0.0094	opt.	20.5	0.27	251,160	1,422	7.7×10^5	2.9×10^6	5.8×10^7
24	0.2411	0.517	0.0087	opt.	16.3	0.29	248,256	1,329	1.4×10^6	4.8×10^6	1.0×10^8
24	0.4	0.839	0.0102	opt.	13.5	0.65	87,533	740	7.9×10^5	1.2×10^6	2.3×10^7
32	0	0.234	0.0054	opt.	80.0	0.23	3,103,919	9,847	7.2×10^6	3.1×10^7	6.8×10^8
32	0.2411	0.373	0.0049	opt.	85.8	0.37	4,979,405	13,617	2.0×10^7	5.3×10^7	1.2×10^9
32	0.4	0.768	0.0062	opt.	16.6	0.44	221,517	1,305	1.9×10^6	4.4×10^6	8.8×10^7
48	0	0.125	0.0025	dya.	146.0	0.13	20,266,400	34,380	3.9×10^7	3.1×10^8	7.4×10^9
48	0.2411	0.191	0.0022	dya.	142.5	0.19	27,888,279	41,586	9.2×10^7	4.8×10^8	1.2×10^{10}
48	0.4	0.640	0.0031	dya.	69.3	0.64	4,816,485	12,414	2.8×10^7	4.3×10^7	9.9×10^8

planned cost rises 9.2× at $f = 0.25$, mostly because the planned success probability $p_g = \gamma F_{\text{pass}}^2$ uses the pessimistic γ, while the actual success rate does not change. Overestimating it by 2% did not break the target here (0 failures), because the leakage term is itself loose.

E. Choosing the ansatz

The trial bond dimension trades circuit depth for overlap. Figure 6 and Table V show the expected total cost for $\chi = 1$ to 8 (the pipeline choosing the cheaper of the dyadic and optimized schedules). A product state ($\chi = 1$) has an exponentially small overlap and is by far the most expensive start (10^7–10^{23} CNOTs). Going to $\chi = 2$ and $\chi = 4$ lowers the cost by orders of magnitude: at $N = 48$, $J_2 = 0.2411$ the $\chi = 4$ plan needs 8.8×10^6 CNOTs and 1.9×10^8 T gates per success. At $\chi = 8$ the trial state alone satisfies $1 - \gamma \leq 10^{-2}$ in 9 of 9 cases ($\gamma = 0.9946$ at $N = 48$, $J_2 = 0.2411$), and the pipeline returns the empty filter: 4,500 CNOTs. For this gapless-to-weakly-gapped one-dimensional chain at $\epsilon = 10^{-2}$, directly compiling a better MPS is therefore much cheaper than filtering a worse one, in agreement with earlier analyses of this model [17]. The filter becomes the better tool when the target is tighter than what a compilable MPS reaches, when a certificate on the output is required, or when the classical method cannot provide a compact high-overlap trial circuit, as for two-dimensional lattices.




FIG. 5. Sensitivity to the inputs ($N = 12$, $J_2 = 0.2411$, $\epsilon = 10^{-2}$). Circles: measured infidelity of the planned circuit on the true trial state. Squares: expected CNOT cost relative to the plan with exact inputs, multiplied by ϵ to share the axis. (a) Assumed gap $f\times$ the true gap; (b) error bar on E_0; (c) assumed overlap $f\times$ the true γ. Source: `results/sensitivity.json`.




FIG. 6. Expected CNOTs per success versus trial bond dimension ($\epsilon = 10^{-2}$, second order, cheaper of dyadic and optimized). Stars: the trial state alone satisfies $1 - \gamma \le \epsilon$ and no filter is used. Source: `results/ansatz.json`.

IV. DISCUSSION

What is guaranteed. Theorem 1 holds whenever its inputs are right. Of these, the spectral upper bound (Weyl), the filter certificate and the Trotter constants are rigorous here. The interval for E_0, the lower bound on E_1 and the overlap γ come from DMRG and are well-converged estimates, not bounds; for $N \le 14$ ED confirms them, beyond that the certificate is conditional. The gap is the critical input: an overestimated gap was the only input error that broke the target in our tests. Rigorous lower bounds on E_1 from classical data (e.g. Temple-type bounds from the energy variance) would make the guarantee unconditional and plug into the same interface.

Where the cost goes. The certified cost is dominated by the Trotter term, whose bound is a median 188× the measured Trotter distance; at the level of step counts the certified second-order plan uses 8.7–39× (median 21) more steps than needed. Second-order formulas recover most of the first-order looseness; bounds restricted to the low-energy subspace [16] or higher-order formulas are the obvious next lever. The leakage term is nearly tight for optimized filters (median 1.4×); for the closed-form schedules it could be tightened by certifying η numerically when L is small enough.

Is the filter worth it here? Not for this model at $\epsilon = 10^{-2}$: a $\chi = 8$ MPS circuit meets the target directly with between one and more than three orders of magnitude fewer CNOTs than the cheapest filtered plan (Table V). The filter's advantages are a certificate on the output and a cost that depends on the trial overlap only through $\ln(1/\eta)$ and $1/p_g$. The pipeline is generic in H, so the same comparison can be run for two-dimensional models where MPS compilation scales worse; we leave that to future work.

TABLE V. Overlap γ and expected CNOTs per success for trial bond dimension $\chi = 1, 2, 4, 8$ ($\epsilon = 10^{-2}$, second order, cheaper schedule; no filter when $1 - \gamma \le \epsilon$).

N	J_2	γ_1	CNOT	γ_2	CNOT	γ_4	CNOT	γ_8	CNOT
16	0	0.028	4.9×10^{7}	0.475	4.2×10^{5}	0.984	4.8×10^{4}	1.000	1.3×10^{3}
16	0.2411	0.019	2.3×10^{8}	0.703	6.2×10^{5}	0.998	2.8×10^{2}	1.000	1.3×10^{3}
16	0.4	0.000	1.4×10^{11}	0.911	2.8×10^{5}	0.999	2.8×10^{2}	1.000	1.3×10^{3}
32	0	0.001	4.9×10^{10}	0.234	3.1×10^{7}	0.913	8.2×10^{5}	0.998	2.9×10^{3}
32	0.2411	0.001	4.3×10^{11}	0.373	5.3×10^{7}	0.972	1.5×10^{6}	0.999	2.9×10^{3}
32	0.4	0.000	2.9×10^{17}	0.768	4.4×10^{6}	0.990	6.0×10^{2}	1.000	2.9×10^{3}
48	0	0.000	9.8×10^{12}	0.125	3.1×10^{8}	0.817	5.3×10^{6}	0.990	4.5×10^{3}
48	0.2411	0.000	1.6×10^{14}	0.191	4.8×10^{8}	0.920	8.8×10^{6}	0.995	4.5×10^{3}
48	0.4	0.000	5.3×10^{23}	0.640	4.3×10^{7}	0.976	3.1×10^{6}	0.998	4.5×10^{3}

Limitations. Noiseless simulation; repeat-until-success rather than early abort; ladder CNOT counts (an upper bound, about 1.5× a compiler's); all-to-all connectivity; trial circuits costed by a generic decomposition bound rather than compiled; validation only up to $N = 14$; the optimized designer can fail for small overlaps; E_1 is taken as the lowest $S^z = 1$ state, which is the first excitation in every ED case here but is an assumption for larger N.

Appendix A: Proof of Theorem 1

Write the trial state as $|\psi\rangle = \sqrt{\gamma'}|g\rangle + \sqrt{1-\gamma'}|\chi\rangle$ with $|g\rangle$ in the ground space (energy $e_0 \in [0, w_0]$ in scaled units), $|\chi\rangle$ orthogonal to it and $\gamma' \ge \gamma$.

Lemma 1 (leakage)**.** *For the exact filter, $v = F(H_s)|\psi\rangle$ has weight outside the ground space at most ℓ, and $\|v\|^2 \ge p_g$.*

Proof. $F(H_s)$ is a function of H_s, so $v = \sqrt{\gamma'}F(e_0)|g\rangle + \sqrt{1-\gamma'}F(H_s)|\chi\rangle$ with the two parts orthogonal. Every component of $|\chi\rangle$ has energy in $[\Delta, 1]$, so $\|F(H_s)\chi\| \le \sup_{[\Delta,1]}|F| \le \eta F_{\text{pass}} \le \eta|F(e_0)|$. The excited weight is $x/(a+x)$ with $a = \gamma' F(e_0)^2$, $x = (1-\gamma')\|F\chi\|^2 \le (1-\gamma')\eta^2 F(e_0)^2$; it is increasing in x and, after dividing by $F(e_0)^2$, decreasing in γ', which gives ℓ. Finally $\|v\|^2 \ge a \ge \gamma F_{\text{pass}}^2$. □

For pure states the trace distance is $\sin\angle$, so $D(\hat{v}, |g\rangle) = \sqrt{\ell'} \le \sqrt{\ell}$ ($\hat{v} = v/\|v\|$).

Lemma 2 (implementation error)**.** *Let $B_i = \frac{1}{2}(e^{-i\phi_i}\tilde{S}_i(t_i) + e^{i\phi_i}\tilde{S}_i(-t_i))$ be the ancilla-0 block of the implemented pulse and $C_i = \cos(H_s t_i + \phi_i)$. Then $\|\prod_i B_i - \prod_i C_i\| \le \epsilon_U$.*

Proof. $C_i = \frac{1}{2}(e^{-i\phi_i}e^{-it_iH_s} + e^{i\phi_i}e^{it_iH_s})$, so $\|B_i - C_i\| \le \frac{1}{2}(\|\tilde{S}_i(t_i) - e^{-it_iH_s}\| + \|\tilde{S}_i(-t_i) - e^{it_iH_s}\|) \le \epsilon_i$, where ϵ_i is the product-formula bound (symmetric in the sign of t) plus the synthesis error of the pulse's rotations. Since $\|B_i\|, \|C_i\| \le 1$, telescoping gives $\|\prod B_i - \prod C_i\| \le \sum_i \epsilon_i$. A synthesized trial circuit prepares $|\tilde{\psi}\rangle$ with $\|\tilde{\psi} - \psi\| \le R_{\text{trial}}\delta$, and $\|\prod B_i\| \le 1$, so the total error of the unnormalized output is at most ϵ_U. □

With $\tilde{v} = \prod B_i|\tilde{\psi}\rangle$, $\|\tilde{v} - v\| \le \epsilon_U$. The distance from v to the line through $\tilde{v}$ is at most $\|v - \tilde{v}\|$, so $\sin\angle(v, \tilde{v}) \le \epsilon_U/\|v\| \le \epsilon_U/\sqrt{p_g}$. The triangle inequality for the trace distance gives (8). The success probability is $\|\tilde{v}\|^2 \ge (\|v\| - \epsilon_U)^2 \ge (\sqrt{p_g} - \epsilon_U)^2$. For the energy, the normalized state has weight at least $1 - D^2$ on the ground space and at most D^2 on levels $\le E_{\text{top}}$, so $\langle H\rangle - E_0 \le (E_{\text{top}} - E_0)D^2$. □

Appendix B: Reproducing the results

`python sbpipe_study/run_study.py all` runs the DMRG front end (cached), the validation (A), scaling (B), sensitivity (C), ansatz (D) and oracle (E) studies and writes `results/*.json`; `python sbpipe_study/make_figures.py` writes every figure, table and the numerical macros used in this text. `python -m pytest sbpipe/tests` runs the component checks (Pauli algebra, Weyl bound, Trotter bounds against dense matrix exponentials, the Dirichlet identity (3), filter certificates against a dense grid, gate counts against an explicit merged sequence and against qiskit, and an end-to-end certificate check).

[1] I. Stetcu, A. Baroni, and J. Carlson, Projection algorithm for state preparation on quantum computers, Phys. Rev. C **108**, L031306 (2023), arXiv:2211.10545.

[2] A. M. Childs, Y. Su, M. C. Tran, N. Wiebe, and S. Zhu, Theory of Trotter error with commutator scaling, Phys. Rev. X **11**, 011020 (2021).

[3] S. R. White, Density matrix formulation for quantum renormalization groups, Phys. Rev. Lett. **69**, 2863 (1992).

[4] U. Schollwöck, The density-matrix renormalization group in the age of matrix product states, Ann. Phys. **326**, 96 (2011).

[5] S.-J. Ran, Encoding of matrix product states into quantum circuits of one- and two-qubit gates, Phys. Rev. A **101**, 032310 (2020).

[6] Y. Ge, J. Tura, and J. I. Cirac, Faster ground state preparation and high-precision ground energy estimation with fewer qubits, J. Math. Phys. **60**, 022202 (2019).

[7] L. Lin and Y. Tong, Near-optimal ground state preparation, Quantum **4**, 372 (2020).

[8] A. Gilyén, Y. Su, G. H. Low, and N. Wiebe, Quantum singular value transformation and beyond, in *Proc. STOC 2019*, p. 193.

[9] Y. Dong, L. Lin, and Y. Tong, Ground-state preparation and energy estimation on early fault-tolerant quantum computers via quantum eigenvalue transformation of unitary matrices, PRX Quantum **3**, 040305 (2022).

[10] K. Choi, D. Lee, J. Bonitati, Z. Qian, and J. Watkins, Rodeo algorithm for quantum computing, Phys. Rev. Lett. **127**, 040505 (2021).

[11] N. J. Ross and P. Selinger, Optimal ancilla-free Clifford+T approximation of z-rotations, Quantum Inf. Comput. **16**, 901 (2016).

[12] V. V. Shende, S. S. Bullock, and I. L. Markov, Synthesis of quantum-logic circuits, IEEE Trans. Comput.-Aided Des. **25**, 1000 (2006).

[13] K. Okamoto and K. Nomura, Fluid-dimer critical point in $S = 1/2$ antiferromagnetic Heisenberg chain with next nearest neighbor interactions, Phys. Lett. A **169**, 433 (1992).

[14] S. Eggert, Numerical evidence for multiplicative logarithmic corrections from marginal operators, Phys. Rev. B **54**, R9612 (1996).

[15] J. Gray, quimb: a python package for quantum information and many-body calculations, J. Open Source Softw. **3**, 819 (2018).

[16] B. Şahinoğlu and R. D. Somma, Hamiltonian simulation in the low-energy subspace, npj Quantum Inf. **7**, 119 (2021).

[17] Earlier analysis of the certified filter for this model in the same repository: `j1j2_filter/WRITEUP.md` and `simple_paper/paper.md`.