

```
1 """
2 Django settings for btre project.
3
4 Generated by 'django-admin startproject' using Django 3.2.14.
5
6 For more information on this file, see
7 https://docs.djangoproject.com/en/3.2/topics/settings/
8
9 For the full list of settings and their values, see
10 https://docs.djangoproject.com/en/3.2/ref/settings/
11 """
12 import os
13 from pathlib import Path
14
15 # Build paths inside the project like this: BASE_DIR / 'subdir'.
16 BASE_DIR = Path(__file__).resolve().parent.parent
17
18
19 # Quick-start development settings - unsuitable for production
20 # See https://docs.djangoproject.com/en/3.2/howto/deployment/checklist/
21
22 # SECURITY WARNING: keep the secret key used in production secret!
23 SECRET_KEY = 'django-insecure-ua$(^$@^g8@i+v&cts-
24 _8ly%^96@8#+ix5lpk4g8ggbf7subq+'
25
26 # SECURITY WARNING: don't run with debug turned on in production!
27 DEBUG = True
28
29 ALLOWED_HOSTS = []
30
31 # Application definition
32 # put a callback function
33 INSTALLED_APPS = [
34     'pages.apps.PagesConfig',
35     'django.contrib.admin',
36     'django.contrib.auth',
37     'django.contrib.contenttypes',
38     'django.contrib.sessions',
39     'django.contrib.messages',
40     'django.contrib.staticfiles',
41 ]
42
43 MIDDLEWARE = [
44     'django.middleware.security.SecurityMiddleware',
45     'django.contrib.sessions.middleware.SessionMiddleware',
46     'django.middleware.common.CommonMiddleware',
47     'django.middleware.csrf.CsrfViewMiddleware',
48     'django.contrib.auth.middleware.AuthenticationMiddleware',
49     'django.contrib.messages.middleware.MessageMiddleware',
50     'django.middleware.clickjacking.XFrameOptionsMiddleware',
51 ]
52
53 ROOT_URLCONF = 'btre.urls'
54
55 TEMPLATES = [
56     {
57         'BACKEND': 'django.template.backends.django.DjangoTemplates',
58         'DIRS': [os.path.join(BASE_DIR, 'templates')],
```

```
59     'APP_DIRS': True,
60     'OPTIONS': {
61         'context_processors': [
62             'django.template.context_processors.debug',
63             'django.template.context_processors.request',
64             'django.contrib.auth.context_processors.auth',
65             'django.contrib.messages.context_processors.messages',
66         ],
67     },
68 },
69 ]
70
71 WSGI_APPLICATION = 'btre.wsgi.application'
72
73
74 # Database
75 # https://docs.djangoproject.com/en/3.2/ref/settings/#databases
76
77 DATABASES = {
78     'default': {
79         'ENGINE': 'django.db.backends.sqlite3',
80         'NAME': BASE_DIR / 'db.sqlite3',
81     }
82 }
83
84
85 # Password validation
86 # https://docs.djangoproject.com/en/3.2/ref/settings/#auth-password-validators
87
88 AUTH_PASSWORD_VALIDATORS = [
89     {
90         'NAME':
91         'django.contrib.auth.password_validation.UserAttributeSimilarityValidator',
92     },
93     {
94         'NAME':
95         'django.contrib.auth.password_validation.MinimumLengthValidator',
96     },
97     {
98         'NAME':
99         'django.contrib.auth.password_validation.CommonPasswordValidator',
100     },
101     {
102         'NAME':
103         'django.contrib.auth.password_validation.NumericPasswordValidator',
104     },
105 ]
106
107 # Internationalization
108 # https://docs.djangoproject.com/en/3.2/topics/i18n/
109
110 LANGUAGE_CODE = 'en-us'
111
112 TIME_ZONE = 'UTC'
113
114 USE_I18N = True
115
116 USE_L10N = True
```

```
114
115 USE_TZ = True
116
117
118 # Static files (CSS, JavaScript, Images)
119 # https://docs.djangoproject.com/en/3.2/howto/static-files/
120
121 STATIC_URL = '/static/'
122
123 # Default primary key field type
124 # https://docs.djangoproject.com/en/3.2/ref/settings/#default-auto-field
125
126 DEFAULT_AUTO_FIELD = 'django.db.models.BigAutoField'
127
```