

Dictionaries, Sets and Sorting

Introduction: Dictionaries for Paired Data

dicts pair unique keys with associated values.

Much of the data we use tends to be *paired*:

- **companies** paired with **annual revenue** for each
 - **employees** with **contact information** for each
 - **students** with **grade point averages**
 - **dates** with the **high temperature** for each
 - **web pages** with the **number of times** each was accessed
- To store paired data, we use a Python container called a *dict*, or dictionary. The dict contains *keys* paired with *values*.

```
customer_balances = { 'jk125': 493.95,      # spacing for clarity
                      'xx3': 122.03,
                      'jp9': 23238.72 }

print customer_balances      # { 'jk125': 493.95, 'xx3': 122.03, 'jp9'
print type(customer_balances) # <type 'dict'>
```

dicts have some of the same features as other containers. When standard container operations are applied, the *keys* are used:

```
print len(customer_balances)      # 3 keys in dict

print 'xx3' in customer_balances  # True:  the key is there

for yyy in customer_balances:
    print yyy                      # prints each key in customer_balance

print customer_balances['jp9']    # 23238.72
```

Introduction: Set comparisons

set operations

```
a = set(['a', 'b', 'c'])
b = set(['b', 'c', 'd'])
print a.difference(b)      # set(['a'])
print a.union(b)           # set(['a', 'b', 'c', 'd'])
print a.intersection(b)    # set(['b', 'c'])
```

Objectives for the Unit: Dictionaries and Sets

This *key/value pairs* container allows us to summarize data in powerful ways:

- Use a dict to store and report a value for each a unique collection of keys, such as date to price, contract to expiration, device to uptime, etc.
- Use a dict to take a "running sum" or "running count", such as summing up revenue by month (based on daily revenue data), counting the number of times a web page was visited, counting the number of error requests each month, etc.
- Use sets to do set comparisons (common, difference, unique, union, etc.)

Summary for Object: Dictionary (dict)

A dictionary (or *dict*) is an *unordered collection of unique key/value pairs* of objects.

The keys in a dict are *unordered* and *unique*. In this way it is like a **set**.

A dict key can be used to obtain the associated *value* ("addressable by key"). In this way it is like a **list** or **tuple** (which use an *integer index* to obtain a value).

initialize a dict

```
mydict = {}                                # empty dict

mydict = {'a':1, 'b':2, 'c':3}             # dict with str keys and int values
```

add a key/value pair to a dict

```
mydict['d'] = 4                # setting a new key and value  
  
print mydict                  # {'a': 1, 'c': 3, 'b': 2, 'd': 4}
```

read a value based on a key

```
dval = mydict['d']            # value for 'd' is 4  
  
xxx = mydict['c']             # value for 'c' is 3
```

Note in the standard container features below, only the *keys* are used:

loop through a dict and read keys and values

```
mydict = {'a': 1, 'b': 2, 'c': 3, 'd': 4}  
  
for key in mydict:  
    print key                # prints 'a', then 'c', then 'b', then 'd'
```

check for key membership

```
mydict = {'a': 1, 'b': 2, 'c': 3}  
  
if 'a' in mydict:  
    print "'a' is a key in mydict"
```

sort a dict's keys

```
mydict = {'xenophon': 10, 'abercrombie': 5, 'denusia': 3}

mykeys = sorted(mydict)           # ['abercrombie', 'denusia', 'xenophon']
```

retrieve list of keys or list of values

```
mydict = {'a': 1, 'b': 2, 'c': 3}

yyy = mydict.keys()               # ['a', 'c', 'b']

zzz = mydict.values()             # [1, 3, 2]
```

Summary dict Method: get()

The **dict get()** method returns a value based on a key. An optional 2nd argument provides a *default* value if the key is missing.

```
mydict = {'a': 1, 'b': 2, 'c': 3}

xx = mydict.get('a', 0)           # 1 (key exists so paired value is ret

yy = mydict.get('zzz', 0)         # 0 (key does not exist so default val
```

The default value is your choice.

This method is sometimes used as an alternative to testing for a key in a dict before reading it -- avoiding the **KeyError** exception that occurs when trying to read a nonexistent key.

Summary dict Methods: keys() and values()

`keys()` returns a list of keys; `values()` returns a list of values.

These methods are used for advanced manipulation of a **dict**.

dict keys() method returns a list of keys

```
mydict = {'a': 1, 'b': 2, 'c': 3}

yyy = mydict.keys()                # ['a', 'c', 'b']
```

We might want a list of a dict's keys for advanced manipulation of a dictionary. We can retrieve the list for sorting, for testing for membership, for checking length, BUT these can also be accomplished by using the dictionary directly: a dict used in a "listy" context always works with its keys.

dict values() method returns a list of values in the dict

```
zzz = mydict.values()              # [1, 3, 2]
```

This method, like, **keys()** is also less often used -- to test for membership or frequency among values, for example.

Container processing: Set Comparisons

We have used the **set** to create a unique collection of objects. The **set** also allows comparisons of sets of objects. Methods like **set.union** (complete member list of two or more sets), **set.difference** (elements found in this set not found in another set) and **set.intersection** (elements common to both sets) are fast and simple to use.

```
set_a = set([1, 2, 3, 4])
set_b = set([3, 4, 5, 6])

print set_a.union(set_b)           # set([1, 2, 3, 4, 5, 6]) (set_a + set_b)
print set_a.difference(set_b)      # set([1, 2])             (set_a - set_b)
print set_a.intersection(set_b)    # set([3, 4])             (what is common between set_a and set_b)
```

Summary Exception: KeyError

The **KeyError** exception indicates that the requested key does not exist in the dictionary.

```
mydict = {'a': 1, 'b': 2, 'c': 3}

xx = mydict['a']                # 1

yy = mydict['NARNAR']           # KeyError
```

The above code results in this exception:

```
Traceback (most recent call last):
  File "./keyerrortest.py", line 7, in
    yy = mydict['NARNAR']
KeyError: 'NARNAR'
```

As you can see, the line of code and the key involved in the error are displayed. If you get this error the debugging procedure should be to check to see first whether the key seems to be in the dict or not; if it is, you may want to check the type of the object, since string '1' is not the same as int 1. String case also matters when Python is looking for a key -- the object value must match the dict's key exactly.

One way to handle an error like this is to test the dict ahead of time using the **in** operator:

```
mydict = {'a': 1, 'b': 2, 'c': 3}

if 'NARNAR' not in mydict:
    yy = 0
else:
    yy = mydict['NARNAR']      # else block only executed
                              # if key NARNAR exists in the dict
```

Another approach is to use the **dict get()** method:

```
mydict = {'a': 1, 'b': 2, 'c': 3}

yy = mydict.get('a', 0)           # 1

zz = mydict.get('zzz', 0)         # 0
```

Summary Task: read and write to a dict

Subscript syntax is used to add or read key/value pairs. The dict's *key* is the key!

Note well: *the syntax is the same* for setting a key/value pair or getting a value based on a key.

Setting a key/value pair in a dict

```
mydict = {}
mydict['a'] = 1           # set a key and value in the dict
mydict['b'] = 2           # same

print mydict             # {'a': 1, 'b': 2}
```

Getting a value from a dict based on a key

```
val1 = mydict['a']        # get a value using a key: 1
val2 = mydict['b']        # get a value using a key: 2
```

Summary Task: Looping through a Dict with *for*

Looping through a dict means looping through its *keys*.

```
mydict = {'a': 1, 'b': 2, 'c': 3, 'd': 4}

for key in mydict:
    print key          # prints 'a', then 'c', then 'b', then 'd'
```

As with all standard container features (e.g. **in**, **for**, **sorted()**) the **in** operator test the **keys** of the dict.

Of course having a key means we can get the value -- here we loop through and print each key *and* value in the dict:

```
mydict = {'a': 1, 'b': 2, 'c': 3, 'd': 4}

for key in mydict:
    print "key: {}; value: {}".format(key, mydict[key])

    ### key: a; value 1
    ### key: c; value 3
    ### key: b; value 2
    ### key: d; value 4
```

Summary Task: Checking for Membership in a Dict with *in*

Checking membership in a dict means checking for the presence of a *key*.

```
mydict = {'a': 1, 'b': 2, 'c': 3}

if 'a' in mydict:
    print "'a' is a key in mydict"
```

As with all standard container features (e.g. **in**, **for**, **sorted()**) the **in** operator test the **keys** of the dict.

Summary Task: Dict Size with len()

len() counts the *pairs* in a dict.

```
mydict = {'a': 1, 'b': 2, 'c': 3}

if 'a' in mydict:
    print "'a' is a key in mydict"
```

Summary Task: Obtaining List of Keys, List of Values, List of key/value Items

keys(), **values()** return a list of objects; **items()** returns a list of *2-element tuples*.

keys(): return a list of keys in the dict

```
mydict = {'a': 1, 'b': 2, 'c': 3}

these_keys = mydict.keys()
print these_keys                    # ['a', 'c', 'b']
```

Of course once we have the keys, we can loop through and get the value for each key.

values(): return a list of values in the dict

```
these_values = mydict.values()
print these_values                    # [1, 3, 2]
```

The values cannot be used to get the keys - it's a one-way lookup from the keys. However, we might want to check for membership in the values, or sort the values, or some other less-used approach.

The dict `items()` method: pairs as a list of 2-element tuples

```
these_items = mydict.items()
print these_items                # [('a', 1), ('c', 3), ('b', 2)]
```

There are three elements here: three tuples. Each tuple contains two elements: a key and value pair from the dict. There are a number of reasons we might wish to use a structure like this -- for example, to sort the dictionary and store it in sorted form. As you know, a dictionary's keys are unordered, but a lists are not. A list of tuples can also be manipulated in other ways pertaining to a list. It is a convenient structure that is preferred by some developers as an alternative to working with the keys.

Review Summary Task: Sorting a Container with `sorted()`

With a list, tuple or set, **`sorted()`** returns a list of sorted elements

```
namelist = ['jo', 'pete', 'michael', 'zeb', 'avram']
slist = sorted(namelist)                # ['avram', 'jo', 'michael', 'pete', 'zeb']
```

Remember that no matter what container is passed to **`sorted()`**, the function returns list -- even a string!

Summary Task: Reversing a Sort

`reverse=True`, a special arg to **`sorted()`**, reverses the order of a sort.

```
namelist = ['jo', 'pete', 'michael', 'zeb', 'avram']
slist = sorted(namelist, reverse=True)  # ['zeb', 'pete', 'michael', 'jo', 'avram']
```

reverse is called a *keyword argument* -- it is no different from a regular *positional* arguments we have seen before; it is simply notated differently.

Summary Task: Sorting a Dict (sorting its *Keys*)

sorted() returns a sorted list of a dict's *keys*

```
bowling_scores = {'jeb': 123, 'zeb': 98, 'mike': 202, 'janice': 184}
keys = bowling_scores.keys()
keys.sort()
print keys                                # [ 'janice', 'jeb', 'mike', 'zeb' ]
for key in keys:
    print key + " = " + str(bowling_scores[key])
```

Or, we can even loop through the sorted dictionary keys directly:

```
bowling_scores = {'jeb': 123, 'zeb': 98, 'mike': 202, 'janice': 184}
for key in sorted(bowling_scores.keys()):
    print key + " = " + str(bowling_scores[key])
```

Summary Task: sorting a dictionary's keys by its values

The dict **get()** method returns a value based on a key -- perfect for sorting keys by values.

```

bowling_scores = {'jeb': 123, 'zeb': 98, 'mike': 202, 'janice': 184}

sorted_keys = sorted(bowling_scores, key=bowling_scores.get)

print sorted_keys          # ['zeb', 'jeb', 'janice', 'mike']

for player in sorted_keys:
    print "{} scored {}".format(player, bowling_scores[player])

    ## zeb scored 98
    ## jeb scored 123
    ## janice scored 184
    ## mike scored 202

```

Practical: Build Up a Dict from Two Fields in a File

As with all containers, we loop through a data source, select and add to a dict.

```

ids_names = dict()                                # initialize an empty
for line in open('student_db.txt'):
    id, address, city, state, zip = line.split(':') # note "multi-target
    ids_names[id] = state                          # key id is paired to

print "here are ids and names from the students.txt file: "
for id in ids_names:
    print "id " + id + " is from this state: " + ids_names[id]

print "here is the state for student 'jb29': "
print ids_names['jb29']                           # NJ

```

Practical: Build a "Counting" or "Summing" Dictionary

We can use a dict's keys and associated values to create an aggregation (correlating a sum or count to each of a collection of keys).

```

state_count = dict() # initialize an empty dict
for line in open('/Users/dblaikie/Desktop/python_data/student_db.txt'):
    items = line.split(':')
    state = items[3]
    if state not in state_count:
        state_count[state] = 0
    state_count[state] = state_count[state] + 1

print "here is the count of states from the students.txt file: "
for state in state_count :
    print "{}: {} occurrences".format(state, state_count[state])

print "here is the count for 'NY': "
print state_count['NY'] # 4

```

Practical: Build and Read a Dict of Lists

A list can be added to a dict just like any other object.

Here we're keying a dict to student id, and setting a list of the remaining elements as its value:

```

ids_data = dict() # initialize an empty dict
for line in open('student_db.txt'):
    item_list = line.split(':') # note "multi-target assignment" of 5 elements
    id = item_list[0]
    data = item_list[1:]
    ids_data[id] = data # key id is paired to student's state and names

print "here is the data for id 'jb29': ", ids_data['jb29'] #

```

Practical: Working with dict items()

dict items() produces a 2-element tuple;

```

mydict = {'a': 1, 'b': 2, 'c': 3}
these_items = mydict.items()
print these_items # [('a', 1), ('c', 3), ('b', 2)]

```

