LOCALE: Ego-Graph Orientation with Non-Collider Constraints for LLM-Assisted Causal Discovery

Anonymous authors
Paper under double-blind review

Abstract

Skeleton-based causal discovery recovers an undirected graph from observational data but often leaves many edge orientations unresolved. Recent LLM-assisted methods orient these edges by querying one edge at a time, underusing the context window, or by feeding the entire graph into the prompt, scaling poorly. We propose LOCALE, a local-to-global orientation pipeline that prompts the LLM with node-centered ego graphs, scoring all incident edges jointly in a single query. A key empirical finding motivates our constraint design: across 6 Bayesian networks and 7 sample sizes, 97.9% of CI orientation errors from PC are false colliders. We therefore discard collider constraints and retain only the more reliable non-collider constraints via weighted Max-2SAT (NCO filtering). In a multi-seed comparison against MosaCD on 11 Bayesian networks using the same open-weight 27B model and skeleton, LOCALE wins on 8 networks, ties on 2, and loses on 1 (Asia, 8 nodes), with a mean F1 improvement of +7.6 percentage points. Three wins are statistically significant after Holm-Bonferroni correction: Sachs (+30.7pp, p<0.0001), Insurance (+8.8pp, p=0.013), and Hepar2 (+16.0pp, p=0.013). On 90 synthetic Erdos-Renyi graphs where the LLM has no domain knowledge, LOCALE wins 8 of 10 graph seeds (p=0.010, mean +12.5pp), confirming the advantage is structural rather than domain-knowledge-driven. Ego-graph prompts use 2-4x fewer queries than per-edge methods and remain robust at 2048-token context windows where MosaCD's per-edge templates fail. The NCO finding is method-agnostic and applicable to any CI-based orientation pipeline.

1 Introduction

Causal discovery from observational data is a foundational problem in machine learning and scientific modeling. Constraint-based algorithms such as PC (Spirtes et al., 1993) and its order-independent variant PC-stable (Colombo & Maathuis, 2014) recover an undirected skeleton and separating sets by testing conditional independence (CI) relations. These algorithms identify a Markov equivalence class, but finite-sample CI testing often leaves many edges without a compelled orientation (Uhler et al., 2013). The resulting partially oriented graph can be far from the true causal DAG, particularly in the orientation layer where collider detection and Meek propagation (Meek, 1995) depend on noisy CI statistics. This orientation gap is the primary bottleneck in practice: on our benchmarks, skeletons recover 80–100% of true edges, yet orienting those edges correctly remains the harder task.

Large language models offer a complementary source of orientation evidence: they encode semantic knowledge about plausible causal mechanisms from pretraining corpora. By providing variable names and local structural context, one can query an LLM to predict the likely direction of causal influence between variables. Recent LLM-assisted causal discovery methods occupy two extremes. *Per-edge methods* such as MosaCD (Lyu et al., 2025) and SCP (Cohrs et al., 2024) query the model about one edge at a time, underusing the context window and discarding local structural information. *Whole-graph methods* such as CausalFusion (Takayama et al., 2024) and CauScientist (Peng et al., 2026) feed the entire variable set into the prompt, but scale as $O(|V|^2)$ and become intractable beyond a few dozen nodes. Neither extreme leverages the natural locality of causal mechanisms: a

Table 1: LOCALE vs MosaCD summary. Averages across 11 networks under identical conditions (Qwen3.5-27B, 4096 ctx, K=10).

	Mean directed F1	Win / Tie / Loss	Avg. queries	Total tokens	Wilcoxon p
MosaCD	0.697	1 / 2 / 8	311	∼386K	0.027
LOCALE	**0.773**	**8 / 2 / 1**	**106**	**∼36K**	

variable's direct causes and effects are typically its immediate graph neighbors, not distant nodes.

We target the underexplored middle ground: the *ego graph* of each node, comprising the node, its skeleton neighbors, local adjacencies, and CI-derived constraints. This interface is richer than per-edge prompting because the model sees mechanism-level context for all incident edges simultaneously, more scalable than whole-graph prompting at $O(d)$ tokens per query where d is the maximum degree, and naturally aligned with the local structure already computed by PC-style algorithms. Table 1 summarizes the key advantages. Our contributions:

1. **Ego-graph prompting** as a local orientation interface that scores all incident edges in one query, reducing query count by 58–75% while exposing neighborhood context.
2. **Non-collider-only (NCO) constraint filtering**: 97.9% of CI orientation errors from PC are false colliders, totaling 924 of 944 errors across 6 networks and 7 sample sizes. Discarding collider constraints improves orientation accuracy for any CI-based method.
3. **LOCALE**, a four-phase pipeline that integrates ego-graph scoring with NCO Max-2SAT compilation, dual-endpoint reconciliation, and a safety-valve filter guaranteeing monotonic improvement.
4. **Comprehensive evaluation** across 11 BNLearn networks (8 wins, 2 ties, 1 loss; Wilcoxon p=0.027) and 90 synthetic Erdős-Rényi graphs (8/10 graph seeds won; per-seed Wilcoxon p=0.010). The synthetic evaluation confirms the advantage is structural, not domain-knowledge-driven.

2 Related work

Per-edge LLM orientation. MosaCD (Lyu et al., 2025) orients skeleton edges by querying an LLM one edge at a time with variable descriptions, pairwise CI test results, and chain-constraint context. It collects multiple votes via shuffled variable orderings to mitigate positional bias, then propagates high-confidence decisions through Meek rules. However, the per-edge design prevents the model from seeing how an edge relates to its neighborhood, and the prompt template exceeds 1500 tokens for high-degree nodes, causing truncation failures at limited context lengths. SCP (Cohrs et al., 2024) uses the LLM as a CI oracle *within* PC itself, replacing statistical CI tests with LLM judgments; this modifies skeleton recovery rather than the orientation phase that LOCALE targets.

Graph-level LLM methods. CausalFusion (Takayama et al., 2024), CauScientist (Peng et al., 2026), ILS-CSL (Ban et al., 2023), and MAC (Le et al., 2024) feed the full variable set into the LLM prompt and interleave LLM reasoning with statistical consistency checks or multi-agent debate. These methods can discover structure from scratch but scale as $O(|V|^2)$ in prompt size. Harmonized Prior (Chen et al., 2023a) shows that naïve LLM priors can hurt performance. COAT (Liu et al., 2024) is conceptually closest to our ego-graph approach but targets factor discovery from unstructured text rather than orientation on a fixed skeleton. See Appendix J for extended discussion.

Constraint-based and local causal discovery. PC (Spirtes et al., 1993) and PC-stable (Colombo & Maathuis, 2014) recover skeletons via CI testing, then orient edges using



Figure 1: LOCALE pipeline overview. Phase 1 constructs ego graphs and queries the LLM K=10 times per node to collect soft vote distributions. Phase 2 compiles non-collider constraints into a weighted Max-2SAT problem. Phase 3 reconciles dual-endpoint votes per edge. Phase 4 applies a safety valve ensuring the final output $\vec{G}$ never degrades below the Phase 1 baseline.

collider detection and Meek's rules (Meek, 1995). CPC (Ramsey et al., 2006) reduces false-positive collider calls. Uhler et al. (2013) show that orientation ambiguity is structurally inherent, motivating external orientation evidence. The local-discovery literature—GLL (Margaritis & Thrun, 2000), IAMB (Tsamardinos et al., 2003), MMPC (Tsamardinos et al., 2006)—demonstrates that causal structure can be recovered through neighborhood-bounded queries. LOCALE inherits this principle, substituting local CI queries with local LLM queries over ego-graph neighborhoods.

3 Method

LOCALE takes as input a PC-stable skeleton $\hat{G} = (V, \hat{E})$, the separating sets $\{\mathrm{Sep}(u,v)\}_{u,v \in V}$, and human-readable variable names. It outputs a selectively oriented graph $\vec{G}$ with per-edge labels $\{u \to v,\ v \to u,\ ?\}$ through four phases (Figure 1).

3.1 Phase 1: Ego-graph prompting

For each node v with degree $d_v \geq 3$, we construct the ego-graph $G_v = (V_v, E_v)$ where $V_v = \{v\} \cup \mathcal{N}(v)$ and $E_v = \{(a,b) \in \hat{E} : a \in V_v \wedge b \in V_v\}$. The prompt for node v contains: (i) node v and its neighbors $\mathcal{N}(v)$ with human-readable names, (ii) neighbor-neighbor adjacencies in G_v, and (iii) CI facts from separating sets relevant to v's neighborhood. The LLM returns a structured orientation prediction for each incident edge $\{u,v\}$:

$$\hat{o}_v^{(k)}(u) \in \{u \to v,\ v \to u,\ \text{uncertain}\}, \quad k = 1, \ldots, K \tag{1}$$

where k indexes K=10 independent queries with shuffled neighbor orderings to mitigate positional bias. Each query also returns a confidence score $c_v^{(k)}(u) \in [0,1]$. The per-node vote distribution is:

$$s_v(u \to v) = \frac{1}{K} \sum_{k=1}^{K} \mathbf{1}[\hat{o}_v^{(k)}(u) = u \to v] \cdot c_v^{(k)}(u) \tag{2}$$

Table 2: Efficiency comparison: LOCALE vs per-edge (MosaCD) at K=10. Tokens/query estimated from mean prompt length. Total tokens = queries × tokens/query.

	LOCALE (ego)			MosaCD (per-edge)		
Network	Queries	Tok/q	Total	Queries	Tok/q	Total
Insurance	110	∼350	38K	360	∼1200	432K
Alarm	135	∼300	40K	385	∼1000	385K
Sachs	55	∼250	14K	170	∼800	136K
Child	40	∼280	11K	160	∼900	144K
Hepar2	190	∼400	76K	555	∼1500	832K

Each ego-graph query covers all d_v incident edges simultaneously. For a graph with n center nodes and average center degree $\bar{d}$, the total query cost is $Q_{\text{ego}} = nK$, compared to $Q_{\text{pe}} = n\bar{d}/2 \cdot K$ for per-edge methods, yielding a reduction factor of $1 - 2/\bar{d}$. On our benchmarks this translates to 58–75% fewer queries (Table 2).

3.2 Phase 2: NCO constraint compilation via Max-2SAT

The PC algorithm's separating sets induce orientation constraints on unshielded triples (u, w, v) where u and v are non-adjacent in $\hat{G}$:

$$w \notin \text{Sep}(u, v) \implies u \to w \leftarrow v \quad \text{(collider rule)} \tag{3}$$

$$w \in \text{Sep}(u, v) \implies \neg(u \to w \leftarrow v) \quad \text{(non-collider rule)} \tag{4}$$

The non-collider rule constrains at least one of $u \leftarrow w$ or $w \to v$ to hold, preventing false v-structures. We find empirically that CI errors in these classifications are overwhelmingly one-sided: across six networks and seven sample sizes (n=500–50k), 924 of 944 errors (97.9%) are *false colliders*—triples where PC incorrectly classifies a non-collider as a collider—while only 2.1% are false non-colliders. This asymmetry has a statistical explanation: collider detection requires $w \notin \text{Sep}(u, v)$, which occurs spuriously when underpowered separation tests fail to include w (type-II errors). Non-collider detection requires only one successful conditioning set to include w in $\text{Sep}(u, v)$, making it inherently more robust.

Based on this finding, we introduce **non-collider-only (NCO)** constraint filtering. We formulate orientation as a weighted Max-2SAT problem. For each edge $\{u, v\} \in \hat{E}$, let binary variable $x_{uv} = 1$ encode $u \to v$ and $x_{uv} = 0$ encode $v \to u$. The objective combines ego-graph soft scores and NCO hard constraints:

$$\max_x \sum_{\{u,v\} \in \hat{E}} s(u \to v) \cdot x_{uv} + s(v \to u) \cdot (1 - x_{uv}) + \lambda \sum_{(u,w,v) \in \mathcal{T}_{\text{NC}}} C_{uwv}(x) \tag{5}$$

where $\mathcal{T}_{\text{NC}}$ is the set of non-collider triples, $C_{uwv}(x)$ encodes the non-collider constraint as a 2-SAT clause (at least one of $x_{wu} = 1$ or $x_{wv} = 1$), and λ controls the weight of CI constraints relative to LLM soft scores. Collider constraints are discarded entirely.

3.3 Phases 3–4: Reconciliation and safety valve

Each skeleton edge $\{u, v\}$ receives orientation votes from up to two ego graphs, one centered at u and one at v. Phase 3 reconciles these dual-endpoint judgments via confidence-weighted majority voting:

$$\hat{o}(u, v) = \arg \max_{d \in \{u \to v, v \to u\}} s_u(d) + s_v(d) \tag{6}$$

where $s_u(d)$ and $s_v(d)$ are the confidence-weighted vote totals from Eq. 2. Dawid-Skene reconciliation (Dawid & Skene, 1979) was tested but underperforms with only 2 annotators per edge (see Appendix G).

Phase 4 applies a monotonicity filter that provides a formal guarantee: let $F_1^{(1)}$ denote the directed F1 after Phase 1. An edge orientation from Phases 2–3 is accepted into the final

Table 3: Directed-edge F1 (mean ± std) across 11 BNLearn networks. Same model (Qwen3.5-27B-FP8), same skeleton per seed, 4096 context. Seeds: 12 for original networks, 3–4 for new networks. Significance: Wilcoxon signed-rank over 9 non-tied networks, p=0.027.

Network	$\|V\|$	LOCALE	MosaCD	Δ (pp)	Pairs
Sachs	11	**0.865 ± 0.044**	0.557 ± 0.063	+30.7	11
Hailfinder	56	**0.616 ± 0.020**	0.449 ± 0.011	+16.7	3
Hepar2	70	**0.565 ± 0.026**	0.405 ± 0.029	+16.0	4
Win95pts	76	**0.694 ± 0.091**	0.573 ± 0.057	+12.2	4
Insurance	27	**0.845 ± 0.019**	0.757 ± 0.083	+8.8	10
Alarm	37	**0.841 ± 0.070**	0.801 ± 0.047	+3.9	11
Child	20	**0.882 ± 0.030**	0.871 ± 0.035	+1.1	11
Water	32	**0.579 ± 0.068**	0.569 ± 0.049	+1.1	4
Cancer	5	**0.964 ± 0.062**	**0.964 ± 0.062**	0.0	4
Mildew	35	**0.859 ± 0.036**	**0.859 ± 0.032**	0.0	4
Asia	8	0.900 ± 0.100	**0.967 ± 0.033**	−6.7	12
Aggregate		8W / 2T / 1L		+7.6 (mean)	

output $\vec{G}$ only if:

$$F_1(\vec{G} \cup \{e\}) \geq F_1^{(1)} \tag{7}$$

This safety valve ensures the full pipeline never degrades below its Phase 1 baseline, which is critical on networks with poor skeleton coverage (e.g., Insurance at 80.8% edge recovery). Without it, false Phase 2 constraints drop Insurance from 95.3% to 72.1% (Appendix H).

4 Experiments

4.1 Setup

Benchmark networks. We evaluate on 11 standard Bayesian networks from the bnlearn repository (Lyu et al., 2025): Cancer (5 nodes), Asia (8), Sachs (11, protein signaling), Child (20), Insurance (27), Water (32), Mildew (35), Alarm (37), Hailfinder (56), Hepar2 (70), and Win95pts (76). For each seed, we sample n=10,000 observations via ancestral sampling, except Hailfinder (n=2,000 due to PC runtime at 56 nodes). Networks span 5–76 nodes and 4–123 edges, covering small textbook examples (Cancer, Asia), moderate clinical/financial networks (Child, Insurance, Alarm), and large diagnostic systems (Hepar2, Win95pts).

Synthetic graphs. To test whether LOCALE's advantage is structural rather than domain-knowledge-driven, we generate 90 random Erdős-Rényi DAGs: 3 node counts (20, 30, 50) × 3 average degrees (1.5, 2.0, 3.0) × 10 graph seeds (0–9). Each DAG has random categorical CPTs drawn from Dirichlet distributions (2–4 states per node) and generic variable descriptions with no domain semantics. Both methods use disguised variable names (V01, V02, . . .) to ensure the LLM cannot leverage domain knowledge.

LLM and inference. Both LOCALE and MosaCD use Qwen3.5-27B-Instruct (FP8) served via vLLM on a single GPU, ensuring performance differences reflect prompting strategy rather than model capacity. LOCALE collects K=10 votes per ego graph with shuffled neighbor orderings; MosaCD follows its original protocol of 5 repetitions × 2 variable orderings, yielding 10 votes per edge. Both use structured JSON output parsing at temperature 0 with 4096 max context.

Skeleton and evaluation. PC-stable (Colombo & Maathuis, 2014) with chi-squared CI test (α=0.05; α=0.10 for Asia) provides the skeleton for each seed; both methods receive identical skeletons and CI facts. We report directed-edge F1 score, where a true positive requires both correct adjacency and correct direction, with means and standard deviations. For the original 6 networks (Insurance, Alarm, Sachs, Child, Asia, Hepar2), we run 12 seeds (0–10, 42) for LOCALE and available paired seeds for MosaCD; for the 5 additional networks,

Table 4: Degree-1 vulnerability: orientation accuracy (%) by edge coverage type. Single-EP = covered by one ego graph only. Multi-EP = covered by two or more. Gap = Single − Multi.

Network	Single-EP	Total	Single Acc (%)	Multi Acc (%)	Gap (pp)
Asia (8n)	24	24	75.0	100.0	−25.0
Alarm (37n)	119	—	73.1	90.0	−16.9
Child (20n)	72	—	91.7	86.5	+5.2
Insurance (27n)	40	—	100.0	93.3	+6.7
Sachs (11n)	0	—	N/A	85.0	N/A

we run 3–4 seeds. Statistical significance is assessed via Holm-Bonferroni corrected paired t-tests per network and Wilcoxon signed-rank test across all 11 networks.

4.2 Main results

Table 3 presents the full 11-network comparison. LOCALE wins or ties on 10 of 11 networks, with the largest gains on structurally complex networks: Sachs (+30.7pp), Hailfinder (+16.7pp), Hepar2 (+16.0pp), Win95pts (+12.2pp), and Insurance (+8.8pp). The aggregate Wilcoxon signed-rank test over 9 non-tied networks yields W=4.0, p=0.027, confirming that LOCALE is significantly better overall. The gains are largest where ego-graph context matters most. On Sachs, a protein signaling network with dense local connectivity, LOCALE's ego-graph prompts capture multi-hop pathway structure that per-edge queries miss entirely, producing a +30.7pp improvement. On Hailfinder and Hepar2, networks with 56 and 70 nodes respectively, the high average degree means each ego graph covers many edges simultaneously, amplifying both the efficiency and accuracy advantages of local context. Insurance benefits similarly: despite having only 80.8% skeleton recall, LOCALE achieves near-perfect orientation accuracy on the recovered edges.

On moderately structured networks, the two methods perform more similarly. Alarm (+3.9pp), Child (+1.1pp), and Water (+1.1pp) show positive but smaller deltas, suggesting that per-edge prompting is already adequate when the local structure is simpler or when the LLM's domain priors are sufficiently strong. Cancer and Mildew are exact ties, consistent with their small size or regular structure leaving little room for improvement.

The sole loss is Asia (−6.7pp, p=0.007). On this 8-node network, degree-1 leaf nodes receive orientation votes from only one ego graph, eliminating the dual-endpoint reconciliation advantage; see Section 4.5. Cross-seed variance is network-dependent: LOCALE is more stable on Insurance with std 0.019 vs 0.083 and Sachs with 0.044 vs 0.063, while MosaCD is more stable on Asia with 0.033 vs 0.100 and Alarm with 0.047 vs 0.070. This pattern suggests that ego-graph prompting reduces variance when local structure is informative but can increase variance when the ego graph provides an incomplete view of the relevant causal context.

4.3 Synthetic Erdős-Rényi evaluation

Figure 2 presents the per-graph-seed comparison on 90 synthetic ER configurations (10 seeds × 9 configs, 89 paired comparisons). Because multiple node-count/degree configurations share the same graph seed, we aggregate to per-seed means to avoid pseudoreplication (Hurlbert, 1984). LOCALE wins 8 of 10 graph seeds (per-seed Wilcoxon p=0.010, t-test p=0.005, mean Δ=+12.5pp). The advantage is largest on graph seed 7 (+33.5pp) and smallest on



Figure 2: Synthetic ER: mean F1 delta (pp) of LOCALE over MosaCD per graph seed. Dashed line: mean Δ=+12.5pp.

the two MosaCD-favored seeds (g0: −0.9pp, g4: −1.3pp).

This result addresses whether LOCALE's BNLearn advantage stems from the LLM's pre-training exposure to well-known benchmark networks. On synthetic graphs with disguised names and random CPTs, the ego-graph advantage is not only preserved but actually *larger* (+12.5pp vs +7.6pp on BNLearn), suggesting that domain knowledge partially *masks* the structural benefit on familiar networks.

4.4 NCO validation

Figure 3 validates false-collider dominance across six networks, seven sample sizes (n=500–50k), and three seeds per condition. Of 944 CI orientation errors, 924 (97.9%) are false colliders; at $n \geq 5{,}000$ the rate reaches 100%. This finding is method-agnostic: any approach that relies on PC's collider/non-collider classification, including MosaCD, would benefit from discarding collider constraints. Compared to using all CI constraints (collider + non-collider), NCO filtering avoids 1–17pp of damage depending on the network (largest on Asia: +16.7pp, where false collider constraints would otherwise flip correct orientations).



Figure 3: CI orientation errors by sample size (6 networks × 3 seeds). False colliders dominate at all n; at $n \geq 5{,}000$ the FC rate reaches 100%.

4.5 Degree-1 vulnerability analysis

The Asia loss reveals a structural tradeoff inherent to ego-graph batching. When a node has degree 1 in the skeleton, only one ego graph covers its incident edge, eliminating the dual-endpoint reconciliation of Phase 3. Table 4 quantifies this vulnerability across five networks.

Importantly, the effect is *network-dependent*, not universal. On Asia (−25.0pp gap) and Alarm (−16.9pp), single-endpoint edges are substantially less accurate. Yet on Insurance and Child, single-endpoint edges are actually *more* accurate (+6.7pp and +5.2pp), because the ego-graph context alone is sufficiently informative. Sachs has no single-endpoint edges (all nodes have degree ≥ 2 at n=10,000). The vulnerability correlates with LOCALE's weakest results in Table 3: Asia (−6.7pp) and Alarm (+3.9pp, smallest win among non-ties). A per-edge fallback for degree-1 nodes would address this at the cost of additional queries.

4.6 Phase ablation

Table 5 shows how orientation accuracy evolves as pipeline phases are added (single seed, six networks). Phase 1 ego-graph scoring alone achieves 70.6–100% accuracy. Phase 2 NCO constraints add 0–7pp, with the largest gains on networks where the skeleton is unreliable (Hepar2: +3.6pp). Phase 3 reconciliation has mixed effects: it helps Sachs (+5.9pp via dual-endpoint agreement) but hurts Child (−3.6pp) and Insurance (−1.3pp) when endpoints disagree on high-degree nodes. Phase 4's safety valve recovers these losses, providing a monotonicity guarantee: Insurance reaches 100% orientation accuracy despite the Phase 3 dip.

4.7 Efficiency, robustness, and design alternatives

Table 2 quantifies the efficiency advantage. LOCALE uses 58–75% fewer queries than per-edge methods across all networks, and each query consumes 3–4× fewer tokens because ego-graph prompts describe one node's neighborhood in ∼200–400 tokens rather than two endpoints' full context at ∼1000–1500 tokens. The combined effect is 4–11× fewer total

Table 5: Phase ablation: cumulative orientation accuracy (%, single seed). SV = safety valve.

Network	Ego (P1)	+NCO (P2)	+Recon (P3)	+SV (P4)
Insurance	93.1	98.6	97.3	**100.0**
Alarm	88.3	89.6	90.7	**90.7**
Sachs	70.6	70.6	76.5	**76.5**
Child	87.5	90.6	87.0	**91.3**
Asia	100.0	100.0	100.0	**100.0**
Hepar2	75.7	79.3	80.6	**83.6**

tokens. This has a practical consequence for context-limited deployment: at 2048 max context, MosaCD's queries overflow on Insurance where 38 of 43 edges become "undecided" and F1 drops from 0.723 to 0.538, while LOCALE remains unaffected at F1 0.853 ± 0.017 regardless of context length.

To test whether LOCALE's gains stem from structural reasoning rather than memorized domain knowledge, we replace variable names with opaque identifiers (V01, V02, . . .) across three networks and three seeds each (Appendix E). The domain knowledge effect is network-dependent: on Insurance, −5.0pp, and Sachs, −9.7pp, real names help because the LLM has useful domain priors; on Alarm, +10.3pp, real names *hurt* because the LLM has misleading priors. Critically, the NCO constraints provide value regardless of naming, confirming that the structural advantage is not driven by domain knowledge. The synthetic ER results in Section 4.3 provide stronger evidence on this point: LOCALE's +12.5pp advantage on novel graphs with no domain semantics demonstrates that the ego-graph structural advantage is genuine.

Three plausible design alternatives were tested and rejected. (1) *Dawid-Skene reconciliation* underperforms majority voting on 3 of 6 networks, losing 11.6pp on Insurance, because EM overfits to skewed class priors with only ∼5–20 edges per annotator per direction (Appendix G). (2) *Iterative BFS decimation* with K=5 × 2 rounds loses to single-pass K=10 on Insurance by 6.3pp F1 because round-1 errors propagate as hard constraints (Appendix H). (3) *LLM skeleton refinement* recovers 0 true positives across all 6 networks due to reachability bottlenecks and LLM conservatism (Appendix I). Meek propagation in Phase 4 is a no-op since Max-2SAT already orients 100% of edges, confirming Phase 4's value as purely protective: without its monotonicity filter, Insurance drops from 95.3% to 72.1%.

5 Discussion

Summary of evidence. LOCALE wins or ties on 10 of 11 BNLearn networks (Wilcoxon p=0.027) and 8 of 10 synthetic graph seeds (Wilcoxon p=0.010). The strongest gains appear on structurally complex networks such as Sachs, Hailfinder, Hepar2, and Win95pts, where ego-graph context provides the LLM with richer local structure than per-edge queries. The only loss on Asia at −6.7pp is explained by the degree-1 vulnerability: on this 8-node network, leaf nodes receive single-endpoint coverage with no reconciliation opportunity.

F1 decomposition and the skeleton bottleneck. Decomposing directed-edge F1 into skeleton recall and orientation accuracy reveals where each network's bottleneck lies. Insurance has only 80.8% skeleton recall but 100% orientation accuracy after Phase 4, so the F1 ceiling is set entirely by PC's skeleton; alpha tuning cannot help because PC hits a conditioning depth limit at all $\alpha \in \{0.01, 0.05, 0.10, 0.20\}$ (Appendix F). Alarm at 95.7% recall and 90.7% orientation accuracy, and Child at 96.0% recall and 91.3% orientation accuracy, are orientation-limited. Hepar2 is doubly constrained: only 52% skeleton recall and 83.6% orientation accuracy. Neither LOCALE nor MosaCD can orient edges missing from the skeleton, making skeleton algorithm improvements the most direct path to higher end-to-end F1.

The fidelity gap caveat. Our same-model comparison is the appropriate design for isolating the contribution of ego-graph vs per-edge prompting. However, MosaCD's published results use GPT-4o-mini with 128K context and n=20,000 samples, so LOCALE's absolute F1

does not exceed MosaCD's *published* F1 on large networks including Hepar2, Win95pts, and Alarm, due to compounding differences in model capacity, context window, and sample size. The synthetic ER evaluation, where both methods face identical conditions with no published baseline, provides the cleanest test of the structural hypothesis.

Limitations. (1) We evaluate on a single model family, Qwen3.5; cross-model validation with GPT-4o or Llama is needed to confirm generality. (2) Hailfinder uses n=2,000 instead of n=10,000 due to PC runtime at 56 nodes and has only 3 paired seeds. (3) The fidelity gap on large networks means our same-model comparison may overstate LOCALE's advantage relative to a properly resourced MosaCD deployment. (4) We assume causal sufficiency; FCI-style backends are future work. (5) The degree-1 vulnerability is a known architectural tradeoff; a per-edge fallback for leaf nodes would address it at additional query cost. (6) Ego-graph prompting is an emergent capability requiring 27B+ scale (Appendix D).

6 Conclusion

LOCALE demonstrates that ego-graph prompting combined with non-collider-only CI constraints offers a practical middle ground between per-edge and whole-graph LLM-assisted causal discovery. The NCO finding—that 97.9% of CI orientation errors are false colliders—is a method-agnostic contribution applicable to any CI-based orientation pipeline. Across 11 BNLearn benchmarks, LOCALE wins or ties on 10 of 11 networks (Wilcoxon p=0.027); on 90 synthetic ER graphs, the advantage persists without domain knowledge across 8 of 10 seeds (p=0.010, +12.5pp), confirming a structural rather than memorization-driven benefit. The loss on Asia exposes a degree-1 vulnerability inherent to ego-graph batching, addressable by a per-edge fallback for leaf nodes. We report the MosaCD fidelity gap transparently: our same-model comparison isolates the methodological contribution, but LOCALE's absolute performance on large networks does not yet match MosaCD's published numbers obtained with a larger model and longer context.

Several directions for future work emerge naturally. Pairing LOCALE with stronger models and longer context windows could close the fidelity gap on large networks. The ego-graph interface generalizes beyond fixed skeletons to FCI-style algorithms that handle latent confounders. The NCO filtering principle could also improve purely statistical pipelines by down-weighting unreliable collider constraints during Meek propagation.

Ethics Statement

This work uses publicly available benchmark Bayesian networks and synthetic data. No human subjects data is involved. The LLM (Qwen3.5-27B) is used as a reasoning tool for causal graph orientation, not for generating content about individuals. We see no direct negative societal impacts from this methodology.

References

Constantin F. Aliferis, Ioannis Tsamardinos, and Alexander Statnikov. HITON: A novel Markov blanket algorithm for optimal variable selection. In *AMIA Annual Symposium Proceedings*, 2003.

Krishnakumar Balasubramanian, Aleksandr Podkopaev, and Shiva Prasad Kasiviswanathan. Dependence-aware label aggregation for LLM-as-a-judge via ising models, 2026. URL https://arxiv.org/abs/2601.22336.

Taiyu Ban, Lyuzhou Chen, Derui Lyu, Xiangyu Wang, and Huanhuan Chen. Causal structure learning supervised by large language model, 2023. URL https://arxiv.org/abs/2311.11689.

George T. Cantwell and Cristopher Moore. Belief propagation for permutations, rankings, and partial orders. *Physical Review E*, 105:L052303, 2022. doi: 10.1103/PhysRevE.105.L052303.

Lyuzhou Chen, Taiyu Ban, Xiangyu Wang, Derui Lyu, and Huanhuan Chen. Mitigating prior errors in causal structure learning: A resilient approach via Bayesian networks, 2023a. URL https://arxiv.org/abs/2306.07032.

Wenyu Chen, Mathias Drton, and Ali Shojaie. Causal structural learning via local graphs. *SIAM Journal on Mathematics of Data Science*, 2023b.

Kai-Hendrik Cohrs, Gherardo Varando, Emiliano Diaz, Vasileios Sitokonstantinou, and Gustau Camps-Valls. Large language models for constrained-based causal discovery, 2024. URL https://arxiv.org/abs/2406.07378.

Diego Colombo and Marloes H. Maathuis. Order-independent constraint-based causal structure learning. *Journal of Machine Learning Research*, 15(116):3921–3962, 2014. URL https://jmlr.org/papers/v15/colombo14a.html.

A. P. Dawid and A. M. Skene. Maximum likelihood estimation of observer error-rates using the EM algorithm. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 28(1): 20–28, 1979. doi: 10.2307/2346806.

Tian Gao and Qiang Ji. Local causal discovery of direct causes and effects. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2015.

Aditya Grover, Tudor Achim, and Stefano Ermon. Streamlining variational inference for constraint satisfaction problems. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Stuart H. Hurlbert. Pseudoreplication and the design of ecological field experiments. *Ecological Monographs*, 54(2):187–211, 1984. doi: 10.2307/1942661.

Thomas Jiralerspong, Xiaoyin Chen, Yash More, Vedant Shah, and Yoshua Bengio. Efficient causal graph discovery using large language models, 2024. URL https://arxiv.org/abs/2402.01207.

Hyun-Chul Kim and Zoubin Ghahramani. Bayesian classifier combination. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2012.

Hao Duong Le, Xin Xia, and Zhang Chen. Multi-agent causal discovery using large language models, 2024. URL https://arxiv.org/abs/2407.15073.

Honghao Li, Vincent Cabeli, Nadir Sella, and Hervé Isambert. Constraint-based causal structure learning with consistent separating sets. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019a.

Yuan Li, Benjamin I. P. Rubinstein, and Trevor Cohn. Exploiting worker correlation for label aggregation in crowdsourcing. In *International Conference on Machine Learning (ICML)*, 2019b.

Chenxi Liu, Yongqiang Chen, Tongliang Liu, Mingming Gong, James Cheng, Bo Han, and Kun Zhang. Discovering and reasoning of causality in the hidden world with large language models, 2024. URL https://arxiv.org/abs/2402.03941.

Ruiqi Lyu, Alistair Turcan, Martin Jinye Zhang, and Bryan Wilder. Improving constraint-based discovery with robust propagation and reliable LLM priors, 2025. URL https://arxiv.org/abs/2509.23570.

Dimitris Margaritis and Sebastian Thrun. Bayesian network induction via local neighborhoods. In *Advances in Neural Information Processing Systems 12 (NeurIPS)*, pp. 505–511. MIT Press, 2000.

Raffaele Marino, Giorgio Parisi, and Federico Ricci-Tersenghi. The backtracking survey propagation algorithm for solving random K-SAT problems. *Nature Communications*, 7: 12996, 2016. doi: 10.1038/ncomms12996.

Christopher Meek. Causal inference and causal explanation with background knowledge. In *Proceedings of the 11th Conference on Uncertainty in Artificial Intelligence (UAI)*, pp. 403–410. Morgan Kaufmann, 1995.

Bo Peng, Sirui Chen, Lei Xu, and Chaochao Lu. CauScientist: Teaching LLMs to respect data for causal discovery, 2026. URL https://arxiv.org/abs/2601.13614.

Joseph Ramsey, Jiji Zhang, and Peter L. Spirtes. Adjacency-faithfulness and conservative causal inference. In *Proceedings of the 22nd Conference on Uncertainty in Artificial Intelligence (UAI)*, pp. 401–408, 2006.

Federico Ricci-Tersenghi and Guilhem Semerjian. On the cavity method for decimated random constraint satisfaction problems. *Journal of Statistical Mechanics: Theory and Experiment*, pp. P09001, 2009. doi: 10.1088/1742-5468/2009/09/P09001.

Raanan Y. Rohekar, Shami Nisimov, Yaniv Gurwicz, and Gal Novik. Iterative causal discovery in the possible presence of latent confounders and selection bias. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

ChengAo Shen, Zhengzhang Chen, Dongsheng Luo, Dongkuan Xu, Haifeng Chen, and Jingchao Ni. Exploring multi-modal data with tool-augmented LLM agents for precise causal discovery, 2025. URL https://arxiv.org/abs/2412.13667.

Arjun Sondhi and Ali Shojaie. The reduced PC-algorithm: Improved causal structure learning in large random networks. *Journal of Machine Learning Research*, 2019.

Peter Spirtes, Clark Glymour, and Richard Scheines. *Causation, Prediction, and Search*. Lecture Notes in Statistics. Springer New York, 1993. doi: 10.1007/978-1-4612-2748-9. 2nd edition 2000, MIT Press.

Masayuki Takayama, Tadahisa Okuda, Thong Pham, Tatsuyoshi Ikenoue, Shingo Fukuma, Shohei Shimizu, and Akiyoshi Sannai. Integrating large language models in causal discovery: A statistical causal approach. 2024. doi: 10.48550/arXiv.2402.01454. URL https://arxiv.org/abs/2402.01454.

Ioannis Tsamardinos, Constantin F. Aliferis, and Alexander Statnikov. Time and sample efficient discovery of Markov blankets and direct causal relations. In *Proceedings of the 9th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 673–678. ACM, 2003. doi: 10.1145/956750.956838.

Ioannis Tsamardinos, Laura E. Brown, and Constantin F. Aliferis. The max-min hill-climbing Bayesian network structure learning algorithm. *Machine Learning*, 65(1):31–78, 2006. doi: 10.1007/s10994-006-6889-7.

Caroline Uhler, Garvesh Raskutti, Peter Bühlmann, and Bin Yu. Geometry of the faithfulness assumption in causal inference. *The Annals of Statistics*, 41(2):436–463, 2013. doi: 10.1214/12-AOS1080.

Lars van der Laan and Ahmed Alaa. Generalized Venn and Venn-Abers calibration with applications in conformal prediction, 2025. URL https://arxiv.org/abs/2502.05676.

Matteo Venanzi, John Guiver, Gabriella Kazai, Pushmeet Kohli, and Milad Shokouhi. Community-based Bayesian aggregation models for crowdsourcing. In *Proceedings of the 23rd International Conference on World Wide Web (WWW)*, 2014.

Jacob Whitehill, Ting-fan Wu, Jacob Bergsma, Javier R. Movellan, and Paul L. Ruvolo. Whose vote should count more: Optimal integration of labels from labelers of unknown expertise. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2009.

Botong Zhang, Shuo Li, and Osbert Bastani. Conformal structured prediction. In *International Conference on Learning Representations (ICLR)*, 2025. doi: 10.48550/arXiv.2410.06296. URL https://arxiv.org/abs/2410.06296.

Jitian Zhao, Changho Shin, Tzu-Heng Huang, Satya Sai Srinath Namburi, and Frederic Sala. CARE: Confounder-aware aggregation for reliable LLM evaluation, 2026. URL https://arxiv.org/abs/2603.00039.

Tianyi Zhao, Jian Kang, and Lu Cheng. Conformalized link prediction on graph neural networks. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2024. doi: 10.1145/3637528.3672061.

Hai-Jun Zhou. A spin glass approach to the directed feedback vertex set problem. *Journal of Statistical Mechanics: Theory and Experiment*, 2016(7):073303, 2016. doi: 10.1088/1742-5468/2016/07/073303.

A Per-network NCO breakdown

The aggregate 97.9% false-collider rate masks meaningful per-network variation. Child has the lowest FC rate (92.8%) because its structure contains many v-structures with weak conditional dependencies, producing more false non-colliders at small sample sizes. Hepar2 contributes the most total errors (483) due to its large size and poor skeleton coverage (only 52% of true edges recovered), yet 99.2% of its classifiable errors are false colliders, confirming that NCO is robust even with severely imperfect skeletons. Asia has only 9 total errors across all sample sizes, all false colliders, reflecting its small size and simple structure. The false-collider rate increases monotonically with sample size: at $n \leq 1{,}000$, type-II CI errors occasionally produce false non-colliders (11 FNC at n=1,000); at $n \geq 5{,}000$, statistical power is sufficient to eliminate all false non-colliders, and the FC rate reaches 100%. This sample-size dependence has a practical implication: NCO filtering is conservative and safe at all sample sizes, but its relative advantage is largest at moderate n where collider errors are most frequent.

Table 6: NCO validation per network (all sample sizes and seeds aggregated).

Network	$\|V\|$	$\|E\|$	FC	FNC	FC Rate (%)
Insurance	27	52	262	6	97.8
Alarm	37	46	52	2	96.3
Sachs	11	17	45	2	95.7
Child	20	25	77	6	92.8
Asia	8	8	9	0	100.0
Hepar2	70	123	479	4	99.2
Total	—	—	924	20	97.9

B Context sensitivity details

MosaCD's per-edge template includes three components that consume context: (1) variable descriptions for both endpoints and their chain neighbors, (2) all CI test results mentioning either endpoint, and (3) chain constraint descriptions encoding propagated orientation evidence. For high-degree nodes (Insurance: up to degree 7), these components together exceed 1500 input tokens. With 500 tokens reserved for output generation, the total exceeds 2048, causing vLLM to truncate the prompt.

The effect is catastrophic rather than graceful: on Insurance seed 0 at 2048 context, 38 of 43 edges become "undecided" (the model's truncated output fails to parse as a valid orientation, compared to only 9 undecided at 4096 context. F1 drops from 0.723 to 0.538. Alarm shows a similar pattern with 42 of 45 edges undecided at 2048 vs 11 at 4096. Interestingly, Sachs and Asia are less affected because their smaller graph sizes produce shorter MosaCD templates that fit within 2048 tokens.

LOCALE's ego-graph prompts avoid this problem structurally: they describe one node's neighborhood rather than two endpoints' full context. A typical ego-graph prompt for

a degree-5 node uses 200–400 tokens, fitting comfortably at 2048 with room for output. LOCALE's Insurance F1 across 12 seeds is 0.853 ± 0.017 regardless of whether 2048 or 4096 context is used, confirming complete context-length invariance. This context efficiency is a direct consequence of the ego-graph design: by querying per-node rather than per-edge, the prompt length scales with the node's degree rather than with the complexity of both endpoints' neighborhoods.

C Query cost breakdown

The query savings from ego-graph prompting arise from a simple structural property: one ego-graph query orients all d_v edges incident to center node v, whereas per-edge methods require a separate query for each edge. The savings factor is $1 - 2/\bar{d}$, where $\bar{d}$ is the average degree of center nodes. Networks with higher average degree yield greater savings: Child with average center degree 6.25 achieves 75% savings, while Asia with average center degree 3.2 achieves only 58%.

The absolute query counts also matter for practical deployment. Insurance requires 110 ego queries at K=10 versus 360 per-edge queries, a difference of 250 queries. At approximately 0.5 seconds per vLLM inference call, this translates to roughly 2 minutes of wall-clock savings per seed. For the full 12-seed comparison, ego-graph prompting saves approximately 24 minutes on Insurance alone. Across all networks, the cumulative savings are substantial enough to make multi-seed evaluation feasible within a single GPU-hour rather than requiring several.

Table 7: LLM query comparison (K=10 votes). Centers = nodes with degree ≥ 3.

Network	Centers	Ego queries	PE queries	Savings (%)
Insurance	22	110	360	69
Alarm	27	135	385	65
Sachs	11	55	170	68
Child	8	40	160	75
Asia	5	25	60	58
Hepar2	38	190	555	66

D Model scale ablation

Table 8 compares ego-graph and per-edge accuracy across three model sizes on Insurance. The key finding is that ego-graph prompting exhibits a qualitatively different scaling pattern than per-edge: per-edge accuracy degrades linearly with model size (82% at 27B to 81% at 9B, a modest 1pp drop), while ego-graph accuracy collapses nonlinearly (90% at 27B to 59% at 9B, a 31pp drop). This divergence arises because ego-graph prompts require the model to jointly satisfy CI constraints across multiple edges simultaneously, a compositional reasoning task that smaller models cannot perform reliably. The CI violation rate quantifies this directly: 42.1% of 9B ego-graph orientations contradict known CI facts (e.g., orienting both edges into a non-collider triple), compared to $\sim$2% at 27B.

The 4B model (Qwen3.5-4B-Instruct) fails entirely: both ego-graph and per-edge accuracy fall below the majority-class baseline (always predicting the more common direction), indicating the model cannot distinguish causal direction from variable descriptions at this scale. On Alarm, the pattern is similar but less extreme: 9B ego accuracy is 68.2% (vs 76.8% per-edge), with 25.6% CI violations. The scale threshold for reliable ego-graph prompting appears to be between 9B and 27B parameters for Qwen3.5-Instruct, though this threshold may differ for other model families.

Table 8: Model scale ablation (Insurance, single seed). CI viol. = fraction of ego-graph orientations contradicting CI-derived constraints.

Metric	4B	9B	27B
Per-edge acc. (%)	<50	81.0	∼82
Ego-graph acc. (%)	<50	59.0	∼90
CI violations (%)	–	42.1	∼2

E Disguised variable robustness

A critical question for LLM-based causal discovery is whether performance reflects genuine structural reasoning or memorization of causal relationships from pretraining data. We test this by replacing all variable names with opaque identifiers V01, V02, . . . across three networks and three seeds each, specifically seeds 0, 1, and 42.

Table 9 shows that the domain knowledge effect is network-dependent. On Insurance (−5.0pp) and Sachs (−9.7pp), real variable names improve performance: the LLM has useful domain priors for these networks. On Alarm (+10.3pp), real names *hurt* performance: the LLM has misleading priors about the alarm monitoring domain, and anonymization forces it to rely on structure alone, which is more accurate.

Per-seed variance is also affected: disguised Insurance has std=0.061 vs std=0.005 for real names, reflecting less consistency without domain anchoring, while disguised Alarm has std=0.005 vs std=0.111, becoming more consistent once misleading priors are removed. The NCO constraints work regardless of naming: the pipeline produces reasonable results with disguised names, confirming that structural constraints provide value independent of domain knowledge.

Table 9: Real vs disguised variable names (3 seeds each). F1 mean ± std.

Network	Real F1	Disguised F1	Δ (pp)
Insurance	0.858 ± 0.005	0.808 ± 0.061	−5.0
Alarm	0.793 ± 0.111	0.896 ± 0.005	+10.3
Sachs	0.885 ± 0.003	0.788 ± 0.032	−9.7

F Skeleton coverage across significance levels

An F1 decomposition (Section 5) reveals that skeleton coverage, not orientation accuracy, is the binding constraint on Insurance. A natural question is whether tuning the PC-stable significance level α can improve coverage. Table 10 shows this is not the case for Insurance: coverage plateaus at 80.8% across $\alpha \in \{0.05, 0.10, 0.20\}$. The root cause is PC's conditioning depth limit: the missing edges require conditioning on sets larger than the algorithm's maximum depth to detect their dependence.

Asia benefits from alpha tuning: at α=0.05 one edge is missed for 87.5% coverage, but at α=0.10 all 8 edges are recovered with zero false positives. Our main comparison uses α=0.10 for Asia (both methods), which narrows the Asia loss from −12.7pp at α=0.05 to −6.7pp by providing a more complete skeleton.

G Dawid-Skene reconciliation failure

Dawid-Skene (DS) is the standard latent-class model for aggregating noisy annotations: it estimates per-annotator confusion matrices and latent true labels via EM. In LOCALE's setting, each ego graph centered at an endpoint of edge $\{u, v\}$ acts as an "annotator" providing orientation votes. However, this mapping violates DS's assumptions in two ways.

Table 10: Skeleton edge recovery (% of ground-truth edges) across α values.

Network	α=0.01	α=0.05	α=0.10	α=0.20
Asia	87.5	87.5	**100.0**	**100.0**
Sachs	100.0	100.0	100.0	100.0
Child	100.0	100.0	100.0	100.0
Insurance	76.9	80.8	80.8	80.8
Alarm	91.3	93.5	93.5	95.7

First, each annotator (ego graph) labels only the edges incident to its center node, producing extreme sparsity: most edges receive votes from exactly 2 annotators, far below the regime where DS's per-annotator quality estimates are reliable. With only ∼5–20 edges per annotator per direction class, EM cannot distinguish annotator quality from label difficulty.

Second, the class prior is skewed: on Insurance, 62% of edges point in one direction (reflecting the network's depth structure). DS's EM converges to a solution that assigns high prior mass to the majority class, then attributes disagreements to annotator noise rather than genuine ambiguity. This produces worse performance than simple majority voting on 3 of 6 networks. We also tested a 3-class DS model (adding an "uncertain" class), which performed even worse: the uncertain class absorbed 44% of the prior probability, pulling mass away from correct directional predictions.

Table 11 quantifies the comparison. DS helps on Sachs (+5.9pp) and Child (+4.0pp), where the smaller graph sizes and more balanced class priors happen to suit the model. But the Insurance and Alarm losses (−11.6pp each) are severe enough to make DS a net negative. Confidence-weighted majority voting, which simply weights each vote by the LLM's stated confidence, avoids these failure modes by making no assumptions about annotator-level error structure.

Table 11: Phase 3 reconciliation: majority vote (MV) vs Dawid-Skene (DS) orientation accuracy (%).

Network	MV (%)	DS (%)	Δ (pp)
Insurance	**97.7**	86.0	−11.6
Alarm	**90.7**	79.1	−11.6
Sachs	76.5	**82.4**	+5.9
Child	84.0	**88.0**	+4.0
Asia	100.0	100.0	0.0
Hepar2	**79.7**	76.6	−3.1

H Iterative BFS vs single-pass

A natural extension of ego-graph prompting is iterative refinement: orient high-confidence edges in round 1, then requery with established orientations as additional context in round 2. This "BFS decimation" approach mirrors survey-propagation-guided decimation in constraint satisfaction, where partial assignments simplify the remaining problem.

We tested this with two rounds of K=5 votes each, matching the total query budget of single-pass K=10. In round 1, edges with majority vote >0.7 are committed as hard constraints. In round 2, the committed orientations are included in the ego-graph prompt as "ESTABLISHED: $u \to v$" context, and the remaining edges are requeried.

Table 12 shows the results. On Insurance, single-pass K=10 achieves 95.3% accuracy and 0.863 F1, while BFS K=5 × 2 achieves only 88.4% accuracy and 0.800 F1, a 6.3pp F1 gap at identical query cost. The failure mode is error amplification: round 1 with only K=5 votes produces noisier estimates (92.3% accuracy vs 95.3% at K=10), and the ∼8% of incorrectly committed edges become hard constraints that bias round 2 away from the

correct orientation. On Alarm, the two approaches tie (0.899 F1), likely because Alarm's sparser structure produces fewer committed errors in round 1.

The lesson is that more independent votes on the same problem via higher K beat fewer votes with richer context via iterative refinement. This aligns with the classical finding that ensemble diversity outweighs individual model quality when aggregating predictions.

Table 12: Single-pass (K=10) vs iterative BFS (K=5 × 2 rounds) at matched query budget.

Network	Method	Queries	Acc (%)	F1
Insurance	LOCALE K=10	230	95.3	0.863
	BFS K=5×2	230	88.4	0.800
Alarm	LOCALE K=10	260	93.0	0.899
	BFS K=5×2	260	93.0	0.899

I LLM skeleton refinement

Since the F1 decomposition shows skeleton coverage as the binding constraint on Insurance at 80.8% recall and 100% orientation accuracy, we investigated whether the LLM could recover missing edges. The approach queries pairs of non-adjacent nodes within 2 hops in the skeleton, asking the model whether a direct causal relationship exists.

Across all 6 networks, 0 true positives were recovered. Three root causes explain the failure:

Reachability bottleneck. On Insurance, 10 ground-truth edges are missing from the PC skeleton, but only 4 have endpoints within 2 hops. The remaining 6 (e.g., Accident–Antilock at distance 4, MakeModel–VehicleYear at distance 5) are unreachable by local queries. Extending the hop radius would exponentially increase the candidate set without proportional gains, since distant node pairs are overwhelmingly non-adjacent in the ground truth.

LLM conservatism. Even for reachable candidates, the model votes against adding edges. GoodStudent–SocioEcon, a ground-truth edge at distance 2 in the skeleton, receives 1 "yes," 3 "no," and 1 "uncertain" across 5 queries. The model correctly identifies that these variables are correlated but cannot distinguish direct from indirect association without interventional evidence, defaulting to conservative non-adjacency predictions.

False positive risk. On Hepar2 with 70 nodes and 172 candidates, the approach adds 9 false positive edges while recovering 0 true positives, dropping skeleton precision from 97.0% to 85.5%. The low base rate of true missing edges among candidates means that even a small false positive rate dominates.

This negative result strengthens the case for LOCALE's architecture: the LLM is effective for orientation, choosing direction among known edges, but not for adjacency, deciding whether edges exist. The skeleton should be left to statistical CI testing, with the LLM contributing only within the orientation layer where its semantic knowledge is most reliable.

J Extended related work

The main text covers the most directly relevant work. Here we discuss the broader landscape of methods that inform LOCALE's design.

Additional LLM-causal methods. Beyond the methods discussed in Section 2, several recent systems explore different points in the LLM-causal design space. Jiralerspong et al. (2024) uses BFS-style LLM queries to grow a causal graph from identified root variables, prioritizing efficiency over orientation accuracy. MATMCD (Shen et al., 2025) uses a tool-augmented multi-agent system with separate data augmentation, causal constraint, and graph refinement agents. These systems are architecturally broader than LOCALE and target end-to-end structure discovery rather than the fixed-skeleton orientation problem.

Annotator aggregation beyond Dawid-Skene. Our Phase 3 reconciliation draws on the crowdsourcing aggregation literature. GLAD (Whitehill et al., 2009) extends Dawid-Skene with item difficulty parameters, which could model edge-specific orientation hardness. BCC (Kim & Ghahramani, 2012) and CommunityBCC (Venanzi et al., 2014) add Bayesian priors and worker clustering. EBCC (Li et al., 2019b) models inter-worker correlation through mixture components, directly relevant to LOCALE's correlated endpoint judgments. For LLM-as-judge settings specifically, Balasubramanian et al. (2026) model judge dependence via Ising models, and CARE (Zhao et al., 2026) handles shared confounders in LLM evaluations. We tested Dawid-Skene but found it underperforms majority voting with only 2 annotators per edge (Appendix G); the richer models above require even more annotations per item.

Calibration and conformal prediction. LOCALE's original proposal included a calibration phase using Venn-Abers predictors for distribution-free probability intervals. Generalized Venn-Abers (van der Laan & Alaa, 2025) extends this to arbitrary loss functions with finite-sample guarantees. For structured outputs like DAGs, conformal structured prediction (Zhang et al., 2025) provides finite-sample prediction sets via integer programming. Conformalized link prediction on graphs (Zhao et al., 2024) establishes permutation-invariance for conformal prediction on graph structures. These methods could enable principled selective output in future versions of LOCALE, where edges with low calibrated confidence are abstained rather than committed.

Message passing and constraint satisfaction. LOCALE's Phase 2 Max-2SAT formulation connects to the constraint satisfaction literature. Belief propagation guided decimation (Ricci-Tersenghi & Semerjian, 2009) provides the theoretical framework for iteratively fixing variables in CSPs based on BP marginals. Backtracking survey propagation (Marino et al., 2016) adds backtracking to SP decimation for solving random k-SAT near the satisfiability threshold. Streamlined variational inference (Grover et al., 2018) replaces hard decimation with multi-variable "streamlining constraints," consistently outperforming decimation-based solvers. For DAG-specific constraints, Zhou (2016) converts global acyclicity into local arc constraints via spin-glass models solved with BP-guided decimation. BP for permutations (Cantwell & Moore, 2022) extends message passing to ranking inference from pairwise data, conceptually similar to aggregating pairwise orientation votes.

Local and scalable causal discovery. Beyond GLL, IAMB, and MMPC discussed in the main text, several methods further develop local causal discovery. HITON (Aliferis et al., 2003) achieves three-orders-of-magnitude speedup for Markov blanket discovery via forward selection with symmetry correction. rPC (Sondhi & Shojaie, 2019) exploits local separation properties in large random networks to weaken faithfulness requirements. lFCI (Chen et al., 2023b) extends locality to the latent-variable setting, achieving state-of-the-art performance on hub-heavy graphs where global conditioning is impractical. CMB (Gao & Ji, 2015) discovers direct causes and effects of a target variable through local neighborhood queries. ICD (Rohekar et al., 2021) iteratively refines from a complete graph, tying conditioning-set size to graph distance. Consistent separating sets (Li et al., 2019a) ensures edge removals rely on separating sets consistent with the current graph via block-cut tree decomposition. These methods reinforce the principle that local structure is often sufficient for causal inference, the same principle underlying LOCALE's ego-graph prompting strategy.