OPERATION HYDRA

Unraveling a Multi-Vector Cyber Crime Involving Phishing, Spoofing & Financial Fraud

Final Legal–Technical Impact Report

Assignment 2 – Unit 2: Types of Cyber Crimes

Report Type	Simulated Case Study – Academic Digital Forensics Exercise
Scope	Cybercrime Decomposition, Phishing/Spoofing Analysis, Malware Behaviour Review, Financial-Fraud Tracing, Legal Mapping
Data Basis	Simulated / dummy logs, sample headers and illustrative indicators (no real victims, systems, or live infrastructure)
Prepared For	Course Instructor / Evaluation Panel
Report Status	Final Submission

Prepared strictly for academic instructional purposes. All attacker infrastructure, financial flows, and malware indicators referenced in this report are simulated or illustrative and do not correspond to real, active campaigns, individuals, or organisations.

Table of Contents

1. Executive Summary	3
2. Cybercrime Decomposition & Legal Mapping	3
3. Phishing & Spoofing Investigation	4
4. Malware Payload Analysis	5
5. Financial Fraud Tracing	6
6. Attack-Chain & Financial-Flow Diagrams	6
7. Impact on Stakeholders	7
8. Ethical Dilemmas	7
9. Recommendations & Policy Suggestions	8
10. Conclusion	8
References	9

1. Executive Summary

This report presents a simulated end-to-end investigation of “Operation Hydra,” a multi-vector cyber-crime campaign constructed for academic analysis under Unit 2: Types of Cyber Crimes. The scenario combines email and web spoofing, credential-harvesting phishing, malware-based data exfiltration, and downstream financial fraud routed through simulated mule accounts and a crypto off-ramp. The exercise applies both technical forensic method and legal reasoning to reconstruct the attacker's modus operandi, classify each constituent offence under Indian and international law, and evaluate the resulting harm to victims and institutions.

Seven distinct offence categories were identified across the kill chain: domain/email spoofing, phishing, unauthorised access, malware deployment, data theft, payment/card fraud, and money laundering. Each is mapped to specific statutory provisions and cross-referenced against comparable international frameworks. The findings support the conclusion that modern financial cyber-crime is rarely a single offence but a chained sequence of smaller crimes, each requiring a different investigative discipline and a different legal remedy.

2. Cybercrime Decomposition & Legal Mapping

Operation Hydra was deconstructed into discrete offence stages, each independently punishable and independently traceable. The table below maps each identified crime to its Indian statutory basis and to an internationally recognised equivalent.

#	Cyber Crime	Indian Law (IT Act / IPC / BNS)	Global Equivalent
1	Domain & Email Spoofing	S.66C & S.66D IT Act, 2000; S.419 IPC (BNS S.319)	CFAA §1030; EU NIS2 Directive
2	Phishing (Credential Theft)	S.66C & S.66D IT Act; S.420 IPC (BNS S.318)	Budapest Convention Art. 8; UK Fraud Act 2006
3	Unauthorised Access / System Intrusion	S.43 & S.66 IT Act, 2000	CFAA §1030(a); Budapest Convention Art. 2
4	Malware Deployment (RAT / Keylogger)	S.43(c) & S.66 IT Act; S.66F (cyber terrorism, if critical infra affected)	Budapest Convention Art. 4–6; EU Cybercrime Directive 2013/40/EU
5	Data Theft / Exfiltration	S.43(b) & S.72 IT Act, 2000	GDPR Art. 5 & 32 (breach obligations); CFAA
6	Card / UPI Payment Fraud	S.66C & S.66D IT Act; S.420 IPC (BNS S.318); Payment & Settlement Systems Act, 2007	PCI-DSS non-compliance exposure; PSD2 (EU); CFAA wire-fraud analogues
7	Money Laundering (Mule Accounts / Crypto)	Prevention of Money Laundering Act (PMLA), 2002	FATF Recommendations; EU AMLD5/6; 18 U.S.C. §1956 (US)

Beyond individual statutes, the chained nature of the campaign means it would likely be charged as a criminal conspiracy (S.120B IPC / BNS equivalent) alongside the specific offences, since the spoofing, intrusion, and laundering stages were executed toward a single common financial objective.

3. Phishing & Spoofing Investigation

Five representative phishing email samples were constructed and analysed for the exercise, modelled on common banking and courier-delivery lures. Each was examined for header anomalies, sender authentication results, and infrastructure fingerprints using open-source tools including MXToolbox, VirusTotal, and AbuseIPDB.

Sample	Lure Theme	SPF	DKIM	DMARC	Finding
E-01	Bank KYC Update	Fail	None	Fail	Envelope sender domain differed from display name; free mail relay
E-02	Courier Delivery Fee	SoftFail	Fail	None	Lookalike domain (0/O, l/1 substitution) registered days prior
E-03	UPI Cashback Offer	Fail	None	None	Shortened URL redirect chain to cloned payment page
E-04	Corporate Invoice	Pass	Fail	Fail	Compromised legitimate mailbox used as relay (business email compromise pattern)
E-05	Password Expiry Alert	Fail	Fail	Fail	Hosting IP flagged on AbuseIPDB for prior phishing complaints

Across the sample set, WHOIS lookups on the associated domains showed a consistent pattern: privacy-shielded registration, domains registered 3–7 days before the observed campaign, and reuse of the same low-cost registrar and nameserver pair. This clustering is a strong indicator of a single infrastructure operator running multiple concurrent lures rather than isolated, unrelated senders.

Consistent SPF/DKIM/DMARC failures across four of five samples confirm that the majority of the campaign relied on outright domain spoofing rather than genuine account compromise; sample E-04 is the exception and is consistent with a business-email-compromise (BEC) technique, where SPF passes because the mail genuinely originates from a hijacked legitimate mailbox.

4. Malware Payload Analysis

A representative attachment from the phishing set (a macro-enabled document delivered under the courier-delivery lure) was analysed in a sandboxed environment. Behavioural analysis indicates the payload is best classified as a lightweight Remote Access Trojan (RAT) with an integrated keylogging module, rather than a self-propagating worm or destructive logic bomb.

IOC Type	Indicator (Illustrative)	Notes
Dropper Hash (SHA-256)	3f9a...c21e (simulated)	Macro-embedded downloader
C2 Domain	update-secure-check[.]net (simulated)	Registered via same cluster as phishing domains
C2 Port	443 (HTTPS masquerade)	Beacons disguised as TLS traffic
Persistence	Registry Run key modification	Ensures execution on reboot
Behaviour	Keystroke logging, clipboard monitoring, screenshot capture	Consistent with credential and OTP theft
Exfiltration Channel	Periodic HTTPS POST to C2	Data staged and compressed before transmission

Mapping this behaviour to the attack vector, the malware's role in the chain is to convert an initial phishing click into durable, silent access — harvesting the one-time passwords and session data that make the subsequent financial-fraud stage possible. The presence of clipboard monitoring is notable, as it is specifically effective against users who copy-paste UPI IDs or card numbers, directly linking the malware capability to the financial-fraud objective described in Section 5.

5. Financial Fraud Tracing

Using dummy transaction logs constructed to mirror typical UPI and card-not-present fraud patterns, the simulated monetary flow was traced from the victim account through two layering accounts before conversion to cryptocurrency. Layering across two mule accounts within a short time window (under 90 minutes in the simulation) is consistent with real-world patterns used to outpace bank fraud-monitoring holds.

Step	Actor	Action (Simulated)	Amount (■, illustrative)
1	Victim	Fraudulent transaction via cloned payment page	48,500
2	Mule Account 1	Received & split into 3 smaller transfers (structuring)	16,000 / 16,000 / 16,500
3	Mule Account 2	Consolidated funds, withdrawn via ATM and P2P exchange	48,500
4	P2P / Exchange	Converted proceeds to cryptocurrency	≈ 0.012 BTC (simulated)
5	Wallet (Simulated)	Final custody; address flagged for illustrative clustering analysis	—

The structuring pattern in Step 2 — splitting a single inbound sum into multiple sub-threshold transfers — is a classic technique to avoid automatic reporting triggers. In a live investigation this would typically be pursued through a Suspicious Transaction Report (STR) filed with the Financial Intelligence Unit-India (FIU-IND) under the PMLA, combined with blockchain-analytics clustering of the receiving wallet to identify related cash-out points.

6. Attack-Chain & Financial-Flow Diagrams

The diagrams below summarise the technical kill chain (Figure 1) and the simulated financial flow (Figure 2) reconstructed from the analysis in Sections 3–5.




Figure 1. End-to-end attack chain for Operation Hydra.




Figure 2. Simulated layering and cash-out flow of defrauded funds.

7. Impact on Stakeholders

- **Financial:** Direct monetary loss to victims, chargeback and reimbursement costs borne by banks/payment processors, and increased compliance costs for affected institutions.
- **Emotional/Psychological:** Victims of financial fraud commonly report anxiety, loss of trust in digital payment systems, and, in BEC-style cases, reputational anxiety among employees who unknowingly facilitated the compromise.
- **Reputational:** Organisations whose domains or mailboxes are spoofed or compromised face brand-trust erosion, customer attrition, and potential regulatory scrutiny.
- **Operational:** Incident response, forensic investigation, and law-enforcement liaison consume significant institutional time and resources disproportionate to the amount defrauded.
- **Systemic:** Repeated campaigns of this type erode general public confidence in UPI and card-based digital payment ecosystems, a risk regulators such as the RBI actively monitor.

8. Ethical Dilemmas

The investigative process raises several ethical tensions that a responding analyst or institution must navigate.

- **Crypto tracing and privacy:** Blockchain clustering analysis used to trace laundering can incidentally expose transaction data belonging to unrelated, innocent wallet holders who share clustering heuristics, raising proportionality concerns.
- **Deceptive honeypots:** Deploying decoy credentials or beaconed documents to identify attackers can itself resemble entrapment or unauthorised-access conduct if not carefully scoped and authorised, and may implicate the investigator under the same statutes used against the attacker.
- **Attribution certainty:** Infrastructure overlap (shared registrars, hosting, or C2 patterns) supports probabilistic attribution but rarely proves individual identity beyond doubt; premature public attribution can cause reputational harm to wrongly implicated parties.
- **Victim disclosure timing:** Notifying victims immediately may tip off attackers still monitoring compromised accounts, while delaying notification prolongs victim exposure — a genuine trade-off between investigative value and victim welfare.

9. Recommendations & Policy Suggestions

- **Mandatory DMARC enforcement:** Regulators should require reject/quarantine-level DMARC policies for financial-sector and government domains, closing the spoofing gap seen in four of five phishing samples analysed.
- **Real-time inter-bank fraud signalling:** Faster sharing of mule-account indicators between banks (beyond current negative lists) would shorten the layering window observed in Section 5.
- **Public awareness campaigns:** Targeted, simple-language advisories on recognising lookalike domains and unsolicited KYC/cashback messages, distributed through the same UPI and banking apps used by the target demographic.
- **Structuring-pattern detection:** Payment processors should tune anomaly detection specifically for rapid multi-way splits following a single large inbound credit.
- **Cross-border cooperation:** Because domains, hosting, and crypto off-ramps are frequently offshore, streamlined mutual legal assistance under Budapest Convention-aligned frameworks would reduce investigative delay.

10. Conclusion

Operation Hydra illustrates that contemporary financial cyber-crime is a composite offence: spoofing and phishing create the entry point, malware converts that entry point into durable access, and the financial-fraud and laundering stages monetise the access while actively evading detection. Effective response therefore requires coordinated technical (SPF/DKIM/DMARC hardening, malware IOC sharing, transaction-pattern analytics) and legal (multi-statute charging, cross-border cooperation, PMLA enforcement) measures applied together rather than in isolation. No single control point in the chain is sufficient on its own; the strongest defence is breaking the chain at as many stages as possible.

References

[1] Information Technology Act, 2000 (India), as amended.

[2] Indian Penal Code, 1860 / Bharatiya Nyaya Sanhita, 2023 (India).

[3] Prevention of Money Laundering Act, 2002 (India).

[4] Payment and Settlement Systems Act, 2007 (India).

[5] Council of Europe, Convention on Cybercrime (Budapest Convention), ETS No. 185, 2001.

[6] Computer Fraud and Abuse Act, 18 U.S.C. § 1030 (United States).

[7] Regulation (EU) 2016/679, General Data Protection Regulation (GDPR).

[8] Directive (EU) 2013/40 on attacks against information systems.

[9] Financial Action Task Force (FATF), International Standards on Combating Money Laundering.

[10] MXToolbox, VirusTotal, and AbuseIPDB — open-source threat-intelligence platforms (tool documentation referenced for methodology).

[11] Reserve Bank of India, circulars and advisories on digital payment fraud risk management.