

Experiment – 5

Aim: To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

Q1. Insert new player Michale Clark with player ID 300311 in the table player

-USE aarya61_match

-INSERT INTO Player (PlayerID,FName,LName) VALUES (300311,'Michael','Clark');

-SELECT * FROM Player WHERE PlayerID=300311;

```
MySQL localhost:33060+ ssl SQL > USE aarya61_match
Default schema set to 'aarya61_match'.
Fetching global names, object names from 'aarya61_match' for auto-completion... Press ^C to stop.
MySQL localhost:33060+ ssl aarya61_match SQL > INSERT INTO Player (PlayerID, FName, LName)
-> VALUES (300311, 'Michael', 'Clark');
Query OK, 1 row affected (0.0204 sec)
MySQL localhost:33060+ ssl aarya61_match SQL > SELECT * FROM Player WHERE PlayerID=300311;
+-----+-----+-----+-----+-----+-----+-----+
| PlayerID | LName | FName | Country | Yborn | Bplace | FTest |
+-----+-----+-----+-----+-----+-----+-----+
| 300311 | Clark | Michael | NULL | NULL | NULL | NULL |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.0013 sec)
```

Q2. Insert new player Sam from India , Ahemdabad with player ID 406317 in the table player.

-DESCRIBE Player

-INSERT INTO Player (PlayerID, FName, Country, Bplace)

VALUES (406317, 'Sam', 'India', 'Ahmedabad');

```
MySQL localhost:33060+ ssl aarya61_match SQL > DESCRIBE Player;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| PlayerID | int unsigned | NO | PRI | NULL | |
| LName | varchar(15) | YES | | NULL | |
| FName | varchar(15) | YES | | NULL | |
| Country | varchar(25) | YES | | NULL | |
| Yborn | int | YES | | NULL | |
| Bplace | varchar(30) | YES | | NULL | |
| FTest | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.0035 sec)
MySQL localhost:33060+ ssl aarya61_match SQL > INSERT INTO Player (PlayerID, FName, Country, Bplace)
-> VALUES (406317, 'Sam', 'India', 'Ahmedabad');
Query OK, 1 row affected (0.0064 sec)
```

-SELECT * FROM Player WHERE PlayerID=406317;

```
MySQL localhost:33060+ ssl aarya61_match SQL > SELECT * FROM Player WHERE PlayerID=406317;
+-----+-----+-----+-----+-----+-----+-----+
| PlayerID | LName | FName | Country | Yborn | Bplace | FTest |
+-----+-----+-----+-----+-----+-----+-----+
| 406317 | NULL | Sam | India | NULL | Ahmedabad | NULL |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.0015 sec)
```

Q3. Create a view for Batsman

-CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score) AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns FROM Player,Batting WHERE PlayerID=PID;

-SELECT * FROM Batsman;

```
MySQL localhost:33060+ ssl aarya61_match SQL > CREATE VIEW Batsman (PID, FName, LName, Country, MID, Score)
-> AS
-> SELECT PlayerID, FName, LName, Country, MatchID, NRuns
-> FROM Player, Batting
-> WHERE PlayerID = PID;

Query OK, 0 rows affected (0.0253 sec)

MySQL localhost:33060+ ssl aarya61_match SQL > SELECT * FROM Batsman;
+----+-----+-----+-----+----+-----+
| PID | FName | LName | Country | MID | Score |
+----+-----+-----+-----+----+-----+
| 23001 | Yuvraj | Singh | India | 2755 | 0 |
| 25001 | MS | Dhoni | India | 2755 | 71 |
| 91001 | Sanath | Jayasuriya | Sri Lanka | 2755 | 60 |
| 94002 | Chaminda | Vaas | Sri Lanka | 2755 | 17 |
| 92002 | Muthiah | Murlitharan | Sri Lanka | 2755 | 1 |
| 89001 | Sachin | Tendulkar | India | 2689 | 91 |
| 23001 | Yuvraj | Singh | India | 2689 | 38 |
| 25001 | MS | Dhoni | India | 2689 | 36 |
| 99002 | Adam | Gilchrist | Australia | 2689 | 2 |
| 95001 | Ricky | Ponting | Australia | 2689 | 1 |
| 24001 | Andrew | Symonds | Australia | 2689 | 42 |
| 99001 | Breet | Lee | Australia | 2689 | 7 |
| 27001 | Praveen | Kumar | India | 2689 | 7 |
| 27001 | Praveen | Kumar | India | 2755 | 2 |
| 98002 | Harbhajan | Singh | India | 2689 | 3 |
| 98002 | Harbhajan | Singh | India | 2755 | 2 |
+----+-----+-----+-----+----+-----+
16 rows in set (0.0032 sec)
```

Q4. Create a view for Bowling in ODI match 2689

-CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets) AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets FROM Player,Bowling WHERE PlayerID=PID AND MatchID=2689;

-SELECT * FROM Bowling2689;

```
MySQL localhost:33060+ ssl aarya61_match SQL > CREATE VIEW Bowling2689 (PID, FName, LName, Country, NOvers, NWickets)
-> AS
-> SELECT PlayerID, FName, LName, Country, NOvers, NWickets
-> FROM Player, Bowling
-> WHERE PlayerID = PID
-> AND MatchID = 2689;

Query OK, 0 rows affected (0.0087 sec)

MySQL localhost:33060+ ssl aarya61_match SQL > SELECT * FROM Bowling2689;
+----+-----+-----+-----+-----+-----+
| PID | FName | LName | Country | NOvers | NWickets |
+----+-----+-----+-----+-----+-----+
| 99001 | Breet | Lee | Australia | 10 | 1 |
| 24001 | Andrew | Symonds | Australia | 3 | 1 |
| 23001 | Yuvraj | Singh | India | 3 | 0 |
| 98002 | Harbhajan | Singh | India | 10 | 1 |
+----+-----+-----+-----+-----+-----+
4 rows in set (0.0028 sec)
```

Q5. Find name of all players who have scored 60 or more runs.

-SELECT FName,LName FROM Player,Batting WHERE PlayerID=PID AND NRuns>=60;

```
MySQL localhost:33060+ ssl aarya61_match SQL > SELECT FName, LName
-> FROM Player, Batting
-> WHERE PlayerID = PID
-> AND NRuns >= 60;

+-----+-----+
| FName | LName |
+-----+-----+
| MS | Dhoni |
| Sanath | Jayasuriya |
| Sachin | Tendulkar |
+-----+-----+
3 rows in set (0.0019 sec)
```

Q6. Find the names of bowlers that have not taken any wickets in ODI match 2689

-SELECT FName,LName FROM Player,Bowling WHERE PlayerID=PID AND MatchID=2689 AND NWickets=0;

```
MySQL localhost:33060+ ssl aarya61_match SQL > SELECT FName, LName
-> FROM Player, Bowling
-> WHERE PlayerID = PID
-> AND MatchID = 2689
-> AND NWickets = 0;

+-----+-----+
| FName | LName |
+-----+-----+
| Yuvraj | Singh |
+-----+-----+
1 row in set (0.0018 sec)
```

Q7. Define a view NPlayer for obtaining the names of the countries and number of players from each country.

-CREATE VIEW NPlayer (Country,NPlayers) AS SELECT Country,COUNT(*) FROM Player GROUP BY Country;

-SELECT * FROM NPlayer;

```
MySQL localhost:33060+ ssl aarya61_match SQL > CREATE VIEW NPlayer (Country, NPlayers)
-> AS
-> SELECT Country, COUNT(*)
-> FROM Player
-> GROUP BY Country;

Query OK, 0 rows affected (0.0078 sec)
MySQL localhost:33060+ ssl aarya61_match SQL > SELECT * FROM NPlayer;

+-----+-----+
| Country | NPlayers |
+-----+-----+
| India   | 11       |
| Australia | 5       |
| West Indies | 1       |
| Sri Lanka | 3       |
| Pakistan | 2       |
| Zimbabwe | 1       |
| South Africa | 4       |
| New Zealand | 2       |
| England | 1       |
| NULL    | 1       |
+-----+-----+
10 rows in set (0.0023 sec)
```